

## Outlet Boxes T&B Catalog Number:

52171-MS1-P

**UPC Number:** 78599104795 **Status:** Active

Description:

4 inch pre-galvanized steel square box with MS bracket, 2-1/8 inch deep, 30.3 cuin. Welded construction with 1/2 inch & 3/4 inch knockouts, ground bump and 10-1/2 inch #12 AWG solid wire pigtail. For use with conduit.

bump and 10-1/2 inch #12 AVVG	solid wire pigtali. For use with conduit.
Features	
	"MS" bracket boxes are the fastest metal stud install in the industry.
	Center mark locator window enables accurate positioning.
	Patented bracket design has teeth that sink into the stud for a secure installation and mounts to open and closed side of stud, providing flexibility.
	Patented bracket design has teeth that sink into the stud for a secure installation and mounts to open and closed side of stud, providing flexibility.
Application	
General	For use with armored/metal clad cable
Cable Entry_IDW	Knockouts
Material	Steel
Finish	Pre-Galvanized
Ground Wire	10-1/2" #12 AWG solid wire
Volume (cu.in.)	30.3
Construction	Welded
Knockouts_IDW	Yes
Dimension Information	
Size (inches)	4
Depth (inches)	2 1/8
Packaging	
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	103 lbs. per 100
Application Support	·
Product Overview	Available on Website
NEC Article 314 - Boxes and Fittings	Available on Website
Product Brochure-4 Inch Square Old	Available on Website
Work Box with Swing Ears	
Product Brochure-MS Bracket Boxes	Available on Website
Product Brochure-Pre-Assemblies & Pre-	Available on Website
Fab Components	
Pre-Assemblies Labor Saving Calculator	Available on Website
Certifications	
RoHS Compliance	No



## Certifications



File Nbr: E 2969

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com