



Select a Language ▾

SEARCH

Supplier Center    Distributor Center

**BROWSE PRODUCTS**

Category:

**PRODUCTS**

- [Bending](#)
- [Bolt Cutters](#)
- [Cable Termination](#)
- [CATV/Broadband Instruments](#)
- [Connectors](#)
- [Electric Test Instruments](#)
- [Fasteners](#)
- [Fiber Connections](#)
- [Fiber Optic Instruments](#)
- [Fishing](#)
- [Hydraulic Tools](#)
- [Knockouts](#)
- [Material Handling](#)
- [Power Tool Accessories](#)
- [Professional Hand Tools](#)
- [Pulling](#)
- [Storage](#)
- [Telco Instruments](#)
- [VDV Instruments](#)
- [VDV Termination](#)
- [VDV Tools](#)
- [Wire Termination](#)

[VDV Instruments](#) > [LOCATORS](#) > [Irrigation](#) > LOCATOR,VALVE (521A)

**LOCATOR,VALVE (521A)**

Images



SAVE PRODUCT TO PDF

**Related Products**

  
Image  
Unavailable

User Reviews

(No Reviews Yet.)

Cat No: **521A**    UPC No: **783310867883**

[Request Product Info or Demo ▶](#)

[Where to Buy ▶](#)

- [Description](#)
- [Specifications](#)
- [Documents](#)
- [Reviews](#)

- Automatic Shut-Off : 90 MINT For Receiver, Turn-Off Bumper For Transmitter
- Battery : Eight D-Cells And One 9 VDC (Included)
- Battery Life : Transmitter: 50 HR Nominal, Receiver: 100 HR Nominal
- Dimensions : 33.5 (851 MM) Length X 8.25 (210 MM) Width X 3.75 (95 MM) Height Case
- Transmitter Frequency : 1748
- Transmitter Power : 750 Vpp, 285 V RMS