

Product selection table



		Single-phase																		
		CP-D						CP-E												
Rated output current		0.42 A	0.83 A	1.3 A	2.1 A	2.5 A	4.2 A	0.625 A	0.75 A	1.25 A	2.5 A	3 A	5 A	10 A	20 A					
Rated output voltage	5 V DC											•								
	12 V DC		•		•						•			•						
	24 V DC	•		•		•	•		•	•	•		•	•	•					
	48 V DC							•			•		•	•						
10 W	12 V DC		•																	
	24 V DC	•																		
15 W	5 V DC											•								
	24 V DC								•											
18 W	12 V DC				•						•									
	24 V DC									•										
30 W	24 V DC			•																
	48 V DC							•												
60 W	24 V DC					•														
	48 V DC									•	•									
100 W	24 V DC						•													
	48 V DC																			
120 W	12 V DC													•						
	24 V DC												•							
240 W	24 V DC													•						
	48 V DC												•							
480 W	24 V DC														•					
	48 V DC													•						
960 W	24 V DC														•					
	48 V DC														•					
Rated input voltage	100-240 V AC	•	•	•	•	•	•	•	•	•	•	•								
	115/230 V AC auto select												•	•	•					
	115-230 V AC													•	•					
	110-240 V AC														•					
	110-120 V AC														•					
	220-240 V AC														•					
	400-500 V AC														•					
Accessories	Redundancy Module							•	•	•	•	•	•	•	•					
	Control Module																			
	Messaging Module																			
	Order code	1SVR427041R0000	1SVR427041R1000	1SVR427043R0100	1SVR427043R1200	1SVR427044R0200	1SVR427045R0400	1SVR427030R2000	1SVR427030R0000	1SVR427031R0000	1SVR427031R2000	1SVR427032R1000	1SVR427032R0000	1SVR427033R3000	1SVR427034R0000	1SVR427034R2000	1SVR427035R1000	1SVR427035R0000	1SVR427035R2000	1SVR427036R0000



		Single-phase						Three-phase						
		CP-S			CP-C			CP-T						
		5 A	10 A	20 A	5 A	10 A	20 A	5 A	10 A	20 A	40 A			
Rated output voltage	5 V DC													
	12 V DC													
	24 V DC	•	•	•	•	•	•	•	•	•	•			
	48 V DC							•	•	•				
10 W	12 V DC													
	24 V DC													
15 W	5 V DC													
	24 V DC													
18 W	12 V DC													
	24 V DC													
30 W	48 V DC													
	24 V DC													
60 W	24 V DC													
	48 V DC													
100 W	24 V DC													
	12 V DC													
120 W	24 V DC	•			•			•						
	48 V DC													
240 W	24 V DC		•			•			•					
	48 V DC							•						
480 W	24 V DC			•			•			•				
	48 V DC								•					
960 W	24 V DC									•	•			
	48 V DC									•				
Rated input voltage	100-240 V AC													
	115/230 V AC auto select													
	115-230 V AC													
	110-240 V AC	•			•	•	•							
	110-120 V AC		•	•										
	220-240 V AC		•	•										
	400-500 V AC							•	•	•	•			
Accessories	Redundancy Module	•	•	•	•	•	•	•	•	•	•			
	Control Module	•	•	•	•	•	•							
	Messaging Module				•	•	•							
	Order code	1SVR427014R0000	1SVR427015R0100	1SVR427016R0100	1SVR427024R0000	1SVR427025R0000	1SVR427026R0000	1SVR427054R0000	1SVR427054R2000	1SVR427055R0000	1SVR427055R2000	1SVR427056R0000	1SVR427056R2000	1SVR427057R0000