



PART#	WIRE RANGE CLASS B,C,D	WIRE RANGE CLASS K,M,I	INTERNAL HEX SIZE	L	W	H
ITG-6	6 - 14 AWG	6 - 14 AWG	1/8	1.13	1.24	1.37
ITG-1	1 - 1/0 AWG	2 - 10 AWG	3/16	1.60	1.55	1.75
ITG-3/0	3/0 - 4 AWG	2/0 - 2 AWG	3/16	1.85	1.60	1.81

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- RATED FOR 90 °C COPPER CONDUCTOR.
- COLD TEMPERATURE RATED TO -45 °C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT.

		POLARIS SALES CO. INC	
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED TWO HOLE CONNECTOR SERIES GREY FINE STRANDED	
<small>NAME</small> S.PARRY		<small>DATE</small> 8/13/2012	
<small>DRAWN BY</small>		<small>DWG. NO.</small> ITG-SERIES	
MATERIAL: 6061-T6511 ALUMINUM		SCALE: 1:1	
		SHEET: 1 OF 1	