

EHS Guy Wire Cutter



Cat. No.	UPC No.	Description
758	01274	Heavy-Duty Ratchet Guy Wire Cutter
03548	03548	Cutter Head Unit (Includes Blades, Blade Holder, Insert and Hardware)

- Cuts 1/2" Extra High Strength (EHS) and standard guy wire.
- Cuts 1/2" (12.7 mm) mild steel rods and bolts.
- Has two cutting actions - single motion cutting for small cable. Ratchet action for heavy-duty cutting.
- Anti-slip mechanism for positive ratchet action.

SPECIFICATIONS

Capacity: 1/2" EHS and standard Guy Wire, 1/2" Mild Steel Rods and Bolt.
Length: 27-3/4" (704 mm). **Weight:** 10 lbs. 12 oz. (4.8 kg)

Hydraulic Cable Cutter



Cat. No.	UPC No.	Description
HK510GL	02644	Hydraulic Cable Cutter
03701	03701	Cutter Blade
03685	03685	Fixed Cutter Head

- Flip open head provides strength while making it easy to cut long lengths.
- Head rotates 180°.
- Thumb release lever for quick blade retraction.

SPECIFICATIONS

Capacity: Aluminum and Copper Cable, ACSR: 3/4" (19 mm)
 Standard Guy Wire, Ground Rod, Rebar: 1/2" (13 mm)
 Soft Steel Bolts: 11/16" (17 mm)
Wire Rope: 3/4" (19 mm)
Length: 14.5" (368 mm) **Weight:** 5.7 lbs. (2.6 kg)

Hydraulic Cable Cutter Sets

750H767 model with
767 Hand Pump



- Cuts in 7 seconds. Jaws slide open quickly to save time between cuts.
- 11-ton (97 kN) ram powers cutting jaws. Jaws are specially hardened and precision ground to hold sharpness.
- Lightweight and easy to use.

SPECIFICATIONS

Capacity: 1000 MCM (500 mm²) copper or aluminum cable
Jaw opening: 1-15/16" (49 mm)
Weight: 750 - 25 lbs. (11.3 kg) 750F1725 - 40 lbs. (18.1 kg)
 750H767 - 29 lbs. (13.2 kg) 750E975 - 84 lbs. (38.1 kg)

Cat. No.	UPC No.	Description
750	29149	Hydraulic Cable Cutter & Ram in Storage Box
750H767	17450	Hydraulic Cable Cutter with 767 Hand Pump, Ram, Hydraulic Hose in Storage Box
750E975	34203	Hydraulic Cable Cutter with 975 Electric Pump, Ram, Hydraulic Hose in Storage Box
751	22279	Hydraulic Cable Cutter Head for use with Greenlee 746 Hydraulic Ram Also order 51385 Elbow (see below).
746C	17451	Ram Unit
23955	23955	Steel Storage Box
51385	51385	Elbow for 746 Ram
17459	17459	Replacement Cutter Blade

Guy Wire Cutter Dies



SPECIFICATIONS


Cutting Capacities:
 Guy Wire: 5/8 in. (16 mm) dia. Ground Rod: 5/8 in. (16 mm) dia.
 EHS Guy Wire: 5/8 in. (16 mm) dia. Soft Steel Bolts: 5/8 in. (16 mm) dia.
 Rebar (grade 60): 5/8 in. (16 mm) dia. ACSR: 477 MCM (240 mm²)

- Works with any crimping tool that accepts 12-ton "U" type dies.
- Less costly than dedicated cutting tools.
- Simple to install in crimping tools.
- Require no adjustments for cutting different materials.
- Will cleanly cut guy wire (including EHS), grade 60 rebar, ground rod, soft steel bolts up to 5/8" (16 mm) and up to 477 MCM (240 mm²) ACSR.
- Patent 5,775,158.

Cat. No.	UPC No.	Description
00949	00949	Cutting dies for 12-ton "U" die type crimping tools

Ratchet Type

Heavy-Duty Ratchet Guy Wire Cutter



SPECIFICATIONS

Capacity: 1/2" EHS and standard Guy Wire, 1/2" Mild Steel Rods and Bolt.
Length: 27-3/4" (704 mm). **Weight:** 10 lbs. 12 oz. (4.8 kg)

- Cuts 1/2" Extra High Strength (EHS) and standard guy wire.
- Cuts 1/2" (12.7 mm) mild steel rods and bolts.
- Has two cutting actions - single motion cutting for small cable. Ratchet action for heavy-duty cutting.
- Anti-slip mechanism for positive ratchet action.

Cat. No.	UPC No.	Description
758	01274	Heavy-Duty Ratchet Guy Wire Cutter
03548	03548	Cutter Head Unit (Includes Blades, Blade Holder, Insert and Hardware)

Hydraulic Type

Hydraulic Cable Cutter



Cat. No.	UPC No.	Description
HK510GL	02644	Hydraulic Cable Cutter
03701	03701	Cutter Blade
03685	03685	Fixed Cutter Head

- Flip open head provides strength while making it easy to cut long lengths.
- Head rotates 180°.
- Thumb release lever for quick blade retraction.

SPECIFICATIONS

Capacity: Aluminum and Copper Cable, ACSR: 3/4" (19 mm)
 Standard Guy Wire, Ground Rod, Rebar: 1/2" (13 mm)
 Soft Steel Bolts: 11/16" (17 mm)

Wire Rope: 3/4" (19 mm)

Length: 14.5" (368 mm) **Weight:** 5.7 lbs. (2.6 kg)

Hydraulic Cable Cutter Sets

750H767 model with
767 Hand Pump



SPECIFICATIONS

Capacity: 1000 MCM (500 mm²) copper or aluminum cable
Jaw opening: 1-15/16" (49 mm)
Weight: 750 - 25 lbs. (11.3 kg) 750F1725 - 40 lbs. (18.1 kg)
 750H767 - 29 lbs. (13.2 kg) 750E975 - 84 lbs. (38.1 kg)

- Cuts in 7 seconds. Jaws slide open quickly to save time between cuts.
- 11-ton (97 kN) ram powers cutting jaws. Jaws are specially hardened and precision ground to hold sharpness.
- Lightweight and easy to use.

Cat. No.	UPC No.	Description
750	29149	Hydraulic Cable Cutter & Ram in Storage Box
750H767	17450	Hydraulic Cable Cutter with 767 Hand Pump, Ram, Hydraulic Hose in Storage Box
750F1725	25570	Hydraulic Cable Cutter with 1725 Foot Pump, Ram, Hydraulic Hose in Storage Box
750E975	34203	Hydraulic Cable Cutter with 975 Electric Pump, Ram, Hydraulic Hose in Storage Box
751	22279	Hydraulic Cable Cutter Head for use with Greenlee 746 Hydraulic Ram Also order 51385 Elbow (see Parts).
746C	17451	Ram Unit
23955	23955	Steel Storage Box
51385	51385	Elbow for 746 Ram
17459	17459	Replacement Cutter Blade

Guy Wire Cutter Dies (for any crimping tool that accepts 12-ton "U" type or Kearney PH2 type dies)



Cat. No.	UPC No.	Description
00949	00949	Cutting dies for 12-ton "U" die type crimping tools
00950	00950	Cutting dies for Kearney PH2 type crimping tools

SPECIFICATIONS

Cutting Capacities:

Guy Wire: 5/8" (16 mm) dia. Ground Rod: 5/8" (16 mm) dia.
 EHS Guy Wire: 5/8" (16 mm) dia. Soft Steel Bolts: 5/8" (16 mm) dia.
 Rebar (grade 60): 5/8" (16 mm) dia. ACSR: 477 MCM (240 mm²)

EHS Guy Wire Cutter



Cat. No.	UPC No.	Description
758	01274	Heavy-Duty Ratchet Guy Wire Cutter
03548	03548	Cutter Head Unit (Includes Blades, Blade Holder, Insert and Hardware)

- Cuts 1/2" Extra High Strength (EHS) and standard guy wire.
- Cuts 1/2" (12.7 mm) mild steel rods and bolts.
- Has two cutting actions - single motion cutting for small cable. Ratchet action for heavy-duty cutting.
- Anti-slip mechanism for positive ratchet action.

SPECIFICATIONS

Capacity: 1/2" EHS and standard Guy Wire, 1/2" Mild Steel Rods and Bolt.
Length: 27-3/4" (704 mm). **Weight:** 10 lbs. 12 oz. (4.8 kg)

Hydraulic Cable Cutter



Cat. No.	UPC No.	Description
HK510GL	02644	Hydraulic Cable Cutter
03701	03701	Cutter Blade
03685	03685	Fixed Cutter Head

- Flip open head provides strength while making it easy to cut long lengths.
- Head rotates 180°.
- Thumb release lever for quick blade retraction.

SPECIFICATIONS

Capacity: Aluminum and Copper Cable, ACSR: 3/4" (19 mm)
 Standard Guy Wire, Ground Rod, Rebar: 1/2" (13 mm)
 Soft Steel Bolts: 11/16" (17 mm)
Wire Rope: 3/4" (19 mm)
Length: 14.5" (368 mm) **Weight:** 5.7 lbs. (2.6 kg)

Hydraulic Cable Cutter Sets



750H767 model with 767 Hand Pump

- Cuts in 7 seconds. Jaws slide open quickly to save time between cuts.
- 11-ton (97 kN) ram powers cutting jaws. Jaws are specially hardened and precision ground to hold sharpness.
- Lightweight and easy to use.

SPECIFICATIONS

Capacity: 1000 MCM (500 mm²) copper or aluminum cable
Jaw opening: 1-15/16" (49 mm)
Weight: 750 - 25 lbs. (11.3 kg) 750F1725 - 40 lbs. (18.1 kg)
 750H767 - 29 lbs. (13.2 kg) 750E975 - 84 lbs. (38.1 kg)

Cat. No.	UPC No.	Description
750	29149	Hydraulic Cable Cutter & Ram in Storage Box
750H767	17450	Hydraulic Cable Cutter with 767 Hand Pump, Ram, Hydraulic Hose in Storage Box
750F1725	25570	Hydraulic Cable Cutter with 1725 Foot Pump, Ram, Hydraulic Hose in Storage Box
750E975	34203	Hydraulic Cable Cutter with 975 Electric Pump, Ram, Hydraulic Hose in Storage Box
751	22279	Hydraulic Cable Cutter Head for use with Greenlee 746 Hydraulic Ram Also order 51385 Elbow (see below).
746C	17451	Ram Unit
23955	23955	Steel Storage Box
51385	51385	Elbow for 746 Ram
17459	17459	Replacement Cutter Blade

Guy Wire Cutter Dies



SPECIFICATIONS

Cutting Capacities:
 Guy Wire: 5/8 in. (16 mm) dia. Ground Rod: 5/8 in. (16 mm) dia.
 EHS Guy Wire: 5/8 in. (16 mm) dia. Soft Steel Bolts: 5/8 in. (16 mm) dia.
 Rebar (grade 60): 5/8 in. (16 mm) dia. ACSR: 477 MCM (240 mm²)

- Works with any crimping tool that accepts 12-ton "U" type or Kearney PH2 type dies.
- Less costly than dedicated cutting tools.
- Simple to install in crimping tools.
- Require no adjustments for cutting different materials.
- Will cleanly cut guy wire (including EHS), grade 60 rebar, ground rod, soft steel bolts up to 5/8" (16 mm) and up to 477 MCM (240 mm²) ACSR.
- Patent 5,775,158.

Cat. No.	UPC No.	Description
00949	00949	Cutting dies for 12-ton "U" die type crimping tools
00950	00950	Cutting dies for Kearney PH2 type crimping tools