



USB-C to HDMI Adapter Cable

Converts DP Alt Mode Signal to HDMI 4K Output, 1 m (3 ft.), Black

Part No.: **152235**

Connect USB-based Audio/Video signals into HDMI format.

The Manhattan USB-C to HDMI Adapter Cable transmits USB audio/video signals to HDMI projectors, flat-panel displays, televisions and other similar devices. Built-in circuitry allows digital media enthusiasts to easily enjoy USB-based multimedia content on UHD displays and TVs while maintaining simultaneous A/V reception at the source. Its ultra high-definition capability supports up to 3840x2160 @30Hz and 4K to serve a wide range of resolutions in many devices and UHD applications including training, retail and trade show settings. Source device must support DP Alt Mode. No setup is required. It effortlessly delivers digital content that is stored on smartphones, tablets, ultrabooks and notebook computers to displays with HDMI input capabilities.

Features:

- Easily connects a USB-C DP Alt Mode device to an HDMI display, monitor or projector
- Delivers clear, sharp resolution up to 3840x2160 @30Hz; supports 4K Ultra HD video aspect ratio of 21:9
- Ideal for connecting HDMI displays to DP Alt Mode capable-smartphones, tablets, Ultrabooks, Laptops and more
- Compatible only with USB-C device that has DP Alt mode; Thunderbolt 3 port compatible
- Slim design makes for clutter-free desktop; direct-connect cable makes it the perfect travel companion
- Also available in 2m (6 ft.) length [search part number 151764 at www.manhattanproducts.com]
- Bus powered: no external power supply needed
- Three-Year Warranty

Specifications:

Standards and Certifications

- CE

- FCC
- RoHS2
- USB 3.1
- HDMI
- HDCP
- DP Alt Mode

General

- Supports lane data rates of 2.7 Gbps High Bit Rate (HBR) and 1.62 Gbps Reduce Bit Rate (RBR)
- Resolution: up to 3840x2160 @30Hz
- Audio and video output through HDMI
- Bus powered: no external power supply
- Supports HDCP pass-through

Connections

- Input: USB 3.1 Type-C male
- Output: HDMI Type-A male

Physical

- Adapter cable: 1 m (3 ft.)
- Weight: 0.09 kg (3.2 oz.)

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- DP Alt Mode-supported device

Package Contents

- USB-C to HDMI Adapter Cable



