

**Liquidtight Flexible Metal Conduit Fittings****T&B Catalog Number:**

LTA100-100

**UPC Number:**

78620986529

**Status:**

Active

**Description:**

1 in. aluminum PVC jacketed liquidtight flexible conduit.

**Features**

Utilizes the flexibility of a light-weight aluminum core, coupled with the advantage of a PVC jacket that is virtually unaffected by sunlight, acid and oil.  
WEEE and RoHS compliant.

**Application**

Used in applications where concerns of excessive weight and corrosion exist.

**General**

|                               |               |
|-------------------------------|---------------|
| Material                      | Aluminum      |
| Material-Conduit Core         | Aluminum      |
| Material-Conduit Outer Jacket | PVC           |
| Color                         | Gray          |
| Inside Bend Radius (inches)   | 4             |
| Working Temperatures          | -20 C to 60 C |

**Dimension Information**

|                             |   |
|-----------------------------|---|
| Size (inches)               | 1 |
| Inside Bend Radius (inches) | 4 |

**Packaging**

|                    |                    |
|--------------------|--------------------|
| T&B Order Multiple | 100                |
| Package in Units   | 100                |
| T&B Sold in UOM    | Feet               |
| T&B Weight Per UOM | 29.75 lbs. per 100 |

**Application Support**

|                    |            |
|--------------------|------------|
| T&B Sales Drawings | wsd-000277 |
|--------------------|------------|

**Certifications**

|                 |     |
|-----------------|-----|
| RoHS Compliance | Yes |
|-----------------|-----|

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com