

ASN SLEEVE



- Manufactured from high strength aluminum alloy which offers maximum conductivity and excellent crimping characteristics.
- Electro-Tin plated for low contact resistance.
- Chamfered entry for easy conductor insertion.
- Color coded end cap identifies the proper compression die.
- Roll marked barrel for easy identification and proper location of crimps.
- Pre-filled with DE-OX prevents oxide from forming.
- Dual rated for Aluminum or Copper conductors.
- UL 486A/B 90° C Listed and CSA Certified.
- If proper high voltage spacing and insulation techniques are used, may be used for high voltage applications up to 35KV.
- UL File E6207

Compare	Item ID	Conductor Size	Expanded Conductor Range	Length	Length (mm)	Color Code	Die Index Number	Outside Diameter	Outside Diameter (mm)	Inside Diameter	Inside Diameter (mm)	Standard Package Quantity	NAED/UPC Number
	ASN-8	#8 AWG		1.8060	45.9	BLUE	374	0.3000	7.6	0.1550	3.9	20	0783669184716
	ASN-6	#6 AWG		1.2050	30.6	GRAY	346	0.3380	8.6	0.1940	4.9	20	0783669184723
	ASN-4	#4 AWG	4-6 AWG	2.2220	56.4	GREEN	375	0.4270	10.8	0.2470	6.3	20	0783669184730
	ASN-2	#2 AWG	2-6 AWG	1.9400	49.3	PINK	348	0.5250	13.3	0.3070	7.8	20	0783669184747
	ASN-1	#1 AWG	1-2 AWG	1.9400	49.3	GOLD	471	0.5440	13.8	0.3580	9.1	10	0783669184754
	ASN-1/0	#1/0 AWG	1/0-1 AWG	2.5730	65.4	TAN	296	0.5990	15.2	0.3850	9.8	10	0783669184761
	ASN-2/0	#2/0 AWG	2/0-1 AWG	2.7100	68.8	OLIVE	297	0.6740	17.1	0.4320	11.0	10	0783669184778
	ASN-3/0	#3/0 AWG	3/0-1 AWG	2.7100	68.8	OLIVE	297	0.7610	19.3	0.4950	12.6	10	0783669184785
	ASN-4/0	#4/0 AWG	4/0-1 AWG	3.0700	78.0	RUBY	467	0.8540	21.7	0.5530	14.0	10	0783669184792
	ASN-250	250 kcmil	250 kcmil-1/0 AWG	3.7350	94.9	RED	324	0.9240	23.5	0.5950	15.1	5	0783669184808
	ASN-300	300 kcmil	300 kcmil-2/0 AWG	3.0700	78.0	BLUE	470	1.0100	25.7	0.6500	16.5	5	0783669184815
	ASN-350	350 kcmil	350 kcmil- 3/0 AWG	5.1250	130.2	BROWN	299	1.1050	28.1	0.7200	18.3	3	0783669184822
	ASN-400	400 kcmil	400 kcmil-4/0 AWG	4.6060	117.0	GREEN	472	1.1880	30.2	0.7620	19.4	3	0783669184839
	ASN-500	500 kcmil	500 kcmil-4/0 AWG	5.1300	130.3	PINK	300	1.3150	33.4	0.8540	21.7	3	0783669184846
	ASN-600	6000 kcmil	600 kcmil-250 kcmil	5.3700	136.4	BLACK	473	1.4400	36.6	0.9200	23.4	1	0783669184853
	ASN-700/750	700/750 kcmil	750 kcmil-500 kcmil	5.9280	150.6	YELLOW	936	1.4600	37.1	1.0300	26.2	1	0783669184860
	ASN-1000	1000 kcmil	1000 kcmil-750 kcmil	5.9920	152.2	BROWN	302	1.8400	46.7	1.1800	30.0	1	0783669184877