



- NOTE:**
- ELETRICAL TEST:**
 - 100% OPEN SHORT MISS WIRE TEST.
 - Min INSULATION RESISTANCE: Min. DC 300V 2Mohm
 - Max. CONDUCTOR RESISTANCE: 3ohm
 - CABLE MARKING:**

www.manhattan-products.com Exxxxxx AWM STYLE 2919 80°C 30V
 LOW VOLTAGE COMPUTER CABLE

4	SCREW	THUMB SCREW(Length 44mm)*4PCS
3	PVC	45P PVC BLACK
2	CONN	HDB 15PIN MALE, PLATED NICKEL, INSULATION BLUE
1	CABLE	{28#1C(7/0.12BC+FPE)*S(22±2/0.12CCA)+PVC}*3COAX+6C*28#(7/0.12BC+PE)+AL-foil+DW28#(7/0.12BC)+B(16/6/0.12ALM)OD=8.0±0.3mm:PVC JACKET:Color:Black
NO.	ITEM	DESCRIPTION

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MANHATTAN AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF MANHATTAN.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1°

TOLERANCE (INCH)	TOLERANCE (MM)
x ±0.02"	x ±0.5mm
x.x ±0.01"	x.x ±0.20mm
x.xx ±0.008"	x.xx ±0.15mm
x.xxx ±0.005"	x.xxx ±0.10mm

manhattan

TITLE:	APPD				
	Check				
CUSTOMER:	Drawer	Date		13.05.22	
CUSTOMER P/N:	Unit	mm	Projection	☞	
ICT P/N:	Scale	1:1	Size.	A4	
DWG. NO:	Sheet	1 of	REV.	A	

311748