

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: White Dry Grout

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Grout

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Custom Building Products

3490 Piedmont Road, Suite 1300

Atlanta, GA 30329

Telephone Number: (562)-598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone INFOTRAC 1-800-535-5053 (US and Canada)

Number: INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

1910.1200 (OSHA HAZCOM2012)

Skin Irritation Category 2
Serious Eye Damage Category 1
STOT-SE Category 3
STOT-RE Category 1
Carcinogenicity Category 1A

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:

DANGER!

2.2b HAZARD STATEMENTS

Causes skin irritation

Causes serious eye damage

May cause respiratory irritation

Causes damage to organs through prolonged or repeated exposure

May cause cancer

Page 1 of 13



2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

| i. | PREVENTION | Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/ vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. |
|------|------------|---|
| ii. | RESPONSE | If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. |
| iii. | STORAGE | Store in a well-ventilated place. Keep container tightly closed. Store locked up. |
| iv. | DISPOSAL | Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations. |

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED Not applicable

2.3b UNKNOWN ACUTE TOXICITY

25% of the mixture consists of ingredient(s) of unknown acute toxicity.

2.3c WHMIS CLASSIFICATION

Class D2B – Skin/Eye Irritant Class D2A - Carcinogenicity

2.3d LABEL ELEMENTS ACCORDING TO WHMIS

i. WHMIS HAZARD SYMBOLS



ii. WHMIS SIGNAL WORD



WARNING!

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

| Chemical Name | CAS Number | Weight % |
|----------------------------|------------|--------------|
| Portland cement | 65997-15-1 | 60 – 100 %* |
| Calcium carbonate | 1317-65-3 | 30 – 60 %* |
| Titanium Dioxide | 13463-67-7 | 5 – 10%* |
| Gypsum | 13397-24-5 | 1 – 5 % * |
| Crystalline Silica, Quartz | 14808-60-7 | 0.5 – 1.5 %* |
| Natural Wollastonite | 13983-17-0 | 0.5 – 1.5 %* |

^{*}Means that the component will fall into one the ranges specified due to batch-to-batch variability.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

| ROUTES OF EXPOSURE | DESCRIPTION |
|--------------------|--|
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately. |
| Skin Contact: | In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. |
| Inhalation: | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| Ingestion: | If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention. |

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

| ROUTES OF EXPOSURE | DESCRIPTION |
|--------------------|---|
| Eye Contact: | Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Skin Contact: | Causes skin irritation. Handling can cause dry skin. |

White Dry Grout Print Date: 30-Dec-14

Page 3 of 13



Inhalation: May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious

disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physicians: Symptoms may not appear immediately.

Special Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:

Treat for surrounding material.

5.2b. Unsuitable Extinguishing Media:

Not available.

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon

5.3b. Explosion Data

i. Sensitivity to Mechanical Impact:

Not available.

ii. Sensitivity to Static Discharge:

Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES



6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Recover all usable material. Pick up large pieces, then place in a

suitable container. Do not flush to sewer or allow to enter

waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Vacuum or sweep material and place in a disposal container.

Dispose of unwanted material properly in accordance with all local,

regional, national and international regulations.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear chemical resistant gloves and

eye protection. Do not mix with other chemical products. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally. Good housekeeping is important to prevent

accumulation of dust.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended

personal protection. Launder contaminated clothing before reuse.

Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store at room temperature and keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable

construction of the storage area.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

| Occupational Exposure Limits | | |
|----------------------------------|-------------------------------------|------------------|
| Chemical Name OSHA-PEL ACGIH-TLV | | |
| Portland cement | 5 mg/m³ (Resp.) 15 mg/m³ (Total) | 10 mg/m³ (Resp.) |
| Calcium carbonate | 5 mg/m³ (Resp.) | 2 mg/m³ (Resp.) |

Page 5 of 13



| | 15 mg/m³ (Total | |
|----------------------------|-----------------------|-------------------------|
| Natural Wollastonite | 5 mg/m³ (Total) | 10 mg/m³ (Resp.) |
| Gypsum | 5 mg/m³ (Resp.) | 0.025 mg/m ³ |
| | 15 mg/m³ (Total) | |
| Crystalline Silica, Quartz | 0.1 mg/m ³ | 0.025 mg/m ³ |
| Titanium Dioxide | 15 mg/m³ (Total) | 10 mg/m³ |

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of

dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- **i. Eye/Face Protection:** Wear approved eye [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)] protection
- ii. Skin Protection:
 - 1. Hand Protection: Wear chemical resistant gloves.
 - 2. Body Protection: Wear suitable protective clothing
- **iii. Respiratory Protection:** A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| Appearance (physical state, color, etc.): | Powder |
|---|----------------|
| Odor: | Characteristic |
| Odor Threshold: | Not available |
| pH: | 9-12 |
| Melting point/Freezing point: | Not available |
| Initial boiling point and boiling range: | Not available |
| Flash point: | Not available |
| Evaporation rate (Water=1): | Not available |
| Flammability: | Not flammable |
| Upper Flammability/Explosive Limit: | Not available |
| Lower Flammability/Explosive Limit: | Not available |
| Vapor Pressure | Not available |

Page 6 of 13



| Vapor Density: | Not available |
|---|--------------------|
| Relative Density: | 22-25 lbs/gal |
| Solubility in Water: | Moderately Soluble |
| Partition coefficient: n-octanol/water: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition Temperature: | Not available |
| Viscosity (cps): | Not available |
| VOC Content: | 0 g/L (0%) |

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5. INCOMPATIBLE MATERIALS

Acids. Aluminum. Ammonium Salts. Alkali and alkaline earth metals.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Skin Contact: Causes skin irritation. Handling can cause dry skin.

Inhalation: May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable

Page 7 of 13



crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

| Acute Toxicity | | |
|----------------------------|-----------------|-----------------------|
| Chemical Name | LC50 | LD50 |
| Portland cement | Not available | Not available |
| Calcium carbonate | Not available | Oral: > 6450 mg/kg |
| Natural Wollastonite | Not available | Not Toxic |
| Gypsum | Not available | Not available |
| Crystalline Silica, Quartz | Not available | Not Toxic |
| Titanium Dioxide | >6.82 mg/L/4hrs | Dermal: Not available |
| | - | Oral: > 5000 mg/kg |

| Chemical Name | Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)* |
|----------------------------|--|
| Portland cement | Not Listed |
| Calcium carbonate | Not Listed |
| Natural Wolastonite | Not Listed |
| Gypsum | Not Listed |
| Crystalline Silica, Quartz | N-A2, I-1, O-1, CP65 |
| Titanium Dioxide | I-2B, CP65, A-A4, O, NIOSH |

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

| SHORT-TERM | |
|-----------------------------------|---|
| Skin Corrosion/Irritation: | Causes skin irritation |
| Serious Eye Damage/Irritation: | Causes severe eye damage |
| Respiratory Sensitization: | Not available |
| Skin Sensitization: | Not available |
| STOT-Single Exposure: | May cause respiratory irritation |
| Aspiration Hazard: | Not available |
| LONG-TERM | |
| Carcinogenicity: | May cause cancer |
| Germ Cell Mutagenicity: | Not available |
| Reproductive Toxicity: | Not available |
| STOT-Repeated Exposure: | May cause damage to organs through prolonged or |
| | repeated exposure |
| Synergistic/Antagonistic Effects: | Not available |



Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

In large amounts, this substance may be potentially dangerous or hazardous to the aquatic environment. Keep from entry into sewers and waterways.

| Ecotoxicity | | |
|----------------------------|--------------------|--------------------|
| Chemical Name | EC50/NOEC-48 Hours | LC50/NOEC-96 Hours |
| Portland cement | Not available | Not available |
| Calcium carbonate | Not available | Not available |
| Natural Wollastonite | Not available | Not available |
| Gypsum | Not available | Not available |
| Crystalline Silica, Quartz | Not available | Not available |
| Titanium Dioxide | Not available | Not available |

12.2. PERSISTENCE AND DEGRADABILITY

Not available

12.3. BIOACCUMULATIVE POTENTIAL

Not available

12.4. MOBILITY IN SOIL

Not available

12.5. OTHER ADVERSE EFFECTS

Not available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not available

Section 14: TRANSPORT INFORMATION

| DOT (U.S.) | TDG (CANADA) |
|------------------------------|------------------------------|
| UN NUMBER: | UN NUMBER: |
| | |
| Not regulated | Not regulated |
| UN PROPER SHIPPING NAME: | UN PROPER SHIPPING NAME: |
| | |
| Not regulated | Not regulated |
| TRANSPORT HAZARD CLASS (ES): | TRANSPORT HAZARD CLASS (ES): |



| Not regulated | Not regulated |
|--------------------------------|--------------------------------|
| PACKING GROUP (if applicable): | PACKING GROUP (if applicable): |
| Not regulated | Not regulated |

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

Not available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

| SARA TITLE III | | | | |
|----------------------------|--------------------------------|-----------------------------|--------------------|----------------------|
| CHEMICAL NAME | SECTION 302 (EHS) TPQ (LBS) | SECTION 304 EHS RQ (LBS) | CERCLA RQ (LBS) | SECTION 313 (TRI) |
| Portland cement | Not Listed | Not Listed | Not Listed | Not Listed |
| Calcium carbonate | Not Listed | Not Listed | Not Listed | Not Listed |
| Natural Wollastonite | Not Listed | Not Listed | Not Listed | Not Listed |
| Gypsum | Not Listed | Not Listed | Not Listed | Not Listed |
| Crystalline Silica, Quartz | Not Listed | Not Listed | Not Listed | Not Listed |
| Titanium Dioxide | Not Listed | Not Listed | Not Listed | Not Listed |

15.3. US STATE RIGHT TO KNOW LAWS:

| California Proposition 65: | WARNING! This product contain chemicals known to the State of California to cause cancer (Crystalline Silica) |
|--|---|
| Other U.S. States "Right to Know" Lists: | |
| | SILICATE, PORTLAND CEMENT: CAS#65997-15-1 |
| New Jersey: | CALCIUM CARBONATE: CAS#1317-65-3 |
| | GYPSUM (CALCIUM SULFATE): VARIOUS |
| | (CAS#10101-41-4/7778-18-9/14978-04-0) |

Page 10 of 13



| Pennsylvania: | CEMENT, PORTLAND, CHEMICALS: CAS#65997-15-1 |
|----------------|---|
| - | CALCIUM CARBONATE: CAS#1317-65-3 |
| | GYPSUM (CALCIUM SULFATE): VARIOUS |
| | (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Massachusetts: | PORTLAND CEMENT: CAS#65997-15-1 |
| | CALCIUM CARBONATE: CAS#1317-65-3 |
| | GYPSUM (CALCIUM SULFATE): VARIOUS |
| | (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Minnesota: | PORTLAND CEMENT: CAS#65997-15-1 |
| | CALCIUM CARBONATE: CAS#1317-65-3 |
| | GYPSUM (CALCIUM SULFATE): VARIOUS |
| | (CAS#10101-41-4/7778-18-9/14978-04-0) |
| Florida: | Not Available |
| Michigan: | Not Available |

15.4. GLOBAL INVENTORIES


| Chemical Name | USA TSCA | Canada DSL/NDSL |
|----------------------------|----------|--------------------|
| Portland cement | Yes | DSL |
| Calcium carbonate | Yes | DSL |
| Natural Wollastonite | Yes | DSL |
| Gypsum | Yes | DSL |
| Crystalline Silica, Quartz | Yes | DSL |
| Titanium Dioxide | Yes | DSL |


Page 11 of 13



15.5. NFPA AND HMIS RATINGS

HEALTH HAZARD FLAMMABILITY HAZARD 4 EXTREME - Highly toxic - May be fatal 4 EXTREME - Extremely flammable gas 3 SERIOUS - Toxic - Full protective suit 3 SERIOUS - Flammable. and breathing apparatus should be worn. Flash Point 73°F to 100°F. 2 MODERATE - Breathing apparatus 2 MODERATE - Combustible. and face mask must be worn. equires moderate heating to ignite. Flash Point below 200°F. 1 SLIGHT - Breathing apparatus may SLIGHT - Slightly combustible. Requires strong heating to ignite. MINIMAL - No precautions MINIMAL - Will not burn under **SPECIFIC HAZARD INSTABILITY HAZARD** 4 EXTREME - Explosive at room OXIDIZER OXY temperature. 3 SERIOUS - May detonate if shocked or ACID ACID heated under confinement or mixed ALKALI ALK 2 MODERATE - Unstable. May react CORROSIVE COR Use NO WATER W 1 SLIGHT - May react if heated or mixed with water. RADIATION * MINIMAL - Normally stable. Does not react with water.





15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

| CP65 | California Proposition 65 |
|-----------|---|
| OSHA (O) | Occupational Safety and Health Administration |
| ACGIH (G) | American Conference of Governmental Industrial Hygienists |
| | A1 – Confirmed human carcinogen |
| | A2 – Suspected human carcinogen |
| | A3 – Animal carcinogen |
| | A4 – Not classifiable as a human carcinogen |
| | A5 – Not suspected a human carcinogen |
| IARC (I) | International Agency for Research on Cancer |
| | 1 – The agent (mixture) is carcinogenic to humans |
| | 2A – The agent (mixture) is probably carcinogenic to humans; there |
| | is limited evidence of carcinogenicity in humans and sufficient |
| | evidence of carcinogenicity in experimental animals. |
| | 2B – The agent (mixture) is possibly carcinogenic to humans; there |
| | is limited evidence of carcinogenicity in humans in the absence of |

Page 12 of 13



| | sufficient evidence of carcinogenicity in experimental animals. 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans. |
|---------|--|
| NTP (N) | National Toxicology Program |
| | 1 – Known to be carcinogens |
| | 2 – Reasonably anticipated to be carcinogens |

Section 16: OTHER INFORMATION

Date of Preparation: September 8, 2014

Version: 1.0

Revision Date: N/A

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by: Custom Building Products

Phone: (562)-968-2980

www.custombuildingproducts.com

End of Safety Data Sheet

Page 13 of 13