

# Shrink-Kon<sup>®</sup>

## Thin-Wall Heat-Shrinkable Tubing

T&B Catalog Number:

CHS34

UPC Number:

78621080322

Status:

Active

Description:

Thin-Wall Heat-Shrinkable Tubing for Cable Range 1 - 3/0 AWG, Expanded Dia. 3/4, Reel of 50 Feet, rated for 600V, 125 degrees C, Material: Polyvinyl Chloride, Clear

### Features

Clear shrink enables user to inspect die and crimp details after installation.

Flexible PVC tubing is suitable for industrial and electronic applications.

UL standard UL224, VW-1 Rated. CSA standard C22.2 no. 198.1 oft.

### General

Style CHS Series - Clear

Color Clear

Temperature Range -55°C - 110°C

Shrink Ratio 2:1

### Dimension Information

Length (feet) 50

Minimum Expanded I.D. (inches) 0.75

Maximum Recovered I.D. (inches) 0.38

Nominal Recovered Wall (inches) 0.04

Cable Range 1 - 3/0 AWG

### Specifications

Shrink Temperature 110°C

### Packaging

Package in Units 1

T&B Sold in UOM Each

T&B Weight Per UOM 1.18 lbs. Each

### Application Support

Specifications Available on Website

Overview Available on Website

### Notes

Standard package is reels. Order by reel, not by feet.

### Certifications

RoHS Compliance Yes

### Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)