349

3M[™] Armorcast Structural Material 4560

3MTM Armorcast Structural Material 4560 is a flexible fiberglass knit fabric strip that has been saturated with a black urethane resin syrup. The material is rolled and packed dry in a sealed foil envelope. Armorcast structural material is completely safe for use in manholes, vaults, and other hazardous environments, because no heat source is required. No flames, electric heaters or chemicals are needed. The only thing your crews will ever have to add is water.

Material Fiberglass
RoHS 2011/65/EU Yes
Agency Approvals RUS



Order No.	UPC	Color	Roll Size	Case Qty.
4560-5	051138-57719	Black	5 ft (1,52 m)	5
4560-10	051138-57717	Black	10 ft (3,05 m)	5
4560-15	051138-57718	Black	15 ft (4,57 m)	5

3M[™] Scotchcast[™] Electrical Insulating Resin 2104

3M[™] Scotchcast[™] Electrical Insulating Resin 2104 is a hard, two-part, polyurethane resin encapsulant designed specifically for permanent splice protection. Resin 2104 is formulated for virtually every electrical application requiring hard, non-reenterable resin with good handling and performance characteristics. Resin 2104 is also used as the insulating material for cable splices operating at 1000 volts or less and is rated for continuous use at 194°F (90°C) with an overload rating of 266°F (130°C). It may be stocked to cover all hard resin needs, ending the need for multiple encapsulant inventories.

Voltage 1000 Volts or less 1 Hour at 70°F (21°C)

Cure Time 20 Hours at 20°F (-4°C)

Energize Time Immediately

Max. Operating Temperature 194°F (90°C) continuous

Color Dark Green

RoHS 2011/65/EU Yes

Used in these kits 72-N; 85 Series



Order No.	UPC	Packaging Description	Weight oz (g)	Volume in³ (cm³)	Containers per Case
2104A	054007-31189	2-part pouch	3.46 (98)	5.7 (93,4)	10
2104B	054007-31382	2-part pouch	7.40 (210)	12.6 (206,4)	10
2104C	054007-31383	2-part pouch	14.82 (420)	25.4 (416,2)	10
2104D	054007-11849	2-part pouch	23.80 (675)	40.8 (668,5)	10
2104E	054007-31187	2-part pouch	10.6 (300)	19.1 (313.5)	10

PHONE: 800-245-3573 www.3M.com/Electrical