



**Rigid/IMC Conduit Fittings-Hazardous Location
T&B Catalog Number:**

UPC Number: LBY15-TB
Status: 78621068914
Description: Active

1/2 in. Hazardous location Capped Elbow, Ductile Iron

Features

Maximum volume for bends within a compact overall size.
 Screw on cover for ease of installation and removal.
 Cover opening on an angle, permitting conductors to be pulled straight through either hub and tapered threaded hubs and integral bushing for rigid threaded conduit.

Application

LBY/GYF elbows are installed in conduit systems within hazardous areas to: (1) Make 90° bends in conduit systems where space is limited; (2) Act as pull outlets; (3) Provide access to conductors for maintenance and future system changes.

General

Material: Ductile Iron

Dimension Information

Hub Size (inches)	1/2
Dimension A (inches)	2 9/16
Dimension B (inches)	2
Throat Diameter-Max (inches)	0.610
Throat Diameter-Min (inches)	0.570

Specifications

3dmodel: Available on Website

Packaging

T&B Inner Pack	10
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	116.4 lbs. per 100

Notes

Class I, Div. 1&2, Groups C, D - Explosionproof
 Class II, Div. 1, Groups E, F, G - Dust-Ignitionproof
 Class III, Div. 1&2 - Raintight
 NEMA 3, 4, 7 CD, 9 EFG - Wet Locations

Certifications

RoHS Compliance: Yes

Certifications



File Nbr:
E 193396

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com