

SIPLUS LOGO! POWER 24V 4A
 SIPLUS LOGO! POWER 24V 4 A FOR MEDIAL STRESS -40...+70
 DEGR C BASED-ON 6EP1332-1SH52 .STABILIZED POWER
 SUPPLY INPUT: AC (110-300 V DC) OUTPUT: 24 V/



Figure similar

Input	
Input	1-phase AC or DC
Rated voltage value V_{in} rated	100 ... 240 V
Voltage range AC	85 ... 264 V
Input voltage	
• at DC	110 ... 300 V
Wide-range input	Yes
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at I_{out} rated, min.	40 ms; at $V_{in} = 187$ V
Rated line frequency	50 ... 60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 120 V	1.95 A
• at rated input voltage 230 V	0.97 A
Switch-on current limiting (+25 °C), max.	30 A
I^2t , max.	2.5 A ² ·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 16 A characteristic B or from 10 A characteristic C

Output	
Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	24 V
Total tolerance, static \pm	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	1.5 %
Residual ripple peak-peak, max.	200 mV
Residual ripple peak-peak, typ.	30 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	300 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	60 mV
Adjustment range	22.2 ... 26.4 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for output voltage OK
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	0.5 s
Voltage rise, typ.	15 ms
Rated current value I_{out} rated	4 A
Current range	0 ... 4 A
• Note	+55 ... +70 °C: Derating 2%/K
Active power supplied typical	96 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency	
Efficiency at V_{out} rated, I_{out} rated, approx.	89 %
Power loss at V_{out} rated, I_{out} rated, approx.	12 W

Closed-loop control	
Dynamic mains compensation (V_{in} rated ± 15 %), max.	0.2 %
Dynamic load smoothing (I_{out} : 10/90/10 %), $U_{out} \pm$ typ.	1.5 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms

Protection and monitoring	
Output overvoltage protection	Yes, according to EN 60950-1
Current limitation, typ.	5.2 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
Enduring short circuit current RMS value	
• maximum	7.9 A
Overload/short-circuit indicator	-

Safety	
Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class II (without protective conductor)
CE mark	Yes
UL/CSA approval	No
Certificate of suitability IECEx	No
Degree of protection (EN 60529)	IP20

EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data	
Ambient temperature <ul style="list-style-type: none"> • during operation — Note • during transport • during storage 	<p>-40 ... +70 °C with natural convection</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p>
Ambient condition relating to ambient temperature - air pressure - installation altitude	T _{min} ... T _{max} at 1080 hPa ... 795 hPa (-1000 m ... +2000 m); T _{min} ... (T _{max} - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m); T _{min} ... (T _{max} - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity with condensation maximum	100 %; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Conformity with EN 60721-3-3, Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
Resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Conformity with EN 60721-3-3, Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
Resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Conformity with EN 60721-3-3, Class 3S4 incl. Sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Mechanics	
Connection technology	screw-type terminals
Connections <ul style="list-style-type: none"> • Supply input • Output • Auxiliary 	<p>L, N: 1 screw terminal each for 0.5 ... 2.5 mm² single-core/finely stranded</p> <p>+, -: 2 screw terminals each for 0.5 ... 2.5 mm²</p> <p>-</p>
Width of the enclosure	90 mm

Height of the enclosure	90 mm
Depth of the enclosure	55 mm
Weight, approx.	0.34 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)