

Product Name:	Bluelab Truncheon® Nutrient Meter V2
Product Code:	TRUNV2
UPC Code:	9421024920012
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	10 kg = 56 units / 25 kg = 135 units
Packaging Information:	
Packaged Weight:	0.28 kg / 0.617 lb
Packaged Length:	415 mm / 16.34 in
Packaged Width:	40 mm / 1.574 in
Packaged Height:	40 mm / 1.574 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

The world's favourite conductivity meter. Simply brilliant, brilliantly simple!

It is essential when growing with a hydroponic solution to KNOW what the strength of the solution is before feeding your plants AND while they are growing.

This is easy if you use the Bluelab Truncheon® Nutrient Meter! To take a reading of your solution - simply place the probe head into the solution for 1-2 minutes to reach the same temperature of your nutrient. The reading is indicated by the flashing lights. Calibration of the Meter is not required.

Meter length: 40.7cm or 16 1/32 in.

Features:

- Fully waterproof
- Auto on/off function
- No calibration required
- Daylight readable blue LED's
- Battery operated
- No buttons, switches or knobs
- Provided with EC, CF, ppm 700 and ppm 500 scales

A version is available with Canadian French-English product labelling and packaging. Product details are:

Name: Bluelab Truncheon® Nutrient Meter French-English V2

Product code: TRUNFV2

UPC Code: 9421024920142.

Images available on request.

Product Image:



Product images available for Screen or Web use:

- Bluelab-Truncheon2-R-MR-flat-RGB.jpg
- Bluelab-Truncheon2-R-WEB.jpg
- Bluelab-Truncheon2-R-Web-Sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-Truncheon2-R-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.2 – 3.6 EC, 2 – 36 CF 100 – 1800 ppm (EC x 500) 140 – 2520 ppm (EC x 700)
Resolution:	0.1 EC, 1 CF 50 ppm (EC x 500) 70 ppm (EC x 700)
Accuracy:	± 0.1 EC, ± 1 CF ± 50 ppm (1385 ppm at 500 ppm) ± 70 ppm (1939 ppm at 700 ppm)
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50°C / 32 – 122°F
Calibration:	Not required
Power Source:	3 x AA alkaline batteries
User Manual Languages Available:	English; Español; Français-Canada; Nederlands; Deutsch
Certifications:	CE and FCC

Product Guarantee:

Five year free repair or replacement guarantee.



{This Product Information Sheet is NOT intended for distribution to end users.}