


Stem kits<sup>1</sup>

**ELA US12** Signature® LE standard or emergency, Precise® LRP with TM option, Quantum®, Titan® LED




NOTES:

- 1 Stem color is brushed aluminum. Standard canopy color is brushed aluminum. To order white or black canopy, add **W** or **B** to catalog number. For other lengths, replace 12 with appropriate stem length in inches. Example: ELA US24.
- 2 See page 450 for additional wireguard information.
- 3 Supplemental emergency circuits designed for normally off operation only.


Wireguards<sup>2</sup>

**ELA WGEX** Back-mount wireguard (shown) 13 5/8"W x 13 5/8"H x 4 3/4"D  
**ELA WGEXT** Top-mount wireguard 14"W x 11"H x 6 3/4"D  
**ELA WGEXE** End-mount wireguard 15"W x 11"H x 4 3/4"D  
**ELA WGHQM** Back mount for LHQM combo 28" W x 15" H x 8" D



DC input kits<sup>3</sup>

LED Signature® Series  
**ELA LEDC6** 6V 12W kit  
**ELA LEDC12** 12V 12W kit



Exit Options and Compatibility

Family	Options													
	EL	N	SD	X2	F	FA	FI	HO	DL	TP	VR	LDC12/48	CSA	4X
LE				■ <sup>1</sup>										
LE EL N		□												
LRE				■ <sup>1</sup>										
LRE EL N		□	□											
LQM				■										
LQM EL N		□												
LHQM	□	■						■						
LRP				■ <sup>1</sup>										
LRP EL N		□												
LX										■				
LX EL N		□								■				
LV				■ <sup>1</sup>						□	□			
LV EL N		□								□	□			

□ Standard  
 ■ Option available  
 (blank) Option not available

Options

- EL** Lead-calcium battery
- N** Nickel-cadmium battery<sup>3</sup>
- SD** Self-diagnostics<sup>3,4</sup>
- X2** Lamps wired on two separate circuits<sup>5,6</sup>
- F** Flashing emergency operation<sup>3,4,6</sup>
- FA** Flashing and audible emergency operation<sup>3,4,6</sup>
- FI** Fire alarm flashing interface<sup>4,5,6</sup>
- HO** High-output battery<sup>5</sup>
- DL** UL Listed for damp locations
- TP** Tamperproof Torx-head screws
- VR** Vandal-resistant shield (polycarbonate, .1" thick)
- LDC12/48** 12-48V DC input for LED lamps<sup>2</sup>
- CSA** CSA Certified
- 4X** NEMA 4X suitable for wet-mounting applications

NOTES:

- 1 Must specify input voltage.
- 2 Supplemental emergency circuits designed for normally off operation only. CSA Certified product only.
- 3 Only available with exits containing battery.
- 4 Not available with X2 option.
- 5 Not available with flashing option.
- 6 Not available with CSA Certified product.

Exit Replacement Batteries

Family	Batteries								
	ELB 06042 lead-calcium L: 2-3/4 (70) W: 1-7/8 (48) H: 4-1/8 (102)	ELB 0607 lead-calcium L: 4 (102) W: 1-1/2 (38) H: 6 (152)	ELB 0610 lead-calcium L: 6 (152) W: 2 (51) D: 4 (102)	ELB 1P201N nickel-cadmium L: 1-5/8 (43) Dia: 3/4 (19)	ELB 4814N nickel-cadmium L: 3-1/2 (89) W: 1 (25) H: 1-3/4 (44)	ELB 0604N nickel-cadmium L: 3-7/8 (98) W: 2-3/8 (60) H: 2-3/8 (60)	ELB 0701N nickel-cadmium L: 5-1/4 (133) W: 1 (25) H: 1-3/4 (44)	ELB 1201N nickel-cadmium L: 1-5/8 (43) Dia: 3/4 (19)	ELB 1P201N2 nickel-cadmium L: 1-5/8 (43) Dia: 3/4 (19)
QM EL/X EL	■								■ <sup>9</sup>
LHQM <sup>1</sup> /LQM EL <sup>2</sup>	■								
LHQM <sup>2</sup> /HQM		■	■ <sup>7</sup>						
LX EL N				■					
LQM EL N <sup>4</sup> /LE EL N <sup>5</sup>							■		
LV EL N					■ <sup>8</sup>		■ <sup>10</sup>		
LQM ELN <sup>6</sup>								■	






■ Battery available  
 (blank) Battery not available

Not all batteries and equipment are shown. Consult factory for additional requirements. All dimensions are inches (millimeters) unless otherwise noted.

NOTES:

- 1 Series 15-16.
- 2 Series 10-12.
- 3 Series 10-14.
- 4 Series 20-23.
- 5 Series 20-21.
- 6 Series 30.
- 7 With HO option.
- 8 Single face, no options.
- 9 With N option.
- 10 Double face, no options.

## Unit Accessories/Replacement Batteries

<p><b>Vandal Shield</b> ELA VS2 ELA VS</p>  <p>1/8" thick, (ELAVS2) high-impact or 3/16" thick (ELAVS) transparent polycarbonate shield. Fits all Lithonia Quantum ELM and ELM2 (ELA VS), and ELM618, ELM627, ELM654, ELM1254, ELM1272 (ELA VS2) units. 10"H x 22" W x 9-3/4" D (ELA VS2); 8 1/2"H x 15" W x 4 3/4" D (ELA VS).</p>	<p><b>Low Voltage Relay</b> ELA LVR</p>  <p>Converts any incandescent low voltage (12V) downlight (75W maximum) to an emergency downlight when remotely from a 12V Lithonia emergency lighting unit (ELT125, etc.).</p>	<p><b>Remote Test Switch Less Pilot Light</b> ELA RTLP</p>  <p>Provides remote testing capability to all Lithonia Lighting unit equipment, exit signs, fluorescent battery packs and emergency downlights. Mounts on standard J-box, ceiling or wall.</p>
<p><b>Mounting Shelves</b> ELA MS4/8<sup>1</sup> ELM4, ELM10, ELAMST<sup>2</sup> ELT125, ELT180, ELT275 ELAMST5<sup>2</sup> ELT16, ELT24, ELT24C, ELT36, ELT36C, ELT50</p> 	<p><b>Indura® Accessories</b>  <b>ELA IND PM</b> Pendant mount kit for Indura® small housing  <b>ELA IND CM1</b> Ceiling mount kit for IND618  <b>ELA IND CM2</b> Ceiling mount kit for IND654, IND1236 and IND1254  <b>ELA IND CM3</b> Ceiling mount kit for IND6100  <b>ELA INDX CM2</b> Ceiling mount kit for INDX654, INDX1236 and INDX1254  <b>ELA IND R3</b> Prepack kit to field install third head on Indura® unit  <b>ELARTT</b> Remote transmitter  <b>ELABS</b> Banding strip  <b>ELA IND RHB</b> Remote head bracket for surface-mounted j-boxes</p> 	

### Replacement Batteries for Emergency Lighting Units

■ Available (blank) Not available

Type	ELB 06042 lead-calcium L: 2-3/4 (70) W: 1-7/8 (48) H: 4-1/8 (102)	ELB 0607 lead-calcium L: 4 (102) W: 1-1/2 (38) H: 6 (152)	ELB 0612A lead-calcium L: 6 (152) W: 2 (51) D: 4 (102)	ELB 0614 lead-calcium L: 4-1/4 (108) W: 2-3/4 (70) H: 5-1/2 (140)	ELB 1228 lead-calcium L: 7-7/8 (198) W: 5-1/4 (133) H: 7-3/8 (187)	ELB 1255 lead-calcium L: 10-1/4 (259) W: 6-3/4 (171) D: 8-3/4 (222)	ELB 0604N nickel-cadmium L: 3-7/8 (98) W: 2-3/8 (60) H: 2-3/8 (60)
ELM/ELM2	■						
ELM618		■					
ELM627			■				
ELM654			■ <sup>3</sup>				
ELM1254			■ <sup>3</sup>				
ELM1272			■ <sup>3</sup>				
ELSQ/ELSQM	■						
ELSQM N							■
ELT16		■					
ELT16 N							
ELT36/36C				■			
ELT50				■ <sup>3</sup>			
ELT125					■		
ELT275						■	
ELR2		■					
ELR2 N							■
ELR4				■ <sup>3</sup>			
ELCC/ELCCT	■						
AFN	■						

**NOTES:**

- Standard color is desert tan. To order white, add **W** to catalog number (Example: **ELA WMS4/8**).
- Standard instrument tan.
- Uses two batteries.
- Replacement batteries are for Indura® Series 12 units. Consult factory for replacement batteries for previous series.

### Indura®/Indura® 4x Replacement Batteries<sup>4</sup>

■ Available (blank) Not available

Type	ELB 0612A L: 4-1/4 (108) W: 2-3/4 (70) H: 5-1/2 (140)	ELB 0636 L: 5-7/8 (150) W: 6 (154) H: 3-5/8 (93)	ELB1224B L: 3-7/8 W: 6 (154) H: 7-3/4 (198)	ELB 1208AH L: 5-7/8 (150) W: 8 (205) H: 3-5/8 (93)	ELB 1228 L: 7-7/8 (198) W: 5-1/4 (133) H: 7-3/8 (187)	ELB1228AH L: 6-3/4 (173) W: 6-1/2 (166) H: 7-3/4 (198)	ELB 1250 L: 8-5/8 (221) W: 5-5/16 (136) H: 8-13/16 (226)	ELB 1255 L: 10-7/32 (262) W: 6-11/16 (171) H: 9-21/32 (247)	ELB 12100 L: 12 (307) W: 6-11/16 (171) H: 9-3/4 (250)	ELB 2412A L: 5-7/8 (150) W: 8 (205) H: 3-5/8 (93)	ELB0607NFH L: 6-3/4 (171) W: 1-1/3 (34) H: 3-3/4 (95)
IND618/INDX618	■										
IND654/INDX654	■										
IND6100/INDX6100	■ <sup>3</sup>										
IND1236/INDX1236		■									
IND1236ULT/INDX1236ULT											■
IND1254/INDX1254	■ <sup>3</sup>										
IND1254ULT/INDX1254ULT				■							
IND12100/INDX12100			■			■					
IND12100ULT/INDX12100ULT					■						
IND12150/INDX12150					■ <sup>3</sup>						
IND12300/INDX12300											
IND12450/INDX12450									■ <sup>3</sup>		
IND24100/INDX24100										■	
IND24450/INDX24450							■ <sup>3</sup>				