


Steel Square Boxes

4" SQUARE OUTLET BOXES AND COVERS



Applications:

- For use with conduit
- Available in red for fire alarm applications

Features:

- Ideal for exposed work applications, providing an easy method for the installation of electrical devices (switches, receptacles, fans, lights, etc.)
- Raised ground screw location in the welded boxes saves time in installation
- Available with pre-installed ground screws and pigtails for increased labor savings
- Knockouts are suitable for use without a bonding jumper in circuits above or below 250 volts
- Available in two depths for differing cubic capacity requirements
- Welded or drawn construction to match customer preference
- Extensive cover offering to meet various customer applications and needs

Certifications and Compliances:

- UL Listed

CP

4" SQUARE OUTLET BOXES – 18.0 CUBIC INCH CAPACITY

1¼" DEEP – FOR CONDUIT

UL LISTED



TP408

KNOCKOUTS

Cat. #	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP408	—	Drawn	12 – ½"	5 – ½"	50	61

Steel Square Boxes

4" SQUARE OUTLET BOXES – 22.0 CUBIC INCH CAPACITY (WELDED)† 21.0 CUBIC INCH CAPACITY (DRAWN)


1½" DEEP – FOR CONDUIT

UL LISTED

CP



TP404/TP404PF




TP404SSB



TP404MSB



TP404RED



TP423



TP469



TP830*



TP405



TP412
TP839*




TP410




TP414RED



TP414



TP418



TP423RED



TP40SPF

KNOCKOUTS

Cat. #	Metal Stud Sizes	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP40SMSB	—	MSB	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	102
TP40SMSBPF†	—	MSB	Welded/Open Back	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	102
TP40SPF‡	—	—	Welded/Open Back	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	104
TP404**	—	—	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	50	72
TP404MSB	—	MSB	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	83
TP404RED	—	—	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	50	72
TP404REDMSB	—	MSB	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	83
TP404PF†**	—	—	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	50	72
TP404SSB	—	SSB	Welded	8 – ½", 4 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	50	83
TP425**	All	"VP"	Welded	6 – ½", 3 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	82
TP423**	All	"VMS"	Welded	6 – ½", 3 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	81
TP423RED	All	"VMS"	Welded	6 – ½", 3 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	81
TP405	—	—	Drawn	4 – ½", 6 – ½" & ¾" C	3 – ½", 2 – ¾"	50	67
TP405MSB	—	MSB	Drawn	4 – ½", 6 – ½" & ¾" C	3 – ½", 2 – ¾"	25	78
TP410	—	—	Drawn	12 – ½"	5 – ½"	50	67
TP410MSB	—	MSB	Drawn	12 – ½"	5 – ½"	50	67
TP412	—	—	Drawn	8 – ¾"	3 – ½", 2 – ¾"	50	67
TP412MSB	—	MSB	Drawn	8 – ¾"	3 – ½", 2 – ¾"	25	78
TP414	—	—	Drawn	8 – ½", 4 – ¾"	3 – ½", 2 – ¾"	50	67
TP414MSB	—	MSB	Drawn	8 – ½", 4 – ¾"	3 – ½", 2 – ¾"	25	78
TP414RED	—	—	Drawn	8 – ½", 4 – ¾"	3 – ½", 2 – ¾"	50	67
TP414REDMSB	—	MSB	Drawn	8 – ½", 4 – ¾"	3 – ½", 2 – ¾"	25	83
TP418	—	"F", Set Flush	Welded	6 – ½", 3 – ½" + ¾" E	2 – ½", 2 – ½" + ¾" E	25	84
TP467	—	—	Welded	8 – ¾"	2 – ½", 2 – ½" + ¾" E	50	72
TP467MSB	—	MSB	Welded	8 – ¾"	2 – ½", 2 – ½" + ¾" E	25	78
TP469	ALL	"VMS"	Welded	6 – ¾"	2 – ½", 2 – ½" + ¾" E	25	81
Air Plenum							
TP830*	—	—	Drawn	8 – ½", 4 – ¾"	3 – ½", 2 – ¾"	50	72
TP839*	—	—	Drawn	8 – ¾" C	3 – ½", 2 – ¾"	50	72

*For Air Plenum (No Mounting Holes) - Not UL Listed

**cUL Listed

†All welded 4" square outlet boxes have a raised dimple for ground screw

‡TP404PF includes ground screw with pigtail lead

§TP40SPF supplied with factory installed pigtail leads and TP472 flat back cover


Crouse-Hinds
by **E.T.N.**

Steel Square Boxes


4" SQUARE OUTLET BOXES – 22.0 CUBIC INCH CAPACITY

1½" DEEP
FOR NONMETALLIC CABLE – CLAMPS IN EACH END


UL LISTED



TP444



TP444MSB



TP449



TP446

CP


KNOCKOUTS

Cat. #	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP444	—	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	50	77
TP444MSB	MSB	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	25	81
TP444SSB	SSB	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	50	88
TP446	"F", Set Flush	Welded	4 – Cable, 2 – ½", 1 – ½" & ¾" E	1 – ½"	25	88
TP449	"VMS"	Welded	4 – Cable, 2 – ½", 1 – ½" & ¾" E	1 – ½"	25	85


4" SQUARE OUTLET BOXES – 22.0 CUBIC INCH CAPACITY

1½" DEEP
FOR ARMORED & METAL CLAD (MCI) CABLE – CLAMPS IN EACH END


UL LISTED




TP454



TP454MSB



TP456



TP459

KNOCKOUTS

Cat. #	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP459	"VMS"	Welded	4 – Cable, 2 – ½", 1 – ½" & ¾" E	1 – ½"	25	89
TP454*	—	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	50	81
TP454MSB	MSB	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	25	91
TP454PF†	—	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	50	81
TP454SSB*	SSB	Welded	4 – Cable, 4 – ½", 2 – ½" & ¾" E	1 – ½"	25	82
TP456*	"F", Set Flush	Welded	4 – Cable, 2 – ½", 1 – ½" & ¾" E	1 – ½"	25	92
TP456PF†	"F", Set Flush	Welded	4 – Cable, 2 – ½", 1 – ½" & ¾" E	1 – ½"	25	92

†TP catalog numbers ending in PF includes ground screw with pigtail lead

*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.

Steel Square Boxes

4" SQUARE OUTLET BOXES – 30.3 CUBIC INCH CAPACITY


2 1/8" DEEP WITH CONDUIT KOs

UL LISTED


CP




TP403/TP403PF



TP403SSB




TP403MSB



TP40DPF



TP432



TP432VMS



TP434




TP438
TP831*




TP403RED



TP434RED



TP451RED



TP451

KNOCKOUTS

Cat. #	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP40DMSB	MSB	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	91
TP40DMSBPF	MSB	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	112
TP40DPF§	—	Welded/Open Back	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	92
TP403**	—	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	84
TP403MSB	MSB	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	95
TP403RED	—	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	84
TP403REDMSB	MSB	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	95
TP403PF†**	—	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	84
TP403SSB	SSB	Welded	8 - 1/2", 4 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	95
TP432**	—	Welded	8 - 3/4"	2 - 1/2", 2 - 1/2" & 3/4" E	25	84
TP432MSB	MSB	Welded	8 - 3/4"	2 - 1/2", 2 - 1/2" & 3/4" E	25	95
TP432REDMSB	MSB	Welded	8 - 3/4"	2 - 1/2", 2 - 1/2" & 3/4" E	25	95
TP432VMS	"VMS"	Welded	6 - 3/4"	2 - 1/2", 2 - 1/2" & 3/4" E	25	99
TP436	—	Welded	8 - 1"	2 - 1/2", 2 - 1/2" & 3/4" E	25	84
TP436MSB	MSB	Welded	8 - 1"	2 - 1/2", 2 - 1/2" & 3/4" E	25	95
TP434	—	Drawn	8 - 1/2", 4 - 3/4"	3 - 1/2", 2 - 3/4"	25	84
TP434MSB	MSB	Drawn	8 - 1/2", 4 - 3/4"	3 - 1/2", 2 - 3/4"	25	95
TP434RED	—	Drawn	8 - 1/2", 4 - 3/4"	3 - 1/2", 2 - 3/4"	25	84
TP434REDMSB	MSB	Drawn	8 - 1/2", 4 - 3/4"	3 - 1/2", 2 - 3/4"	25	95
TP438	—	Drawn	4 - 1/2", 6 - 1/2" & 3/4" C	3 - 1/2", 2 - 3/4"	25	84
TP438MSB	MSB	Drawn	4 - 1/2", 6 - 1/2" & 3/4" C	3 - 1/2", 2 - 3/4"	25	95
TP438PF†	—	Drawn	4 - 1/2", 6 - 1/2" & 3/4" C	3 - 1/2", 2 - 3/4"	25	84
TP451	"VMS"	Welded	6 - 1/2", 3 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	96
TP451PF†	"VMS"	Welded	6 - 1/2", 3 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	96
TP451RED	"VMS"	Welded	6 - 1/2", 3 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	96
TP437	"VMS"	Welded	6 - 1/2", 3 - 1/2" & 3/4" E	2 - 1/2", 2 - 1/2" & 3/4" E	25	98
Air Plenum						
TP831*	—	Drawn	8 - 1/2", 4 - 3/4"	3 - 1/2", 2 - 3/4"	25	90

*For Air Plenum (No Mounting Holes) - Not UL Listed

†TP catalog numbers ending in PF includes ground screw with pigtail lead

**cUL Listed


§TP40DPF supplied with factory installed pigtail leads and TP472 flat back cover

Crouse-Hinds
by **E.T.N**


Steel Square Boxes

4" SQUARE OUTLET BOXES – 30.3 CUBIC INCH CAPACITY 2 1/8" DEEP


FOR NONMETALLIC CABLE – CLAMPS IN EACH END
UL LISTED




TP450



TP450MSB



TP450SSB




TP452

KNOCKOUTS


Cat. #	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP450	—	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	90
TP450MSB	MSB	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	101
TP450SSB	SSB	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	101
TP452	"VMS"	Welded	4 – Cable, 2 – 1/2", 1 – 1/2" & 3/4" E	1 – 1/2"	25	104

4" SQUARE OUTLET BOXES – 30.3 CUBIC INCH CAPACITY 2 1/8" DEEP


FOR ARMORED & METAL CLAD (MCI) CABLE – CLAMPS IN EACH END
UL LISTED



TP431



TP431MSB



TP440

KNOCKOUTS

Cat. #	Metal Stud Sizes	Bracket	Description	Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
TP431*	—	—	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	91
TP431PF†	—	—	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	91
TP431MSB	—	MSB	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	91
TP431SSB*	—	SSB	Welded	4 – Cable, 4 – 1/2", 2 – 1/2" & 3/4" E	1 – 1/2"	25	102
TP440*	All	"VMS"	Welded	4 – Cable, 2 – 1/2", 1 – 1/2" & 3/4" E	1 – 1/2"	25	103

†TP catalog numbers ending in PF includes ground screw with pigtail lead

*UL approved for use with aluminum interlocking grounding metal clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.

Steel Square Boxes & Covers


4" SQUARE TWO-DEVICE BOXES – 30.3 CUBIC INCH CAPACITY

2 1/8" DEEP

UL LISTED



TP391



TP395

KNOCKOUTS

Cat. #	Bracket	Description	Sides	Bottom	Std. Unit Pkg.	Wt. Lbs. Per 100
TP391	"VS", Set 7/8"	Drawn	6 – 1/2", 3 – 3/4"	3 – 1/2", 2 – 3/4"	25	95
TP395	—	Drawn	8 – 1/2", 4 – 3/4"	3 – 1/2", 2 – 3/4"	25	84

4" SQUARE EXTENSION RINGS


1 1/2" DEEP WITH CONDUIT KNOCKOUTS – 21.0 CUBIC INCH CAPACITY

2 1/8" DEEP WITH CONDUIT KNOCKOUTS – 30.3 CUBIC INCH CAPACITY

UL LISTED



TP424



TP422†



TP426



TP428RED



TP443 (2 1/8" Deep)



TP428, TP833*

Cat. #	KNOCKOUTS Sides	Bottom	Unit Qty.	Wt. Lbs. Per 100
1 1/2" DEEP				
TP424	12 – 1/2"	—	50	46
TP422	8 – 1/2", 4 – 1/2" + 3/4" E	—	50	50
TP426	8 – 3/4"	—	50	46
TP428	8 – 1/2", 4 – 3/4"	—	50	46
TP428RED	8 – 1/2", 4 – 3/4"	—	50	46
TP833*	8 – 1/2", 4 – 3/4"	—	50	48
2 1/8" DEEP				
TP443	8 – 1/2", 4 – 3/4"	—	25	66
TP465	8 – 1"	—	25	60

*For Air Plenum (No Mounting Holes). Requires the use of TP854, purchase separately - Not UL Listed

†For use as extension with switch box, not four square box

FLEXIBLE FIXTURE HANGERS

Eaton's Crouse-Hinds TPSFH square flexible fixture hangers are used in commercial or light industrial applications where HID high bay and low bay lighting fixtures are used. Specific applications include storage facilities, shipping warehouses, retail and DIY facilities.

Features and Benefits:

- Suitable for use with 1/2" or 3/4" fixture conduit stems these hangers allow the conduit stem of the fixture (luminaire) to swing in any direction. Maximum swing angle is 26° from vertical max slope angles 22 1/2°
- Available for attachment to 4" square steel boxes.
- Quickly and easily attached by two screws.
- Hangers are drilled and tapped for use with 3/4" conduit stem as standard and come supplied with a 3/4" – 1/2" reducer for 1/2" conduit stem applications.

Certifications and Compliances:

- UL Listed – UL 1598
- CSA C22.2 No. 250
- Suitable for Damp Locations

Standard Materials and Finishes:

- Material: Sheet Steel
- Finish: Zinc Chromate for corrosion resistance



Description	Support Wt. (lbs)	Cat. #
For use with 4" Square boxes	50	TPSFH12

Crouse-Hinds
by **E.T.N**