



**PS/2-USB KVM Switch  
CS82U / CS84U**

**User Manual**



## Specifications

Function			CS82U	CS84U
Computer Connections			2	4
Port Selection			Front Panel Pushbuttons; Hotkey, USB Mouse	
Connectors	Console Ports	Keyboard	1 x USB Type A Female (Black), 1 x 6-pin Mini-DIN Female (Purple)	
		Video	1 x HDB-15 Female (Blue)	
		Mouse	1 x USB Type A Female (Black), 1 x 6-pin Mini-DIN Female (Green)	
	KVM Ports		2 x SPHD-18 Female (Yellow)	4 x SPHD-18 Female (Yellow)
	Power (Optional)		1 x DC Jack	1 x DC Jack
Switches	Selected		2 x Pushbutton	4 x Pushbutton
LEDs	On Line		2 (Orange)	4 (Orange)
	Selected		2 (Green)	4 (Green)
Emulation	Keyboard / Mouse		USB	
Video			2048 x 1536 @ 60 Hz; DDC2B	
Scan Interval			3, 5, 10, 20 secs. (5 secs. default)	
Power Consumption			DC 5V, 1.1 W	DC 5V, 1.2 W
Environment	Operating Temp.		0–50°C	
	Storage Temp.		-20–60°C	
	Humidity		0–80% RH, Non-condensing	
Physical Properties	Housing		Metal	
	Weight		0.54 kg	0.77 kg
	Dimensions (L x W x H)		14.00 x 8.70 x 5.50 cm	21.00 x 8.70 x 5.50 cm