


Type: _____
Project Name: _____
Notes: _____


Sample **CEAK** **S** **8** **4G** **OT** **GFI-IU** **BBT**
Ordering _____ / _____ / _____ / _____ / _____ / _____ / _____
A **B** **C** **D** **E** **F** **G**

DETAILS




Bolt Circle

9 1/2" bolt circle



Perspective



- 8
- 7
- 6
- 5
- 4
- 3
- 2
- 1

available EPA index

AASHTO 2001 wind zones (mph)

| catalog # | wall thickness | nominal height | AASHTO 2001 wind zones (mph) | | | | | | |
|--------------|----------------|----------------|------------------------------|-----|-----|-----|-----|-----|-----|
| | | | 90 | 100 | 110 | 120 | 130 | 140 | 150 |
| CEAK/S/10/4G | .125" | 10' | 7.3 | 5.5 | 4.3 | 3.3 | 2.8 | 2.3 | 1.9 |
| CEAK/S/12/4G | .125" | 12' | 5.5 | 4.0 | 3.0 | 2.2 | 1.8 | 1.4 | 1.2 |
| CEAK/S/14/4M | .188" | 14' | 6.6 | 5.0 | 3.7 | 2.9 | 2.3 | 1.9 | 1.6 |
| CEAK/S/14/4P | .226" | 14' | 7.4 | 5.6 | 4.3 | 3.3 | 2.7 | 2.3 | 1.9 |
| CEAK/S/16/4M | .188" | 16' | 5.1 | 3.6 | 2.6 | 1.8 | 1.5 | 1.1 | 0.9 |
| CEAK/S/16/4P | .226" | 16' | 5.8 | 4.2 | 3.1 | 1.2 | 0.0 | 0.0 | 0.0 |
| CEAK/S/18/4P | .226" | 18' | 4.3 | 3.0 | 2.0 | 1.3 | 1.0 | 0.7 | 0.5 |
| CEAK/F/10/4G | .125" | 10' | 6.3 | 4.8 | 3.6 | 2.7 | 2.0 | 1.5 | 1.0 |
| CEAK/F/12/4M | .188" | 12' | 6.5 | 4.9 | 3.7 | 2.8 | 2.0 | 1.6 | 1.1 |
| CEAK/F/14/4M | .188" | 14' | 4.9 | 3.5 | 2.5 | 1.7 | 1.1 | 0.7 | 0.3 |
| CEAK/F/16/4M | .188" | 16' | 3.5 | 2.3 | 1.5 | 0.8 | 0.3 | 0.0 | 0.0 |

CAUTION: Consult factory for structural approval prior to ordering poles. Warranty void if pole is cut, welded, drilled or otherwise modified outside Beacon factory.

A. MODEL

CEAK Centennial AK

B. PROFILE

S smooth
F fluted

C. HEIGHT

6 6'
8 8'
10 10'
12 12'

OTHER _____

D. SHAFT

4G Ø4", .125" wall thickness (S) (F)
4M Ø4", .188" wall thickness (S) (F)
4P Ø4", .226" wall thickness (S)

E. POLE TOP

OT open top
ARC acorn finial
BAL ball finial
TN tenon
OTHER _____

F. OPTIONS

GFI-IU 20AMP GFCI receptacle
OTHER _____

G. COLOR

BBT basic black textured
BMT black matte textured
WHT white textured
MBT metallic bronze textured
BZT bronze textured
DBT dark bronze textured
GYS gray smooth
DPS dark platinum smooth
GNT green textured
MST metallic silver textured
MTT metallic titanium textured
OWI old world iron
RAL _____

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Construction: All cast aluminum parts shall be low copper alloy A356. All extruded aluminum parts shall be alloy 6061-T6, 6063-T5 or equal. Standard fluted shaft profile shall be 16-flat flutes for 3"OD and 12-flat flutes for 4", 5", & 6"OD.

Base Covers: require specification of smooth or fluted shafts of the size required to meet wind load requirements

Vibration Dampeners: Vibration dampener pads shall be provided when required by customer or deemed necessary by Beacon Products. Please consult factory for bridge mounted applications.

EPA (effective projected area): EPA is defined as (projected surface area X drag factor) and measured in ft2. Allowable post, luminaire arm, luminaire and accessory EPAs are derived from the most current published AASHTO (American Association of State Highway and Transportation Officials) standard, currently AASHTO 2001 (50yr design life). Customer assumes all responsibility for selecting the appropriate post for installation (consult factory for assistance). Luminaire arm, luminaire and accessory EPA must be equal to or less than allowable EPA of post. Consult a professional engineer for compliance with local codes and standards.

Anchor Bolt: Anchor bolts, sized as required, double hex nuts and flat washers shall be hot dipped galvanized steel. A bolt circle template shall be provided for installation.

Fasteners: All fasteners shall be Corrosion Resistant. When tamper resistant fasteners are required, spanner HD (snake eye) style shall be provided (special tool required, available at additional cost).

Finish: Finish shall be a Beacote V polyester powder-coat electrostatically applied and thermocured. Beacote V finish shall consist of a five stage iron phosphate chemical pretreatment regimen with a polymer primer sealer, oven dry off, and top coated with a thermoset super TGIC polyester powder coat finish. The finish shall meet the AAMA 605.2 performance specification which includes passing a 3000 hour salt spray test for corrosion resistance and resists cracking or loss of adhesion per ASTM D522 and resists surface impacts of up to 160 inch-pound.

Limited Warranty: Beacon Products warrants its products, to the original purchaser, against defects in materials and workmanship for proper usage for a period of 5 years after date of production, when properly installed, maintained and appropriately specified. See Warranty Information on www.beaconproducts.com for complete details and exclusions.