F640/F644
SERIES
STEPLIGHTS

Cat. #		Approvals
Job	Туре	



SPECIFICATIONS

- Rugged Devine Design housing. F640 is cast aluminum with optional cast bronze housing. F644 has a fabricated aluminum housing with protective powder paint finish. Both concrete pour or drywall versions available. Wiring hubs are 3/4".
- · Cast aluminum or optional cast bronze louvered faces with tempered clear glass lens. Provided with stainless steel allenhead screw closure.
- Formed aluminum reflectors for maximum light output through louvered faces.
- Low wattage incandescent, compact fluorescent, and 50 or 70 watt HPS on F644.
- Standard finishes are dark bronze, black, white and platinum.
- Units are designed for use in wet locations.



	A	В	Depth
F640	53/4"	103/8"	31/8"
	146 mm	264 mm	79 mm
F644	85/8"	85/8"	71/4"
	219 mm	219 mm	184 mm

Note: Rough-in for drywall installation: F640 = 4 5/8" x 9 3/8" x 3 5/8" F644 = 8" dia. x 7 1/4"

ORDERING INFORMATION

ORDERING EXAMPLE: F644-50HPS-120-DB-DW



SERIES

F640	F640 Series Vertical	
F644	F644 Series Round	

WATTAGE/SOURCE

PL7	G23 Base Magnetic
PL9	G23 Base Magnetic
60INC	60W Incandescent Medium Base
	F644
50HPS	50W HPS Medium Base
70HPS	70W HPS Medium Base
60INC	60W Incandescent Medium Base
PLC13	GX23-2 Base Mag.

VOLTAGE 120

120	1200	
277	277V	
347	347V	
EINICU		

, ,,,,,,,,	
DB	Dark Bronze
BLK	Black
WHT	White
SAL	Platinum

OPTIONS

DW 1	Drywall
CP1	Concrete Pour
BZ	Cast Bronze Face
BZ1	All Cast Bronze Fixture
JBTW	Junction Box Through Wire
F	Fusing
LP	Lamp Included

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



¹ Must select drywall or concrete pour.