

LED VAPORTITE SERIES – HAZARDOUS LOCATION

COMPONENT CATALOG NUMBERS

CATALOG NUMBER	DESCRIPTION
VP1	Pendent Mount 1/2" Hub
VP2	Pendent Mount 3/4" Hub
VX1 & VAP	Ceiling Outlet Box and Adapter Plate, Hub
VX2 & VAP	
VAP	Ceiling Plate Adapter Only
VW1 & VX1	Wall Arm Outlet Box, 1/2" Hub
VW1 & VX2	Wall Arm Outlet Box, 3/4" Hub
VW1	Wall Arm Mount Only
VD-4	Stanchion Mount, 1 1/4" Hub
VH8LU15	Small LED Body
VL15LG	Frosted Glass Globe
VCG-15 ¹	Cast Aluminum Guard
VRSD-15	White Poly-Pro Guard



BASE MODEL	INPUT WATTS	NUMBER OF LEDS	DRIVE MA	COLOR TEMP	TEMP CODE
V8LU15	20WATTS	8 LEDS	700MA	5000K	T5


1. Not for use with flat acrylic lens.

PHOTOMETRIC REPORT

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%FIXT
0-30	320	29.8
0-40	523	48.8
0-60	886	82.6
0-90	1073	100.00
90-180	0	0.0
0-180	1073	100.0

REPORT NUMBER: 3676



COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

EFFECTIVE FLOOR CAVITY REFLECTANCE 0.20

RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	102	102	102	100
1	109	105	101	97	107	107	107	107	98	95	93	95	92	90	91	89	87	87	87	87	85
2	100	92	86	80	97	90	84	79	87	82	77	83	79	76	80	77	74	74	74	74	72
3	91	81	73	67	89	80	72	67	77	71	65	74	69	64	72	67	63	63	63	63	61
4	84	72	64	57	82	71	63	57	69	62	56	66	60	55	64	59	55	55	55	55	53
5	77	65	56	50	75	64	55	49	62	54	49	60	53	48	58	52	48	48	48	48	46
6	71	58	50	43	70	58	49	43	56	48	43	54	48	43	53	47	42	42	42	42	40
7	66	53	45	39	65	52	44	38	49	43	38	48	42	38	48	42	38	38	38	38	36
8	62	49	40	34	60	48	40	34	47	39	34	45	39	34	44	38	34	34	34	34	32
9	58	45	37	31	56	44	36	31	43	36	31	42	35	31	41	35	31	31	31	31	29
10	54	41	33	28	53	41	33	28	40	33	28	39	32	28	38	32	28	28	28	28	26

ALL CANDELA, LUMENS, LUMINANCE, AND VCP VALUES IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.