

LIGHTWATT2 HAZARDOUS LOCATION



HUBBELL
Industrial Lighting

[LINK TO PRODUCT PAGE](#)

| | | |
|-------|------|-----------|
| CAT.# | | APPROVALS |
| JOB | TYPE | |

SPECIFICATIONS

Applications -

For special environments like damp, wet, heavy dust, heavy vibration or Class I, Division 2/Zone 2 listed areas. For hazardous locations and demanding areas such as power plants, chemical, petrochemical and tank farms. Ideal for demanding dusttight and hosedown applications such as papermills and cement plants.

Specifications -

- 2:1 lamp-to-ambient light ratio
- Minimum of 2 lamp applications, efficiency and cost
- Protection of IP65
- Available in HID and fluorescent lamp fixtures
- Luminaires shipped with lamps installed for ease of installation
- Enclosed and gasketed ceiling thru wire mounting available in HID and fluorescent light sources
- Choice of mogul base HPS and triple tube fluorescent
- External hardware - Hubbell Guard®

Listings -

- Class 1, Division 2: Groups A, B, C, D/Class 1, Zone 2, Group IIC, IIB and IIA
- UL 844 hazardous and 1570/1572 wet location listed/CSA C 22.2 No. 137-M1981
- IP Suitability: IP65 and gasketed luminaire is available in HID and fluorescent light sources



DISCONTINUED



ORDERING INFORMATION


| Ceiling Mount | | Watt-Lamp | Volts | Reflector | Finish |
|---------------|----------------|-----------|-------|-----------|--------|
| LW2C15S8AWH | LW2C-15S8-A-WH | 150S | 8 | A | WH |
| LW2C84F1AWH | LW2C-84F1-A-WH | 84F | 1 | | |

ACCESSORY

(order as separate part #)

LW-G Steel Wire Guard

DIMENSIONS



| A | B |
|--------|--------|
| 14¼" | 14¾" |
| 362 mm | 375 mm |



Due to our continued efforts to improve our products, specifications are subject to change without notice. Copyright © 2015 Hubbell Lighting. All Rights Reserved.

For more information visit our web site: <http://www.hubbellindustrial.com/>
Phone: 1-864-678-1000

