



SAFETY DATA SHEET
PVC SOLVENT CLEANER

Page 1
Issued: 13/5/10
Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name: PVC SOLVENT CLEANER
Product code: PVCS1
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP: Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes and respiratory system. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This mixture meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: WHITE SPIRITS, NAPHTHA (PETROLEUM) 50-70%

- 4-METHYLPENTAN-2-ONE 10-30%

EINECS: 203-550-1 CAS: 108-10-1

[F] R11; [Xn] R20; [Xi] R36/37; [-] R66

CLP Class: Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335

- 2-BUTOXYETHANOL 10-30%

EINECS: 203-905-0 CAS: 111-76-2

[Xn] R20/21/22; [Xi] R36/38

CLP Class: Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315

[cont...]

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: WHITE SPIRITS, NAPHTHA (PETROLEUM)

UK - 8 hour TWA: 600mg/m³

- 4-METHYLPENTAN-2-ONE

UK - 8 hour TWA: 208 mg/m³

UK - 15 min. STEL: 416 mg/m³

- 2-BUTOXYETHANOL

UK - 8 hour TWA: 25 ppm

UK - 15 min. STEL: 50 ppm

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Sweet-smelling

Viscosity: Non-viscous

Boiling point/range°C: 115

Flash point°C: -18

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes and respiratory system. May cause lung damage if swallowed.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

SAFETY DATA SHEET
PVC SOLVENT CLEANER

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1993

ADR Class: 3

Packing group: II

Classification code: F1

Shipping name: FLAMMABLE LIQUID, N.O.S.

Labelling: 3+EHS

Hazard ID no: 33



IMDG / IMO

UN no: 1993

Class: 3

Packing group: II

EmS: 3-07/

Marine pollutant: .

Labelling: 3+EHS

IATA / ICAO

UN no: 1993

Class: 3

Packing group: II

Packing instructions: 305(P&CA); 307(PAO)

Labelling: 3+EHS

15. REGULATORY INFORMATION (CHIP)

Hazard symbols: Highly flammable.
Dangerous for the environment.
Harmful.



SAFETY DATA SHEET

PVC SOLVENT CLEANER

Risk phrases: R11: Highly flammable.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36/37: Irritating to eyes and respiratory system.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.
S16: Keep away from sources of ignition - No smoking.
S29: Do not empty into drains.
S36/37: Wear suitable protective clothing and gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Haz. ingredients (label): WHITE SPIRITS, NAPHTHA (PETROLEUM); 4-METHYLPENTAN-2-ONE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

15. REGULATORY INFORMATION (CLP)**16. OTHER INFORMATION**

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.
* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R10: Flammable.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R11: Highly flammable.
R20: Harmful by inhalation.
R36/37: Irritating to eyes and respiratory system.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.