



Type:
Project Name:
Notes:

Sample AS-6-SIN-CB DTP 3MTC BBT
Ordering / / /
A B C D


AS-6X12-CB




AS-6X12-CB




AS-6X12-CB




AS-12X18H-CB



AS-12X18H-CB



AS-12X18H-CB



A. MODEL-RECTANGLE SIGNS

- AS-6X12-CB** 6"H x 12"W
- AS-12X18H-CB** 18"H x 12"W
- AS-12X18-CB** 24"H x 18"W
- AS-24-SIN-CB** 30"H x 24"W
- AS-24X30-CB** 12"H x 36"W
- AS-24X12-CB** 12"H x 36"W

B. STYLE OPTIONS

- DTP** decorative top plate
- DBP** decorative bottom plate
- CLP** chamfered logo plate

C. MOUNTING

- BO** bolt-on
- 3MTC** 3" post mounting collar
- 4MTC** 4" post mounting collar
- 5MTC** 5" post mounting collar
- 6MTC** 6" post mounting collar

D. COLOR

- BBT** basic black textured
- BMT** black matte textured
- WHT** white textured
- MBT** metallic bronze textured
- BZT** bronze textured
- DBT** dark bronze textured
- GYS** gray smooth
- DPS** dark platinum smooth
- GNT** green textured
- MST** metallic silver textured
- MTT** metallic titanium textured
- OWI** old world iron
- RAL** _____

Construction: All cast aluminum parts shall be low copper alloy A356. All extruded aluminum parts shall be alloy 6061-T6, 6063-T5 or equal.

Fasteners: All fasteners shall be Corrosion Resistant. When tamper resistant fasteners are required, spanner HD (snake eye) style shall be provided (special tool required, available at additional cost).

Finish: Finish shall be a Beacote V polyester powder-coat electro-statically applied and thermocured. Beacote V finish shall consist of a five stage iron phosphate chemical pretreatment regimen with a polymer primer sealer, oven dry off, and top coated with a thermoset super TGIC polyester powder coat finish. The finish shall meet the AAMA 605.2 performance specification which includes passing a 3000 hour salt spray test for corrosion resistance and resists cracking or loss of adhesion per ASTM D522 and resists surface impacts of up to 160 inch-pound.

Limited Warranty: Beacon Products warrants its products, to the original purchaser, against defects in materials and workmanship for proper usage for a period of 5 years after date of production, when properly installed, maintained and appropriately specified. See Warranty Information on www.beaconproducts.com for complete details and exclusions.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.