

VENT FREE FLARE VF-FF-70-H

FLARE FRONT MODERN OUTDOOR FIREPLACE

SUBJECT	DETAILS		
Type of Gas	Natural Gas (NG) or Liquid Propane (LP)		
Firebox Construction	Stainless Steel		
Safety Standard	CSA	ANSI Z21.97-2014/CSA2.41-2014	
Operation	Honeywell Electronic Ignition		
Electrical Requirements	110 volts, 15 amps, GFI Protected, (Dedicated Breaker Recommended)		
Fireplace Opening Heights	N/A	24"	
RGB-LED System	Multi-Colored Interior RGB-LED Lighting System		
Burners	Stainless Steel Burner		
Weight	IN CRATE (LB)	NO CRATE (LB)	
	240	170	
Interior Media Options	FIRE GLASS 1/2" & 1/4"	<i>1/4" Reflective Silver</i>	<i>1/2" Clear Fireglass</i>
		<i>1/4" Reflective Bronze</i>	<i>1/2" Black Fireglass</i>
		<i>1/4" Reflective Ice</i>	<i>1/2" Gold Fireglass</i>
	FIRE BEADS	<i>Ice Fire Beads</i>	<i>Amber Fire Beads</i>
		<i>Black Fire Beads</i>	<i>Blue Fire Beads</i>
		<i>Green Fire Beads</i>	Link To All Media Options
	ZIRCON DIAMONDS	<i>Black Diamonds</i>	
		<i>Ruby Red Diamonds</i>	
		<i>Rain Drop Diamonds</i>	

Vent Free Product Specifications

The fireplace has been certified for use with either Natural Gas (NG) or Propane (LP).

0

All Vent Free Flare Fireplaces operate with a Honeywell commercial gas valve. For outdoor installation only, they must be installed maintaining required clearances to combustibles. Refer to [Installation Manual](#) for clearance distances.

The Fireplace must be installed according to Flare Fireplaces requirements as presented in Installation Manual, as well as complying with all local codes that exist. If no codes exist, then the current CSA installation code must be followed.

Gas Pressure & Power Output

MODELS	GAS	INLET PRESSURES		MANIFOLD PRESSURES		HEAT OUTPUT	ORIFICE SIZE		BURNER SIZE	
		MIN.	MAX.	MIN.	MAX.	MAX.	Burner 1	Burner 2	Burner 1	Burner 2
VF-FF-70-H	(NG)	7.0" WC	8.0" WC	2.7 WC	3.2 WC	86,000	1000	1000	30.5	30.5
VF-FF-70-H	(LP)	10.0" WC	13.0" WC	6.3 WC	6.7 WC	80,000	260	260		

Parts Included

- Flare Fireplace
- Wind Guard Glass Panel(s)
- One Choice from Our Classic Media Selection to Fill Up Your Fireplace
- Spark/Pilot/Thermal Coupling Unit
- Spare Parts Kit
- Mounting Brackets
- AC Power Supply
- FREE SHIPPING (US ONLY)

Optional Features

- Remote
- Timer
- Black Reflective Black

CSA FILE NUMBER: