



Coupling design is simple, long established and easy to clean. (AO and/or HUDSON)

Excellent cleanability - Nitinol (Nickel-Titanium) alloy allows for a smooth cannulated shaft that provides the required flexibility and minimises the cleaning problems associated with coil-cut or spring shaft designs.

Small shaft diameters allow debris to be removed and transported up to the open proximal end of the medullary canal.

Deep cutting flutes allow debris to be moved proximally away from the reamer head, maintaining cutting edge efficiency.

Ellipsoidal head shape allows the cutting edge to remove bone gradually and transport debris away, while bone chipping design decreases the size of debris, reducing canal pressure.

Reverse cutting feature minimises the potential for the reamer to catch in the medullary canal.

This material is intended for health care professionals and the Biomet sales force only. Distribution to any other recipient is prohibited. All content herein is protected by copyright, trademarks and other intellectual property rights owned by or licensed to Biomet Inc. or its affiliates unless otherwise indicated. This material must not be redistributed, duplicated or disclosed, in whole or in part, without the express written consent of Biomet.

Check for country product clearances and reference product specific instructions for use. For complete product information, including indications, contraindications, warnings, precautions, and potential adverse effects, see the package insert and Biomet's website.

Not for distribution in France.



One Surgeon. One Patient. ©2014 Biomet Trauma • Form No. BMET0618.0-GBL • REV0814 ***

Legal Manufacturer Biomet Trauma 56 East Bell Drive P.O. Box 587 Warsaw, Indiana 46581 USA

Monobloc Reamer AO End

Cat. No.	Diameter
2810-03-060	6.0 mm
2810-03-065	6.5 mm
2810-03-070	7.0 mm
2810-03-075	7.5 mm
2810-03-080	8.0 mm
2810-03-085	8.5 mm

Modular Reamer Head

Cat. No.	Diameter
2810-04-090	9.0 mm
2810-04-095	9.5 mm
2810-04-100	10.0 mm
2810-04-105	10.5 mm
2810-04-110	11.0 mm
2810-04-115	11.5 mm
2810-04-120	12.0 mm
2810-04-125	12.5 mm
2810-04-130	13.0 mm
2810-04-135	13.5 mm
2810-04-140	14.0 mm
2810-04-145	14.5 mm
2810-04-150	15.0 mm
2810-04-155	15.5 mm
2810-04-160	16.0 mm
2810-04-165	16.5 mm
2810-04-170	17.0 mm
2810-04-175	17.5 mm
2810-04-180	18.0 mm
2810-04-185	18.5 mm
2810-04-190	19.0 mm
2810-04-195	19.5 mm
2810-04-200	20.0 mm
2810-04-205	20.5 mm
2810-04-210	21.0 mm
2810-04-215	21.5 mm
2810-04-220	22.0 mm

Monobloc Reamer Hudson

Cat. No.	Diameter
2810-02-060	6.0 mm
2810-02-065	6.5 mm
2810-02-070	7.0 mm
2810-02-075	7.5 mm
2810-02-080	8.0 mm
2810-02-085	8.5 mm
2810-02-090	9.0 mm
2810-02-095	9.5 mm
2810-02-100	10.0 mm
2810-02-105	10.5 mm
2810-02-110	11.0 mm
2810-02-115	11.5 mm
2810-02-120	12.0 mm
2810-02-125	12.5 mm
2810-02-130	13.0 mm

Nitinol Modular Reamer Shaft AO

Cat. No.	Length
2810-03-400	400 mm
2810-03-470	470 mm

Nitinol Modular Reamer Shaft Hudson

Cat. No.	Length
2810-02-400	400 mm
2810-02-470	470 mm

Reamer Extension

Cat. No.	Length
2810-02-015	150 mm

Ball Nose Guide Wires

Cat. No.	Length
3.0 mm	
(use with 8.0-22.0 mm Reamers)	
2810-01-080	800 mm
2810-01-100	1000 mm
2.0 mm (use with 6.0-7.5 mm Reamers)	
2810-17-006	700 mm

Flexible Reamer Case

Cat. No.	
2810-02-016	

EC REP

Authorised Representative Biomet UK Ltd. Waterton Industrial Estate Bridgend, South Wales

Bridgend, South Wales
CF31 3XA