

BUFR User's Guide

Milan Dragosavac

Operations Department

November 2007

*This paper has not been published and should be regarded as an Internal Report from ECMWF.
Permission to quote from it should be obtained from the ECMWF.*



European Centre for Medium-Range Weather Forecasts
Europäisches Zentrum für mittelfristige Wettervorhersage
Centre européen pour les prévisions météorologiques à moyen terme

©Copyright 2007

European Centre for Medium-Range Weather Forecasts
Shinfield Park, Reading, RG2 9AX, United Kingdom

Literary and scientific copyrights belong to ECMWF and are reserved in all countries.

The information within this publication is given in good faith and considered to be true, but ECMWF accepts no liability for error, omission and for loss or damage arising from its use.

Contents

1	Introduction	3
2	BUFR format	4
2.1	Indicator section	4
2.2	Identification section	4
2.3	Optional section	5
2.4	Data description section	6
2.5	Data section	7
2.6	End section	7
3	BUFR software	8
3.1	Buftr tables	8
3.2	Defaults	8
3.3	Decoding and encoding	10
3.3.1	Subroutine BUFREX	10
3.3.2	Subroutine BUFREN	14
3.4	Error codes	18
3.5	Partial expansion	20
3.5.1	Subroutine BUSRQ	20
3.5.2	Example	22
3.6	Printing routines	25
3.6.1	To print Section 0	25
3.6.2	To print Section 1	25
3.6.3	To print Section 2	25
3.6.4	To print Section 3	27
3.6.5	To print data	27
3.7	Buftr software tools	29
3.7.1	Subroutine BUS012	29
3.7.2	Subroutine BUS0123	32
3.7.3	Subroutine BUSEL	35
3.7.4	Subroutine BUSEL2	36

3.7.5	Subroutine BUUKEY	37
3.7.6	Subroutine BUPKEY	41
3.7.7	Subroutine BUXDES	44
3.7.8	Subroutine BUBOX	46
3.7.9	Subroutine BUPRTBOX	48
3.8	Performance	49
4	Quality control in BUFR	50
4.1	Quality control example	53
5	Examples	64
5.1	To unpack and print data	64
5.2	To expand data descriptors only	78
5.3	To create bufr message	81
5.4	An example of C program calling fortran bufr subroutines	87
6	WMO observation templates	89
6.1	WMO AWS (automatic and manned station) template, one hour period	89
6.2	WMO SYNOP template	94
6.3	WMO BUOY template	98
6.4	WMO CLIMATE SYNOP template	103
6.5	WMO SAREP template	109
6.6	WMO TEMP template	111

1 Introduction

FM-94 BUFR (Binary Universal Form for data Representation) has been designed to achieve efficient exchange and storage of meteorological and oceanographic data. It is self defining, table driven and very flexible data representation system, especially for huge volumes of data.

The User's Guide is described in six sections.

Section 2 describes Bufr format in general, and it is useful for those who are not familiar with the Bufr concept.

Section 3 explains Bufr software usage. It contains FORTRAN subroutines for expanding and packing Bufr data. A number of routines described shall be used as a tools.

A quality control representation in the Bufr is given in section 4.

Section 5 contains few example programs to decode/repack bufr data, create a new bufr message and expand data descriptors only.

Useful WMO example templates are given in the section 6.

2 BUFR format

A full definition of the BUFR form is given in **WMO Manual on Codes, Volume I, International Codes, Part B-Binary Codes, WMO-No.306, FM 94-IX Ext. BUFR**. This section offers a brief description of the basic structure and representation of the BUFR code.

The BUFR form is a binary representation of meteorological data. It is a continuous bit stream made up of a sequence of octets (one octet is eight bits). The only part of BUFR where information does not end on byte boundaries is the data section, where a length of BUFR table B elements can have any number of bits (although it must not exceed the number of bits in a computer word for non-character data).

A BUFR message consists of six sections, some of which may be completely optional (section 2) or partially optional (section 1).

The representation of data in the form of a series of bits is independent of any particular machine representation. It is important to stress that the BUFR representation is not suitable for data visualisation without computer interpretation.

The data section consists of one or more data subsets of related meteorological data which are defined, described and represented by a single Bufr table D entry. For observational data, one subset corresponds to one observation. The data section can be in compressed or uncompressed form.

Each section included in the message always contain an even number of octets. If necessary, sections must be appended with bits set to zero to fulfil this requirement.

A BUFR message is comprised of the following sections:

- Indicator section
- Identification section
- Optional section
- Data description section
- Data section
- End section

2.1 Indicator section

Indicator section or Section 0 of a Bufr message has a fixed length of eight octets. Information about the total size of the BUFR message in octets 5-7 is very useful for reading BUFR data from pure binary files. The content of Section 0 is given in the [Table 1](#).

2.2 Identification section

This section contains information relevant to data recognition without performing complete expansion of data. Data type and observation date and time are the most important parts of it. In the case of multi-subset data the time of the earliest observation should be packed into section 1. This section also contains all information necessary to define the Bufr tables used.

Table 1: Bufr Section - 0

Octet number	Content
1-4	BUFR four letters in CCITT International Alphabet No.5
5-7	Total length of Bufr message in bytes
8	Bufr Edition number (currently 4)

The layout of the Identification section is given in Table 2.

Table 2: Bufr Section - 1

Octet number	Content
1-3	Length of section 1
4	Bufr master table (zero if standard WMO FM 94-IX BUFR tables are used)
5-6	Identification of originating/generating centre
7-8	Identification of originating/generating sub-centre
9	Update sequence number (zero for original BUFR messages; incremented by one for updates)
10	Bit 1 = 0 No optional section Bit 1 = 1 Optional section follows Bit 2-8 Set to zero (reserved)
11	Data Category (Table A)
12	International data sub-category
13	Local sub-category
14	Version number of master table used (currently 12 for WMO FM 94-IX Ext. BUFR tables)
15	Version number of local tables used to augment the master table in use
16-17	Year (4 digits)
18	Month
19	Day
20	Hour
21	Minute
22	second
23-	Reserved for local use by ADP centres

2.3 Optional section

The presence of Section 2 of the Bufr message is indicated by a flag in the 8th byte of Section 1. This section can be used locally by Automated Data Processing centres. This Section is used to keep the Report Data Base key.

The layout of Section 2 is given in table 3.

Table 3: Bufr Section - 2

Octet number	Content
1-3	Length of section in bytes
4	Set to zero (reserved)
5-	reserved for local use by ADP centres

2.4 Data description section

This section describes the data in the data section. The information which can be found in the first seven octets is the number of subsets in the message, their form and the type of data (observation/non-observation). The data descriptors start in the 8th octet of the section 3. Each descriptor is spread over two bytes and contains three parts. If $F = 0$, the descriptor is an element descriptor and values of X and Y define entries in Bufr Table

Table 4: Descriptor reference

F	X	Y
2 bits	6 bits	8 bits

B. For $F = 1$, the descriptor is a replication descriptor. If $F = 2$, the descriptor is one of the operators from bufr Table C. $F = 3$ means that the descriptor represents the sequence descriptor from Bufr Table D. The table D entries contain a list of element descriptors, operators, and/or other sequence descriptors.

In an ideal situation, data in Section 4 should be described by one Bufr Table D entry only.

X stands for class of elements in the range from 0-63 and Y is an entry within class 0-255. Classes 48-63 are reserved for local use and entries from 192-255 within all classes are also reserved for local usage.

Layout of Data description section is given in the Table 5.

Table 5: Data description section

Octet number	Content
1-3	Length of section
4	set to zero (reserved)
5-6	Number of data subsets
7	Bit 1 = 1 Observed data Bit 1 = 0 Other data Bit 2 = 1 Compressed data Bit 2 = 0 Non compressed data Bits 3-8 set to zero (reserved)
8-	A collection of element descriptors, replication descriptors, operator descriptors and sequence descriptors, which define the form and contents of individual data elements comprising one data subset in the data section.

2.5 Data section

The Data section, like all sections, starts with the length of Section 4 followed by a continuous stream of bits from byte 5 onward.

Layout of Data section is given in the Table 6.

Table 6: Data section

Octet number	Content
1-3	Length of section in bytes
4	set to zero (reserved)
5-	Binary data as defined by sequence descriptors

2.6 End section

The End section is comprised of four "7" characters in CCITT International Alphabet No.5 and this marks the end of the Bufr message. The layout of the End section is given in the Table 7.

Table 7: End section

Octet number	Content
1-4	"7777" (coded according to the CCITTIA No 5)

3 BUFR software

The first version of ECMWF Bufr software was designed and implemented in 1987. A great deal of experience has been gathered in handling binary coded observations since. Bufr software is written in FORTRAN 77.

Versions for C90, VAX, IBM, SGI, SUN, HP and for all UNIX and LINUX based platforms are available. It has been installed on Mac OSX as well.

3.1 Bufr tables

BUFR is a table driven system. It uses three main tables.

- Bufr Table B - classification elements
- Bufr Table C - text and meaning of all code/flag tables
- Bufr Table D - list of common sequences

Bufr Tables B and D are used to collect all necessary information to pack/unpack Bufr data. Which table is to be loaded is decided at runtime using information from Section 1 of the Bufr message. The naming convention for Bufr binary tables is as follows:

Bssswwwwxxxxxyyyzzz.TXT Cssswwwwxxxxxyyyzzz.TXT Dssswwwwxxxxxyyyzzz.TXT where

- sss - Master table number (zero for WMO meteorological tables)
- wwwww - Originating sub-centre
- xxxxx - Originating centre
- yyy - Version number of master table used
- zzz - Version number of local table used

ECMWF is currently using B000000000098013001.TXT, C000000000098013001.TXT and D000000000098013001.TXT tables. Keep in mind that Bufr Table C in this software is a code table. Bufr has Table C in its definition, where Bufr Operators are defined. If standard WMO tables are used, the Originating centre xxxxx will be set to 00000.

Current version of the software will keep in memory up to JTMAX=10 versions of tables in the round robin fashion.

3.2 Defaults

Integer **missing value** indicator:

NVIND = 2147483647

Real **missing value** indicator:

RVIND = 1.7E38

Default path for Bufr Tables is hard coded in the software. To change the path set environmental variable BUFR_TABLES :

```
export BUFR_TABLES=/.../
```

The path must end with "/"

During decoding Bufr table path and the names are printed. If user does not want that, set: VARIABLE **PRINT_TABLE_NAMES=false**

```
export PRINT_TABLE_NAMES=false
```

3.3 Decoding and encoding

3.3.1 Subroutine *BUFREX*

Purpose

Decodes Bufr message into fully expanded form, returning information relevant to all Bufr Sections, expanded values, Bufr Table B element names and units.

Interface

```
CALL BUFREX (KBUFL, KBUFF, KSUP, KSEC0, KSEC1, KSEC2, KSEC3, KSEC4,
            KELEM, CNAME, CUNITS, KVALS, VALUES, CVALS, KERR)
```

where:

- Integer variables are denoted by first letter K.
- Real variables are denoted by first letter V.
- Character variables are denoted by first letter C.

Input arguments

- KBUFL - An INTEGER variable containing length of Bufr message in words.
- KBUFF - An INTEGER array containing Bufr message.
- KELEM - An INTEGER variable containing expected number of expanded elements
- KVALS - An INTEGER variable containing expected number of data values.

Output arguments

- KSEC0 - An INTEGER array (size 3) containing Bufr Section 0 information.
- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly.
- KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2 information. ECMWF uses this section to store Report Data Base key.
- KSEC3 - An INTEGER array of 4 words containing Bufr Section 3 information.
- KSEC4 - An INTEGER array of 2 words containing Section 4 information.
- KSUP - An INTEGER array (size 9) containing supplementary information.

- C NAMES - CHARACTER*64 array of KELEM words containing element names.
- C UNITS - CHARACTER*24 array of KELEM words containing element units.
- VALUES - REAL*8 array of KVALS words containing element values.
- C VALS - CHARACTER*80 array of KVALS containing CCITT IA No.5 element entries.
- KERR - An INTEGER containing an error code.

KSEC0 - An INTEGER array (size 3) containing Bufr Section 0 information

Array index	Word content
1	Length of section 0 in bytes
2	Total length of Bufr message in bytes
3	Bufr Edition number (currently 4)

KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information

Array index	Word content
1	Length of section 1 in bytes
2	Bufr Edition number (currently 4)
3	Originating centre
4	Update sequence number
5	Flag (presence of Section 2 in the message)
6	Bufr message type (Bufr Table A)
7	Bufr message subtype (local use)
8	Version number of local table used
9	Year
10	Month
11	Day
12	Hour
13	Minute
14	Bufr Master Table used
15	Version number of Master table used
16	Originating sub-centre
17	International sub-category
18	Second
19-	Local ADP centre information (byte by byte)

KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2 information

Array index	Word content
1	Length of Section 2 in bytes
2-	Report Data Base key in packed form

KSEC3 - An INTEGER array of 4 words containing Bufr Section 3 information

Array index	Word content
1	Length of Section 3 in bytes
2	Reserved
3	Number of subsets
4	Flag (data type, compression)

KSEC4 - An INTEGER array of 2 words containing Section 4 information

Array index	Word content
1	Length of Section 4 in bytes
2-	Reserved

KSUP - An INTEGER array (size 9) containing supplementary information

Array index	Word content
1	Dimension of KSEC1 array
2	Dimension of KSEC2 array
3	Dimension of KSEC3 array
4	Dimension of KSEC4 array
5	Real number of expanded elements
6	Number of subsets
7	Real number of elements in CVALS array
8	Total Bufr message length in bytes
9	Dimension of KSEC0 array

Method

A Bufr message passed as an argument to this routine is decoded section by section. Before Section 3 expansion Bufr tables are loaded using KSEC1 information to create table names. The loaded Bufr tables are kept in memory and swapped only if the next message is requesting different tables.

Section 3 Data descriptors are unpacked and expanded applying all necessary operators in force and creating a list of Bufr Table B elements which correspond one to one to the data in the Data section of the Bufr message. Word and bit pointers are calculated for each element in the message.

Having all this information, unpacking of the data is performed applying reference value and scaling to get the final value for one element in the Bufr message. Unpacked data are stored in VALUES array. The corresponding element names and units are stored in the C NAMES and C UNITS arrays respectively.

To achieve efficiency, original Data descriptors are saved for the following comparison. If the Data descriptors for the next observation are not different from the previous, the former word and bit pointers to the elements are used saving time for data descriptors expansion.



If a Bufr Table B element is type character, the corresponding VALUES element contains a real number which, when truncated to an integer represents

index * 1000 + length

where:

- index - subscript of the element in CVALS where character string is stored.
- length - number of characters represented.

In the case of multi subset data, the one dimensional array VALUES contains all subsets of data. The formula to find the index to the VALUES array of the i-th element of observation is:

index=i + (nsub-1)*KELEM

so start of next subset is KELEM apart.

Current version of the Bufr software can handle KELEM up to 160000 and KVALS up to 4096000.

Externals

```
BUEXS0 - Expands Section 0 of Bufr message
BUEXS1 - Expands Section 1 of Bufr message
BUEXS2 - Expands Section 2 of Bufr message
BUEXS3 - Expands Section 3 of Bufr message
BUGBTS - Loads Bufr tables
BUEXS4 - Expands Section 4 of Bufr message
BUEXS5 - Expands Section 5 of Bufr message
```

Reference

WMO -No. 306 Manual on Codes Volume I, Part B - Binary Codes: J.K. Gibson and M. Dragosavac 1988: Decoding Data Represented in FM 94-IX Ext. BUFR

3.3.2 Subroutine *BUFREN*

Purpose

Creates a packed Bufr message from the information contained in the arguments of the subroutine.

Interface

```
CALL BUFREN(KSEC0,KSEC1,KSEC2,KSEC3,KSEC4,  
            KTDLEN,KTDLST,KDLEN,KDATA,KELEM,KVALS,  
            VALUES,CVALS,KBUFL,KBUFF,KERR)
```

where

- Integer variables are denoted by first letter K.
- Real variables are denoted by first letter V.
- Character variables are denoted by first letter C

Input arguments

- KSEC0 - An INTEGER array (size 3) containing Bufr Section 0 information
- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly.
- KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2 information. ECMWF uses this section to store Report Data Base key.
- KSEC3 - An INTEGER array of 4 words containing Bufr Section 3
- KSEC4 - An INTEGER array of 2 words containing Section 4 information.
- KTDLEN - An INTEGER variable containing the number of data descriptors to be packed in Section 3 of Bufr message
- KTDLST - An INTEGER array containing the list of KTDLEN data descriptors
- KDLEN - An INTEGER variable containing the dimension of KDATA array
- KDATA - An INTEGER array containing the delayed replication factors which appear in the Data section of Bufr message
- KELEM - An INTEGER variable containing the expected number of expanded elements
- KVALS - An INTEGER variable containing the expected number of data values
- VALUES - REAL*8 array of KVALS words containing element values.
- CVALS - CHARACTER*80 array of KVALS containing CCITT IA No.5 element entries.

KSEC0 An INTEGER array (size 3) containing Bufr Section 0 information

Array index	Word content
1	Length of section 0 in bytes
2	Total length of Bufr message in bytes
3	Bufr Edition number (currently 4)

KSEC1 An INTEGER array of at least 40 words containing Bufr Section 1

Array index	Word content
1	Length of section 1 in bytes
2	Bufr Edition number (currently 4)
3	Originating centre
4	Update sequence number
5	Flag (presence of Section 2 in the message)
6	Bufr message type (Bufr Table A)
7	Bufr message subtype (local use)
8	Version number of local table used
9	Year
10	Month
11	Day
12	Hour
13	Minute
14	Bufr Master Table used
15	Version number of Master table used
16	Originating sub-centre
17	International sub-category
18	Second
19-	Local ADP centre information (byte by byte)

KSEC2 An INTEGER array of 4096 words containing Bufr Section 2

Array index	Word content
1	Length of Section 2 in bytes
2-	Report Data Base key in packed form

KSEC3 An INTEGER array of 4 words containing Bufr Section 3

Array index	Word content
1	Length of Section 3 in bytes
2	Reserved
3	Number of subsets
4	Flag (data type, compression)

KSEC4 An INTEGER array of 2 words containing Section 4 information

Array index	Word content
1	Length of Section 4 in bytes
2-	Reserved

Output arguments

- KBUFL - An INTEGER variable containing the length of the Bufr message in words.
- KBUFF - An INTEGER array containing the Bufr message.
- KERR - An INTEGER containing an error code.

Method

A basic approach when this software was designed to have a one to one correspondence between expanded data descriptors and the data itself.

The input arguments have to be filled in before packing,. The lengths of the Sections and the total Bufr message length are set by the software. The lengths of the Section 1 and 2 must be supplied by the user. The other Section lengths ought to be set to zero. The default size of the Section 1 is 18 octets and 22 octets for Bufr Edition 4, if there are no local entries. The Section 2 is optional section, and ECMWF uses it to store Report Data Base key. In this case the length of the Section 2 is 52 octets.

Before setting values in the VALUES array, it is recommended to initialise it with the MISSING value indicator.

The Optional Section 2 and a local part of Section 1 must be in the packed form because encoder packs these information in byte by byte manner.

The Data descriptors stored in the KTDLST array are expanded taking delayed replication factor values from KDATA array if needed. The order of replication factor values must be as they appear in the data. If 203YYY change reference value operator is used a reference value shall be in KDATA array.

The VALUES array must be filled in correspondence with previously described data elements. In the case of multi subsets, the pointer of the ith element in VALUES array is:

$$\text{index} = i + (\text{nsb} - 1) * \text{KELEM}$$

which implies that the first element of the second subset begins at KELEM+1 position even if the number of elements in the observation is less than KELEM.

For character information or elements having CCITT IA No.5 as units, VALUES array element contains a real number which, when truncated to an integer represents



value=isub*1000+length

where isub is a subscript of the element in CVALS array, where the character string is stored and the length represents number of bytes/character occupied by this element.

To find out what one observation should look like, the BUXDES routine can be used. This routine expands data descriptors for the user. The procedure to print an expanded list of the data descriptors is the same as to print Section 3 of Bufr message.

Externals

BUENS0 - Packs Section 0 of Bufr message
BUENS1 - Packs Section 1 of Bufr message
BUENS2 - Packs Section 2 of Bufr message
BUENS3 - Packs Section 3 of Bufr message
BUETAB - Loads required Bufr tables
BUENS4 - Packs Section 4 of Bufr message
BUENS5 - Packs Section 5 of Bufr message

Reference

WMO -No. 306 Manual on Codes Volume I, Part B - Binary Codes: J.K. Gibson and M. Dragosavac 1988:Decoding Data Represented in FM 94-IX

3.4 Error codes

The errors returned by the Bufr decoding/encoding routines can be zero, negative and positive. The zero returned error code means no errors detected, negative error is a warning error which can occur during packing. If the value to be packed is too big, BUFREN will pack the truncated value and return a negative error code. The hard errors are positive.

The Error codes are given in Table 8.

Table 8: Return error codes

Error number	Meaning
1	Start of BUFR message not found
2	End of BUFR message not found
3	Array to receive BUFR message too small
4	JSEC1 parameter too small. Local ADP centre information skipped
5	JSEC2 parameter too small. Local ADP centre information skipped
6	Error during read BUFR table B
7	Error during read BUFR table C
8	Error during read BUFR table D
9	Open error
10	Error during closing BUFR table B
11	Error during close BUFR table C
12	Error during close BUFR table D
13	Number of bits to be extracted greater than number of bits per computer word
14	Argument KVALS too small
15	Increment value for compressed data too big
16	JSUBS parameter too small
17	JWORK parameter too small
18	Replication factor equal to zero
19	Delayed replication factor too big.
20	Table D reference not found
21	Data descriptors operator not found
22	BUFR Operator name not found
23	Table B reference not found
24	Augmented table B reference not found
25	KELEM argument too small
26	Word pointer out of range
27	Too many subsets to be packed
28	Number to be packed too big

continued on next page

continued from previous page

Error number	Meaning
29	Number of descriptors KTDLEN too big
30	Number of elements greater than JELEM
31	Too few elements in KDATA array
32	Number of subsets equal to zero
33	Negative value to be packed
34	Number of bits to be packed greater than number of bits per computer word
35	Not used
36	Bad order of data descriptors
37	Wrong data descriptors
38	Partial expansion on total message not supported
39	Can not recognise feedback data in this message
40	Request flag illegal
41	Bit map not set
42	This element must be data present indicator
43	Table B element must follow bit map
44	Requested subset does not exist
45	There is no one requested element in the data
46	Input array is too small to receive information

3.5 Partial expansion

It is possible to expand only the requested subset of elements without unpacking the whole Bufr message. This method is called partial expansion.

To do partial expansion, the request has to be set by calling the BUSRQ routine before calling BUFREX.

3.5.1 Subroutine BUSRQ

Purpose

Sets flags and Bufr table B reference numbers of the requested elements for partial expansion.

Interface

```
CALL BUSRQ (KREQ, KRQL, KRQ, RQV, KERR)
```

where:

- Integer variables are denoted by first letter K.
- Real variables are denoted by first letter R.

Input arguments

- KREQ - An INTEGER array of 2 containing flags.

```
KREQ(1) - 0 All elements
          1 All original observation without quality control
          2 All original elements with quality control
          2 All original elements with quality control
          3 Only feedback information
```

```
KREQ(2) - Flag of 6 bits
```

Bit number	Meaning
1	0 not used
2	0 - No partial expansion 1 - Partial expansion
3	0 - No quality control 1 - quality control
4	0 - No statistics 1 - Statistics
5	0 - No difference statistics 1 - Difference statistics



6 0 - No substituted values
 1 - Substituted values

Bit number 1 is right most bit.

- KRQL - An INTEGER containing the number of requested elements
- KRQ - An INTEGER array containing the list of requested elements (Bufr table B reference numbers)
- RQV - A REAL*8 array of KRQL containing a list of values signifying requested elements

Output arguments

- KERR - Error code

Method

The lists of flags and Bufr Table B reference numbers are used to designate requested Bufr elements. The elements from class 7 and 8 are possible qualifiers for the other elements if supplied with corresponding values.

The partial expansion is not supported for the whole analysis feedback Bufr messages (includes original observation and analysis variables followed by the statistics e.t.c.)

The list of the requested elements and corresponding word and bit pointers are created before expansion. These pointers are used to extract data from the Data section of the Bufr message.

The KRQ and RQV arrays have to be initialised by missing value indicators NVIND and RVIND respectively.

The KREQ(1) is useful to split the feedback Bufr message into original, quality control and analysis feed back data.

Externals

BUNPCK - Unpacks bit pattern
BUNPKS - Unpacks bit pattern in repeated way.

Reference

None

3.5.2 Example

Running BUFR program and answering prompts as below, 500 mb level information is unpacked by the BUFREX routine.

```
DO YOU WANT TO PRINT( Y/N ) :y
CODE TABLES TO BE PRINTED ( Y/N ) :n
DO YOU WANT ENCODING( Y/N ) :n
RECORD NUMBER TO START FROM :1
REQUESTED ELEMENT : 007004
REQUESTED VALUE   : 50000.
REQUESTED ELEMENT : 008001
REQUESTED VALUE   :
REQUESTED ELEMENT : 010003
REQUESTED VALUE   :
REQUESTED ELEMENT : 012001
REQUESTED VALUE   :
REQUESTED ELEMENT : 012003
REQUESTED VALUE   :
REQUESTED ELEMENT : 011001
REQUESTED VALUE   :
REQUESTED ELEMENT : 011002
REQUESTED VALUE   :
REQUESTED ELEMENT :
REQUESTED VALUE   :
REQUESTED FLAG 1  : 1
REQUESTED FLAG 2  : 2

DO YOU WANT TO PRINT SECTION 0-3( Y/N ) :y
```

This is the output from the program:

ECMWF

BUFR DECODING SOFTWARE VERSION - 7.1
07 June 2005.

Your path for bufr tables is :

/home/ma/maa/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables

BUFR TABLES TO BE LOADED B0000000000098006001,D0000000000098006001

1

BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)	8
TOTAL LENGTH OF BUFR MESSAGE (BYTES)	1406
BUFR EDITION NUMBER	3

1

BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)	18
BUFR EDITION NUMBER	3
ORIGINATING SUB-CENTRE	0
ORIGINATING CENTRE	98
UPDATE SEQUENCE NUMBER	1
FLAG (PRESENCE OF SECTION 2)	128
BUFR MESSAGE TYPE	2
BUFR MESSAGE SUBTYPE	101
VERSION NUMBER OF LOCAL TABLE	1
YEAR	5
MONTH	5
DAY	9
HOUR	10
MINUTE	0



```

VERSION NUMBER OF MASTER TABLE      6
BUFR MASTER TABLE                   0
1
    BUFR SECTION 2

LENGTH OF SECTION 2                   52

    REPORT DATA BASE KEY

RDB DATA TYPE                        5
RDB DATA SUBTYPE                     101
YEAR                                  2005
MONTH                                  5
DAY                                    9
HOUR                                  10
MINUTE                                0
SECOND                                0
LATITUDE 1                            51.20
LONGITUDE 1                           -1.80
IDENTIFIER                             03743
TOTAL BUFR MESSAGE LENGTH             1406
DAY (RDB INSERTION)                   9
HOUR (RDB INSERTION)                  10
MINUTE (RDB INSERTION)                53
SECOND (RDB INSERTION)                 7
DAY (MDB ARRIVAL)                     9
HOUR (MDB ARRIVAL)                    10
MINUTE (MDB ARRIVAL)                  50
SECOND (MDB ARRIVAL)                  20
CORRECTION NUMBER                     1
PART OF MESSAGE                       1
CORRECTION NUMBER                     1
PART OF MESSAGE                       1
CORRECTION NUMBER                     0
PART OF MESSAGE                       0
CORRECTION NUMBER                     0
PART OF MESSAGE                       0
CORRECTION NUMBER                     0
PART OF MESSAGE                       0
QUALITY CONTROL % CONF                 70
1
    BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)           40
RESERVED                               0
NUMBER OF DATA SUBSETS                1
FLAG (DATA TYPE/DATA COMPRESSION)     128

```

DATA DESCRIPTORS (UNEXPANDED)

```

1 309007
2 104000
3 031001
4 007004
5 008001
6 011061
7 011062
8 222000
9 101000
10 031002
11 031031
12 001031
13 001032
14 101000
15 031002
16 033007

```

DATA DESCRIPTORS (EXPANDED)



```
1 007004 PRESSURE
2 008001 VERTICAL SOUNDING SIGNIFICANCE
3 010003 GEOPOTENTIAL
4 012001 TEMPERATURE/DRY BULB TEMPERATURE
5 012003 DEW POINT TEMPERATURE
6 011001 WIND DIRECTION
7 011002 WIND SPEED
```

```
STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1
```

EXPANDED BUFR MESSAGE

```
1 PRESSURE          0.5000000000E+05 PA
2 VERTICAL SOUNDI   0.3600000000E+02 FLAG TABLE 008001
3 GEOPOTENTIAL     0.5374000000E+05 M**2/S**2
4 TEMPERATURE/DRY  0.2475000000E+03 K
5 DEW POINT TEMPE  0.2245000000E+03 K
6 WIND DIRECTION   0.3050000000E+03 DEGREE TRUE
7 WIND SPEED       0.2600000000E+02 M/S
```

The equivalent request in batch mode will be:

```
KREQ(1)=1
KREQ(2)=2
KRQL=7
```

```
KRQ(1)=007004      RQV(1)=50000.
KRQ(2)=008001      RQV(2)=RMISS
KRQ(3)=010003      RQV(3)=RMISS
KRQ(4)=012001      RQV(4)=RMISS
KRQ(5)=012003      RQV(5)=RMISS
KRQ(6)=011001      RQV(6)=RMISS
KRQ(7)=011002      RQV(7)=RMISS
```

where RMISS is missing value indicator RMISS=1.7E38

```
CALL BURQS(KREQ,KRQL,KRQ,RQV,KERR)
```

getting the same result as previously.



3.6 Printing routines

Bufr form is a binary representation of meteorological data and as such is not suitable for visualization. After expanding Bufr data using the BUFREX routine a number of printing routines can be used to print different parts of the Bufr message.

3.6.1 To print Section 0

```
CALL BUPRS0(KSEC0)
```

3.6.2 To print Section 1

```
CALL BUPRS1(KSEC1)
```

3.6.3 To print Section 2

Section 2 of the Bufr message is an optional section and every ADP centre can pack any information in this section. The Bufr software decodes this local information and stores it into KSEC2 array. ECMWF is storing RDB key in the Section 2 of the Bufr messages. To print content of the Section 2, subroutine BUUKEY must be called before the BUPRS2 routine.

For other cases, special routines have to be written to unpack this information.

```
CALL BUUKEY(KSEC1, KSEC2, KEY, KSUP, KERR)
```

```
CALL BUPRS2(KSUP, KEY)
```

where

- KEY - An INTEGER array containing RDB key information
- The other arguments were described in previous routines.

KEY - An INTEGER array containing RDB key information

Array index	Word content
1	Length of Section 2 in bytes
2	RDB type

continued on next page

continued from previous page

Array index	Word content
3	RDB subtype
4	Year
5	Month
6	Day
7	Hour
8	Minute
9	Second
10	Longitude 1
10	Latitude 1
12	Longitude 2
13	Latitude 2
14	Number of subsets
15	Ident (numeric as satellite number)
16	Ident (CCITTIA5) one character
17	Ident (CCITTIA5) one character
18	Ident (CCITTIA5) one character
19	Ident (CCITTIA5) one character
20	Ident (CCITTIA5) one character
21	Ident (CCITTIA5) one character
22	Ident (CCITTIA5) one character
23	Ident (CCITTIA5) one character
24	Ident (CCITTIA5) one character
25	Total Bufr message length in bytes
26	Day (RDB insertion)
27	Hour (RDB insertion)
28	Minute (RDB insertion)
29	Second (RDB insertion)
30	Day (MDB insertion)
31	Hour MDB insertion)
32	Minute (MDB insertion)
33	Second (MDB insertion)
34	Correction number
35	Part received (for TEMP/PILOT observations)
36	Not used
37	Correction number
38	Part received (for TEMP/PILOT observations)
39	Not used
40	Correction number

continued on next page

continued from previous page

Array index	Word content
41	Part received (for TEMP/PILOT observations)
42	Not used
43	Correction number
44	Part received (for TEMP/PILOT observations)
45	Not used
46	The lowest quality control % confidence

3.6.4 To print Section 3

Prior to calling the BUPRS3 routine, the BUSEL or BUSEL2 routine has to be called to get lists of unexpanded and fully expanded Data descriptors. In the case of multi-subset uncompressed bufr data the expanded list of descriptors might be different for different subsets.

```
CALL BUSEL (KTDLEN ,KTDLST ,KTDEXL ,KTDEXP ,KERR )
```

or

```
CALL BUSEL2 (KSUBSET ,KELEM ,KTDLEN ,KTDLST ,KTDEXL ,KTDEXP ,CNAMES ,CUNITS ,KERR )
```

```
CALL BUPRS3 (KSEC3 ,KTDLEN ,KTDLST ,KTDEXL ,KTDEXP ,KELEM ,CNAMES )
```

3.6.5 To print data

```
CALL BUPRT (K ,KSUB1 ,KSUB2 ,KELEM ,CNAMES ,CUNITS ,CVALS ,
           KVALS ,VALUES ,KSUP ,KSEC1 ,KERR )
```

where

- K - An INTEGER set to 0 - No Code table entry
1 - Code table entry
- KSUB1 - An INTEGER containing the starting subset to print.
- KSUB2 - An INTEGER containing the ending subset to print.
- KELEM - An INTEGER containing the expected number of expanded elements.
- CNAMES - A CHARACTER*64 array containing the element names.
- CUNITS - A CHARACTER*24 array containing the units.
- CVALS -A CHARACTER*80 array containing character values.
- KVALS -An INTEGER containing the expected number of data values.
- VALUES - A REAL*8 array containing the expanded values.

- KSUP - AN INTEGER array containing supplementary information.
- KSEC1 -An INTEGER array containing Section 1 information.
- KERR - An INTEGER containing an error code.

3.7 Bufr software tools

3.7.1 Subroutine *BUS012*

Purpose

Expands only Sections 0, 1 and 2 of Bufr message.

Interface

```
CALL BUS012(KBUFL, KBUFF, KSUP, KSEC0, KSEC1, KSEC2, KERR)
```

where

- Integer variables are denoted by first letter K.

Input arguments

- KBUFL - An INTEGER variable containing the length of Bufr message in words.
- KBUFF - An INTEGER array containing the Bufr message.

Output argument

- KSUP - An INTEGER array size 9 containing supplementary information
- KSEC0 - An INTEGER array size 3 containing Bufr Section 0 information
- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly.
- KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2 information. ECMWF uses this section to store Report Data Base key.
- KERR - An Integer containing an error code.

KSUP AN INTEGER array containing supplementary information

Array index	Word content
1	Dimension of KSEC1 array
2	Dimension of KSEC2 array
3	Dimension of KSEC3 array
4	Dimension of KSEC4 array
5	Real number of expanded elements
6	Number of subsets
7	Real number of elements in CVALS array
8	Total Bufr message length in bytes
9	Dimension of KSEC0 array

KSEC0 An INTEGER array size 3 containing Bufr Section 0 information

Array index	Word content
1	Length of section 0 in bytes
2	Total length of Bufr message in bytes
3	Bufr Edition number (currently 4)

KSEC1 An INTEGER array of at least 40 words containing Bufr Section 1

Array index	Word content
1	Length of section 1 in bytes
2	Bufr Edition number (currently 4)
3	Originating centre
4	Update sequence number
5	Flag (presence of Section 2 in the message)
6	Bufr message type (Bufr Table A)
7	Bufr message subtype (local use)
8	Version number of local table used
9	Year
10	Month
11	Day
12	Hour
13	Minute
14	Bufr Master Table used
15	Version number of Master table used
16	Originating sub-centre
17	International sub-category
18	Second
19-	Local ADP centre information (byte by byte)

KSEC2 An INTEGER array of 4096 words containing Bufr Section 2

Array index	Word content
1	Length of Section 2 in bytes
2-	Report Data Base key in packed form

Method

None .

Externals

BUEXS0 - Expands Section 0 of Bufr message

BUEXS1 - Expands Section 1 of Bufr message

BUEXS2 - Expands Section 2 of Bufr message

Reference

None .

3.7.2 Subroutine *BUS0123*

Purpose

Expands only Sections 0, 1, 2 and 3 of Bufr message.

Interface

```
CALL BUS0123 (KBUFL, KBUFF, KSUP, KSEC0, KSEC1, KSEC2, KSEC3, KERR)
```

where

- Integer variables are denoted by first letter K.

Input arguments

- KBUFL - An INTEGER variable containing the length of Bufr message in words.
- KBUFF - An INTEGER array containing the Bufr message.

Output argument

- KSUP - An INTEGER array size 9 containing supplementary information
- KSEC0 - An INTEGER array size 3 containing Bufr Section 0 information
- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly.
- KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2 information. ECMWF uses this section to store Report Data Base key.
- KSEC3 - An INTEGER array of 4 containing Bufr section 3 header information
- KERR - An Integer containing an error code.

KSUP AN INTEGER array containing supplementary information

Array index	Word content
1	Dimension of KSEC1 array
2	Dimension of KSEC2 array
3	Dimension of KSEC3 array
4	Dimension of KSEC4 array
5	Real number of expanded elements
6	Number of subsets
7	Real number of elements in CVALS array
8	Total Bufr message length in bytes
9	Dimension of KSEC0 array

KSEC0 An INTEGER array size 3 containing Bufr Section 0 information

Array index	Word content
1	Length of section 0 in bytes
2	Total length of Bufr message in bytes
3	Bufr Edition number (currently 4)

KSEC1 An INTEGER array of at least 40 words containing Bufr Section 1

Array index	Word content
1	Length of section 1 in bytes
2	Bufr Edition number (currently 4)
3	Originating centre
4	Update sequence number
5	Flag (presence of Section 2 in the message)
6	Bufr message type (Bufr Table A)
7	Bufr message subtype (local use)
8	Version number of local table used
9	Year
10	Month
11	Day
12	Hour
13	Minute
14	Bufr Master Table used
15	Version number of Master table used
16	Originating sub-centre
17	International sub-category
18	Second
19-	Local ADP centre information (byte by byte)

KSEC2 An INTEGER array of 4096 words containing Bufr Section 2

Array index	Word content
1	Length of Section 2 in bytes
2-	Report Data Base key in packed form

KSEC3 - An INTEGER array of 4 words containing Bufr Section 3 information

Array index	Word content
1	Length of Section 3 in bytes
2	Reserved
3	Number of subsets
4	Flag (data type, compression)

Method

None .

Externals

- BUEXS0 - Expands Section 0 of Bufr message
- BUEXS1 - Expands Section 1 of Bufr message
- BUEXS2 - Expands Section 2 of Bufr message
- BUEXS3 - Expands Section 3 of Bufr message

Reference

None .

3.7.3 Subroutine *BUSEL*

Purpose

Returns lists of unexpanded and expanded data descriptors from the Bufr message. The lists contains Bufr Table D sequence numbers, and the Bufr Table B reference numbers.

Interface

```
CALL BUSEL( KTDLEN , KTDLST , KTDEXL , KTDEXP , KERR )
```

where

- Integer variables are denoted by first letter K.

Input arguments

None .

Output arguments

- KTDLEN - An INTEGER variable containing number of data descriptors in KTDLST array
- KTDLST - An INTEGER array containing the list of KTDLEN data descriptors
- KTDEXL - An INTEGER variable containing number of expanded data descriptors
- KTDEXP - An INTEGER array containing the list of KTDEXL data descriptors
- KERR - An INTEGER containing error code.

Method

None

Externals

None

Reference

None

3.7.4 Subroutine *BUSEL2*

Purpose

Returns lists of unexpanded and expanded data descriptors from the Bufr message for particular subset.

Interface

```
CALL BUSEL2 ( KSUBSET , KELEM , KTDLEN , KTDLST , KTDEXL , KTDEXP , C NAMES , C UNITS , KERR )
```

where

- Integer variables are denoted by first letter K.

Input arguments

- KSUBSET - Subset number
- KELEM - Number of expected elements

Output arguments

- KTDLEN - An INTEGER variable containing number of data descriptors in KTDLST array
- KTDLST - An INTEGER array containing the list of KTDLEN data descriptors
- KTDEXL - An INTEGER variable containing number of expanded data descriptors
- KTDEXP - An INTEGER array containing the list of KTDEXL data descriptors
- C NAMES - CHARACTER array containing element name
- C UNITS - CHARACTER array containing element unit
- KERR - An INTEGER containing error code.

Method

None

Externals

None

Reference

None

3.7.5 Subroutine BUUKEY

Purpose

Unpacks ECMWF Report Data Base Key.

Interface

```
CALL BUUKEY (KSEC1 , KSEC2 , KEY , KSUP , KERR )
```

where: zz

- Integer variables are denoted by first letter K.

Input arguments

- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly.
- KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2 information. ECMWF uses this section to store Report Data Base Key.
- KSUP - An INTEGER array (size 9) containing supplementary information.

KSEC1 An INTEGER array of at least 40 words containing Bufr Section 1

Array index	Word content
1	Length of section 1 in bytes
2	Bufr Edition number (currently 4)
3	Originating centre
4	Update sequence number
5	Flag (presence of Section 2 in the message)
6	Bufr message type (Bufr Table A)
7	Bufr message subtype (local use)
8	Version number of local table used
9	Year
10	Month
11	Day
12	Hour
13	Minute
14	Bufr Master Table used
15	Version number of Master table used
16	Originating sub-centre
17	International sub-category
18	Second
19-	Local ADP centre information (byte by byte)

KSEC2 An INTEGER array of 4096 words containing Bufr Section 2

Array index	Word content
1	Length of Section 2 in bytes
2-	Report Data Base key in packed form

KSUP An INTEGER array size 9 containing supplementary information

Array index	Word content
1	Dimension of KSEC1 array
2	Dimension of KSEC2 array
3	Dimension of KSEC3 array
4	Dimension of KSEC4 array
5	Real number of expanded elements
6	Number of subsets
7	Real number of elements in CVALS array
8	Total Bufr message length in bytes
9	Dimension of KSEC0 array

Output arguments

- **KEY** - An INTEGER array of 46 words containing unpacked RDB key.
- **KERR** - Error cod

KEY - An INTEGER array of 46 words containing unpacked RDB key.

Array index	Word content
1	Length of Section 2 in bytes
2	RDB type
3	RDB subtype
4	Year
5	Month
6	Day
7	Hour
8	Minute
9	Second
10	Longitude 1

continued on next page

continued from previous page

Array index	Word content
10	Latitude 1
12	Longitude 2
13	Latitude 2
14	Number of subsets
15	Ident (numeric as satellite number)
16	Ident (CCITTIA5) one character
17	Ident (CCITTIA5) one character
18	Ident (CCITTIA5) one character
19	Ident (CCITTIA5) one character
20	Ident (CCITTIA5) one character
21	Ident (CCITTIA5) one character
22	Ident (CCITTIA5) one character
23	Ident (CCITTIA5) one character
24	Ident (CCITTIA5) one character
25	Total Bufr message length in bytes
26	Day (RDB insertion)
27	Hour (RDB insertion)
28	Minute (RDB insertion)
29	Second (RDB insertion)
30	Day (MDB insertion)
31	Hour MDB insertion)
32	Minute (MDB insertion)
33	Second (MDB insertion)
34	Correction number
35	Part received (for TEMP/PILOT observations)
36	Not used
37	Correction number
38	Part received (for TEMP/PILOT observations)
39	Not used
40	Correction number
41	Part received (for TEMP/PILOT observations)
42	Not used
43	Correction number
44	Part received (for TEMP/PILOT observations)
45	Not used
46	The lowest quality control % confidence

Method

The latitudes and longitudes are unpacked and stored as integers. To get real values apply the following

calculation:

$RLAT1 = (KEY(11) - 9000000)/100000.$

$RLON1 = (KEY(10) - 18000000)/100000.$

$RLAT2 = (KEY(13) - 9000000)/100000.$

$RLON2 = (KEY(12) - 18000000)/100000.$

Externals

BUNPCK - Unpack Bit pattern

BUNPKS - Unpacks bit pattern in repeated way

Reference

None .

3.7.6 Subroutine BUPKEY

Purpose

Packs ECMWF RDB Key into KSEC2 array.

Interface

```
CALL BUPKEY (KEY , KSEC1 , KSEC2 , KERR )
```

where:

- Integer variables are denoted by first letter K.

Input arguments

- KEY - An INTEGER array of 46 words containing unpacked RDB
- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly.
- KSEC2 - An INTEGER array of 4096 words containing Bufr Section 2.

KEY An INTEGER array of 46 words containing unpacked RDB key.

Array index	Word content
1	Length of Section 2 in bytes
2	RDB type
3	RDB subtype
4	Year
5	Month
6	Day
7	Hour
8	Minute
9	Second
10	Longitude 1
10	Latitude 1

continued on next page

continued from previous page

Array index	Word content
12	Longitude 2
13	Latitude 2
14	Number of subsets
15	Ident (numeric as satellite number)
16	Ident (CCITTIA5) one character
17	Ident (CCITTIA5) one character
18	Ident (CCITTIA5) one character
19	Ident (CCITTIA5) one character
20	Ident (CCITTIA5) one character
21	Ident (CCITTIA5) one character
22	Ident (CCITTIA5) one character
23	Ident (CCITTIA5) one character
24	Ident (CCITTIA5) one character
25	Total Bufr message length in bytes
26	Day (RDB insertion)
27	Hour (RDB insertion)
28	Minute (RDB insertion)
29	Second (RDB insertion)
30	Day (MDB insertion)
31	Hour MDB insertion)
32	Minute (MDB insertion)
33	Second (MDB insertion)
34	Correction number
35	Part received (for TEMP/PILOT observations)
36	Not used
37	Correction number
38	Part received (for TEMP/PILOT observations)
39	Not used
40	Correction number
41	Part received (for TEMP/PILOT observations)
42	Not used
43	Correction number
44	Part received (for TEMP/PILOT observations)
45	Not used
46	The lowest quality control % confidence

KSEC1 The content of the KSEC1 array is given in the following Table:

Array index	Word content
1	Length of section 1 in bytes
2	Bufr Edition number (currently 4)
3	Originating centre
4	Update sequence number
5	Flag (presence of Section 2 in the message)
6	Bufr message type (Bufr Table A)
7	Bufr message subtype (local use)
8	Version number of local table used
9	Year
10	Month
11	Day
12	Hour
13	Minute
14	Bufr Master Table used
15	Version number of Master table used
16	Originating sub-centre
17	International sub-category
18	Second
19-	Local ADP centre information (byte by byte)

KSEC2 The content of the KSEC2 array is given in the following Table:

Array index	Word content
1	Length of Section 2 in bytes
2-	Report Data Base key in packed form

Output arguments

- KERR - Error code

Method

The integer values in the KEY array for latitude and longitude must be calculated as:

$$\text{KEY}(10) = \text{NINT}(\text{RLON1} * 100000. + 18000000)$$

$$\text{KEY}(11) = \text{NINT}(\text{RLAT1} * 100000. + 9000000)$$

$$\text{KEY}(12) = \text{NINT}(\text{RLON2} * 100000. + 18000000)$$

$$\text{KEY}(13) = \text{NINT}(\text{RLAT2} * 100000. + 9000000)$$

Externals

 BUPCK - Packs bit pattern

3.7.7 Subroutine *BUXDES*

Purpose

A basic principle in encoding Bufr data is to have a one to one correspondence between data descriptors and the values to be packed.

This routine is a tool to achieve this requirement. It expands Data descriptors and prints unexpanded and expanded lists. The Unexpanded list should be part of Section 3 of the Bufr message and the VALUES array ought to be filled with element values corresponding to the expanded data descriptors.

Interface

```
CALL BUXDES ( K , KSEC1 , KTDLEN , KTDLST , KDLEN , KDATA , KELEM ,  
             KTDEXL , KTDEXP , CNames , CUnits , KERR )
```

where:

- Integer variables are denoted by first letter K.
- Character variables are denoted by first letter C.

Input arguments

- K - An INTEGER variable containing 0 - no print 1 - print
- KSEC1 - An INTEGER array of at least 40 words containing Bufr Section 1 information. When Section 1 contains data for local use, KSEC1 should be sized accordingly. The following words of KSEC1 must be filled:
KSEC1(2) - Bufr Edition number (currently 4) KSEC1(3) - Originating centre KSEC1(8) - Version number of local tables used KSEC1(15) - Version number of Master table used
- KTDLEN - An INTEGER containing number of data descriptors
- KTDLST - An INTEGER array containing data descriptors for Bufr Section 3
- KDLEN - An INTEGER containing dimension of array KDATA
- KDATA - An INTEGER array containing delayed replication factors in the order they appear in the expanded list
- KELEM - An INTEGER containing expected number of expanded elements

Output arguments

- KTDEXL - An INTEGER containing number of expanded elements.
- KTDEXP - An INTEGER array containing list of expanded elements.
- CNAMES - CHARACTER*64 array containing list names of expanded element
- CUNITS -Character*24 array containing list of units for expanded elements
- KERR - Return error code.

Method

None .

Externals

BUETAB - Loads required Bufr tables .

BUEDD - Expands data descriptors

Reference

None .

3.7.8 Subroutine BUBOX

Purpose

The expanded Bufr message can be very lengthy containing many bit maps referring backwards to the data. This routine resolves bit maps for the user, returning two dimensional arrays containing the expanded observation and the corresponding applications (quality controls, statistics, differences e.t.c). Every application appears as a new column. A new data are following each other in the first column, starting with the generating centre/application information.

Interface

```
CALL BUBOX( KSUB , KSUP , KELEM , KWTR , CNames , CUnits , KVALS ,  
           VALUES , KBOX , KAPP , KLEN , KBOXR , VALS , CBOXN , CBOXU , KERR )
```

where:

- Integer variables are denoted by first letter K.
- Real variable are denoted by first letter V.
- Character variables are denoted by first letter C.

Input arguments

- KSUB - An INTEGER containing subset number.
- KSUP - An INTEGER array size 9 containing supplementary information.
- KELEM - An INTEGER variable containing expected number of expanded. elements. It must be the same as used in BUFREX routine previously called.
- KWTR - An INTEGER array containing list of expanded Bufr table B reference numbers (KTDEXP output from BUSEL routine).
- CNames - A CHARACTER*64 array of KELEM words containing element names.
- CUnits - A CHARACTER*24 array of KELEM words containing element units.
- KVALS - An INTEGER variable containing expected number of data values.
- VALUES - A REAL*8 array of KVALS words containing element values.

Output arguments

- KBOX - An INTEGER containing number of elements in first column of box.
- KAPP - An INTEGER containing number of applications
- KLEN - An INTEGER containing max index for number of rows. The next column starts at KLEN +1 element or $\text{index} = i + (\text{KAPP} - 1) * \text{KLEN}$ to address any value in the box.
- KBOXR - An INTEGER array of 80000 containing Bufr table B reference numbers.
- VALS - A REAL*8 array of 80000 containing boxed values.
- CBOXN - A CHARACTER*64 array of 80000 containing boxed element names.
- CBOXU - A CHARACTER*24 array of 80000 containing boxed units.
- KERR - An INTEGER containing error code

Method

The expanded Bufr message is passed in the subroutine to resolve backward reference bit maps associating all applications to the particular element. The output arrays containing boxed data are one dimensional arrays containing information as two dimensional table.

The first column contains in first 6 rows reserved information and the original observation starts at the index 7. Columns 2- KAPP are different generating applications corresponding through bit maps to the data in the column 1. Column 1 contains KLEN elements. Index to the i-th element can be calculated as:

$$\text{index} = i + (\text{KAPP}-1) * \text{KLEN}$$

The first row, columns 2 to KAPP contain quality control operators (222000, 225000 e.t.c) Rows 2 to 6, columns 2 to KAPP contain generating centre, generating application, statistics, incremental update number and minimisation simulation number respectively.

Externals

BUERR - Prints error

Reference

None.

3.7.9 Subroutine *BUPRTBOX*

Purpose

Prints boxed expanded Bufr message.

Interface

```
CALL BUPRTBOX( KBOX , KAPP , KLEN , KBOXR , VALS , CBOXN , CBOXU )
```

Input arguments

- KBOX - An INTEGER containing number of elements in first column of box.
- KAPP - An INTEGER containing number of applications
- KLEN - An INTEGER containing max index for number of rows. The next column starts at KLEN +1 element or index= $i + (KAPP - 1) * KLEN$ to address any value in the box.
- KBOXR - An INTEGER array containing Bufr table B reference numbers.
- VALS - A REAL*8 array containing boxed values.
- CBOXN - A CHARACTER*64 array containing boxed element names.
- CBOXU - A CHARACTER*24 array containing boxed units.

Output arguments

None .

Method

None .

Externals

None .

Reference

None .



3.8 Performance

The speed to decode Bufr messages is proportional to the number of messages. Since the same number of the same kind of observations can be packed into Bufr form in many ways, it is recommended to use multi subsets in compressed form whenever possible. To get the best performance from the software it is recommended that:

- The input file for expansion should contain Bufr messages sorted according to their types.
- Avoid usage of delayed data descriptor replication factors if possible.
- Avoid usage of Operator 203yyy to change reference values.
- Encode data into Bufr form in multi subset compressed form.

Here are some figures of real times used on IBM RS600, single processor computer to expand:

- All conventional data for one analysis cycle (56945 Bufr messages, 197696 subsets) 18 seconds.
- All AIRS data for one analysis cycle (70 Mbytes, 7775 bufr messages with 80563 subsets) 122 seconds.

4 Quality control in BUFR

A quality control information in the Bufr shall be represented using Quality control operators from the Bufr Table C. Table 9 contains definition of possible operators and their usage.

Table 9: Bufr Tables C quality control operators

Table Reference F X	Operand	Operator name	Operation definition
2 22	000	Quality information	The Class 33 quality information which follows relates to the following N fully expanded (including all replications) data descriptors; this operator shall be followed by a replication operator and the data present indicator (031031); the replication factor shall define N, while the bit map defined within the data by the replicated 031031 descriptor shall indicate those elements for which quality control information is given.
2 23	000	Substituted values operator	The substituted values which follow relate to the previous N fully expanded (including all replications) data descriptors; this operator shall be followed by a replication operator and the data present indicator (031031); the replication factor shall define N, while the bit map defined within the data by the replicated 031031 descriptor shall indicate those elements for which substituted values are given
2 23	255	Substituted value marker operator	This operator shall indicate the relative position of the data element in the data stream where the descriptor(s) indicated as relevant by the 031031 descriptor shall have effect. This device allows for additional descriptors (and data) to be placed after the 031031 descriptor (and its associated bit map in the data) without losing the correspondence between the original descriptors and the substituted values.
2 24	000	First order statistical values follow	The statistical values which follow relate to the previous N fully expanded (including all replications) data descriptors; this operator shall be followed by a replication operator and the data present indicator (031031); the replication factor shall define N, while the bit map defined within the data described by the replicated 031031 descriptor shall indicate those elements for which statistical values are given; each statistical value shall be represented in the data according to the scheme described by the corresponding data descriptor, as possibly modified by any operator having scope over that descriptor when first used.

continued on next page

continued from previous page

Table Reference F X	Operand	Operator name	Operation definition
2 24	255	First order statistical values marker operator	This operator shall indicate the relative position of the data element in the data stream where the descriptor(s) indicated as relevant by the 031031 operator shall have effect. This device allows for additional descriptors (and data) to be placed after the 031031 descriptor (and its associated bit map in the data) without losing the correspondence between the original descriptors and the statistical values.
2 25	000	Difference statistical values follow	The statistical values which follow relate to the previous N fully expanded (including all replications) data descriptors; this operator shall be followed by a replication operator and the data present indicator (031031); the replication factor shall define N, while the bit map defined within the data by the replicated 031031 descriptor shall indicate those elements for which statistical values are given; each statistical value shall be represented in the data according to the scheme described by the corresponding data descriptor, as possibly modified by any operator having scope over that descriptor when first used, but with a reference value of $-2n$ and data width of $(n+1)$, where n is the data width given by the original descriptor. This special reference value allows the statistical difference values to be centred around zero.
2 25	255	Difference statistical values marker operator	This operator shall indicate the relative position of the data element in the data stream where the descriptor(s) indicated as relevant by the 031031 operator shall have effect. This device allows for additional descriptors (and data) to be placed after the 031031 descriptor (and its associated bit map in the data) without losing the correspondence between the original descriptors and the statistical values.
2 32	000	Replaced/ retained values follow	The replaced retained values which follows relate to the previous N fully expanded (including all replications) data descriptors; this operator shall be followed by a replication operator and the data present indicator (031031); the replication factor shall define N, while the bit map defined within the data by the replicated 031031 descriptor shall indicate those elements for which replace/retained values are given.

continued on next page

continued from previous page

Table Reference F X	Operand	Operator name	Operation definition
2 32	255	Replaced/retained value marker operator	This operator shall indicate the relative position of the data element in the data stream where the descriptor(s) indicated as relevant by the 031031 operator shall have effect. This device allows for additional descriptors (and data) to be placed after the 031031 descriptor (and its associated bit map in the data) without losing the correspondence between the original descriptors and the replaced/retained values.
2 35	000	Cancel backward data reference	This operator terminates all previously define backward references.
2 36	000	Define backward reference bit map	This operator is used when defining backward reference bit maps which are likely to be reused; this operator shall be followed by a replication operator and the data present indicator (031031); the replication factor shall define N, while the bit map defined within the data by the replicated 031031 descriptor shall indicate the elements selected.
2 37	000	Used defined bit map	This operator may be used instead of the sequence "replication operator followed by data present indicator (031031)"; use of this operator shall indicate that the bit map defined by the operator 236000 be used again.
2 37	255	Cancel use defined bit map	This operator cancels the reuse of a previously defined bit map.



DATA DESCRIPTORS (UNEXPANDED)

1 311001
2 222000
3 101018
4 031031
5 001031
6 001032
7 101018
8 033007
9 001031
10 001032
11 033220
12 033232
13 033222
14 033233
15 235000
16 001031
17 001032
18 007004
19 011003
20 011004
21 010195
22 012001
23 222000
24 236000
25 101005
26 031031
27 001031
28 001032
29 101005
30 033209
31 222000
32 237000
33 001031
34 001032
35 101005
36 033208
37 222000
38 237000
39 001031
40 001032
41 101005
42 033207
43 222000
44 237000
45 001031
46 001032
47 101005
48 033206
49 222000
50 237000
51 001031
52 001032
53 101005
54 033205
55 222000
56 237000
57 001031
58 001032
59 101005
60 033236
61 222000
62 237000
63 001031
64 001032
65 101005
66 033249
67 222000
68 237000
69 001031
70 001032
71 101005
72 033238
73 222000
74 237000
75 001031
76 001032
77 101005
78 033234
79 222000
80 237000
81 001031
82 001032
83 101005
84 033250
85 222000
86 237000
87 001031
88 001032



89 101005
90 033251
91 224000
92 237000
93 001031
94 001032
95 008023
96 101005
97 224255
98 224000
99 237000
100 001031
101 001032
102 008023
103 101005
104 224255
105 224000
106 237000
107 001031
108 001032
109 008023
110 101005
111 224255
112 224000
113 237000
114 001031
115 001032
116 008023
117 101005
118 224255
119 224000
120 237000
121 001031
122 001032
123 008023
124 101005
125 224255
126 225000
127 237000
128 001031
129 001032
130 008024
131 101005
132 225255
133 225000
134 237000
135 001031
136 001032
137 008024
138 033210
139 033211
140 101005
141 225255
142 225000
143 237000
144 001031
145 001032
146 008024
147 033210
148 033211
149 101005
150 225255
151 225000
152 237000
153 001031
154 001032
155 008024
156 033210
157 033211
158 101005
159 225255
160 225000
161 237000
162 001031
163 001032
164 008024
165 033210
166 033211
167 101005
168 225255
169 225000
170 237000
171 001031
172 001032
173 008024
174 033210
175 033211
176 101005
177 225255
178 225000
179 237000
180 001031
181 001032

182 008024
183 033210
184 033211
185 101005
186 225255
187 225000
188 237000
189 001031
190 001032
191 008024
192 033210
193 033211
194 101005
195 225255
196 225000
197 237000
198 001031
199 001032
200 008024
201 033210
202 033211
203 101005
204 225255
205 225000
206 237000
207 001031
208 001032
209 008024
210 033210
211 033211
212 101005
213 225255

DATA DESCRIPTORS (EXPANDED)

1 001006 AIRCRAFT FLIGHT NUMBER
2 002061 AIRCRAFT NAVIGATIONAL SYSTEM
3 004001 YEAR
4 004002 MONTH
5 004003 DAY
6 004004 HOUR
7 004005 MINUTE
8 005001 LATITUDE (HIGH ACCURACY)
9 006001 LONGITUDE (HIGH ACCURACY)
10 008004 PHASE OF AIRCRAFT FLIGHT
11 007002 HEIGHT OR ALTITUDE
12 012001 TEMPERATURE/DRY BULB TEMPERATURE
13 011001 WIND DIRECTION
14 011002 WIND SPEED
15 011031 DEGREE OF TURBULENCE
16 011032 HEIGHT OF BASE OF TURBULENCE
17 011033 HEIGHT OF TOP OF TURBULENCE
18 020041 AIRFRAME ICING
19 222000 QUALITY INFORMATION FOLLOW
20 031031 DATA PRESENT INDICATOR
21 031031 DATA PRESENT INDICATOR
22 031031 DATA PRESENT INDICATOR
23 031031 DATA PRESENT INDICATOR
24 031031 DATA PRESENT INDICATOR
25 031031 DATA PRESENT INDICATOR
26 031031 DATA PRESENT INDICATOR
27 031031 DATA PRESENT INDICATOR
28 031031 DATA PRESENT INDICATOR
29 031031 DATA PRESENT INDICATOR
30 031031 DATA PRESENT INDICATOR
31 031031 DATA PRESENT INDICATOR
32 031031 DATA PRESENT INDICATOR
33 031031 DATA PRESENT INDICATOR
34 031031 DATA PRESENT INDICATOR
35 031031 DATA PRESENT INDICATOR
36 031031 DATA PRESENT INDICATOR
37 031031 DATA PRESENT INDICATOR
38 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
39 001032 GENERATING APPLICATION
40 033007 % CONFIDENCE
41 033007 % CONFIDENCE
42 033007 % CONFIDENCE
43 033007 % CONFIDENCE
44 033007 % CONFIDENCE
45 033007 % CONFIDENCE
46 033007 % CONFIDENCE
47 033007 % CONFIDENCE
48 033007 % CONFIDENCE
49 033007 % CONFIDENCE
50 033007 % CONFIDENCE
51 033007 % CONFIDENCE
52 033007 % CONFIDENCE
53 033007 % CONFIDENCE
54 033007 % CONFIDENCE
55 033007 % CONFIDENCE
56 033007 % CONFIDENCE
57 033007 % CONFIDENCE

```
58 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
59 001032 GENERATING APPLICATION
60 033220 VARIATIONAL ANALYSIS REPORT EVENTS (1)
61 033232 REPORT BLACK LIST EVENTS
62 033222 VARIATIONAL ANALYSIS AIREP EVENTS (2)
63 033233 VARIATIONAL ANALYSIS REPORT STATUS
64 235000 CANCEL BACKWARD DATA REFERENCE
65 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
66 001032 GENERATING APPLICATION
67 007004 PRESSURE
68 011003 U-COMPONENT
69 011004 V-COMPONENT
70 010195 HEIGHT(HIGH ACCURACY)
71 012001 TEMPERATURE/DRY BULB TEMPERATURE
72 222000 QUALITY INFORMATION FOLLOW
73 236000 BACKWARD REFERENCE BIT MAP
74 031031 DATA PRESENT INDICATOR
75 031031 DATA PRESENT INDICATOR
76 031031 DATA PRESENT INDICATOR
77 031031 DATA PRESENT INDICATOR
78 031031 DATA PRESENT INDICATOR
79 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
80 001032 GENERATING APPLICATION
81 033209 VARIATIONAL ANALYSIS FINAL FLAG
82 033209 VARIATIONAL ANALYSIS FINAL FLAG
83 033209 VARIATIONAL ANALYSIS FINAL FLAG
84 033209 VARIATIONAL ANALYSIS FINAL FLAG
85 033209 VARIATIONAL ANALYSIS FINAL FLAG
86 222000 QUALITY INFORMATION FOLLOW
87 237000 USE PREVIOUSLY DEFINED BIT MAP
88 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
89 001032 GENERATING APPLICATION
90 033208 VARIATIONAL ANALYSIS FIRST QUESS CHECK FLAG
91 033208 VARIATIONAL ANALYSIS FIRST QUESS CHECK FLAG
92 033208 VARIATIONAL ANALYSIS FIRST QUESS CHECK FLAG
93 033208 VARIATIONAL ANALYSIS FIRST QUESS CHECK FLAG
94 033208 VARIATIONAL ANALYSIS FIRST QUESS CHECK FLAG
95 222000 QUALITY INFORMATION FOLLOW
96 237000 USE PREVIOUSLY DEFINED BIT MAP
97 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
98 001032 GENERATING APPLICATION
99 033207 VARIATIONAL ANALYSIS DEPARTURE FLAG
100 033207 VARIATIONAL ANALYSIS DEPARTURE FLAG
101 033207 VARIATIONAL ANALYSIS DEPARTURE FLAG
102 033207 VARIATIONAL ANALYSIS DEPARTURE FLAG
103 033207 VARIATIONAL ANALYSIS DEPARTURE FLAG
104 222000 QUALITY INFORMATION FOLLOW
105 237000 USE PREVIOUSLY DEFINED BIT MAP
106 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
107 001032 GENERATING APPLICATION
108 033206 VARIATIONAL ANALYSIS QUALITY CONTROL FLAG
109 033206 VARIATIONAL ANALYSIS QUALITY CONTROL FLAG
110 033206 VARIATIONAL ANALYSIS QUALITY CONTROL FLAG
111 033206 VARIATIONAL ANALYSIS QUALITY CONTROL FLAG
112 033206 VARIATIONAL ANALYSIS QUALITY CONTROL FLAG
113 222000 QUALITY INFORMATION FOLLOW
114 237000 USE PREVIOUSLY DEFINED BIT MAP
115 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
116 001032 GENERATING APPLICATION
117 033205 VARIATIONAL ANALYSIS BLACK LIST FLAG
118 033205 VARIATIONAL ANALYSIS BLACK LIST FLAG
119 033205 VARIATIONAL ANALYSIS BLACK LIST FLAG
120 033205 VARIATIONAL ANALYSIS BLACK LIST FLAG
121 033205 VARIATIONAL ANALYSIS BLACK LIST FLAG
122 222000 QUALITY INFORMATION FOLLOW
123 237000 USE PREVIOUSLY DEFINED BIT MAP
124 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
125 001032 GENERATING APPLICATION
126 033236 VARIATIONAL ANALYSIS DATUM EVENTS (1)
127 033236 VARIATIONAL ANALYSIS DATUM EVENTS (1)
128 033236 VARIATIONAL ANALYSIS DATUM EVENTS (1)
129 033236 VARIATIONAL ANALYSIS DATUM EVENTS (1)
130 033236 VARIATIONAL ANALYSIS DATUM EVENTS (1)
131 222000 QUALITY INFORMATION FOLLOW
132 237000 USE PREVIOUSLY DEFINED BIT MAP
133 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
134 001032 GENERATING APPLICATION
135 033249 DATUM BLACK LIST EVENTS
136 033249 DATUM BLACK LIST EVENTS
137 033249 DATUM BLACK LIST EVENTS
138 033249 DATUM BLACK LIST EVENTS
139 033249 DATUM BLACK LIST EVENTS
140 222000 QUALITY INFORMATION FOLLOW
141 237000 USE PREVIOUSLY DEFINED BIT MAP
142 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
143 001032 GENERATING APPLICATION
144 033238 VARIATIONAL ANALYSIS AIREP DATUM EVENTS (2)
145 033238 VARIATIONAL ANALYSIS AIREP DATUM EVENTS (2)
146 033238 VARIATIONAL ANALYSIS AIREP DATUM EVENTS (2)
147 033238 VARIATIONAL ANALYSIS AIREP DATUM EVENTS (2)
148 033238 VARIATIONAL ANALYSIS AIREP DATUM EVENTS (2)
149 222000 QUALITY INFORMATION FOLLOW
150 237000 USE PREVIOUSLY DEFINED BIT MAP
```

151 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
152 001032 GENERATING APPLICATION
153 033234 VARIATIONAL ANALYSIS DATUM STATUS
154 033234 VARIATIONAL ANALYSIS DATUM STATUS
155 033234 VARIATIONAL ANALYSIS DATUM STATUS
156 033234 VARIATIONAL ANALYSIS DATUM STATUS
157 033234 VARIATIONAL ANALYSIS DATUM STATUS
158 222000 QUALITY INFORMATION FOLLOW
159 237000 USE PREVIOUSLY DEFINED BIT MAP
160 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
161 001032 GENERATING APPLICATION
162 033250 PROBABILITY OF GROSS ERROR
163 033250 PROBABILITY OF GROSS ERROR
164 033250 PROBABILITY OF GROSS ERROR
165 033250 PROBABILITY OF GROSS ERROR
166 033250 PROBABILITY OF GROSS ERROR
167 222000 QUALITY INFORMATION FOLLOW
168 237000 USE PREVIOUSLY DEFINED BIT MAP
169 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
170 001032 GENERATING APPLICATION
171 033251 RANGE OF POSSIBLE VALUES
172 033251 RANGE OF POSSIBLE VALUES
173 033251 RANGE OF POSSIBLE VALUES
174 033251 RANGE OF POSSIBLE VALUES
175 033251 RANGE OF POSSIBLE VALUES
176 224000 FIRST ORDER STATISTICS FOLLOW
177 237000 USE PREVIOUSLY DEFINED BIT MAP
178 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
179 001032 GENERATING APPLICATION
180 008023 FIRST ORDER STATISTICS
181 224255 PRESSURE
182 224255 U-COMPONENT
183 224255 V-COMPONENT
184 224255 HEIGHT(HIGH ACCURACY)
185 224255 TEMPERATURE/DRY BULB TEMPERATURE
186 224000 FIRST ORDER STATISTICS FOLLOW
187 237000 USE PREVIOUSLY DEFINED BIT MAP
188 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
189 001032 GENERATING APPLICATION
190 008023 FIRST ORDER STATISTICS
191 224255 PRESSURE
192 224255 U-COMPONENT
193 224255 V-COMPONENT
194 224255 HEIGHT(HIGH ACCURACY)
195 224255 TEMPERATURE/DRY BULB TEMPERATURE
196 224000 FIRST ORDER STATISTICS FOLLOW
197 237000 USE PREVIOUSLY DEFINED BIT MAP
198 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
199 001032 GENERATING APPLICATION
200 008023 FIRST ORDER STATISTICS
201 224255 PRESSURE
202 224255 U-COMPONENT
203 224255 V-COMPONENT
204 224255 HEIGHT(HIGH ACCURACY)
205 224255 TEMPERATURE/DRY BULB TEMPERATURE
206 224000 FIRST ORDER STATISTICS FOLLOW
207 237000 USE PREVIOUSLY DEFINED BIT MAP
208 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
209 001032 GENERATING APPLICATION
210 008023 FIRST ORDER STATISTICS
211 224255 PRESSURE
212 224255 U-COMPONENT
213 224255 V-COMPONENT
214 224255 HEIGHT(HIGH ACCURACY)
215 224255 TEMPERATURE/DRY BULB TEMPERATURE
216 224000 FIRST ORDER STATISTICS FOLLOW
217 237000 USE PREVIOUSLY DEFINED BIT MAP
218 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
219 001032 GENERATING APPLICATION
220 008023 FIRST ORDER STATISTICS
221 224255 PRESSURE
222 224255 U-COMPONENT
223 224255 V-COMPONENT
224 224255 HEIGHT(HIGH ACCURACY)
225 224255 TEMPERATURE/DRY BULB TEMPERATURE
226 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
227 237000 USE PREVIOUSLY DEFINED BIT MAP
228 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
229 001032 GENERATING APPLICATION
230 008024 DIFFERENCE STATISTICS
231 225255 PRESSURE
232 225255 U-COMPONENT
233 225255 V-COMPONENT
234 225255 HEIGHT(HIGH ACCURACY)
235 225255 TEMPERATURE/DRY BULB TEMPERATURE
236 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
237 237000 USE PREVIOUSLY DEFINED BIT MAP
238 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
239 001032 GENERATING APPLICATION
240 008024 DIFFERENCE STATISTICS
241 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
242 033211 MINIMISATION SIMULATION NUMBER
243 225255 PRESSURE

244 225255 U-COMPONENT
245 225255 V-COMPONENT
246 225255 HEIGHT(HIGH ACCURACY)
247 225255 TEMPERATURE/DRY BULB TEMPERATURE
248 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
249 237000 USE PREVIOUSLY DEFINED BIT MAP
250 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
251 001032 GENERATING APPLICATION
252 008024 DIFFERENCE STATISTICS
253 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
254 033211 MINIMISATION SIMULATION NUMBER
255 225255 PRESSURE
256 225255 U-COMPONENT
257 225255 V-COMPONENT
258 225255 HEIGHT(HIGH ACCURACY)
259 225255 TEMPERATURE/DRY BULB TEMPERATURE
260 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
261 237000 USE PREVIOUSLY DEFINED BIT MAP
262 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
263 001032 GENERATING APPLICATION
264 008024 DIFFERENCE STATISTICS
265 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
266 033211 MINIMISATION SIMULATION NUMBER
267 225255 PRESSURE
268 225255 U-COMPONENT
269 225255 V-COMPONENT
270 225255 HEIGHT(HIGH ACCURACY)
271 225255 TEMPERATURE/DRY BULB TEMPERATURE
272 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
273 237000 USE PREVIOUSLY DEFINED BIT MAP
274 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
275 001032 GENERATING APPLICATION
276 008024 DIFFERENCE STATISTICS
277 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
278 033211 MINIMISATION SIMULATION NUMBER
279 225255 PRESSURE
280 225255 U-COMPONENT
281 225255 V-COMPONENT
282 225255 HEIGHT(HIGH ACCURACY)
283 225255 TEMPERATURE/DRY BULB TEMPERATURE
284 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
285 237000 USE PREVIOUSLY DEFINED BIT MAP
286 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
287 001032 GENERATING APPLICATION
288 008024 DIFFERENCE STATISTICS
289 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
290 033211 MINIMISATION SIMULATION NUMBER
291 225255 PRESSURE
292 225255 U-COMPONENT
293 225255 V-COMPONENT
294 225255 HEIGHT(HIGH ACCURACY)
295 225255 TEMPERATURE/DRY BULB TEMPERATURE
296 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
297 237000 USE PREVIOUSLY DEFINED BIT MAP
298 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
299 001032 GENERATING APPLICATION
300 008024 DIFFERENCE STATISTICS
301 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
302 033211 MINIMISATION SIMULATION NUMBER
303 225255 PRESSURE
304 225255 U-COMPONENT
305 225255 V-COMPONENT
306 225255 HEIGHT(HIGH ACCURACY)
307 225255 TEMPERATURE/DRY BULB TEMPERATURE
308 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
309 237000 USE PREVIOUSLY DEFINED BIT MAP
310 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
311 001032 GENERATING APPLICATION
312 008024 DIFFERENCE STATISTICS
313 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
314 033211 MINIMISATION SIMULATION NUMBER
315 225255 PRESSURE
316 225255 U-COMPONENT
317 225255 V-COMPONENT
318 225255 HEIGHT(HIGH ACCURACY)
319 225255 TEMPERATURE/DRY BULB TEMPERATURE
320 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
321 237000 USE PREVIOUSLY DEFINED BIT MAP
322 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
323 001032 GENERATING APPLICATION
324 008024 DIFFERENCE STATISTICS
325 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
326 033211 MINIMISATION SIMULATION NUMBER
327 225255 PRESSURE
328 225255 U-COMPONENT
329 225255 V-COMPONENT
330 225255 HEIGHT(HIGH ACCURACY)
331 225255 TEMPERATURE/DRY BULB TEMPERATURE
332 225000 DIFFERENCE STATISTICAL VALUES FOLLOW
333 237000 USE PREVIOUSLY DEFINED BIT MAP
334 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
335 001032 GENERATING APPLICATION
336 008024 DIFFERENCE STATISTICS



337 033210 INCREMENTAL VARIATIONAL ANALYSIS UPDATE NUMBER
338 033211 MINIMISATION SIMULATION NUMBER
339 225255 PRESSURE
340 225255 U-COMPONENT
341 225255 V-COMPONENT
342 225255 HEIGHT(HIGH ACCURACY)
343 225255 TEMPERATURE/DRY BULB TEMPERATURE

STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1

1 AIRCRAFT FLIGHT 0.1008000000E+04 CCITTIA5 UAL364
2 AIRCRAFT NAVIGA MISSING CODE TABLE 002061
3 YEAR 0.2004000000E+04 YEAR
4 MONTH 0.5000000000E+01 MONTH
5 DAY 0.2000000000E+02 DAY
6 HOUR 0.3000000000E+01 HOUR
7 MINUTE 0.1000000000E+01 MINUTE
8 LATITUDE (HIGH 0.4015000000E+02 DEGREE
9 LONGITUDE (HIGH -0.9261000000E+02 DEGREE
10 PHASE OF AIRCRA MISSING CODE TABLE 008004
11 HEIGHT OR ALTIT 0.1006000000E+05 M
12 TEMPERATURE/DRY 0.2282000000E+03 K
13 WIND DIRECTION 0.2800000000E+03 DEGREE TRUE
14 WIND SPEED 0.1500000000E+02 M/S
15 DEGREE OF TURBU MISSING CODE TABLE 011031
16 HEIGHT OF BASE MISSING M
17 HEIGHT OF TOP O MISSING M
18 AIRFRAME ICING MISSING CODE TABLE 020041
19 QUALITY INFORMA 0.0000000000E+00
20 DATA PRESENT IN 0.0000000000E+00 NUMERIC
21 DATA PRESENT IN 0.0000000000E+00 NUMERIC
22 DATA PRESENT IN 0.0000000000E+00 NUMERIC
23 DATA PRESENT IN 0.0000000000E+00 NUMERIC
24 DATA PRESENT IN 0.0000000000E+00 NUMERIC
25 DATA PRESENT IN 0.0000000000E+00 NUMERIC
26 DATA PRESENT IN 0.0000000000E+00 NUMERIC
27 DATA PRESENT IN 0.0000000000E+00 NUMERIC
28 DATA PRESENT IN 0.0000000000E+00 NUMERIC
29 DATA PRESENT IN 0.0000000000E+00 NUMERIC
30 DATA PRESENT IN 0.0000000000E+00 NUMERIC
31 DATA PRESENT IN 0.0000000000E+00 NUMERIC
32 DATA PRESENT IN 0.0000000000E+00 NUMERIC
33 DATA PRESENT IN 0.0000000000E+00 NUMERIC
34 DATA PRESENT IN 0.0000000000E+00 NUMERIC
35 DATA PRESENT IN 0.0000000000E+00 NUMERIC
36 DATA PRESENT IN 0.0000000000E+00 NUMERIC
37 DATA PRESENT IN 0.0000000000E+00 NUMERIC
38 IDENTIFICATION 0.9800000000E+02 CODE TABLE 001031
39 GENERATING APPL 0.1000000000E+01 CODE TABLE 001032
40 % CONFIDENCE 0.7000000000E+02 NUMERIC
41 % CONFIDENCE 0.7000000000E+02 NUMERIC
42 % CONFIDENCE 0.7000000000E+02 NUMERIC
43 % CONFIDENCE 0.7000000000E+02 NUMERIC
44 % CONFIDENCE 0.7000000000E+02 NUMERIC
45 % CONFIDENCE 0.7000000000E+02 NUMERIC
46 % CONFIDENCE 0.7000000000E+02 NUMERIC
47 % CONFIDENCE 0.8900000000E+02 NUMERIC
48 % CONFIDENCE 0.8900000000E+02 NUMERIC
49 % CONFIDENCE 0.7000000000E+02 NUMERIC
50 % CONFIDENCE 0.7900000000E+02 NUMERIC
51 % CONFIDENCE 0.7000000000E+02 NUMERIC
52 % CONFIDENCE 0.7000000000E+02 NUMERIC
53 % CONFIDENCE 0.7000000000E+02 NUMERIC
54 % CONFIDENCE 0.7000000000E+02 NUMERIC
55 % CONFIDENCE 0.7000000000E+02 NUMERIC
56 % CONFIDENCE 0.7000000000E+02 NUMERIC
57 % CONFIDENCE 0.7000000000E+02 NUMERIC
58 IDENTIFICATION 0.9800000000E+02 CODE TABLE 001031
59 GENERATING APPL 0.6400000000E+02 CODE TABLE 001032
60 VARIATIONAL ANA 0.4000000000E+01 FLAG TABLE 33220
61 REPORT BLACK LI 0.0000000000E+00 FLAG TABLE 33232
62 VARIATIONAL ANA 0.0000000000E+00 FLAG TABLE 33222
63 VARIATIONAL ANA 0.8000000000E+01 FLAG TABLE 33233
64 CANCEL BACKWARD 0.0000000000E+00
65 IDENTIFICATION 0.9800000000E+02 CODE TABLE 001031
66 GENERATING APPL 0.6500000000E+02 CODE TABLE 001032
67 PRESSURE 0.2622000000E+05 PA
68 U-COMPONENT 0.1480000000E+02 M/S
69 V-COMPONENT -0.2600000000E+01 M/S
70 HEIGHT(HIGH ACC MISSING M
71 TEMPERATURE/DRY 0.2282000000E+03 K
72 QUALITY INFORMA 0.0000000000E+00
73 BACKWARD REFERE 0.0000000000E+00
74 DATA PRESENT IN 0.0000000000E+00 NUMERIC
75 DATA PRESENT IN 0.0000000000E+00 NUMERIC
76 DATA PRESENT IN 0.0000000000E+00 NUMERIC
77 DATA PRESENT IN 0.0000000000E+00 NUMERIC
78 DATA PRESENT IN 0.0000000000E+00 NUMERIC
79 IDENTIFICATION 0.9800000000E+02 CODE TABLE 001031
80 GENERATING APPL 0.6600000000E+02 CODE TABLE 001032
81 VARIATIONAL ANA MISSING CODE TABLE 33209
82 VARIATIONAL ANA 0.0000000000E+00 CODE TABLE 33209



83	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33209
84	VARIATIONAL ANA		MISSING CODE TABLE	33209
85	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33209
86	QUALITY INFORMA	0.0000000000E+00		
87	USE PREVIOUSLY	0.0000000000E+00		
88	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
89	GENERATING APPL	0.6600000000E+02	CODE TABLE	001032
90	VARIATIONAL ANA		MISSING CODE TABLE	033208
91	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	033208
92	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	033208
93	VARIATIONAL ANA		MISSING CODE TABLE	033208
94	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	033208
95	QUALITY INFORMA	0.0000000000E+00		
96	USE PREVIOUSLY	0.0000000000E+00		
97	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
98	GENERATING APPL	0.6600000000E+02	CODE TABLE	001032
99	VARIATIONAL ANA		MISSING CODE TABLE	33207
100	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33207
101	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33207
102	VARIATIONAL ANA		MISSING CODE TABLE	33207
103	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33207
104	QUALITY INFORMA	0.0000000000E+00		
105	USE PREVIOUSLY	0.0000000000E+00		
106	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
107	GENERATING APPL	0.6600000000E+02	CODE TABLE	001032
108	VARIATIONAL ANA		MISSING CODE TABLE	33206
109	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33206
110	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33206
111	VARIATIONAL ANA		MISSING CODE TABLE	33206
112	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33206
113	QUALITY INFORMA	0.0000000000E+00		
114	USE PREVIOUSLY	0.0000000000E+00		
115	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
116	GENERATING APPL	0.6600000000E+02	CODE TABLE	001032
117	VARIATIONAL ANA		MISSING CODE TABLE	33205
118	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33205
119	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33205
120	VARIATIONAL ANA		MISSING CODE TABLE	33205
121	VARIATIONAL ANA	0.0000000000E+00	CODE TABLE	33205
122	QUALITY INFORMA	0.0000000000E+00		
123	USE PREVIOUSLY	0.0000000000E+00		
124	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
125	GENERATING APPL	0.6700000000E+02	CODE TABLE	001032
126	VARIATIONAL ANA		MISSING FLAG TABLE	33236
127	VARIATIONAL ANA	0.2621440000E+06	FLAG TABLE	33236
128	VARIATIONAL ANA	0.2621440000E+06	FLAG TABLE	33236
129	VARIATIONAL ANA		MISSING FLAG TABLE	33236
130	VARIATIONAL ANA	0.2621440000E+06	FLAG TABLE	33236
131	QUALITY INFORMA	0.0000000000E+00		
132	USE PREVIOUSLY	0.0000000000E+00		
133	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
134	GENERATING APPL	0.6700000000E+02	CODE TABLE	001032
135	DATUM BLACK LIS		MISSING FLAG TABLE	33249
136	DATUM BLACK LIS	0.0000000000E+00	FLAG TABLE	33249
137	DATUM BLACK LIS	0.0000000000E+00	FLAG TABLE	33249
138	DATUM BLACK LIS		MISSING FLAG TABLE	33249
139	DATUM BLACK LIS	0.0000000000E+00	FLAG TABLE	33249
140	QUALITY INFORMA	0.0000000000E+00		
141	USE PREVIOUSLY	0.0000000000E+00		
142	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
143	GENERATING APPL	0.6700000000E+02	CODE TABLE	001032
144	VARIATIONAL ANA		MISSING FLAG TABLE	033238
145	VARIATIONAL ANA	0.0000000000E+00	FLAG TABLE	033238
146	VARIATIONAL ANA	0.0000000000E+00	FLAG TABLE	033238
147	VARIATIONAL ANA		MISSING FLAG TABLE	033238
148	VARIATIONAL ANA	0.0000000000E+00	FLAG TABLE	033238
149	QUALITY INFORMA	0.0000000000E+00		
150	USE PREVIOUSLY	0.0000000000E+00		
151	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
152	GENERATING APPL	0.6700000000E+02	CODE TABLE	001032
153	VARIATIONAL ANA		MISSING FLAG TABLE	33234
154	VARIATIONAL ANA	0.8000000000E+01	FLAG TABLE	33234
155	VARIATIONAL ANA	0.8000000000E+01	FLAG TABLE	33234
156	VARIATIONAL ANA		MISSING FLAG TABLE	33234
157	VARIATIONAL ANA	0.8000000000E+01	FLAG TABLE	33234
158	QUALITY INFORMA	0.0000000000E+00		
159	USE PREVIOUSLY	0.0000000000E+00		
160	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
161	GENERATING APPL	0.6500000000E+02	CODE TABLE	001032
162	PROBABILITY OF		MISSING NUMERIC	
163	PROBABILITY OF		MISSING NUMERIC	
164	PROBABILITY OF		MISSING NUMERIC	
165	PROBABILITY OF		MISSING NUMERIC	
166	PROBABILITY OF		MISSING NUMERIC	
167	QUALITY INFORMA	0.0000000000E+00		
168	USE PREVIOUSLY	0.0000000000E+00		
169	IDENTIFICATION	0.9800000000E+02	CODE TABLE	001031
170	GENERATING APPL	0.6500000000E+02	CODE TABLE	001032
171	RANGE OF POSSIB		MISSING NUMERIC	
172	RANGE OF POSSIB	0.5000000000E+01	NUMERIC	
173	RANGE OF POSSIB	0.5000000000E+01	NUMERIC	
174	RANGE OF POSSIB		MISSING NUMERIC	
175	RANGE OF POSSIB	0.5000000000E+01	NUMERIC	



```
176 FIRST ORDER STA      0.0000000000E+00
177 USE PREVIOUSLY      0.0000000000E+00
178 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
179 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
180 FIRST ORDER STA      0.3500000000E+02 CODE TABLE 008023
181 PRESSURE             MISSING PA
182 U-COMPONENT          0.3300000000E+01 M/S
183 V-COMPONENT          0.3300000000E+01 M/S
184 HEIGHT(HIGH ACC     MISSING M
185 TEMPERATURE/DRY     0.1200000000E+01 K
186 FIRST ORDER STA      0.0000000000E+00
187 USE PREVIOUSLY      0.0000000000E+00
188 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
189 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
190 FIRST ORDER STA      0.3300000000E+02 CODE TABLE 008023
191 PRESSURE             MISSING PA
192 U-COMPONENT          0.3300000000E+01 M/S
193 V-COMPONENT          0.3300000000E+01 M/S
194 HEIGHT(HIGH ACC     MISSING M
195 TEMPERATURE/DRY     0.1200000000E+01 K
196 FIRST ORDER STA      0.0000000000E+00
197 USE PREVIOUSLY      0.0000000000E+00
198 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
199 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
200 FIRST ORDER STA      0.3400000000E+02 CODE TABLE 008023
201 PRESSURE             MISSING PA
202 U-COMPONENT          MISSING M/S
203 V-COMPONENT          MISSING M/S
204 HEIGHT(HIGH ACC     MISSING M
205 TEMPERATURE/DRY     MISSING K
206 FIRST ORDER STA      0.0000000000E+00
207 USE PREVIOUSLY      0.0000000000E+00
208 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
209 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
210 FIRST ORDER STA      0.3600000000E+02 CODE TABLE 008023
211 PRESSURE             MISSING PA
212 U-COMPONENT          MISSING M/S
213 V-COMPONENT          MISSING M/S
214 HEIGHT(HIGH ACC     MISSING M
215 TEMPERATURE/DRY     MISSING K
216 FIRST ORDER STA      0.0000000000E+00
217 USE PREVIOUSLY      0.0000000000E+00
218 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
219 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
220 FIRST ORDER STA      0.3200000000E+02 CODE TABLE 008023
221 PRESSURE             MISSING PA
222 U-COMPONENT          0.2000000000E+01 M/S
223 V-COMPONENT          0.2000000000E+01 M/S
224 HEIGHT(HIGH ACC     MISSING M
225 TEMPERATURE/DRY     0.5000000000E+00 K
226 DIFFERENCE STAT     0.0000000000E+00
227 USE PREVIOUSLY      0.0000000000E+00
228 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
229 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
230 DIFFERENCE STAT     0.3200000000E+02 CODE TABLE 008024
231 PRESSURE             MISSING PA
232 U-COMPONENT          -0.1400000000E+01 M/S
233 V-COMPONENT          -0.1000000000E+00 M/S
234 HEIGHT(HIGH ACC     MISSING M
235 TEMPERATURE/DRY     0.1000000000E+00 K
236 DIFFERENCE STAT     0.0000000000E+00
237 USE PREVIOUSLY      0.0000000000E+00
238 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
239 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
240 DIFFERENCE STAT     0.3300000000E+02 CODE TABLE 008024
241 INCREMENTAL VAR     0.1000000000E+01 NUMERIC
242 MINIMISATION SI     0.0000000000E+00 NUMERIC
243 PRESSURE             MISSING PA
244 U-COMPONENT          MISSING M/S
245 V-COMPONENT          MISSING M/S
246 HEIGHT(HIGH ACC     MISSING M
247 TEMPERATURE/DRY     MISSING K
248 DIFFERENCE STAT     0.0000000000E+00
249 USE PREVIOUSLY      0.0000000000E+00
250 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
251 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
252 DIFFERENCE STAT     0.3300000000E+02 CODE TABLE 008024
253 INCREMENTAL VAR     0.1000000000E+01 NUMERIC
254 MINIMISATION SI     0.1001000000E+04 NUMERIC
255 PRESSURE             MISSING PA
256 U-COMPONENT          -0.1400000000E+01 M/S
257 V-COMPONENT          -0.1000000000E+00 M/S
258 HEIGHT(HIGH ACC     MISSING M
259 TEMPERATURE/DRY     0.1000000000E+00 K
260 DIFFERENCE STAT     0.0000000000E+00
261 USE PREVIOUSLY      0.0000000000E+00
262 IDENTIFICATION      0.9800000000E+02 CODE TABLE 001031
263 GENERATING APPL     0.6500000000E+02 CODE TABLE 001032
264 DIFFERENCE STAT     0.3300000000E+02 CODE TABLE 008024
265 INCREMENTAL VAR     0.1000000000E+01 NUMERIC
266 MINIMISATION SI     0.1002000000E+04 NUMERIC
267 PRESSURE             MISSING PA
268 U-COMPONENT          MISSING M/S
```




```

269 V-COMPONENT                MISSING M/S
270 HEIGHT(HIGH ACC           MISSING M
271 TEMPERATURE/DRY          MISSING K
272 DIFFERENCE STAT          0.0000000000E+00
273 USE PREVIOUSLY           0.0000000000E+00
274 IDENTIFICATION            0.9800000000E+02 CODE TABLE 001031
275 GENERATING APPL           0.6500000000E+02 CODE TABLE 001032
276 DIFFERENCE STAT          0.3300000000E+02 CODE TABLE 008024
277 INCREMENTAL VAR          0.1000000000E+01 NUMERIC
278 MINIMISATION SI           0.9990000000E+03 NUMERIC
279 PRESSURE                   MISSING PA
280 U-COMPONENT               MISSING M/S
281 V-COMPONENT               MISSING M/S
282 HEIGHT(HIGH ACC           MISSING M
283 TEMPERATURE/DRY          MISSING K
284 DIFFERENCE STAT          0.0000000000E+00
285 USE PREVIOUSLY           0.0000000000E+00
286 IDENTIFICATION            0.9800000000E+02 CODE TABLE 001031
287 GENERATING APPL           0.6500000000E+02 CODE TABLE 001032
288 DIFFERENCE STAT          0.3300000000E+02 CODE TABLE 008024
289 INCREMENTAL VAR          0.2000000000E+01 NUMERIC
290 MINIMISATION SI           0.0000000000E+00 NUMERIC
291 PRESSURE                   MISSING PA
292 U-COMPONENT               MISSING M/S
293 V-COMPONENT               MISSING M/S
294 HEIGHT(HIGH ACC           MISSING M
295 TEMPERATURE/DRY          MISSING K
296 DIFFERENCE STAT          0.0000000000E+00
297 USE PREVIOUSLY           0.0000000000E+00
298 IDENTIFICATION            0.9800000000E+02 CODE TABLE 001031
299 GENERATING APPL           0.6500000000E+02 CODE TABLE 001032
300 DIFFERENCE STAT          0.3300000000E+02 CODE TABLE 008024
301 INCREMENTAL VAR          0.2000000000E+01 NUMERIC
302 MINIMISATION SI           0.1001000000E+04 NUMERIC
303 PRESSURE                   MISSING PA
304 U-COMPONENT               MISSING M/S
305 V-COMPONENT               MISSING M/S
306 HEIGHT(HIGH ACC           MISSING M
307 TEMPERATURE/DRY          MISSING K
308 DIFFERENCE STAT          0.0000000000E+00
309 USE PREVIOUSLY           0.0000000000E+00
310 IDENTIFICATION            0.9800000000E+02 CODE TABLE 001031
311 GENERATING APPL           0.6500000000E+02 CODE TABLE 001032
312 DIFFERENCE STAT          0.3300000000E+02 CODE TABLE 008024
313 INCREMENTAL VAR          0.2000000000E+01 NUMERIC
314 MINIMISATION SI           0.1002000000E+04 NUMERIC
315 PRESSURE                   MISSING PA
316 U-COMPONENT               MISSING M/S
317 V-COMPONENT               MISSING M/S
318 HEIGHT(HIGH ACC           MISSING M
319 TEMPERATURE/DRY          MISSING K
320 DIFFERENCE STAT          0.0000000000E+00
321 USE PREVIOUSLY           0.0000000000E+00
322 IDENTIFICATION            0.9800000000E+02 CODE TABLE 001031
323 GENERATING APPL           0.6500000000E+02 CODE TABLE 001032
324 DIFFERENCE STAT          0.3300000000E+02 CODE TABLE 008024
325 INCREMENTAL VAR          0.2000000000E+01 NUMERIC
326 MINIMISATION SI           0.9990000000E+03 NUMERIC
327 PRESSURE                   MISSING PA
328 U-COMPONENT               MISSING M/S
329 V-COMPONENT               MISSING M/S
330 HEIGHT(HIGH ACC           MISSING M
331 TEMPERATURE/DRY          MISSING K
332 DIFFERENCE STAT          0.0000000000E+00
333 USE PREVIOUSLY           0.0000000000E+00
334 IDENTIFICATION            0.9800000000E+02 CODE TABLE 001031
335 GENERATING APPL           0.6500000000E+02 CODE TABLE 001032
336 DIFFERENCE STAT          0.3300000000E+02 CODE TABLE 008024
337 INCREMENTAL VAR          0.9000000000E+01 NUMERIC
338 MINIMISATION SI           0.9990000000E+03 NUMERIC
339 PRESSURE                   MISSING PA
340 U-COMPONENT               -0.1400000000E+01 M/S
341 V-COMPONENT               -0.4000000000E+00 M/S
342 HEIGHT(HIGH ACC           MISSING M
343 TEMPERATURE/DRY          0.0000000000E+00 K

```

5 Examples

5.1 To unpack and print data

This program is an interactive version to expand Bufr data. It can decode and encode unpacked data as a single or multi-subset Bufr messages. It calls BUBOX and BUPRTBOX routines to resolve the bit map. The outputs of the expanded AIREP data using Bufr print routines and BUPRTBOX are attached.

```
PROGRAM BUFR
C
C**** *BUFR*
C
C
C PURPOSE.
C -----
C     EXAMPLE OF USING BUFR UNPACKING/PACKING SOFTWARE.
C
C
C** INTERFACE.
C -----
C
C     NONE.
C
C METHOD.
C -----
C
C     NONE.
C
C EXTERNALS.
C -----
C
C     CALL BUSEL2
C     CALL BUFREX
C     CALL BUFREN
C     CALL BUPRS0
C     CALL BUPRS1
C     CALL BUPRS2
C     CALL BUPRS3
C     CALL BUPRT
C     CALL BUUKEY
C
C REFERENCE.
C -----
C
C     NONE.
C
C AUTHOR.
C -----
C
C     M. DRAGOSAVAC *ECMWF* 15/09/87.
C
C MODIFICATIONS.
C -----
C
C     NONE.
C
C IMPLICIT LOGICAL(L,O,G), CHARACTER*8(C,H,Y)
C
C PARAMETER(JSUP = 9,JSEC0= 3,JSEC1= 40,JSEC2=4096,JSEC3= 4,
1 JSEC4=2,JELEM=160000,JSUBS=400,JCVAl=150 ,JBUFL=512000,
2 JBPW = 32,JTAB =3000,JCTAB=3000,JCTST=3000,JCTEXT=6000,
3 JWORK=4096000,JKEY=46, JTMAX=10,JTCLAS=64,JTEL=255)
C
C PARAMETER (KELEM=80000)
C PARAMETER (KVALS=4096000)
C
C DIMENSION KBUF(JBUFL)
C DIMENSION KBUFR(JBUFL)
C DIMENSION KSUP(JSUP) ,KSEC0(JSEC0),KSEC1(JSEC1)
C DIMENSION KSEC2(JSEC2),KSEC3(JSEC3),KSEC4(JSEC4)
C DIMENSION KEY (JKEY),KREQ(2)
C DIMENSION NREQUEST(2)
C
C REAL*8 VALUES(KVALS),VALUE(KVALS)
C DIMENSION KTDLST(JELEM),KTDEXP(JELEM),KRQ(KELEM)
C REAL*8 RQV(KELEM)
C DIMENSION KDATA(200),KBOXR(JELEM*4)
C REAL*8 VALS(KVALS)
C
C CHARACTER*256 CF,COUT,CARG(4)
```

```

CHARACTER*64 CNames(KELEM),CBOXN(JELEM*4)
CHARACTER*24 CUNITS(KELEM),CBOXU(JELEM*4)
CHARACTER*80 CVALS(kelem)
CHARACTER*80 CVAL(kelem)
CHARACTER*80 YENC
REAL*8 RVIND
REAL*8 EPS

C
EXTERNAL GETARG

C
C -----
C*      1. INITIALIZE CONSTANTS AND VARIABLES.
C -----
100 CONTINUE
C
C MISSING VALUE INDICATOR
C
NBYTPW=JBPW/8
RVIND=1.7E38
NVIND=21474834096647
IOBS=0
EPS=10.E-10
NPACK=0
IYEAR=NVIND
N=0
NCOM=0
OO=.FALSE.

C
C
C
C GET INPUT AND OUTPUT FILE NAME.
C
NARG=IARGC()

C
C DO 104 J=1,NARG
CALL GETARG(J,CARG(J))
104 CONTINUE

II=0
IO=0
DO 105 J=1,NARG
IF(CARG(J).EQ.'-i') THEN
  IN=J
ELSEIF(CARG(J).EQ.'-o') THEN
  IO=J
END IF
105 CONTINUE
IF(IN.EQ.0) THEN
  PRINT*,'USAGE -- decode_buftr -i infile'
  STOP
END IF
IF(IO.EQ.0.and.IN.EQ.0) THEN
  PRINT*,'USAGE -- decode_buftr -i infile -o outfile'
  STOP
END IF

C
IF(IO.NE.0) COUT=CARG(IO+1)

C
IF(IO.LT.IN) THEN
  IST=IN+1
  IEND=NARG
ELSE
  IST=IN+1
  IEND=IO-1
END IF

C
IF(IO.NE.0) THEN
  JJ=INDEX(COUT,' ')
  JJ=JJ-1
  CALL PBOPEN(IUNIT1,COUT(1:JJ),'W',IRET)
  IF(IRET.EQ.-1) STOP 'OPEN FAILED ON BUFR.DAT'
  IF(IRET.EQ.-2) STOP 'INVALID FILE NAME'
  IF(IRET.EQ.-3) STOP 'INVALID OPEN MODE SPECIFIED'
END IF

C
DO 101 II=IST,IEND

CF=CARG(II)
ILN=INDEX(CF,' ')
ILN=ILN-1

KRQL=0
NR=0
KREQ(1)=0
KREQ(2)=0
DO 103 I=1,KELEM
  RQV(I)=RVIND
  KRQ(I)=NVIND
103 CONTINUE
C

```

```
C*      1.2 OPEN FILE CONTAINING BUFR DATA.
C      -----
120 CONTINUE
C
      IRET=0
      CALL PBOPEN(IUNIT,CF(1:ILN),'R',IRET)
      IF(IRET.EQ.-1) STOP 'OPEN FAILED'
      IF(IRET.EQ.-2) STOP 'INVALID FILE NAME'
      IF(IRET.EQ.-3) STOP 'INVALID OPEN MODE SPECIFIED'
C
      IF(IO.NE.0) THEN
        CALL PBOPEN(IUNIT1,COUT(1:JJ),'W',IRET)
        IF(IRET.EQ.-1) STOP 'OPEN FAILED ON BUFR.DAT'
        IF(IRET.EQ.-2) STOP 'INVALID FILE NAME'
        IF(IRET.EQ.-3) STOP 'INVALID OPEN MODE SPECIFIED'
      END IF
C
C
C      -----
C*      2. SET REQUEST FOR EXPANSION.
C      -----
200 CONTINUE
C
      OPRT=.FALSE.
      OENC=.FALSE.
      WRITE(*,'(A,$)') ' DO YOU WANT TO PRINT( Y/N ) : '
      READ (*,'(A)') YENC
      IF(YENC(1:1).EQ.'Y'.OR.YENC(1:1).EQ.'y') THEN
        OPRT=.TRUE.
      END IF
      ICODE=0
      WRITE(*,'(A,$)') ' CODE TABLES TO BE PRINTED ( Y/N ) : '
      READ (*,'(A)') YCODC
      IF(YCODC(1:1).EQ.'Y'.OR.YCODC(1:1).EQ.'y') THEN
        ICODE=1
      END IF
      WRITE(*,'(A,$)') ' DO YOU WANT ENCODING( Y/N ) : '
      READ (*,'(A)') YENC
      IF(YENC(1:1).EQ.'Y'.OR.YENC(1:1).EQ.'y') THEN
        OENC=.TRUE.
        WRITE(*,'(A,$)') ' NUMBER OF SUBSETS TO PACK : '
        READ(*,'(BN,I4)') NCOM
        OCOMP=.FALSE.
        WRITE(*,'(A,$)') ' DO YOU WANT COMPRESSION( Y/N ) : '
        READ (*,'(A)') YCOMP
        IF(YCOMP(1:1).EQ.'Y'.OR.YCOMP(1:1).EQ.'y') OCOMP=.TRUE.
      END IF
      WRITE(*,'(A,$)') ' RECORD NUMBER TO START FROM : '
      READ(*,'(BN,I6)') NR
C
201 CONTINUE
C
      WRITE(*,'(A,$)') ' REQUESTED ELEMENT : '
      READ(*,'(BN,I6)') IEL
      WRITE(*,'(A,$)') ' REQUESTED VALUE : '
      READ(*,'(BN,F12.2)') VAL
      IF(IEL.EQ.0) THEN
        KRQL=J
      ELSE
        J=J+1
        KRQ(J)=IEL
        RQV(J)=VAL
        IF(VAL.EQ.0.) RQV(J)=RVIND
        GO TO 201
      END IF
C
      WRITE(*,'(A,$)') ' REQUESTED FLAG 1 : '
      READ(*,'(BN,I6)') KREQ(1)
C
      WRITE(*,'(A,$)') ' REQUESTED FLAG 2 : '
      READ(*,'(BN,I6)') KREQ(2)
C
      WRITE(*,'(A,$)') ' DO YOU WANT TO PRINT SECTION 0-3( Y/N ) : '
      READ (*,'(A,$)') YENC
      OSEC3=.FALSE.
      IF(YENC(1:1).EQ.'Y'.OR.YENC(1:1).EQ.'y') OSEC3=.TRUE.
C
C*      2.1 SET REQUEST FOR PARTIAL EXPANSION.
C      -----
210 CONTINUE
C
      IERR=0
      CALL BUSRQ(KREQ,KRQL,KRQ,RQV,IERR)
C
      SET VARIABLE TO PACK BIG VALUES AS MISSING VALUE INDICATOR
C
      KPMISS=1
      KPRUS=0
      KOKEY=0
      CALL BUPRQ(KPMISS,KPRUS,KOKEY)
C
```

```

C -----
C IF(NCOM.NE.0) THEN
C   KEL1=KVALS/NCOM
C   IF(KEL1.GT.KELEM) KEL1=KELEM
C END IF
C
C*   3. READ BUFR MESSAGE.
C -----
C 300 CONTINUE
C
C   IERR=0
C   KBUFL=0
C
C CALL PBBUFR(IUNIT,KBUFF,JBYTE*4,KBUFL,IERR)
C IF(IERR.EQ.-1) THEN
C   IF(NPACK.NE.0) GO TO 600
C   PRINT*,'NUMBER OF SUBSETS      ',IOBS
C   PRINT*,'NUMBER OF MESSAGES    ',N
C   STOP 'EOF'
C END IF
C IF(IERR.EQ.-2) STOP 'FILE HANDLING PROBLEM'
C IF(IERR.EQ.-3) STOP 'ARRAY TOO SMALL FOR PRODUCT'
C
C   N=N+1
C   PRINT*,'-----',N,' ',KBUFL
C   KBUFL=KBUFL/NBYTPW+1
C   IF(N.LT.NR) GO TO 300
C
C -----
C*   4. EXPAND BUFR MESSAGE.
C -----
C 400 CONTINUE
C
C CALL BUS0123( KBUFL,KBUFF,KSUP,KSEC0,KSEC1,KSEC2,KSEC3,IERR)
C IF(IERR.NE.0) THEN
C   PRINT*,'ERROR IN BUS012: ',IERR
C   PRINT*,' BUFR MESSAGE NUMBER ',N,' CORRUPTED.'
C   IERR=0
C   GO TO 300
C END IF
C
C   KEL=KVALS/KSEC3(3)
C   IF(KEL.GT.KELEM) KEL=KELEM
C
C CALL BUFREX(KBUFL,KBUFF,KSUP,KSEC0 ,KSEC1,KSEC2 ,KSEC3 ,KSEC4,
C 1   KEL,CNAMES,CUNITS,KVALS,VALUES,CVALS,IERR)
C
C IF(IERR.NE.0) THEN
C   CALL EXIT(2)
C END IF
C
C
C   IOBS=IOBS+KSEC3(3)
C
C   ISUBSET=1
C   CALL BUSEL2(ISUBSET,KEL,KTDLN,KTDLST,KTDEXL,KTDEXP,CNAMES,
C 1   CUNITS,IERR)
C IF(IERR.NE.0) CALL EXIT(2)
C
C
C   DO 401 IK=1,KSEC3(3)
C
C     CALL BUSEL2(IK,KEL,KTDLN,KTDLST,KTDEXL,KTDEXP,CNAMES,
C 1     CUNITS,IERR)
C     KSEP(5)=KTDEXL
C     CALL BUBOX(IK,KSUP,KEL,KTDEXP,CNAMES,CUNITS,KVALS,VALUES,
C 1     KBOX,KAPP,KLEN,KBOXR,VALS,CBOXN,CBOXU,IERR)
C
C 401 CONTINUE
C
C
C*   4.1 PRINT CONTENT OF EXPANDED DATA.
C -----
C 410 CONTINUE
C
C   IF(.NOT.OPRT) GO TO 500
C   IF(.NOT.OSEC3) GO TO 450
C
C*   4.2 PRINT SECTION ZERO OF BUFR MESSAGE.
C -----
C 420 CONTINUE
C
C   CALL BUPRS0(KSEC0)
C
C*   4.3 PRINT SECTION ONE OF BUFR MESSAGE.
C -----
C 430 CONTINUE
C
C   CALL BUPRS1(KSEC1)
C
C

```

```
C*      4.4 PRINT SECTION TWO OF BUFR MESSAGE.
C      -----
C 440 CONTINUE
C
C      AT ECMWF SECTION 2 CONTAINS RDB KEY.
C      SO UNPACK KEY
C
C      CALL BUUKEY(KSEC1,KSEC2,KEY,KSUP,IERR)
C
C      PRINT KEY
C
C      CALL BUPRS2(KSUP ,KEY)
C
C*      4.5 PRINT SECTION 3 OF BUFR MESSAGE.
C      -----
C 450 CONTINUE
C
C      FIRST GET DATA DESCRIPTORS
C
C      Multi subset uncompressed data descriptors for the 1st subset
C      Each subset can contain completely different list of expanded
C      descriptors
C
C      ISUBSET=1
C      CALL BUSEL2(ISUBSET,KEL,KTDLLEN,KTDLST,KTDEXL,KTDEXP,CNAMES,
1         CUNITS,IERR)
C      IF(IERR.NE.0) CALL EXIT(2)
C
C      PRINT CONTENT
C
C      IF(OSEC3) THEN
C          CALL BUPRS3(KSEC3,KTDLLEN,KTDLST,KTDEXL,KTDEXP,KEL,CNAMES)
C      END IF
C
C*      4.6 PRINT SECTION 4 (DATA).
C      -----
C 460 CONTINUE
C
C      IN THE CASE OF MANY SUBSETS DEFINE RANGE OF SUBSETS
C
C      IF(.NOT.OO) THEN
C          WRITE(*,'(A,$)') ' STARTING SUBSET TO BE PRINTED : '
C          READ(*,'(BN,I4)') IST
C          WRITE(*,'(A,$)') ' ENDING SUBSET TO BE PRINTED : '
C          READ(*,'(BN,I4)') IEND
C          OO=.FALSE.
C      END IF
C
C      PRINT DATA
C
C      ICODE=0
C
C      IF(KSEC1(6).EQ.11) THEN
C
C          IST=1
C          IEND=KSEC3(3)
C
C          CALL BUPRT(ICODE,IST,IEND,KEL,CNAMES,CUNITS,CVALS,
1         KVALS,VALUES,KSUP,KSEC1,IERR)
C      ELSE
C
C          RESOLVE BIT MAPS FOR EACH SUBSET
C
C          ist=1
C          iend=ksec3(3)
C
C          IF(IEND.GT.KSEC3(3)) IEND=KSEC3(3)
C
C          DO 461 IK=IST,IEND
C
C          CALL BUSEL2(IK,KEL,KTDLLEN,KTDLST,KTDEXL,KTDEXP,CNAMES,
1         CUNITS,IERR)
C
C          KSUP(5)=KTDEXL
C          CALL BUBOX(IK,KSUP,KEL,KTDEXP,CNAMES,CUNITS,KVALS,VALUES,
1         KBOX,KAPP,KLEN,KBOXR,VALS,CBOXN,CBOXU,IERR)
C          IF(IERR.NE.0) CALL EXIT(2)
C
C          CALL BUPRTBOX(KBOX,KAPP,KLEN,KBOXR,VALS,CBOXN,CBOXU)
C 461 CONTINUE
C      END IF
C
C      -----
C*      5. COLLECT DATA FOR REPACKING.
C      -----
C 500 CONTINUE
C
C
C      IF(.NOT.OENC) GO TO 300
C
C      ISUBS=KSEC3(3)
C      DO J=1,ISUBS
```

```

C
NPACK=NPACK+1
C
C      FIRST GET DATA DESCRIPTORS
C
CALL BUSEL2(J,KEL,KTDLN,KTDLST,KTDEXL,KTDEXP,CNAMES,
1      CUNITS,IERR)
IF(IERR.NE.0) CALL EXIT(2)
C
DO I=1,KTDEXL
IO=I+(NPACK-1)*KEL
IN=I+(J-1)*KEL
C
IF(CUNITS(I).EQ.'CCITIA5') THEN
IPOS =VALUES(IN)/1000.
ICH=NINT(VALUES(IN)-IPOS*1000)
KKK=KKK+1
VALUE(IO)=KKK*1000+ICH
CVAL(KKK)=CVALS(IPOS)
ELSE
VALUE(IO)=VALUES(IN)
END IF
IF(KTDEXP(I).EQ.31001.OR.KTDEXP(I).EQ.31002) THEN
KK=KK+1
KDATA(KK)=NINT(VALUE(IO))
END IF
IF(KTDEXP(I).EQ.004001) THEN
IF(IYEAR.EQ.NVIND) THEN
IYEAR=NINT(VALUE(IO))
END IF
END IF
END DO
C
KDLN=KK
IF(NPACK.EQ.NCOM) THEN
KSEC3(3)=NPACK
KSEC1(5)=0
KSEC1(8)=1
KSEC1(15)=12
IF(KSEC0(3).LT.4) THEN
KSEC1(17)=255
KSEC1(18)=0
END IF
KSEC0(3)=4      ! EDITION 4 OF BUFR MESSAGE
IF(KSEC0(3).GE.4) KSEC1(1)=22
KSEC3(4)=0      ! NO COMPRESSION
IF(KSEC1(9).LT.101) THEN
KSEC1(9)=IYEAR
END IF
IF(OCOMP) KSEC3(4)=64 ! COMPRESSION
KBUFL=JBUFL
CALL BUFREN( KSEC0,KSEC1,KSEC2,KSEC3,KSEC4,
1      KTDLEN,KTDLST,KDLN,KDATA,KEL1,
2      KVALS,VALUE,CVAL,KBUFL,KBUFR,IERR)
IF(IERR.NE.0) THEN
PRINT*,'ERROR IS ',IERR
PRINT*,'ERROR DURING ENCODING.'
CALL EXIT(2)
END IF
C
ILEN=KBUFL*NBYTPW
C
IERR=0
C
CALL PBWRITE(IUNIT1,KBUFR,ILEN,IERR)
IF(IERR.LT.0) THEN
PRINT*,'ERROR WRITING INTO TARGET FILE.'
CALL EXIT(2)
END IF
PRINT*,'RECORD WRITTEN INTO FILE '
C
NPACK=0
KKK=0
KK=0
END IF
C
END DO
C
GO TO 300
C
-----
C*      6. PACK BUFR MESSAGE BACK INTO BUFR.
C      -----
600 CONTINUE
C
KSEC3(3)=NPACK
KSEC1(8)=1
KSEC1(15)=12
KSEC0(3)=4      ! EDITION 4 OF BUFR MESSAGE
IF(KSEC0(3).GE.4) KSEC1(1)=22

```

```
IF(KSECO(3).LT.4) THEN
  KSECL(17)=255
  KSECL(18)=0
END IF

KSEC3(4)=0          ! NO COMPRESSION
IF(KSECL(9).LT.101) THEN
  KSECL(9)=IYEAR
END IF

C
IF(OCOMP) KSEC3(4)=64 ! COMPRESSION
KBUFL=JBUFL

C
C
C*      6.2 ENCODE DATA INTO BUFR MESSAGE.
C      -----
620 CONTINUE
C
CALL BUFREN( KSECO,KSECL,KSEC2,KSEC3,KSEC4,
1           KTDLEN,KTDLST,KDLEN,KDATA,KELL,
2           KVALS,VALUE,CVAL,KBUFL,KBUFR,IERR)
IF(IERR.NE.0) THEN
  PRINT*,'ERROR IS ',IERR
  PRINT*,'ERROR DURING ENCODING.'
  CALL EXIT(2)
END IF

C
C      6.3 WRITE PACKED BUFR MESSAGE INTO FILE.
C      -----
630 CONTINUE
C
ILEN=KBUFL*NBYTPW

CALL PBWRITE(IUNIT1,KBUFR,ILEN,IERR)
IF(IERR.LT.0) THEN
  PRINT*,'ERROR WRITING INTO TARGET FILE.'
  CALL EXIT(2)
END IF
PRINT*,'RECORD WRITTEN INTO FILE '

C
NPACK=0
KKK=0

GO TO 300
-----
810 CONTINUE
C
WRITE*,'(1H ,A)' 'OPEN ERROR ON INPUT FILE'
GO TO 900

C
800 CONTINUE
C
IF(IRET.EQ.-1) THEN
  PRINT*,'NUMBER OF RECORDS PROCESSED ',N
  PRINT*,'NUMBER OF OBSERVATIONS      ',IOBS
ELSE
  PRINT*,' BUFR : ERROR= ',IERR
END IF

C
900 CONTINUE
C
CALL PBCLOSE(IUNIT,IRET)
101 CONTINUE
CALL PBCLOSE(IUNIT1,IRET)

C
END
```




This is an example of the expanded AIREP data containing quality control information.

```

ECMWF

BUFR DECODING SOFTWARE VERSION - 7.1
07 June 2005.

Your path for bufr tables is :
/home/ma/maa/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables
BUFR TABLES TO BE LOADED B0000000000098006001,D0000000000098006001
1
  BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)      8
TOTAL LENGTH OF BUFR MESSAGE (BYTES) 162
BUFR EDITION NUMBER              3
1
  BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)      18
BUFR EDITION NUMBER              3
ORIGINATING SUB-CENTRE           0
ORIGINATING CENTRE               98
UPDATE SEQUENCE NUMBER           1
FLAG (PRESENCE OF SECTION 2)    128
BUFR MESSAGE TYPE                 4
BUFR MESSAGE SUBTYPE             142
VERSION NUMBER OF LOCAL TABLE   1
YEAR                              5
MONTH                             5
DAY                               9
HOUR                             9
MINUTE                           6
VERSION NUMBER OF MASTER TABLE  6
BUFR MASTER TABLE               0
1
  BUFR SECTION 2

LENGTH OF SECTION 2              52

  REPORT DATA BASE KEY

RDB DATA TYPE                    7
RDB DATA SUBTYPE                 142
YEAR                             2005
MONTH                             5
DAY                               9
HOUR                             9
MINUTE                           6
SECOND                           4
LATITUDE 1                        23.50
LONGITUDE 1                       -62.55
IDENTIFIER                        DRD0872
TOTAL BUFR MESSAGE LENGTH         162
DAY (RDB INSERTION)                9
HOUR (RDB INSERTION)               9
MINUTE (RDB INSERTION)             28
SECOND (RDB INSERTION)             17
DAY (MDB ARRIVAL)                  9
HOUR (MDB ARRIVAL)                 9
MINUTE (MDB ARRIVAL)              24
SECOND (MDB ARRIVAL)               8
CORRECTION NUMBER                  0
PART OF MESSAGE                    1
CORRECTION NUMBER                  0
PART OF MESSAGE                    0
CORRECTION NUMBER                  0
PART OF MESSAGE                    0
CORRECTION NUMBER                  0
PART OF MESSAGE                    0
CORRECTION NUMBER                  0
PART OF MESSAGE                    0
CORRECTION NUMBER                  0
PART OF MESSAGE                    0
QUALITY CONTROL % CONF             70
1
  BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)      24
RESERVED                          0
NUMBER OF DATA SUBSETS           1
FLAG (DATA TYPE/DATA COMPRESSION) 128

  DATA DESCRIPTORS (UNEXPANDED)

1 311001
2 222000
3 101018
4 031031
5 001031

```

6 001032
7 101018
8 033007

DATA DESCRIPTORS (EXPANDED)

1 001006 AIRCRAFT FLIGHT NUMBER
2 002061 AIRCRAFT NAVIGATIONAL SYSTEM
3 004001 YEAR
4 004002 MONTH
5 004003 DAY
6 004004 HOUR
7 004005 MINUTE
8 005001 LATITUDE (HIGH ACCURACY)
9 006001 LONGITUDE (HIGH ACCURACY)
10 008004 PHASE OF AIRCRAFT FLIGHT
11 007002 HEIGHT OR ALTITUDE
12 012001 TEMPERATURE/DRY BULB TEMPERATURE
13 011001 WIND DIRECTION
14 011002 WIND SPEED
15 011031 DEGREE OF TURBULENCE
16 011032 HEIGHT OF BASE OF TURBULENCE
17 011033 HEIGHT OF TOP OF TURBULENCE
18 020041 AIRFRAME ICING
19 222000 QUALITY INFORMATION FOLLOW
20 031031 DATA PRESENT INDICATOR
21 031031 DATA PRESENT INDICATOR
22 031031 DATA PRESENT INDICATOR
23 031031 DATA PRESENT INDICATOR
24 031031 DATA PRESENT INDICATOR
25 031031 DATA PRESENT INDICATOR
26 031031 DATA PRESENT INDICATOR
27 031031 DATA PRESENT INDICATOR
28 031031 DATA PRESENT INDICATOR
29 031031 DATA PRESENT INDICATOR
30 031031 DATA PRESENT INDICATOR
31 031031 DATA PRESENT INDICATOR
32 031031 DATA PRESENT INDICATOR
33 031031 DATA PRESENT INDICATOR
34 031031 DATA PRESENT INDICATOR
35 031031 DATA PRESENT INDICATOR
36 031031 DATA PRESENT INDICATOR
37 031031 DATA PRESENT INDICATOR
38 001031 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
39 001032 GENERATING APPLICATION
40 033007 % CONFIDENCE
41 033007 % CONFIDENCE
42 033007 % CONFIDENCE
43 033007 % CONFIDENCE
44 033007 % CONFIDENCE
45 033007 % CONFIDENCE
46 033007 % CONFIDENCE
47 033007 % CONFIDENCE
48 033007 % CONFIDENCE
49 033007 % CONFIDENCE
50 033007 % CONFIDENCE
51 033007 % CONFIDENCE
52 033007 % CONFIDENCE
53 033007 % CONFIDENCE
54 033007 % CONFIDENCE
55 033007 % CONFIDENCE
56 033007 % CONFIDENCE
57 033007 % CONFIDENCE

STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1

1 AIRCRAFT FLIGHT	0.10080000000E+04	CCITTIA5	DRD0872
2 AIRCRAFT NAVIGA		MISSING CODE TABLE 002061	
3 YEAR	0.20050000000E+04	YEAR	
4 MONTH	0.50000000000E+01	MONTH	
5 DAY	0.90000000000E+01	DAY	
6 HOUR	0.90000000000E+01	HOUR	
7 MINUTE	0.60000000000E+01	MINUTE	
8 LATITUDE (HIGH	0.23500000000E+02	DEGREE	
9 LONGITUDE (HIGH	-0.62550000000E+02	DEGREE	
10 PHASE OF AIRCRA		MISSING CODE TABLE 008004	
11 HEIGHT OR ALTIT	0.12190000000E+05	M	
12 TEMPERATURE/DRY	0.21320000000E+03	K	
13 WIND DIRECTION	0.25500000000E+03	DEGREE TRUE	
14 WIND SPEED	0.41000000000E+02	M/S	
15 DEGREE OF TURBU		MISSING CODE TABLE 011031	
16 HEIGHT OF BASE		MISSING M	
17 HEIGHT OF TOP O		MISSING M	
18 AIRFRAME ICING		MISSING CODE TABLE 020041	
19 QUALITY INFORMA	0.00000000000E+00		
20 DATA PRESENT IN	0.00000000000E+00	NUMERIC	
21 DATA PRESENT IN	0.00000000000E+00	NUMERIC	
22 DATA PRESENT IN	0.00000000000E+00	NUMERIC	
23 DATA PRESENT IN	0.00000000000E+00	NUMERIC	
24 DATA PRESENT IN	0.00000000000E+00	NUMERIC	
25 DATA PRESENT IN	0.00000000000E+00	NUMERIC	



```

26 DATA PRESENT IN      0.0000000000E+00 NUMERIC
27 DATA PRESENT IN      0.0000000000E+00 NUMERIC
28 DATA PRESENT IN      0.0000000000E+00 NUMERIC
29 DATA PRESENT IN      0.0000000000E+00 NUMERIC
30 DATA PRESENT IN      0.0000000000E+00 NUMERIC
31 DATA PRESENT IN      0.0000000000E+00 NUMERIC
32 DATA PRESENT IN      0.0000000000E+00 NUMERIC
33 DATA PRESENT IN      0.0000000000E+00 NUMERIC
34 DATA PRESENT IN      0.0000000000E+00 NUMERIC
35 DATA PRESENT IN      0.0000000000E+00 NUMERIC
36 DATA PRESENT IN      0.0000000000E+00 NUMERIC
37 DATA PRESENT IN      0.0000000000E+00 NUMERIC
38 IDENTIFICATION        0.9800000000E+02 CODE TABLE 001031
39 GENERATING APPL       0.1000000000E+01 CODE TABLE 001032
40 % CONFIDENCE           0.7000000000E+02 NUMERIC
41 % CONFIDENCE           0.7000000000E+02 NUMERIC
42 % CONFIDENCE           0.7000000000E+02 NUMERIC
43 % CONFIDENCE           0.7000000000E+02 NUMERIC
44 % CONFIDENCE           0.7000000000E+02 NUMERIC
45 % CONFIDENCE           0.7000000000E+02 NUMERIC
46 % CONFIDENCE           0.7000000000E+02 NUMERIC
47 % CONFIDENCE           0.7000000000E+02 NUMERIC
48 % CONFIDENCE           0.7000000000E+02 NUMERIC
49 % CONFIDENCE           0.7000000000E+02 NUMERIC
50 % CONFIDENCE           0.7900000000E+02 NUMERIC
51 % CONFIDENCE           0.7000000000E+02 NUMERIC
52 % CONFIDENCE           0.7000000000E+02 NUMERIC
53 % CONFIDENCE           0.7000000000E+02 NUMERIC
54 % CONFIDENCE           0.7000000000E+02 NUMERIC
55 % CONFIDENCE           0.7000000000E+02 NUMERIC
56 % CONFIDENCE           0.7000000000E+02 NUMERIC
57 % CONFIDENCE           0.7000000000E+02 NUMERIC

```

Output of the AIREP data after calling BUBOX and BUPRTBOX routines.

```

1 OPERATOR                ***** 222000.0
2 GENERATING CENTRE( CODE TABLE 00 ***** 98.0
3 GENERATING APPLICATION (CODE TAB ***** 1.0
4 STATISTICS (008024/008023) *****
5 INCREMENTAL UPDATE NUMBER *****
6 MINIMISATION SIMULATION NUMBER *****
7 AIRCRAFT FLIGHT NUMBER      1008.0 70.0
8 AIRCRAFT NAVIGATIONAL SYSTEM ***** 70.0
9 YEAR                      2005.0 70.0
10 MONTH                     5.0 70.0
11 DAY                        9.0 70.0
12 HOUR                       9.0 70.0
13 MINUTE                      6.0 70.0
14 LATITUDE (HIGH ACCURACY)    23.5 70.0
15 LONGITUDE (HIGH ACCURACY)   -62.5 70.0
16 PHASE OF AIRCRAFT FLIGHT ***** 70.0
17 HEIGHT OR ALTITUDE          12190.0 79.0
18 TEMPERATURE/DRY BULB TEMPERATURE 213.2 70.0
19 WIND DIRECTION              255.0 70.0
20 WIND SPEED                   41.0 70.0
21 DEGREE OF TURBULENCE ***** 70.0
22 HEIGHT OF BASE OF TURBULENCE ***** 70.0
23 HEIGHT OF TOP OF TURBULENCE ***** 70.0
24 AIRFRAME ICING              ***** 70.0

```



An example of Bufr edition 4 data:

```
ECMWF

BUFR DECODING SOFTWARE VERSION - 7.1
07 January 2005.

Your path for bufr tables is :
/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables/
BUFR TABLES TO BE LOADED B0000000000098012001,D0000000000098012001
1
    BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)          8
TOTAL LENGTH OF BUFR MESSAGE (BYTES) 332
BUFR EDITION NUMBER                   4
1
    BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)          22
BUFR MASTER TABLE                    0
ORIGINATING CENTRE                    98
ORIGINATING SUB-CENTRE                 0
UPDATE SEQUENCE NUMBER                 1
FLAG (PRESENCE OF SECTION 2)          0
DATA CATEGORY                           0
DATA SUB-CATEGORY                       0
LOCAL DATA SUB-CATEGORU               1
VERSION NUMBER OF MASTER TABLE        12
VERSION NUMBER OF LOCAL TABLE         1
YEAR                                   2005
MONTH                                  12
DAY                                    1
HOUR                                   12
MINUTE                                 0
SECOND                                 0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.
1
    BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)          148
RESERVED                               0
NUMBER OF DATA SUBSETS                1
FLAG (DATA TYPE/DATA COMPRESSION)      0

DATA DESCRIPTORS (UNEXPANDED)

1 301001
2 001011
3 001003
4 002001
5 301011
6 301012
7 301021
8 007030
9 007031
10 302001
11 007004
12 010009
13 007032
14 012101
15 012103
16 013003
17 007032
18 020001
19 007032
20 013023
21 007032
22 302004
23 101004
24 302005
25 105003
26 008002
27 020011
28 020012
29 020014
30 020017
31 020062
32 013013
33 012113
34 020003
35 004024
36 020004
```

37 020005
 38 004024
 39 002004
 40 013033
 41 004024
 42 014031
 43 004025
 44 014002
 45 014004
 46 014016
 47 014028
 48 014029
 49 014030
 50 007032
 51 102002
 52 004024
 53 013011
 54 007032
 55 101002
 56 004024
 57 012111
 58 004024
 59 012112
 60 007032
 61 002002
 62 008021
 63 004025
 64 011001
 65 011002
 66 008021
 67 103002
 68 004025
 69 011043
 70 011041

DATA DESCRIPTORS (EXPANDED)

1 001001 WMO BLOCK NUMBER
 2 001002 WMO STATION NUMBER
 3 001011 SHIP OR MOBILE LAND STATION IDENTIFIER
 4 001003 WMO REGION NUMBER/GEOGRAPHICAL AREA
 5 002001 TYPE OF STATION
 6 004001 YEAR
 7 004002 MONTH
 8 004003 DAY
 9 004004 HOUR
 10 004005 MINUTE
 11 005001 LATITUDE (HIGH ACCURACY)
 12 006001 LONGITUDE (HIGH ACCURACY)
 13 007030 HEIGHT OF STATION GROUND ABOVE MEAN SEA LEVEL (SEE NOTE 3)
 14 007031 HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL (SEE NOTE 4)
 15 010004 PRESSURE
 16 010051 PRESSURE REDUCED TO MEAN SEA LEVEL
 17 010061 3-HOUR PRESSURE CHANGE
 18 010063 CHARACTERISTIC OF PRESSURE TENDENCY
 19 007004 PRESSURE
 20 010009 GEOPOTENTIAL HEIGHT
 21 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 22 012101 TEMPERATURE/DRY-BULB TEMPERATURE
 23 012103 DEW-POINT TEMPERATURE
 24 013003 RELATIVE HUMIDITY
 25 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 26 020001 HORIZONTAL VISIBILITY
 27 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 28 013023 TOTAL PRECIPITATION PAST 24 HOURS
 29 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 30 020010 CLOUD COVER (TOTAL)
 31 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
 32 020011 CLOUD AMOUNT
 33 020013 HEIGHT OF BASE OF CLOUD
 34 020012 CLOUD TYPE
 35 020012 CLOUD TYPE
 36 020012 CLOUD TYPE
 37 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
 38 020011 CLOUD AMOUNT
 39 020012 CLOUD TYPE
 40 020013 HEIGHT OF BASE OF CLOUD
 41 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
 42 020011 CLOUD AMOUNT
 43 020012 CLOUD TYPE
 44 020013 HEIGHT OF BASE OF CLOUD
 45 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
 46 020011 CLOUD AMOUNT
 47 020012 CLOUD TYPE
 48 020013 HEIGHT OF BASE OF CLOUD
 49 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
 50 020011 CLOUD AMOUNT
 51 020012 CLOUD TYPE
 52 020013 HEIGHT OF BASE OF CLOUD
 53 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
 54 020011 CLOUD AMOUNT
 55 020012 CLOUD TYPE



56 020014 HEIGHT OF TOP OF CLOUD
57 020017 CLOUD TOP DESCRIPTION
58 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
59 020011 CLOUD AMOUNT
60 020012 CLOUD TYPE
61 020014 HEIGHT OF TOP OF CLOUD
62 020017 CLOUD TOP DESCRIPTION
63 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
64 020011 CLOUD AMOUNT
65 020012 CLOUD TYPE
66 020014 HEIGHT OF TOP OF CLOUD
67 020017 CLOUD TOP DESCRIPTION
68 020062 STATE OF THE GROUND (WITH OR WITHOUT SNOW)
69 013013 TOTAL SNOW DEPTH
70 012113 GROUND MINIMUM TEMPERATURE, PAST 12 HOURS
71 020003 PRESENT WEATHER (SEE NOTE 1)
72 004024 TIME PERIOD OR DISPLACEMENT
73 020004 PAST WEATHER (1) (SEE NOTE 2)
74 020005 PAST WEATHER (2) (SEE NOTE 2)
75 004024 TIME PERIOD OR DISPLACEMENT
76 002004 TYPE OF INSTRUMENTATION FOR EVAPORATION MEASUREMENT OR TYPE OF C
77 013033 EVAPORATION/EVAPOTRANSPIRATION
78 004024 TIME PERIOD OR DISPLACEMENT
79 014031 TOTAL SUNSHINE
80 004025 TIME PERIOD OR DISPLACEMENT
81 014002 LONG-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
82 014004 SHORT-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
83 014016 NET RADIATION, INTEGRATED OVER PERIOD SPECIFIED
84 014028 GLOBAL SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
85 014029 DIFFUSE SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD
86 014030 DIRECT SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
87 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
88 004024 TIME PERIOD OR DISPLACEMENT
89 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALENT
90 004024 TIME PERIOD OR DISPLACEMENT
91 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALENT
92 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
93 004024 TIME PERIOD OR DISPLACEMENT
94 004024 TIME PERIOD OR DISPLACEMENT
95 012111 MAXIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
96 004024 TIME PERIOD OR DISPLACEMENT
97 012112 MINIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
98 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
99 002002 TYPE OF INSTRUMENTATION FOR WIND MEASUREMENT
100 008021 TIME SIGNIFICANCE
101 004025 TIME PERIOD OR DISPLACEMENT
102 011001 WIND DIRECTION
103 011002 WIND SPEED
104 008021 TIME SIGNIFICANCE
105 004025 TIME PERIOD OR DISPLACEMENT
106 011043 MAXIMUM WIND GUST DIRECTION
107 011041 MAXIMUM WIND GUST SPEED
108 004025 TIME PERIOD OR DISPLACEMENT
109 011043 MAXIMUM WIND GUST DIRECTION
110 011041 MAXIMUM WIND GUST SPEED

STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1

1	WMO BLOCK NUMBE	0.1300000000E+02	NUMERIC	
2	WMO STATION NUM	0.2720000000E+03	NUMERIC	
3	SHIP OR MOBILE	0.1009000000E+04	CCITTIA5	SURCIN
4	WMO REGION NUMB	0.6000000000E+01	CODE TABLE 1003	
5	TYPE OF STATION	0.0000000000E+00	CODE TABLE 2001	
6	YEAR	0.2005000000E+04	YEAR	
7	MONTH	0.1200000000E+02	MONTH	
8	DAY	0.1000000000E+01	DAY	
9	HOUR	0.1200000000E+02	HOUR	
10	MINUTE	0.0000000000E+00	MINUTE	
11	LATITUDE (HIGH	0.4482000000E+02	DEGREE	
12	LONGITUDE (HIGH	0.2028000000E+02	DEGREE	
13	HEIGHT OF STATI	0.9600000000E+02	M	
14	HEIGHT OF BAROM	0.9900000000E+02	M	
15	PRESSURE	0.1010000000E+04	PA	
16	PRESSURE REDUCE	0.1030000000E+04	PA	
17	3-HOUR PRESSURE	-0.1900000000E+03	PA	
18	CHARACTERISTIC	0.7000000000E+01	CODE TABLE 10063	
19	PRESSURE		MISSING PA	
20	GEOPOTENTIAL HE		MISSING GPM	
21	HEIGHT OF SENSO	0.2000000000E+01	M	
22	TEMPERATURE/DRY	0.2926000000E+03	K	
23	DEW-POINT TEMPE	0.2880000000E+03	K	
24	RELATIVE HUMIDI		MISSING %	
25	HEIGHT OF SENSO	0.1000000000E+01	M	
26	HORIZONTAL VISI	0.2000000000E+05	M	
27	HEIGHT OF SENSO	0.3000000000E+00	M	
28	TOTAL PRECIPITA		MISSING KG/M**2	
29	HEIGHT OF SENSO		MISSING M	
30	CLOUD COVER (TO	0.4000000000E+02	%	
31	VERTICAL SIGNIF	0.1000000000E+01	CODE TABLE 8002	
32	CLOUD AMOUNT	0.0000000000E+00	CODE TABLE 20011	
33	HEIGHT OF BASE	0.8000000000E+04	M	
34	CLOUD TYPE	0.3000000000E+02	CODE TABLE 20012	



35 CLOUD TYPE	0.2000000000E+02	CODE TABLE 20012
36 CLOUD TYPE	0.1100000000E+02	CODE TABLE 20012
37 VERTICAL SIGNIF		MISSING CODE TABLE 8002
38 CLOUD AMOUNT		MISSING CODE TABLE 20011
39 CLOUD TYPE		MISSING CODE TABLE 20012
40 HEIGHT OF BASE		MISSING M
41 VERTICAL SIGNIF		MISSING CODE TABLE 8002
42 CLOUD AMOUNT		MISSING CODE TABLE 20011
43 CLOUD TYPE		MISSING CODE TABLE 20012
44 HEIGHT OF BASE		MISSING M
45 VERTICAL SIGNIF		MISSING CODE TABLE 8002
46 CLOUD AMOUNT		MISSING CODE TABLE 20011
47 CLOUD TYPE		MISSING CODE TABLE 20012
48 HEIGHT OF BASE		MISSING M
49 VERTICAL SIGNIF		MISSING CODE TABLE 8002
50 CLOUD AMOUNT		MISSING CODE TABLE 20011
51 CLOUD TYPE		MISSING CODE TABLE 20012
52 HEIGHT OF BASE		MISSING M
53 VERTICAL SIGNIF		MISSING CODE TABLE 8002
54 CLOUD AMOUNT		MISSING CODE TABLE 20011
55 CLOUD TYPE		MISSING CODE TABLE 20012
56 HEIGHT OF TOP O		MISSING M
57 CLOUD TOP DESCR		MISSING CODE TABLE 20017
58 VERTICAL SIGNIF		MISSING CODE TABLE 8002
59 CLOUD AMOUNT		MISSING CODE TABLE 20011
60 CLOUD TYPE		MISSING CODE TABLE 20012
61 HEIGHT OF TOP O		MISSING M
62 CLOUD TOP DESCR		MISSING CODE TABLE 20017
63 VERTICAL SIGNIF		MISSING CODE TABLE 8002
64 CLOUD AMOUNT		MISSING CODE TABLE 20011
65 CLOUD TYPE		MISSING CODE TABLE 20012
66 HEIGHT OF TOP O		MISSING M
67 CLOUD TOP DESCR		MISSING CODE TABLE 20017
68 STATE OF THE GR		MISSING CODE TABLE 20062
69 TOTAL SNOW DEPT		MISSING M
70 GROUND MINIMUM		MISSING K
71 PRESENT WEATHER	0.2000000000E+01	CODE TABLE 20003
72 TIME PERIOD OR	0.2400000000E+02	HOUR
73 PAST WEATHER (1	0.1000000000E+01	CODE TABLE 20004
74 PAST WEATHER (2	0.1000000000E+01	CODE TABLE 20005
75 TIME PERIOD OR		MISSING HOUR
76 TYPE OF INSTRUM		MISSING CODE TABLE 2004
77 EVAPORATION/EVA		MISSING KG/M**2
78 TIME PERIOD OR		MISSING HOUR
79 TOTAL SUNSHINE		MISSING MINUTE
80 TIME PERIOD OR		MISSING MINUTE
81 LONG-WAVE RADIA		MISSING J/M**2
82 SHORT-WAVE RADI		MISSING J/M**2
83 NET RADIATION,		MISSING J/M**2
84 GLOBAL SOLAR RA		MISSING J/M**2
85 DIFFUSE SOLAR R		MISSING J/M**2
86 DIRECT SOLAR RA		MISSING J/M**2
87 HEIGHT OF SENSO	0.0000000000E+00	M
88 TIME PERIOD OR	-0.6000000000E+01	HOUR
89 TOTAL PRECIPITA	0.2000000000E+01	KG/M**2
90 TIME PERIOD OR		MISSING HOUR
91 TOTAL PRECIPITA		MISSING KG/M**2
92 HEIGHT OF SENSO		MISSING M
93 TIME PERIOD OR	-0.2400000000E+02	HOUR
94 TIME PERIOD OR	0.0000000000E+00	HOUR
95 MAXIMUM TEMPERA	0.2752200000E+03	K
96 TIME PERIOD OR	-0.6000000000E+01	HOUR
97 MINIMUM TEMPERA	0.2687000000E+03	K
98 HEIGHT OF SENSO	0.1000000000E+02	M
99 TYPE OF INSTRUM	0.1000000000E+01	FLAG TABLE 2002
100 TIME SIGNIFICAN	0.2000000000E+01	CODE TABLE 8021
101 TIME PERIOD OR	-0.1000000000E+02	MINUTE
102 WIND DIRECTION	0.1000000000E+03	DEGREE TRUE
103 WIND SPEED	0.1000000000E+01	M/S
104 TIME SIGNIFICAN		MISSING CODE TABLE 8021
105 TIME PERIOD OR		MISSING MINUTE
106 MAXIMUM WIND GU		MISSING DEGREE TRUE
107 MAXIMUM WIND GU		MISSING M/S
108 TIME PERIOD OR		MISSING MINUTE
109 MAXIMUM WIND GU		MISSING DEGREE TRUE
110 MAXIMUM WIND GU		MISSING M/S

5.2 To expand data descriptors only

```
PROGRAM TDEXP
C
C**** *TDEXP*
C
C
C PURPOSE.
C -----
C     Expands list of Bufr data descriptors.
C
C
C** INTERFACE.
C -----
C
C     NONE.
C
C METHOD.
C -----
C
C     NONE.
C
C EXTERNALS.
C -----
C
C     CALL BUSEL
C     CALL BUFREX
C     CALL BUFREN
C     CALL BUPRS0
C     CALL BUPRS1
C     CALL BUPRS2
C     CALL BUPRS3
C     CALL BUPRT
C     CALL BUUKEY
C
C REFERENCE.
C -----
C
C     NONE.
C
C AUTHOR.
C -----
C
C     M. DRAGOSAVAC   *ECMWF*   June 2005.
C
C MODIFICATIONS.
C -----
C
C     NONE.
C
C IMPLICIT LOGICAL(L,O,G), CHARACTER*8(C,H,Y)
C
C PARAMETER (JSEC1=40,JSEC3=4)
C PARAMETER (KDLEN=200,KELEM=40000,KVALS=360000)
C
C DIMENSION KSEC1(JSEC1)      ! ,KSEC3(JSEC3)
C
C DIMENSION KTDLST(KELEM),KTDEXP(KELEM)
C DIMENSION KDATA(KDLEN)
C
C CHARACTER*64 CNAME(KELEM)
C CHARACTER*24 CUNITS(KELEM)
C
C -----
C* 1. INITIALIZE CONSTANTS AND VARIABLES.
C -----
100 CONTINUE
C
C
C RVIND=1.7E38
C
C INITIALIZE DELAYED REPLICATION FACTORS OR REFERENCE VALUES ETD.
C
C
C KDATA(1)=2
C KDATA(2)=14
C KDATA(3)=2
C KDATA(4)=2
C
C SET DATA DECSRIPTORS
C
C KTDLST( 1)=301001
C KTDLST( 2)=301011
C KTDLST( 3)=301012
C KTDLST( 4)=301021
C KTDLST( 5)=107000
```



```

KTDLST( 6)=031001
KTDLST( 7)=007004
KTDLST( 8)=008001
KTDLST( 9)=010003
KTDLST(10)=012001
KTDLST(11)=012003
KTDLST(12)=011003
KTDLST(13)=011004
KTDLST(14)=224000
KTDLST(15)=236000
KTDLST(16)=101000
KTDLST(17)=031001
KTDLST(18)=031031
KTDLST(19)=001031
KTDLST(20)=001032
KTDLST(21)=008023
KTDLST(22)=105000
KTDLST(23)=031001
KTDLST(24)=204002
KTDLST(25)=031021
KTDLST(26)=204002
KTDLST(27)=031021
KTDLST(28)=224255
KTDLST(29)=204000
KTDLST(30)=225000
KTDLST(31)=237000
KTDLST(32)=001031
KTDLST(33)=001032
KTDLST(34)=008024
KTDLST(35)=101000
KTDLST(36)=031001
KTDLST(37)=225255

C
KTDLEN=37

C
SET DATA DESCRIPTORS

C
SECTION 1 CONTENT

C
KSECL(2)=4      ! BUFR EDITION NUMBER
KSECL(14)=0     ! BUFR MASTER TABLE USED
ksecl(16)=0     ! ORIGINATING SUB-CENTRE
KSECL(3)=98    ! ORIGINATING CENTRE
KSECL(8)=1     ! VERSION NUMBER OF LOCAL TABLE USED
KSECL(15)=12   ! VERSION NUMBER OF MASTER TABLE USED

C
SECTION 3 CONTENT

C
K=1
CALL BUXDES(K,KSECL,KTDLEN,KDLEN,KDATA,KELEM,
1          KTDEXL,KTDEXP,CNAMES,CUNITS,KERR)

C
END

```

The output of the expanded data using BUXDES routine is given below.

```

          ECMWF

BUFR ENCODING SOFTWARE VERSION - 7.1
      07 June 2005.

Your path for bufr tables is :
/home/ma/maa/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables
BUFR TABLES TO BE LOADED B000000000098012001,D000000000098012001

```

```

          DATA DESCRIPTORS (UNEXPANDED)

1  301001
2  301011
3  301012
4  301021
5  107000
6  031001
7  007004
8  008001
9  010003
10 012001
11 012003
12 011003
13 011004
14 224000
15 236000
16 101000

```

17 031001
18 031031
19 001031
20 001032
21 008023
22 105000
23 031001
24 204002
25 031021
26 204002
27 031021
28 224255
29 204000
30 225000
31 237000
32 001031
33 001032
34 008024
35 101000
36 031001
37 225255

DATA DESCRIPTORS (EXPANDED)

	ELEMENT NAME	UNIT
1	001001 WMO BLOCK NUMBER	NUMERIC
2	001002 WMO STATION NUMBER	NUMERIC
3	004001 YEAR	YEAR
4	004002 MONTH	MONTH
5	004003 DAY	DAY
6	004004 HOUR	HOUR
7	004005 MINUTE	MINUTE
8	005001 LATITUDE (HIGH ACCURACY)	DEGREE
9	006001 LONGITUDE (HIGH ACCURACY)	DEGREE
10	031001 DELAYED DESCRIPTOR REPLICATION FACTOR	NUMERIC
11	007004 PRESSURE	PA
12	008001 VERTICAL SOUNDING SIGNIFICANCE	FLAG TABLE 8001
13	010003 GEOPOTENTIAL	M**2/S**2
14	012001 TEMPERATURE/DRY-BULB TEMPERATURE	K
15	012003 DEW-POINT TEMPERATURE	K
16	011003 U-COMPONENT	M/S
17	011004 V-COMPONENT	M/S
18	007004 PRESSURE	PA
19	008001 VERTICAL SOUNDING SIGNIFICANCE	FLAG TABLE 8001
20	010003 GEOPOTENTIAL	M**2/S**2
21	012001 TEMPERATURE/DRY-BULB TEMPERATURE	K
22	012003 DEW-POINT TEMPERATURE	K
23	011003 U-COMPONENT	M/S
24	011004 V-COMPONENT	M/S
25	224000 FIRST ORDER STATISTICS FOLLOW	
26	236000 BACKWARD REFERENCE BIT MAP	
27	031001 DELAYED DESCRIPTOR REPLICATION FACTOR	NUMERIC
28	031031 DATA PRESENT INDICATOR	NUMERIC
29	031031 DATA PRESENT INDICATOR	NUMERIC
30	031031 DATA PRESENT INDICATOR	NUMERIC
31	031031 DATA PRESENT INDICATOR	NUMERIC
32	031031 DATA PRESENT INDICATOR	NUMERIC
33	031031 DATA PRESENT INDICATOR	NUMERIC
34	031031 DATA PRESENT INDICATOR	NUMERIC
35	031031 DATA PRESENT INDICATOR	NUMERIC
36	031031 DATA PRESENT INDICATOR	NUMERIC
37	031031 DATA PRESENT INDICATOR	NUMERIC
38	031031 DATA PRESENT INDICATOR	NUMERIC
39	031031 DATA PRESENT INDICATOR	NUMERIC
40	031031 DATA PRESENT INDICATOR	NUMERIC
41	031031 DATA PRESENT INDICATOR	NUMERIC
42	001031 IDENTIFICATION OF ORIGINATING/GENERATING	CODE TABLE 1031
43	001032 GENERATING APPLICATION	CODE TABLE 1032
44	008023 FIRST ORDER STATISTICS	CODE TABLE 8023
45	031001 DELAYED DESCRIPTOR REPLICATION FACTOR	NUMERIC
46	031021 ASSOCIATED FIELD SIGNIFICANCE	CODE TABLE 31021
47	031021 ASSOCIATED FIELD SIGNIFICANCE	CODE TABLE 31021
48	000000 ASSOCIATED FIELD	
49	224255 FIRST ORDER STATISTICS VALUE MARKER	
50	031021 ASSOCIATED FIELD SIGNIFICANCE	CODE TABLE 31021
51	031021 ASSOCIATED FIELD SIGNIFICANCE	CODE TABLE 31021
52	000000 ASSOCIATED FIELD	
53	224255 FIRST ORDER STATISTICS VALUE MARKER	
54	225000 DIFFERENCE STATISTICAL VALUES FOLLOW	
55	237000 USE PREVIOUSLY DEFINED BIT MAP	
56	999999 ASSOCIATED FIELD	
57	001031 IDENTIFICATION OF ORIGINATING/GENERATING	CODE TABLE 1031
58	999999 ASSOCIATED FIELD	
59	001032 GENERATING APPLICATION	CODE TABLE 1032
60	999999 ASSOCIATED FIELD	
61	008024 DIFFERENCE STATISTICS	CODE TABLE 8024
62	031001 DELAYED DESCRIPTOR REPLICATION FACTOR	NUMERIC
63	000000 ASSOCIATED FIELD	
64	225255 DIFFERENCE STATISTICS VALUE MARKER	
65	000000 ASSOCIATED FIELD	
66	225255 DIFFERENCE STATISTICS VALUE MARKER	



5.3 To create bufr message

```

PROGRAM BUFR
C
C**** *BUFR*
C
C
C PURPOSE.
C -----
C      An example of using Bufr packing/unpacking software.
C      It will create synop data in bufr edition 4
C
C** INTERFACE.
C -----
C
C      NONE.
C
C METHOD.
C -----
C
C      NONE.
C
C EXTERNALS.
C -----
C
C REFERENCE.
C -----
C
C      NONE.
C
C AUTHOR.
C -----
C
C      M. DRAGOSAVAC *ECMWF* 05/04/2005.
C
C MODIFICATIONS.
C -----
C
C      NONE.
C
C IMPLICIT LOGICAL(O,G), CHARACTER*8(C,H,Y)
C
C
C PARAMETER(JSUP = 9,JSEC0= 3,JSEC1= 40,JSEC2=4096,JSEC3= 4,
1 JSEC4=2,JELEM=160000,JSUBS=400,JCVAL=150 ,JBUFL=512000,
#ifdef JBPW_64
2 JBPW = 64,JTAB =3000,JCTAB=3000,JCTST=3000,JCTEXT=6000,
#else
2 JBPW = 32,JTAB =3000,JCTAB=3000,JCTST=3000,JCTEXT=6000,
#endif
3 JWORK=4096000,JKEY=46, JTMAX=10,JTCLAS=64,JTEL=255)
C
C PARAMETER (KDLEN=200,KELEM=4000)
parameter (KVALS=4000,KVALS1=4000)
C
C DIMENSION KBUFR(JBUFL)
C DIMENSION KSUP(JSUP) ,KSEC0(JSEC0),KSEC1(JSEC1)
C DIMENSION KSEC2(JSEC2),KSEC3(JSEC3),KSEC4(JSEC4)
C DIMENSION KEY (JKEY)
C DIMENSION ISUP(JSUP) ,ISEC0(JSEC0),ISEC1(JSEC1)
C DIMENSION ISEC2(JSEC2),ISEC3(JSEC3),ISEC4(JSEC4)
C
#ifdef R_4
REAL*8 VALUES(KVALS),VALUE(KVALS1)
REAL*8 RQV(KELEM)
REAL*8 RVIND
#else
REAL VALUES(KVALS),VALUE(KVALS1)
REAL RQV(KELEM)
REAL RVIND
#endif
C
DIMENSION KIDLST(KELEM),KTDEXP(KELEM),KRQ(KELEM)
DIMENSION ITDLST(KELEM),ITDEXP(KELEM)
DIMENSION KDATA(KDLEN),IDATA(KDLEN)
C
C CHARACTER*8 CF
C CHARACTER*64 CNAME(KELEM),CNAME(KELEM)
C CHARACTER*24 CUNITS(KELEM),CUNIT(KELEM)
C CHARACTER*80 CVALS(KVALS)
C CHARACTER*80 CVAL(KVALS1)
C CHARACTER*80 YENC
C
C
C -----
C* 1. INITIALIZE CONSTANTS AND VARIABLES.

```

```
C -----
100 CONTINUE
C
C
C   RVIND=1.7E38
C
C   CALL POPEN(IUNIT1,'synop.bufr','W',IRET)
C   IF(IRET.EQ.-1) STOP 'OPEN FAILED ON synop.dat'
C   IF(IRET.EQ.-2) STOP 'INVALID FILE NAME'
C   IF(IRET.EQ.-3) STOP 'INVALID OPEN MODE SPECIFIED'
C
C
C   INITIALIZE DELAYED REPLICATION FACTORS OR REFERENCE VALUES ETD.
C
C   DO 101 I=1,KDLEN
C     KDATA(I)=0
C     VALUES(I)=RVIND
101 CONTINUE
C
C   KDATA(1)=10
C
C   KDLENG=3
C
C   SET DATA DECSRIPTORS
C
C
C   ktdlst( 1)= 301001
C   ktdlst( 2)= 001011
C   ktdlst( 3)= 001003
C   ktdlst( 4)= 002001
C   ktdlst( 5)= 301011
C   ktdlst( 6)= 301012
C   ktdlst( 7)= 301021
C   ktdlst( 8)= 007030
C   ktdlst( 9)= 007031
C   ktdlst(10)= 302001
C   ktdlst(11)= 007004
C   ktdlst(12)= 010009
C
C   !      Temperature data
C   ktdlst(13)= 007032
C   ktdlst(14)= 012101
C   ktdlst(15)= 012103
C   ktdlst(16)= 013003
C
C   !      Visibility data
C   ktdlst(17)= 007032
C   ktdlst(18)= 020001
C
C   !      Precipitation past 24 hours
C   ktdlst(19)= 007032
C   ktdlst(20)= 013023
C   ktdlst(21)= 007032
C
C   !      Cloud data
C   ktdlst(22)= 302004
C   ktdlst(23)= 101004
C   ktdlst(24)= 302005
C
C   !      Clouds with bases below station level
C   ktdlst(25)= 105003
C   ktdlst(26)= 008002
C   ktdlst(27)= 020011
C   ktdlst(28)= 020012
C   ktdlst(29)= 020014
C   ktdlst(30)= 020017
C
C   !      State of ground, snow depth, ground minimum temperature
C   ktdlst(31)= 020062
C   ktdlst(32)= 013013
C   ktdlst(33)= 012113
C
C   !      Present weather
C   ktdlst(34)= 020003
C   ktdlst(35)= 004024
C   ktdlst(36)= 020004
C   ktdlst(37)= 020005
C
C   !      Evaporation measurements
C   ktdlst(38)= 004024
C   ktdlst(39)= 002004
C   ktdlst(40)= 013033
C
C   !      Sunshine data
C   ktdlst(41)= 004024
C   ktdlst(42)= 014031
C
C   !      Radiation data
C   ktdlst(43)= 004025
C   ktdlst(44)= 014002
C   ktdlst(45)= 014004
C   ktdlst(46)= 014016
C   ktdlst(47)= 014028
C   ktdlst(48)= 014029
C   ktdlst(49)= 014030
C
C   !      Precipitation measurements
C   ktdlst(50)= 007032
C   ktdlst(51)= 102002
C   ktdlst(52)= 004024
```



```

ktdlst( 53)= 013011
! Extreme temperature data
ktdlst( 54)= 007032
ktdlst( 55)= 101002
ktdlst( 56)= 004024
ktdlst( 57)= 012111
ktdlst( 58)= 004024
ktdlst( 59)= 012112
! Wind data
ktdlst( 60)= 007032
ktdlst( 61)= 002002
ktdlst( 62)= 008021
ktdlst( 63)= 004025
ktdlst( 64)= 011001
ktdlst( 65)= 011002
ktdlst( 66)= 008021
ktdlst( 67)= 103002
ktdlst( 68)= 004025
ktdlst( 69)= 011043
ktdlst( 70)= 011041

ktdlen=70

values( 1)=13. ! 001001 WMO BLOCK NUMBER NUMERIC
values( 2)=272. ! 001002 WMO STATION NUMBER NUMERIC
values( 3)=1009. ! 001011 SHIP OR MOBILE LAND STATION IDENTIFIER CCITTIA5
values( 4)=6. ! 001003 WMO REGION NUMBER/GEOGRAPHICAL AREA CODE TABLE 001003
values( 5)=0. ! 002001 TYPE OF STATION CODE TABLE 002001
values( 6)=2005. ! 004001 YEAR YEAR
values( 7)=12. ! 004002 MONTH MONTH
values( 8)=1. ! 004003 DAY DAY
values( 9)=12. ! 004004 HOUR HOUR
values( 10)=0. ! 004005 MINUTE MINUTE
values( 11)=44.82 ! 005001 LATITUDE (HIGH ACCURACY) DEGREE
values( 12)=20.28 ! 006001 LONGITUDE (HIGH ACCURACY) DEGREE
values( 13)=96 ! 007030 HEIGHT OF STATION GROUND ABOVE MEAN SEA M

! Pressure
values( 14)=99 ! 007031 HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL M
values( 15)=1014. ! 010004 PRESSURE PA
values( 16)=1026.1 ! 010051 PRESSURE REDUCED TO MEAN SEA LEVEL PA
values( 17)=-190. ! 010061 3 HOUR PRESSURE CHANGE PA
values( 18)=7. ! 010063 CHARACTERISTIC OF PRESSURE TENDENCY CODE TABLE 010063
values( 19)=rvind ! 007004 PRESSURE PA
values( 20)=rvind ! 010009 GEOPOTENTIAL HEIGHT GPM

! Temperature data
values( 21)=2. ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M
values( 22)=292.6 ! 012101 TEMPERATURE/DRY BULB TEMPERATURE K
values( 23)=288. ! 012103 DEW-POINT TEMPERATURE K
values( 24)=rvind ! 013003 RELATIVE HUMIDITY %

! Visibility data
values( 25)=1. ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M
values( 26)=20000 ! 020001 HORIZONTAL VISIBILITY M

! Precipitation past 24 hours
values( 27)=0.3 ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M
values( 28)=rvind ! 013023 TOTAL PRECIPITATION PAST 24 HOURS KG/M**2
values( 29)=rvind ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M

! Cloud data
values( 30)=40. ! 020010 CLOUD COVER (TOTAL) %
values( 31)=1. ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 32)=0. ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 33)=8000. ! 020013 HEIGHT OF BASE OF CLOUD M
values( 34)=30. ! 020012 CLOUD TYPE CODE TABLE 020012
values( 35)=20. ! 020012 CLOUD TYPE CODE TABLE 020012
values( 36)=11. ! 020012 CLOUD TYPE CODE TABLE 020012
values( 37)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 38)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 39)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 40)=rvind ! 020013 HEIGHT OF BASE OF CLOUD M
values( 41)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 42)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 43)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 44)=rvind ! 020013 HEIGHT OF BASE OF CLOUD M
values( 45)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 46)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 47)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 48)=rvind ! 020013 HEIGHT OF BASE OF CLOUD M
values( 49)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 50)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 51)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 52)=rvind ! 020013 HEIGHT OF BASE OF CLOUD M

! Clouds with bases below station level
values( 53)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 54)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 55)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 56)=rvind ! 020014 HEIGHT OF TOP OF CLOUD M
values( 57)=rvind ! 020017 CLOUD TOP DESCRIPTION CODE TABLE 020017

```

```

values( 58)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 59)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 60)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 61)=rvind ! 020014 HEIGHT OF TOP OF CLOUD M
values( 62)=rvind ! 020017 CLOUD TOP DESCRIPTION CODE TABLE 020017
values( 63)=rvind ! 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATI CODE TABLE 008002
values( 64)=rvind ! 020011 CLOUD AMOUNT CODE TABLE 020011
values( 65)=rvind ! 020012 CLOUD TYPE CODE TABLE 020012
values( 66)=rvind ! 020014 HEIGHT OF TOP OF CLOUD M
values( 67)=rvind ! 020017 CLOUD TOP DESCRIPTION CODE TABLE 020017

!
State of ground, snow depth, ground minimum temperature
values( 68)=rvind ! 020062 STATE OF THE GROUND (WITH OR WITHOUT SNO CODE TABLE 020062
values( 70)=rvind ! 013013 TOTAL SNOW DEPTH M
values( 71)=rvind ! 012113 GROUND MINIMUM TEMPERATURE, PAST 12 HOUR K

!
Present weather
values( 71)=2. ! 020003 PRESENT WEATHER CODE TABLE 020003
values( 72)=24. ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 73)=1. ! 020004 PAST WEATHER (1) CODE TABLE 020004
values( 74)=1. ! 020005 PAST WEATHER (2) CODE TABLE 020005

!
Evaporation measurements
values( 75)=rvind ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 76)=rvind ! 002004 TYPE OF INSTRUMENTATION FOR EVAPORATION CODE TABLE 002004
values( 77)=rvind ! 013033 EVAPORATION/EVAPOTRANSPIRATION KG/M**2

!
Sunshine data
values( 78)=rvind ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 79)=rvind ! 014031 TOTAL SUNSHINE MINUTE

!
Radiation data
values( 80)=rvind ! 004025 TIME PERIOD OR DISPLACEMENT MINUTE
values( 81)=rvind ! 014002 LONG-WAVE RADIATION,INTEGRATED OVER PERI J/M**2
values( 82)=rvind ! 014004 SHORT-WAVE RADIATION,INTEGRATED OVER PER J/M**2
values( 83)=rvind ! 014016 NET RADIATION,INTEGRATED OVER PERIOD SPE J/M**2
values( 84)=rvind ! 014028 GLOBAL SOLAR RADIATION INTEGRATED OVERPE J/M**2
values( 85)=rvind ! 014029 DIFFUSE SOLAR RADIATION INTEGRATED OVERP J/M**2
values( 86)=rvind ! 014030 DIRECT SOLAR RADIATION INTEGRATED OVERPE J/M**2

!
Precipitation measurements
values( 87)=0. ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M
values( 88)=-6 ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 89)=2. ! 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALE KG/M**2

!
Extreme temperature data
values( 90)=rvind ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 91)=rvind ! 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALE KG/M**2
values( 92)=rvind ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M
values( 93)=-24 ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 94)=0 ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 95)=275.22 ! 012111 MAXIMUM TEMPERATURE,AT HEIGHT AND OVER P K
values( 96)=-6 ! 004024 TIME PERIOD OR DISPLACEMENT HOUR
values( 97)=268.7 ! 012112 MINIMUM TEMPERATURE,AT HEIGHT AND OVER P K

!
Wind data
values( 98)=10. ! 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND ( OR M
values( 99)=1. ! 002002 TYPE OF INSTRUMENTATION FOR WIND MEASURE FLAG TABLE 002002
values( 100)=2. ! 008021 TIME SIGNIFICANCE CODE TABLE 008021
values( 101)=-10. ! 004025 TIME PERIOD OR DISPLACEMENT MINUTE
values( 102)=100. ! 011001 WIND DIRECTION DEGREE TRUE
values( 103)=1. ! 011002 WIND SPEED M/S
values( 104)=rvind ! 008021 TIME SIGNIFICANCE CODE TABLE 008021
values( 105)=rvind ! 004025 TIME PERIOD OR DISPLACEMENT MINUTE
values( 106)=rvind ! 011043 MAXIMUM WIND GUST DIRECTION DEGREE TRUE
values( 107)=rvind ! 011041 MAXIMUM WIND SPEED (GUSTS) M/S
values( 108)=rvind ! 004025 TIME PERIOD OR DISPLACEMENT MINUTE
values( 109)=rvind ! 011043 MAXIMUM WIND GUST DIRECTION DEGREE TRUE
values( 110)=rvind ! 011041 MAXIMUM WIND SPEED (GUSTS) M/S

C
C
SET CCITTIA5 STATION OR SITE NAME

cvals(1)='SURCIN'

C
C
SECTION 0 CONTENT

KSEC0(1)=0 ! TOTAL LENGTH OF SECTION 0
KSEC0(2)=0 ! TOTAL LENGTH OF BUFR MESSAGE
KSEC0(3)=4 ! BUFR EDITION NUMBER

C
C
SECTION 1 CONTENT

KSEC1(1)=22 ! TOTTAL LENGTH OF SECTION 1 ( set to 18 for edition <= 3)
KSEC1(2)=4 ! BUFR EDITION NUMBER
KSEC1(3)=98 ! ORIGINATING CENTRE
KSEC1(4)=1 ! UPDATE SEQUENCE NUMBER
KSEC1(5)=0 !128 ! FLAG (PRESENCE OF SECTION 2)
KSEC1(6)=0 ! BUFR MESSAGE TYPE
KSEC1(7)=1 ! BUFR_MESSAGE SUBTYPE
KSEC1(8)=1 ! VERSION NUMBER OF LOCAL TABLE USED
KSEC1(9)=nint(values(6))
if(KSEC1(2).le.3) then
    
```



```

        if(ksec1(9).gt.2000) then
            ksec1(9)=ksec1(9)-2000
        else
            ksec1(9)=ksec1(9)-1900
        end if
    end if
    KSEC1(10)=nint(values(7))
    KSEC1(11)=nint(values(8)) ! DAY
    KSEC1(12)=nint(values(9)) ! HOUR
    KSEC1(13)=nint(values(10)) ! MINUTE
    KSEC1(14)=0 ! BUFR MASTER TABLE( ZERO) FOR METEOROLOGICAL DATA)
    KSEC1(15)=12 ! VERSION NUMBER OF MASTER TABLE USED
    KSEC1(16)=0 ! ORIGINATING SUB-CENTRE
    KSEC1(17)=0 ! International sub-category
    KSEC1(18)=0 ! Second

C
C SECTION 2 CONTENT
C
C KSEC2(1)=52
C
C DO 110 I=2,JSEC2
110 KSEC2(I)=0
CONTINUE
C
C SECTION 3 CONTENT
C
C KSEC3(1)=0 ! TOTAL LENGTH OF SECTION 3
C KSEC3(2)=0 ! RESERVED
C KSEC3(3)=1
C KSEC3(4)=0 ! 64 FOR COMPRESSION/ 0 MANY SUBSETS

C
C IREP=0
C
C
C* 6. PACK BUFR MESSAGE
C -----
600 CONTINUE
C
C-----
C This call is not needed for packing. It just
C prints expanded list corresponding to ktdlst sequence
C and delayed replications in kdata array. This four
C lines can be deleted or commented out.
C
C K=1
C CALL BUXDES(K,KSEC1,KTDLN,KTDLST,KDLENG,KDATA,KELEM,
1 KTDEXL,KTDEXP,CNAMES,CUNITS,KERR)
C
C IF(KERR.NE.0) CALL EXIT(2)
C-----
C
C
C* 6.2 ENCODE DATA INTO BUFR MESSAGE.
C -----
620 CONTINUE
C
C KBUFL=3000
C KPMISS=1
C KPRUS=1
C NOKEY=0
C CALL BUPRQ(KPMISS,KPRUS,NOKEY)
C
C KERR=0
C CALL BUFREN( KSEC0,KSEC1,KSEC2,KSEC3,KSEC4,
1 KTDLN,KTDLST,KDLENG,KDATA,KELEM,
2 KVALS,VALUES,CVALS,KBUFL,KBUFR,KERR)
C
C IF(KERR.GT.0) THEN
C CALL EXIT(2)
C ELSEIF(KERR.LT.0) then
C print*,'Encoding return_code=',kerr
C END IF
C
C ILEN=KBUFL*JBPW/8
C
C IERR=0
C CALL PBWRITE(IUNIT1,KBUFR,ILEN,IERR)
C IF(IERR.LT.0) THEN
C PRINT*,'ERROR WRITING INTO TARGET FILE.'
C CALL EXIT(2)
C END IF

C
C-----
C* 7. UNPACK MESSAGE.
C -----
700 CONTINUE
C
C DO 702 I=1,KVALS1
C VALUE(I)=RVIND
702 CONTINUE
C

```

```
701 CONTINUE
C
  CALL BUFREX(KBUFL,KBUFR,ISUP,ISEC0 ,ISEC1,ISEC2 ,ISEC3 ,ISEC4,
1  KELEM,CNAME,CUNIT,KVALS1,VALUE,CVAL,IERR)
C
  IF(IERR.NE.0) CALL EXIT(2)
C
  CALL BUPRS0(ISEC0)
  CALL BUPRS1(ISEC1)
  CALL BUUKEY(ISEC1,ISEC2,KEY,ISUP,KERR)
  CALL BUPRS2(ISUP ,KEY)
  ISUBSET=1
  CALL BUSEL2(ISUBSET,KELEM,KTDLEN,KTDLST,KTDEXL,KTDEXP,CNAMES,
1  CUNITS,IERR)
  CALL BUPRS3(ISEC3,KTDLEN,KTDLST,KTDEXL,KTDEXP,KELEM,CNAME)
C
  WRITE(*,'(a,$)') ' STARTING SUBSET TO BE PRINTED : '
  READ(*,'(I5)') IST
  WRITE(*,'(a,$)') ' ENDING SUBSET TO BE PRINTED : '
  READ(*,'(I6)') IEND
C
  ICODE=0
  CALL BUPRT(ICODE,IST,IEND,KELEM,CNAME,CUNIT,CVAL,
1  KVALS1,VALUE,ISUP,ISEC1,IERR)
C
C
  IREP=IREP+1
C
  IF(IREP.GT.3) GO TO 900
  GO TO 900
C
810 CONTINUE
C
  WRITE(*,'(1H ,A)') 'OPEN ERROR ON INPUT FILE'
  GO TO 900
C
800 CONTINUE
C
  IF(IERR.EQ.-1) THEN
    print*,'Number of records processed ',IREP
  ELSE
    print*,' BUFR : error= ',ierr
  END IF
C
900 CONTINUE
C
  STOP
  END
```




5.4 An example of C program calling fortran bufr subroutines

```

#include "stdio.h"
#include "stdlib.h"

int main(int argc, char *argv[])
/*****
*
* Program : Bufr_decode
*
* Author: Milan Dragosavac   ECMWF   July 1996
*
* Purpose: Decode bufr message
*
*
* Usage:
*
*
* References:
*
*
* File formats:
*
*
* Restrictions:
*
*
* Error handling:
*
*
* Notes:
*
*
*****/
{
#define KVALS 360000
#define KELEM 40000

FILE *fp;
char bufr_message[15000];
char filename[256];
long int length=15000;
long int status;
int Nbpw;

unsigned long int *kbuff;
long int ksup[9];
long int ksec0[3];
long int ksec1[40];
long int ksec2[4096];
long int ksec3[4];
long int ksec4[2];
long int key[46];
long int kerr;

int i;
long kelem = KELEM,kvals = KVALS;

static char cnames[KELEM][64],cunits[KELEM][24];

char cvals[KVALS][80];

float values[KVALS],vals[KVALS];
long icode = 0;
long ktdlst[KELEM],ktdexp[KELEM],ktdlen,ktdexl;

if(sizeof(long) == 4) Nbpw=32;
else if(sizeof(long) == 8) Nbpw=64;
else{
printf("Abort....\n");
}

printf("%d\n",Nbpw);

/*      Get input and output file name.  */
/*      ----- */

if(argc != 3) {

```

```
    printf("Usage: bufr_decode -i infile \n");
    printf("Please try again. \n");
    exit(1);
}

printf("%c",argc);

if(!strcmp(argv[1],"-i") ) strcpy(filename,argv[2]);
else {
    printf("Usage: bufr_decode -i infile \n");
    exit(1);
}

/*      Open input file          */
/*      -----                */

if((fp = fopen(filename,"r") == NULL) {
    printf("cannot open file\n");
    exit(1);
}

/*      Read in bufr messages */
/*      -----                */

while(status >= 0){
    status = readbufr( fp,&bufr_message,&length);

    if(      status == -1 ) printf("End of file.\n");
    else if(status == -2 ) printf("Error in file handling\n");
    else if(status == -3 ) printf("Too small input array.\n");
    else if(status == -4 ) printf("Too small input array.\n");
    else {
        printf("It is OK.\n");
        printf("message read ");
        printf("%d\n",length);
        printf("%s\n",&bufr_message[0]);
    }
    status=-1;
}

/*      Expand bufr message calling fortran program */
    kbuff = (long *) bufr_message;
    length /= 4;

    bus012_(&length, kbuff , ksup, ksec0, ksec1, ksec2, &kerr) ;
    buprs0_(ksec0);
    buprs1_(ksec1);

    if (ksup[5] > 1)
        kelem = kvals/ksup[5];
    else
        kelem = KELEM;

    if ( kelem > KELEM ) kelem = KELEM;
    kerr = 0;
    bufrex_(&length, (long *)kbuff,ksup,ksec0,ksec1,ksec2,ksec3,ksec4,
            &kelem, (char **)cnames, (char **)cunits,&kvals,
            values, (char **)cvals,&kerr);

    if ( kerr )
    {
        kerr = 0;
    }

    buukey_(ksec1,ksec2,key,ksup,&kerr);

    busel_(&ktdlen,ktdlst,&ktdexl,ktdex,&kerr);
    buprs3_(ksec3,&ktdlen,ktdlst,&ktdexl,ktdex,&kelem, (char **)cnames);

    icode = 0;
    long current_ss;
    current_ss = 1;
    buprt_(&icode,&current_ss,&current_ss,&kelem, (char **)cnames,
            (char **)cunits, (char **)cvals,
            &kvals, values,ksup,ksec1,&kerr);

}

return kerr;
}
```

6 WMO observation templates

6.1 WMO AWS (automatic and manned station) template, one hour period

```
ECMWF

BUFR DECODING SOFTWARE VERSION - 7.1
07 June 2005.

Your path for bufr tables is :
/home/ma/maa/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables
BUFR TABLES TO BE LOADED B0000000000078011007,D0000000000078011007
1
    BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)          8
TOTAL LENGTH OF BUFR MESSAGE (BYTES) 320
BUFR EDITION NUMBER                   3
1
    BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)          18
BUFR EDITION NUMBER                   3
ORIGINATING SUB-CENTRE                 0
ORIGINATING CENTRE                     78
UPDATE SEQUENCE NUMBER                 0
FLAG (PRESENCE OF SECTION 2)          0
BUFR MESSAGE TYPE                      0
BUFR MESSAGE SUBTYPE                   0
VERSION NUMBER OF LOCAL TABLE         7
YEAR                                    5
MONTH                                   5
DAY                                     4
HOUR                                    9
MINUTE                                  0
VERSION NUMBER OF MASTER TABLE        11
BUFR MASTER TABLE                     0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.
1
    BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)          74
RESERVED                               0
NUMBER OF DATA SUBSETS                1
FLAG (DATA TYPE/DATA COMPRESSION)     128

DATA DESCRIPTORS (UNEXPANDED)

1 301090
2 008010
3 301091
4 302001
5 007004
6 010009
7 302072
8 101005
9 307063
10 302069
11 007032
12 007033
13 020031
14 020032
15 002038
16 022043
17 302021
18 302078
19 302073
20 302074
21 302075
22 004025
23 302076
24 302071
25 302077
26 007033
27 302079
28 007032
29 302080
30 302081
31 302082
32 004025
33 013059
```

DATA DESCRIPTORS (EXPANDED)

1	001001	WMO BLOCK NUMBER
2	001002	WMO STATION NUMBER
3	001015	STATION OR SITE NAME
4	002001	TYPE OF STATION
5	004001	YEAR
6	004002	MONTH
7	004003	DAY
8	004004	HOUR
9	004005	MINUTE
10	005001	LATITUDE (HIGH ACCURACY)
11	006001	LONGITUDE (HIGH ACCURACY)
12	007030	HEIGHT OF STATION GROUND ABOVE MEAN SEA LEVEL (SEE NOTE 3)
13	007031	HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL (SEE NOTE 4)
14	008010	SURFACE QUALIFIER (TEMPERATURE DATA)
15	002180	MAIN PRESENT WEATHER DETECTING SYSTEM
16	002181	SUPPLEMENTARY PRESENT WEATHER SENSOR
17	002182	VISIBILITY MEASUREMENT SYSTEM
18	002183	CLOUD DETECTION SYSTEM
19	002184	TYPE OF LIGHTNING DETECTION SENSOR
20	002179	TYPE OF SKY CONDITION ALGORITHM
21	002186	CAPABILITY TO DETECT PRECIPITATION PHENOMENA
22	002187	CAPABILITY TO DETECT OTHER WEATHER PHENOMENA
23	002188	CAPABILITY TO DETECT OBSCURATION
24	002189	CAPABILITY TO DISCRIMINATE LIGHTNING STRIKES
25	010004	PRESSURE
26	010051	PRESSURE REDUCED TO MEAN SEA LEVEL
27	010061	3-HOUR PRESSURE CHANGE
28	010063	CHARACTERISTIC OF PRESSURE TENDENCY
29	007004	PRESSURE
30	010009	GEOPOTENTIAL HEIGHT
31	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
32	007033	HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
33	012101	TEMPERATURE/DRY-BULB TEMPERATURE
34	012103	DEW-POINT TEMPERATURE
35	013003	RELATIVE HUMIDITY
36	007061	DEPTH BELOW LAND SURFACE
37	012130	SOIL TEMPERATURE
38	007061	DEPTH BELOW LAND SURFACE
39	012130	SOIL TEMPERATURE
40	007061	DEPTH BELOW LAND SURFACE
41	012130	SOIL TEMPERATURE
42	007061	DEPTH BELOW LAND SURFACE
43	012130	SOIL TEMPERATURE
44	007061	DEPTH BELOW LAND SURFACE
45	012130	SOIL TEMPERATURE
46	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
47	007033	HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
48	033041	ATTRIBUTE OF FOLLOWING VALUE
49	020001	HORIZONTAL VISIBILITY
50	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
51	007033	HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
52	020031	ICE DEPOSIT (THICKNESS)
53	020032	RATE OF ICE ACCRETION
54	002038	METHOD OF WATER TEMPERATURE AND/OR SALINITY MEASUREMENT
55	022043	SEA/WATER TEMPERATURE
56	022001	DIRECTION OF WAVES
57	022011	PERIOD OF WAVES
58	022021	HEIGHT OF WAVES
59	002176	METHOD OF STATE OF GROUND MEASUREMENT
60	020062	STATE OF THE GROUND (WITH OR WITHOUT SNOW)
61	002177	METHOD OF SNOW DEPTH MEASUREMENT
62	013013	TOTAL SNOW DEPTH
63	020010	CLOUD COVER (TOTAL)
64	008002	VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
65	020011	CLOUD AMOUNT
66	020012	CLOUD TYPE
67	033041	ATTRIBUTE OF FOLLOWING VALUE
68	020013	HEIGHT OF BASE OF CLOUD
69	008002	VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
70	020011	CLOUD AMOUNT
71	020012	CLOUD TYPE
72	033041	ATTRIBUTE OF FOLLOWING VALUE
73	020013	HEIGHT OF BASE OF CLOUD
74	008002	VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
75	020011	CLOUD AMOUNT
76	020012	CLOUD TYPE
77	033041	ATTRIBUTE OF FOLLOWING VALUE
78	020013	HEIGHT OF BASE OF CLOUD
79	008002	VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
80	020011	CLOUD AMOUNT
81	020012	CLOUD TYPE
82	033041	ATTRIBUTE OF FOLLOWING VALUE
83	020013	HEIGHT OF BASE OF CLOUD
84	020003	PRESENT WEATHER (SEE NOTE 1)
85	004025	TIME PERIOD OR DISPLACEMENT
86	020004	PAST WEATHER (1) (SEE NOTE 2)
87	020005	PAST WEATHER (2) (SEE NOTE 2)
88	008021	TIME SIGNIFICANCE
89	004025	TIME PERIOD OR DISPLACEMENT
90	013055	INTENSITY OF PRECIPITATION



91 013058 SIZE OF PRECIPITATING ELEMENT
 92 008021 TIME SIGNIFICANCE
 93 004025 TIME PERIOD OR DISPLACEMENT
 94 020021 TYPE OF PRECIPITATION
 95 020022 CHARACTER OF PRECIPITATION
 96 026020 DURATION OF PRECIPITATION
 97 020023 OTHER WEATHER PHENOMENA
 98 020024 INTENSITY OF PHENOMENA
 99 020025 OBSCURATION
 100 020026 CHARACTER OF OBSCURATION
 101 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 102 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
 103 008021 TIME SIGNIFICANCE
 104 004025 TIME PERIOD OR DISPLACEMENT
 105 011001 WIND DIRECTION
 106 011002 WIND SPEED
 107 008021 TIME SIGNIFICANCE
 108 004025 TIME PERIOD OR DISPLACEMENT
 109 011043 MAXIMUM WIND GUST DIRECTION
 110 011041 MAXIMUM WIND GUST SPEED
 111 004025 TIME PERIOD OR DISPLACEMENT
 112 011043 MAXIMUM WIND GUST DIRECTION
 113 011041 MAXIMUM WIND GUST SPEED
 114 004025 TIME PERIOD OR DISPLACEMENT
 115 011016 EXTREME COUNTERCLOCKWISE WIND DIRECTION OF A VARIABLE WIND
 116 011017 EXTREME CLOCKWISE WIND DIRECTION OF A VARIABLE WIND
 117 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 118 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
 119 004025 TIME PERIOD OR DISPLACEMENT
 120 012111 MAXIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
 121 012112 MINIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
 122 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 123 004025 TIME PERIOD OR DISPLACEMENT
 124 012112 MINIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
 125 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
 126 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 127 002175 METHOD OF PRECIPITATION MEASUREMENT
 128 002178 METHOD OF LIQUID CONTENT MEASUREMENT OF PRECIPITATION
 129 004025 TIME PERIOD OR DISPLACEMENT
 130 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALENT
 131 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
 132 002185 METHOD OF EVAPORATION MEASUREMENT
 133 004025 TIME PERIOD OR DISPLACEMENT
 134 013033 EVAPORATION/EVAPOTRANSPIRATION
 135 004025 TIME PERIOD OR DISPLACEMENT
 136 014031 TOTAL SUNSHINE
 137 004025 TIME PERIOD OR DISPLACEMENT
 138 014002 LONG-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
 139 014004 SHORT-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
 140 014016 NET RADIATION, INTEGRATED OVER PERIOD SPECIFIED
 141 014028 GLOBAL SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
 142 014029 DIFFUSE SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD
 143 014030 DIRECT SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
 144 004025 TIME PERIOD OR DISPLACEMENT
 145 013059 NUMBER OF FLASHES (THUNDERSTORM)

STARTING SUBSET TO BE PRINTED : 1
 ENDING SUBSET TO BE PRINTED : 1

1	WMO BLOCK NUMBE	0.1000000000E+02	NUMERIC	
2	WMO STATION NUM	0.3930000000E+03	NUMERIC	
3	STATION OR SITE	0.1020000000E+04	CCITTIA5	Lindenberg
4	TYPE OF STATION	0.1000000000E+01	CODE TABLE 2001	
5	YEAR	0.2005000000E+04	YEAR	
6	MONTH	0.5000000000E+01	MONTH	
7	DAY	0.4000000000E+01	DAY	
8	HOUR	0.9000000000E+01	HOUR	
9	MINUTE	0.0000000000E+00	MINUTE	
10	LATITUDE (HIGH)	0.5220970000E+02	DEGREE	
11	LONGITUDE (HIGH)	0.1412030000E+02	DEGREE	
12	HEIGHT OF STATI	0.9800000000E+02	M	
13	HEIGHT OF BAROM	0.1038000000E+03	M	
14	SURFACE QUALIFI	0.3000000000E+01	CODE TABLE 8010	
15	MAIN PRESENT WE	0.0000000000E+00	CODE TABLE 2180	
16	SUPPLEMENTARY P	0.1048576000E+07	FLAG TABLE 2181	
17	VISIBILITY MEAS	0.0000000000E+00	CODE TABLE 2182	
18	CLOUD DETECTION	0.1000000000E+01	CODE TABLE 2183	
19	TYPE OF LIGHTNI	0.0000000000E+00	CODE TABLE 2184	
20	TYPE OF SKY CON	0.0000000000E+00	CODE TABLE 2179	
21	CAPABILITY TO D	0.0000000000E+00	FLAG TABLE 2186	
22	CAPABILITY TO D	0.0000000000E+00	FLAG TABLE 2187	
23	CAPABILITY TO D	0.0000000000E+00	FLAG TABLE 2188	
24	CAPABILITY TO D	0.2048000000E+04	FLAG TABLE 2189	
25	PRESSURE	0.9966000000E+05	PA	
26	PRESSURE REDUCE	0.1008900000E+06	PA	
27	3-HOUR PRESSURE	0.5000000000E+02	PA	
28	CHARACTERISTIC	0.2000000000E+01	CODE TABLE 10063	
29	PRESSURE		MISSING PA	
30	GEOPOTENTIAL HE		MISSING GPM	
31	HEIGHT OF SENSO	0.2000000000E+01	M	
32	HEIGHT OF SENSO		MISSING M	
33	TEMPERATURE/DRY	0.2881500000E+03	K	
34	DEW-POINT TEMPE	0.2843500000E+03	K	



```
35 RELATIVE HUMIDI      0.7800000000E+02 %
36 DEPTH BELOW LAN     0.5000000000E-01 M
37 SOIL TEMPERATUR    0.2896500000E+03 K
38 DEPTH BELOW LAN     0.1000000000E+00 M
39 SOIL TEMPERATUR    0.2893500000E+03 K
40 DEPTH BELOW LAN     0.2000000000E+00 M
41 SOIL TEMPERATUR    0.2892500000E+03 K
42 DEPTH BELOW LAN     0.5000000000E+00 M
43 SOIL TEMPERATUR    0.2883500000E+03 K
44 DEPTH BELOW LAN     0.1000000000E+01 M
45 SOIL TEMPERATUR    0.2850500000E+03 K
46 HEIGHT OF SENSO     0.2000000000E+01 M
47 HEIGHT OF SENSO     MISSING M
48 ATTRIBUTE OF FO     0.0000000000E+00 CODE TABLE 33041
49 HORIZONTAL VISI     0.1200000000E+05 M
50 HEIGHT OF SENSO     MISSING M
51 HEIGHT OF SENSO     MISSING M
52 ICE DEPOSIT (TH     MISSING M
53 RATE OF ICE ACC     MISSING CODE TABLE 20032
54 METHOD OF WATER      MISSING CODE TABLE 2038
55 SEA/WATER TEMPE     MISSING K
56 DIRECTION OF WA     MISSING DEGREE TRUE
57 PERIOD OF WAVES     MISSING S
58 HEIGHT OF WAVES     MISSING M
59 METHOD OF STATE      0.0000000000E+00 CODE TABLE 2176
60 STATE OF THE GR     MISSING CODE TABLE 20062
61 METHOD OF SNOW       MISSING CODE TABLE 2177
62 TOTAL SNOW DEPT    MISSING M
63 CLOUD COVER (TO    0.8700000000E+02 %
64 VERTICAL SIGNIF     0.1000000000E+01 CODE TABLE 8002
65 CLOUD AMOUNT        0.4000000000E+01 CODE TABLE 20011
66 CLOUD TYPE          0.8000000000E+01 CODE TABLE 20012
67 ATTRIBUTE OF FO     0.0000000000E+00 CODE TABLE 33041
68 HEIGHT OF BASE      0.6300000000E+03 M
69 VERTICAL SIGNIF     0.2000000000E+01 CODE TABLE 8002
70 CLOUD AMOUNT        0.7000000000E+01 CODE TABLE 20011
71 CLOUD TYPE          0.6000000000E+01 CODE TABLE 20012
72 ATTRIBUTE OF FO     0.0000000000E+00 CODE TABLE 33041
73 HEIGHT OF BASE      0.9000000000E+03 M
74 VERTICAL SIGNIF     MISSING CODE TABLE 8002
75 CLOUD AMOUNT        MISSING CODE TABLE 20011
76 CLOUD TYPE          MISSING CODE TABLE 20012
77 ATTRIBUTE OF FO     MISSING CODE TABLE 33041
78 HEIGHT OF BASE      MISSING M
79 VERTICAL SIGNIF     MISSING CODE TABLE 8002
80 CLOUD AMOUNT        MISSING CODE TABLE 20011
81 CLOUD TYPE          MISSING CODE TABLE 20012
82 ATTRIBUTE OF FO     MISSING CODE TABLE 33041
83 HEIGHT OF BASE      MISSING M
84 PRESENT WEATHER     0.5080000000E+03 CODE TABLE 20003
85 TIME PERIOD OR      0.1800000000E+03 MINUTE
86 PAST WEATHER (1     0.1000000000E+02 CODE TABLE 20004
87 PAST WEATHER (2     0.1000000000E+02 CODE TABLE 20005
88 TIME SIGNIFICAN     0.2000000000E+01 CODE TABLE 8021
89 TIME PERIOD OR      -0.1000000000E+02 MINUTE
90 INTENSITY OF PR     MISSING KG/(M**2)S
91 SIZE OF PRECIPI     MISSING M
92 TIME SIGNIFICAN     MISSING CODE TABLE 8021
93 TIME PERIOD OR      -0.1000000000E+02 MINUTE
94 TYPE OF PRECIPI     MISSING FLAG TABLE 20021
95 CHARACTER OF PR     MISSING CODE TABLE 20022
96 DURATION OF PRE     MISSING MINUTE
97 OTHER WEATHER P     MISSING FLAG TABLE 20023
98 INTENSITY OF PH     MISSING CODE TABLE 20024
99 OBSCURATION         MISSING FLAG TABLE 20025
100 CHARACTER OF OB    MISSING CODE TABLE 20026
101 HEIGHT OF SENSO     0.1040000000E+02 M
102 HEIGHT OF SENSO     MISSING M
103 TIME SIGNIFICAN     0.2000000000E+01 CODE TABLE 8021
104 TIME PERIOD OR      -0.1000000000E+02 MINUTE
105 WIND DIRECTION      0.2800000000E+03 DEGREE TRUE
106 WIND SPEED          0.6000000000E+01 M/S
107 TIME SIGNIFICAN     MISSING CODE TABLE 8021
108 TIME PERIOD OR      -0.1000000000E+02 MINUTE
109 MAXIMUM WIND GU     MISSING DEGREE TRUE
110 MAXIMUM WIND GU     0.9000000000E+01 M/S
111 TIME PERIOD OR      -0.6000000000E+02 MINUTE
112 MAXIMUM WIND GU     MISSING DEGREE TRUE
113 MAXIMUM WIND GU     0.1000000000E+02 M/S
114 TIME PERIOD OR      -0.1000000000E+02 MINUTE
115 EXTREME COUNTER     MISSING DEGREE TRUE
116 EXTREME CLOCKWI     MISSING DEGREE TRUE
117 HEIGHT OF SENSO     0.2300000000E+01 M
118 HEIGHT OF SENSO     MISSING M
119 TIME PERIOD OR      -0.9000000000E+03 MINUTE
120 MAXIMUM TEMPERA     MISSING K
121 MINIMUM TEMPERA     0.2868500000E+03 K
122 HEIGHT OF SENSO     0.5000000000E-01 M
123 TIME PERIOD OR      -0.9000000000E+03 MINUTE
124 MINIMUM TEMPERA     0.2871500000E+03 K
125 HEIGHT OF SENSO     MISSING M
126 HEIGHT OF SENSO     0.1000000000E+01 M
127 METHOD OF PRECI     0.2000000000E+01 CODE TABLE 2175
```



```
128 METHOD OF LIQUI      0.0000000000E+00 CODE TABLE 2178
129 TIME PERIOD OR     -0.6000000000E+02 MINUTE
130 TOTAL PRECIPITA    0.0000000000E+00 KG/M**2
131 HEIGHT OF SENSO    MISSING M
132 METHOD OF EVAPO     MISSING CODE TABLE 2185
133 TIME PERIOD OR     -0.6000000000E+02 MINUTE
134 EVAPORATION/EVA    MISSING KG/M**2
135 TIME PERIOD OR     -0.6000000000E+02 MINUTE
136 TOTAL SUNSHINE     0.1000000000E+01 MINUTE
137 TIME PERIOD OR     -0.6000000000E+02 MINUTE
138 LONG-WAVE RADIA    MISSING J/M**2
139 SHORT-WAVE RADI    MISSING J/M**2
140 NET RADIATION,     MISSING J/M**2
141 GLOBAL SOLAR RA    0.7100000000E+06 J/M**2
142 DIFFUSE SOLAR R    0.6300000000E+06 J/M**2
143 DIRECT SOLAR RA    MISSING J/M**2
144 TIME PERIOD OR     -0.6000000000E+02 MINUTE
145 NUMBER OF FLASH    MISSING NUMERIC
```

6.2 WMO SYNOP template

BUFR TABLES TO BE LOADED B0000000000000013000.TXT,D0000000000000013000.TXT

BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)	8
TOTAL LENGTH OF BUFR MESSAGE (BYTES)	2498
BUFR EDITION NUMBER	4

BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)	22
BUFR MASTER TABLE	0
ORIGINATING CENTRE	89
ORIGINATING SUB-CENTRE	0
UPDATE SEQUENCE NUMBER	0
FLAG (PRESENCE OF SECTION 2)	0
DATA CATEGORY	0
DATA SUB-CATEGORY	0
LOCAL DATA SUB-CATEGORY	0
VERSION NUMBER OF MASTER TABLE	13
VERSION NUMBER OF LOCAL TABLE	0
YEAR	2007
MONTH	10
DAY	10
HOUR	20
MINUTE	0
SECOND	0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.

BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)	10
RESERVED	0
NUMBER OF DATA SUBSETS	36
FLAG (DATA TYPE/DATA COMPRESSION)	64

DATA DESCRIPTORS (UNEXPANDED)

1 307080

DATA DESCRIPTORS (EXPANDED)

1	001001	WMO BLOCK NUMBER
2	001002	WMO STATION NUMBER
3	001015	STATION OR SITE NAME
4	002001	TYPE OF STATION
5	004001	YEAR
6	004002	MONTH
7	004003	DAY
8	004004	HOUR
9	004005	MINUTE
10	005001	LATITUDE (HIGH ACCURACY)
11	006001	LONGITUDE (HIGH ACCURACY)
12	007030	HEIGHT OF STATION GROUND ABOVE MEAN SEA LEVEL (SEE NOTE 3)
13	007031	HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL (SEE NOTE 4)
14	010004	PRESSURE
15	010051	PRESSURE REDUCED TO MEAN SEA LEVEL
16	010061	3-HOUR PRESSURE CHANGE
17	010063	CHARACTERISTIC OF PRESSURE TENDENCY
18	010062	24-HOUR PRESSURE CHANGE
19	007004	PRESSURE
20	010009	GEOPOTENTIAL HEIGHT
21	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
22	012101	TEMPERATURE/DRY-BULB TEMPERATURE
23	012103	DEW-POINT TEMPERATURE
24	013003	RELATIVE HUMIDITY
25	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
26	020001	HORIZONTAL VISIBILITY
27	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
28	013023	TOTAL PRECIPITATION PAST 24 HOURS
29	007032	HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
30	020010	CLOUD COVER (TOTAL)
31	008002	VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
32	020011	CLOUD AMOUNT
33	020013	HEIGHT OF BASE OF CLOUD
34	020012	CLOUD TYPE
35	020012	CLOUD TYPE
36	020012	CLOUD TYPE
37	031001	DELAYED DESCRIPTOR REPLICATION FACTOR
38	008002	VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
39	020011	CLOUD AMOUNT
40	020012	CLOUD TYPE



```

41 020013 HEIGHT OF BASE OF CLOUD
42 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
43 020011 CLOUD AMOUNT
44 020012 CLOUD TYPE
45 020013 HEIGHT OF BASE OF CLOUD
46 031001 DELAYED DESCRIPTOR REPLICATION FACTOR
47 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
48 020011 CLOUD AMOUNT
49 020012 CLOUD TYPE
50 020014 HEIGHT OF TOP OF CLOUD
51 020017 CLOUD TOP DESCRIPTION
52 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
53 020054 TRUE DIRECTION FROM WHICH CLOUDS ARE MOVING
54 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
55 020054 TRUE DIRECTION FROM WHICH CLOUDS ARE MOVING
56 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
57 020054 TRUE DIRECTION FROM WHICH CLOUDS ARE MOVING
58 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
59 005021 BEARING OR AZIMUTH
60 007021 ELEVATION (SEE NOTE 2)
61 020012 CLOUD TYPE
62 005021 BEARING OR AZIMUTH
63 007021 ELEVATION (SEE NOTE 2)
64 020062 STATE OF THE GROUND (WITH OR WITHOUT SNOW)
65 013013 TOTAL SNOW DEPTH
66 012113 GROUND MINIMUM TEMPERATURE, PAST 12 HOURS
67 020003 PRESENT WEATHER (SEE NOTE 1)
68 004024 TIME PERIOD OR DISPLACEMENT
69 020004 PAST WEATHER (1) (SEE NOTE 2)
70 020005 PAST WEATHER (2) (SEE NOTE 2)
71 004024 TIME PERIOD OR DISPLACEMENT
72 014031 TOTAL SUNSHINE
73 004024 TIME PERIOD OR DISPLACEMENT
74 014031 TOTAL SUNSHINE
75 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
76 004024 TIME PERIOD OR DISPLACEMENT
77 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALENT
78 004024 TIME PERIOD OR DISPLACEMENT
79 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALENT
80 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
81 004024 TIME PERIOD OR DISPLACEMENT
82 004024 TIME PERIOD OR DISPLACEMENT
83 012111 MAXIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
84 004024 TIME PERIOD OR DISPLACEMENT
85 004024 TIME PERIOD OR DISPLACEMENT
86 012112 MINIMUM TEMPERATURE, AT HEIGHT AND OVER PERIOD SPECIFIED
87 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
88 002002 TYPE OF INSTRUMENTATION FOR WIND MEASUREMENT
89 008021 TIME SIGNIFICANCE
90 004025 TIME PERIOD OR DISPLACEMENT
91 011001 WIND DIRECTION
92 011002 WIND SPEED
93 008021 TIME SIGNIFICANCE
94 004025 TIME PERIOD OR DISPLACEMENT
95 011043 MAXIMUM WIND GUST DIRECTION
96 011041 MAXIMUM WIND GUST SPEED
97 004025 TIME PERIOD OR DISPLACEMENT
98 011043 MAXIMUM WIND GUST DIRECTION
99 011041 MAXIMUM WIND GUST SPEED
100 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
101 004024 TIME PERIOD OR DISPLACEMENT
102 002004 TYPE OF INSTRUMENTATION FOR EVAPORATION MEASUREMENT OR TYPE OF C
103 013033 EVAPORATION/EVAPOTRANSPIRATION
104 004024 TIME PERIOD OR DISPLACEMENT
105 014002 LONG-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
106 014004 SHORT-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
107 014016 NET RADIATION, INTEGRATED OVER PERIOD SPECIFIED
108 014028 GLOBAL SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
109 014029 DIFFUSE SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD
110 014030 DIRECT SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
111 004024 TIME PERIOD OR DISPLACEMENT
112 014002 LONG-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
113 014004 SHORT-WAVE RADIATION, INTEGRATED OVER PERIOD SPECIFIED
114 014016 NET RADIATION, INTEGRATED OVER PERIOD SPECIFIED
115 014028 GLOBAL SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
116 014029 DIFFUSE SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD
117 014030 DIRECT SOLAR RADIATION (HIGH ACCURACY), INTEGRATED OVER PERIOD S
118 004024 TIME PERIOD OR DISPLACEMENT
119 004024 TIME PERIOD OR DISPLACEMENT
120 012049 TEMPERATURE CHANGE OVER SPECIFIED PERIOD

```

```

STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1

```

```

1 WMO BLOCK NUMBER 0.11000000000000E+002 NUMERIC
2 WMO STATION NUMBER 0.42300000000000E+003 NUMERIC
3 STATION OR SITE NAME 0.10200000000000E+004 CCITIA5 Primda
4 TYPE OF STATION 0.10000000000000E+001 CODE TABLE 2001
5 YEAR 0.20070000000000E+004 YEAR
6 MONTH 0.10000000000000E+002 MONTH
7 DAY 0.10000000000000E+002 DAY
8 HOUR 0.20000000000000E+002 HOUR
9 MINUTE 0.00000000000000E+000 MINUTE

```



10	LATITUDE (HIGH ACCURACY)	0.496694400000000E+002	DEGREE
11	LONGITUDE (HIGH ACCURACY)	0.126777800000000E+002	DEGREE
12	HEIGHT OF STATION GROUND ABOVE M	0.742200000000000E+003	M
13	HEIGHT OF BAROMETER ABOVE MEAN S	0.747000000000000E+003	M
14	PRESSURE	0.937700000000000E+005	PA
15	PRESSURE REDUCED TO MEAN SEA LEV		MISSING PA
16	3-HOUR PRESSURE CHANGE	0.900000000000000E+002	PA
17	CHARACTERISTIC OF PRESSURE TENDE	0.200000000000000E+001	CODE TABLE 10063
18	24-HOUR PRESSURE CHANGE		MISSING PA
19	PRESSURE	0.925000000000000E+005	PA
20	GEOPOTENTIAL HEIGHT	0.860000000000000E+003	GPM
21	HEIGHT OF SENSOR ABOVE LOCAL GRO	0.195000000000000E+001	M
22	TEMPERATURE/DRY-BULB TEMPERATURE	0.279450000000000E+003	K
23	DEW-POINT TEMPERATURE	0.277450000000000E+003	K
24	RELATIVE HUMIDITY	0.870000000000000E+002	%
25	HEIGHT OF SENSOR ABOVE LOCAL GRO	0.480000000000000E+001	M
26	HORIZONTAL VISIBILITY	0.130000000000000E+005	M
27	HEIGHT OF SENSOR ABOVE LOCAL GRO	0.112000000000000E+001	M
28	TOTAL PRECIPITATION PAST 24 HOUR		MISSING KG/M**2
29	HEIGHT OF SENSOR ABOVE LOCAL GRO		MISSING M
30	CLOUD COVER (TOTAL)	0.130000000000000E+002	%
31	VERTICAL SIGNIFICANCE (SURFACE O	0.700000000000000E+001	CODE TABLE 8002
32	CLOUD AMOUNT	0.100000000000000E+001	CODE TABLE 20011
33	HEIGHT OF BASE OF CLOUD	0.990000000000000E+003	M
34	CLOUD TYPE	0.350000000000000E+002	CODE TABLE 20012
35	CLOUD TYPE	0.200000000000000E+002	CODE TABLE 20012
36	CLOUD TYPE	0.110000000000000E+002	CODE TABLE 20012
37	DELAYED DESCRIPTOR REPLICATION F	0.200000000000000E+001	NUMERIC
38	VERTICAL SIGNIFICANCE (SURFACE O	0.100000000000000E+001	CODE TABLE 8002
39	CLOUD AMOUNT	0.100000000000000E+001	CODE TABLE 20011
40	CLOUD TYPE	0.600000000000000E+001	CODE TABLE 20012
41	HEIGHT OF BASE OF CLOUD	0.990000000000000E+003	M
42	VERTICAL SIGNIFICANCE (SURFACE O		MISSING CODE TABLE 8002
43	CLOUD AMOUNT		MISSING CODE TABLE 20011
44	CLOUD TYPE		MISSING CODE TABLE 20012
45	HEIGHT OF BASE OF CLOUD		MISSING M
46	DELAYED DESCRIPTOR REPLICATION F	0.100000000000000E+001	NUMERIC
47	VERTICAL SIGNIFICANCE (SURFACE O		MISSING CODE TABLE 8002
48	CLOUD AMOUNT		MISSING CODE TABLE 20011
49	CLOUD TYPE		MISSING CODE TABLE 20012
50	HEIGHT OF TOP OF CLOUD		MISSING M
51	CLOUD TOP DESCRIPTION		MISSING CODE TABLE 20017
52	VERTICAL SIGNIFICANCE (SURFACE O	0.700000000000000E+001	CODE TABLE 8002
53	TRUE DIRECTION FROM WHICH CLOUDS		MISSING DEGREE TRUE
54	VERTICAL SIGNIFICANCE (SURFACE O	0.800000000000000E+001	CODE TABLE 8002
55	TRUE DIRECTION FROM WHICH CLOUDS		MISSING DEGREE TRUE
56	VERTICAL SIGNIFICANCE (SURFACE O	0.900000000000000E+001	CODE TABLE 8002
57	TRUE DIRECTION FROM WHICH CLOUDS		MISSING DEGREE TRUE
58	VERTICAL SIGNIFICANCE (SURFACE O		MISSING CODE TABLE 8002
59	BEARING OR AZIMUTH		MISSING DEGREE TRUE
60	ELEVATION (SEE NOTE 2)		MISSING DEGREE
61	CLOUD TYPE		MISSING CODE TABLE 20012
62	BEARING OR AZIMUTH		MISSING DEGREE TRUE
63	ELEVATION (SEE NOTE 2)		MISSING DEGREE
64	STATE OF THE GROUND (WITH OR WIT		MISSING CODE TABLE 20062
65	TOTAL SNOW DEPTH		MISSING M
66	GROUND MINIMUM TEMPERATURE, PAST		MISSING K
67	PRESENT WEATHER (SEE NOTE 1)	0.508000000000000E+003	CODE TABLE 20003
68	TIME PERIOD OR DISPLACEMENT	-0.100000000000000E+001	HOUR
69	PAST WEATHER (1) (SEE NOTE 2)	0.100000000000000E+002	CODE TABLE 20004
70	PAST WEATHER (2) (SEE NOTE 2)	0.100000000000000E+002	CODE TABLE 20005
71	TIME PERIOD OR DISPLACEMENT	-0.100000000000000E+001	HOUR
72	TOTAL SUNSHINE		MISSING MINUTE
73	TIME PERIOD OR DISPLACEMENT	-0.240000000000000E+002	HOUR
74	TOTAL SUNSHINE		MISSING MINUTE
75	HEIGHT OF SENSOR ABOVE LOCAL GRO	0.112000000000000E+001	M
76	TIME PERIOD OR DISPLACEMENT		MISSING HOUR
77	TOTAL PRECIPITATION/TOTAL WATER		MISSING KG/M**2
78	TIME PERIOD OR DISPLACEMENT	-0.100000000000000E+001	HOUR
79	TOTAL PRECIPITATION/TOTAL WATER	0.000000000000000E+000	KG/M**2
80	HEIGHT OF SENSOR ABOVE LOCAL GRO	0.195000000000000E+001	M
81	TIME PERIOD OR DISPLACEMENT	-0.120000000000000E+002	HOUR
82	TIME PERIOD OR DISPLACEMENT	0.000000000000000E+000	HOUR
83	MAXIMUM TEMPERATURE, AT HEIGHT A		MISSING K
84	TIME PERIOD OR DISPLACEMENT	-0.120000000000000E+002	HOUR
85	TIME PERIOD OR DISPLACEMENT	0.000000000000000E+000	HOUR
86	MINIMUM TEMPERATURE, AT HEIGHT A		MISSING K
87	HEIGHT OF SENSOR ABOVE LOCAL GRO	0.102500000000000E+002	M
88	TYPE OF INSTRUMENTATION FOR WIND	0.800000000000000E+001	FLAG TABLE 2002
89	TIME SIGNIFICANCE	0.200000000000000E+001	CODE TABLE 8021
90	TIME PERIOD OR DISPLACEMENT	-0.100000000000000E+002	MINUTE
91	WIND DIRECTION	0.900000000000000E+002	DEGREE TRUE
92	WIND SPEED	0.400000000000000E+001	M/S
93	TIME SIGNIFICANCE		MISSING CODE TABLE 8021
94	TIME PERIOD OR DISPLACEMENT	-0.100000000000000E+002	MINUTE
95	MAXIMUM WIND GUST DIRECTION		MISSING DEGREE TRUE
96	MAXIMUM WIND GUST SPEED		MISSING M/S
97	TIME PERIOD OR DISPLACEMENT	-0.600000000000000E+002	MINUTE
98	MAXIMUM WIND GUST DIRECTION		MISSING DEGREE TRUE
99	MAXIMUM WIND GUST SPEED		MISSING M/S
100	HEIGHT OF SENSOR ABOVE LOCAL GRO		MISSING M
101	TIME PERIOD OR DISPLACEMENT	-0.240000000000000E+002	HOUR
102	TYPE OF INSTRUMENTATION FOR EVAP		MISSING CODE TABLE 2004



```
103 EVAPORATION/EVAPOTRANSPIRATION          MISSING KG/M**2
104 TIME PERIOD OR DISPLACEMENT             -0.100000000000000000E+001 HOUR
105 LONG-WAVE RADIATION, INTEGRATED          MISSING J/M**2
106 SHORT-WAVE RADIATION, INTEGRATED         MISSING J/M**2
107 NET RADIATION, INTEGRATED OVER P        MISSING J/M**2
108 GLOBAL SOLAR RADIATION (HIGH ACC        MISSING J/M**2
109 DIFFUSE SOLAR RADIATION (HIGH AC        MISSING J/M**2
110 DIRECT SOLAR RADIATION (HIGH ACC        MISSING J/M**2
111 TIME PERIOD OR DISPLACEMENT             -0.240000000000000000E+002 HOUR
112 LONG-WAVE RADIATION, INTEGRATED          MISSING J/M**2
113 SHORT-WAVE RADIATION, INTEGRATED         MISSING J/M**2
114 NET RADIATION, INTEGRATED OVER P        MISSING J/M**2
115 GLOBAL SOLAR RADIATION (HIGH ACC        MISSING J/M**2
116 DIFFUSE SOLAR RADIATION (HIGH AC        MISSING J/M**2
117 DIRECT SOLAR RADIATION (HIGH ACC        MISSING J/M**2
118 TIME PERIOD OR DISPLACEMENT             MISSING HOUR
119 TIME PERIOD OR DISPLACEMENT             MISSING HOUR
120 TEMPERATURE CHANGE OVER SPECIFIE        MISSING K
```

6.3 WMO BUOY template

ECMWF

BUFR DECODING SOFTWARE VERSION - 7.2
1 APRIL 2007.

Your path for bufr tables is :
/home/ma/maa/bigtmp/wmo_bufr_crex_000250/bufr_000360/bufrtables/
BUFR TABLES TO BE LOADED B000000000000011000.TXT,D000000000000011000.TXT

BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)	8
TOTAL LENGTH OF BUFR MESSAGE (BYTES)	380
BUFR EDITION NUMBER	3

BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)	18
BUFR EDITION NUMBER	3
ORIGINATING SUB-CENTRE	0
ORIGINATING CENTRE	216
UPDATE SEQUENCE NUMBER	1
FLAG (PRESENCE OF SECTION 2)	0
BUFR MESSAGE TYPE	1
BUFR MESSAGE SUBTYPE	0
VERSION NUMBER OF LOCAL TABLE	0
YEAR	5
MONTH	5
DAY	4
HOUR	5
MINUTE	44
VERSION NUMBER OF MASTER TABLE	11
BUFR MASTER TABLE	0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.

BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)	176
RESERVED	0
NUMBER OF DATA SUBSETS	1
FLAG (DATA TYPE/DATA COMPRESSION)	128

DATA DESCRIPTORS (UNEXPANDED)

1	001003
2	001020
3	001005
4	002001
5	002036
6	002149
7	301011
8	301012
9	008021
10	301011
11	301012
12	008021
13	301021
14	027004
15	028004
16	007030
17	001051
18	002148
19	001012
20	001014
21	002040
22	033022
23	033023
24	033027
25	022063
26	302021
27	302022
28	302023
29	008081
30	025026
31	008081
32	025026
33	008081
34	025026
35	008081
36	002034
37	022060



38 007070
 39 002190
 40 025086
 41 002035
 42 002168
 43 020031
 44 002038
 45 306004
 46 002030
 47 306005
 48 007031
 49 008081
 50 012064
 51 302001
 52 008081
 53 007032
 54 007033
 55 012101
 56 012103
 57 013003
 58 007032
 59 007033
 60 008082
 61 007033
 62 002169
 63 002002
 64 008021
 65 004025
 66 011001
 67 011002
 68 008021
 69 004025
 70 011043
 71 011041
 72 008082
 73 007033
 74 007032
 75 004024
 76 013011
 77 007032
 78 008021
 79 004024
 80 014021
 81 008021
 82 025028
 83 025028
 84 025028

DATA DESCRIPTORS (EXPANDED)

1 001003 WMO REGION NUMBER/GEOGRAPHICAL AREA
 2 001020 WMO REGION SUB-AREA
 3 001005 BUOY/PLATFORM IDENTIFIER
 4 002001 TYPE OF STATION
 5 002036 BUOY TYPE
 6 002149 TYPE OF DATA BUOY
 7 004001 YEAR
 8 004002 MONTH
 9 004003 DAY
 10 004004 HOUR
 11 004005 MINUTE
 12 008021 TIME SIGNIFICANCE
 13 004001 YEAR
 14 004002 MONTH
 15 004003 DAY
 16 004004 HOUR
 17 004005 MINUTE
 18 008021 TIME SIGNIFICANCE
 19 005001 LATITUDE (HIGH ACCURACY)
 20 006001 LONGITUDE (HIGH ACCURACY)
 21 027004 ALTERNATE LATITUDE (HIGH ACCURACY)
 22 028004 ALTERNATE LONGITUDE (HIGH ACCURACY)
 23 007030 HEIGHT OF STATION GROUND ABOVE MEAN SEA LEVEL (SEE NOTE 3)
 24 001051 PLATFORM TRANSMITTER ID NUMBER
 25 002148 DATA COLLECTION AND/OR LOCATION SYSTEM
 26 001012 DIRECTION OF MOTION OF MOVING OBSERVING PLATFORM**
 27 001014 PLATFORM DRIFT SPEED (HIGH PRECISION)
 28 002040 METHOD OF REMOVING VELOCITY AND MOTION OF PLATFORM FROM CURRENT
 29 033022 QUALITY OF BUOY SATELLITE TRANSMISSION
 30 033023 QUALITY OF BUOY LOCATION
 31 033027 LOCATION QUALITY CLASS (RANGE OF RADIUS OF 66 % CONFIDENCE)
 32 022063 TOTAL WATER DEPTH
 33 022001 DIRECTION OF WAVES
 34 022011 PERIOD OF WAVES
 35 022021 HEIGHT OF WAVES
 36 022002 DIRECTION OF WIND WAVES
 37 022012 PERIOD OF WIND WAVES
 38 022022 HEIGHT OF WIND WAVES
 39 022003 DIRECTION OF SWELL WAVES
 40 022013 PERIOD OF SWELL WAVES
 41 022023 HEIGHT OF SWELL WAVES
 42 008081 TYPE OF EQUIPMENT



43 025026 BATTERY VOLTAGE (LARGE RANGE)
44 008081 TYPE OF EQUIPMENT
45 025026 BATTERY VOLTAGE (LARGE RANGE)
46 008081 TYPE OF EQUIPMENT
47 025026 BATTERY VOLTAGE (LARGE RANGE)
48 008081 TYPE OF EQUIPMENT
49 002034 DROGUE TYPE
50 022060 LAGRANGIAN DRIFTER DROGUE STATUS
51 007070 DROGUE DEPTH
52 002190 LAGRANGIAN DRIFTER SUBMERGENCE (% TIME SUBMERGED)
53 025086 DEPTH CORRECTION INDICATOR
54 002035 CABLE LENGTH
55 002168 HYDROSTATIC PRESSURE OF LOWER END OF CABLE (THERMISTOR STRING)
56 020031 ICE DEPOSIT (THICKNESS)
57 002038 METHOD OF WATER TEMPERATURE AND/OR SALINITY MEASUREMENT
58 002032 INDICATOR FOR DIGITIZATION
59 002033 METHOD OF SALINITY/DEPTH MEASUREMENT
60 031001 DELAYED DESCRIPTOR REPLICATION FACTOR
61 007062 DEPTH BELOW SEA/WATER SURFACE
62 022043 SEA/WATER TEMPERATURE
63 022062 SALINITY
64 007062 DEPTH BELOW SEA/WATER SURFACE
65 022043 SEA/WATER TEMPERATURE
66 022062 SALINITY
67 007062 DEPTH BELOW SEA/WATER SURFACE
68 022043 SEA/WATER TEMPERATURE
69 022062 SALINITY
70 007062 DEPTH BELOW SEA/WATER SURFACE
71 022043 SEA/WATER TEMPERATURE
72 022062 SALINITY
73 007062 DEPTH BELOW SEA/WATER SURFACE
74 022043 SEA/WATER TEMPERATURE
75 022062 SALINITY
76 007062 DEPTH BELOW SEA/WATER SURFACE
77 022043 SEA/WATER TEMPERATURE
78 022062 SALINITY
79 007062 DEPTH BELOW SEA/WATER SURFACE
80 022043 SEA/WATER TEMPERATURE
81 022062 SALINITY
82 002030 METHOD OF CURRENT MEASUREMENT
83 002031 DURATION AND TIME OF CURRENT MEASUREMENT
84 031001 DELAYED DESCRIPTOR REPLICATION FACTOR
85 007031 HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL (SEE NOTE 4)
86 008081 TYPE OF EQUIPMENT
87 012064 INSTRUMENT TEMPERATURE
88 010004 PRESSURE
89 010051 PRESSURE REDUCED TO MEAN SEA LEVEL
90 010061 3-HOUR PRESSURE CHANGE
91 010063 CHARACTERISTIC OF PRESSURE TENDENCY
92 008081 TYPE OF EQUIPMENT
93 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
94 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
95 012101 TEMPERATURE/DRY-BULB TEMPERATURE
96 012103 DEW-POINT TEMPERATURE
97 013003 RELATIVE HUMIDITY
98 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
99 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
100 008082 (CBS) ARTIFICIAL CORRECTION OF SENSOR HEIGHT TO ANOTHER VALUE
101 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
102 002169 ANEMOMETER TYPE
103 002002 TYPE OF INSTRUMENTATION FOR WIND MEASUREMENT
104 008021 TIME SIGNIFICANCE
105 004025 TIME PERIOD OR DISPLACEMENT
106 011001 WIND DIRECTION
107 011002 WIND SPEED
108 008021 TIME SIGNIFICANCE
109 004025 TIME PERIOD OR DISPLACEMENT
110 011043 MAXIMUM WIND GUST DIRECTION
111 011041 MAXIMUM WIND GUST SPEED
112 008082 (CBS) ARTIFICIAL CORRECTION OF SENSOR HEIGHT TO ANOTHER VALUE
113 007033 HEIGHT OF SENSOR ABOVE WATER SURFACE (SEE NOTE 6)
114 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
115 004024 TIME PERIOD OR DISPLACEMENT
116 013011 TOTAL PRECIPITATION/TOTAL WATER EQUIVALENT
117 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
118 008021 TIME SIGNIFICANCE
119 004024 TIME PERIOD OR DISPLACEMENT
120 014021 GLOBAL SOLAR RADIATION, INTEGRATED OVER PERIOD SPECIFIED
121 008021 TIME SIGNIFICANCE
122 025028 OPERATOR OR MANUFACTURER DEFINED PARAMETER
123 025028 OPERATOR OR MANUFACTURER DEFINED PARAMETER
124 025028 OPERATOR OR MANUFACTURER DEFINED PARAMETER

STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1

1	WMO REGION NUMBER/GEOGRAPHICAL AREA	0.500000000000000E+001	CODE TABLE 1003
2	WMO REGION SUB-AREA	0.200000000000000E+001	NUMERIC
3	BUOY/PLATFORM IDENTIFIER	0.870000000000000E+002	NUMERIC
4	TYPE OF STATION	0.000000000000000E+000	CODE TABLE 2001
5	BUOY TYPE	0.100000000000000E+001	CODE TABLE 2036
6	TYPE OF DATA BUOY	0.220000000000000E+002	CODE TABLE 2149
7	YEAR	0.200500000000000E+004	YEAR



8	MONTH	0.500000000000000E+001	MONTH	
9	DAY	0.400000000000000E+001	DAY	
10	HOURL	0.300000000000000E+001	HOURL	
11	MINUTE	0.000000000000000E+000	MINUTE	
12	TIME SIGNIFICANCE	0.260000000000000E+002	CODE TABLE 8021	
13	YEAR	0.200500000000000E+004	YEAR	
14	MONTH	0.500000000000000E+001	MONTH	
15	DAY	0.400000000000000E+001	DAY	
16	HOURL	0.200000000000000E+001	HOURL	
17	MINUTE	0.450000000000000E+002	MINUTE	
18	TIME SIGNIFICANCE		MISSING CODE TABLE 8021	
19	LATITUDE (HIGH ACCURACY)	0.764704000000000E+001	DEGREE	
20	LONGITUDE (HIGH ACCURACY)	0.136699940000000E+003	DEGREE	
21	ALTERNATE LATITUDE (HIGH ACCURAC	0.166040500000000E+002	DEGREE	
22	ALTERNATE LONGITUDE (HIGH ACCURA	0.968663000000000E+002	DEGREE	
23	HEIGHT OF STATION GROUND ABOVE M	0.000000000000000E+000	M	
24	PLATFORM TRANSMITTER ID NUMBER	0.101200000000000E+004	CCITTIA5	03595
25	DATA COLLECTION AND/OR LOCATION	0.100000000000000E+001	CODE TABLE 2148	
26	DIRECTION OF MOTION OF MOVING OB		MISSING DEGREE TRUE	
27	PLATFORM DRIFT SPEED (HIGH PRECI		MISSING M/S	
28	METHOD OF REMOVING VELOCITY AND		MISSING CODE TABLE 2040	
29	QUALITY OF BUOY SATELLITE TRANSM	0.000000000000000E+000	CODE TABLE 33022	
30	QUALITY OF BUOY LOCATION	0.000000000000000E+000	CODE TABLE 33023	
31	LOCATION QUALITY CLASS (RANGE OF	0.100000000000000E+001	CODE TABLE 33027	
32	TOTAL WATER DEPTH		MISSING M	
33	DIRECTION OF WAVES		MISSING DEGREE TRUE	
34	PERIOD OF WAVES		MISSING S	
35	HEIGHT OF WAVES		MISSING M	
36	DIRECTION OF WIND WAVES		MISSING DEGREE TRUE	
37	PERIOD OF WIND WAVES		MISSING S	
38	HEIGHT OF WIND WAVES		MISSING M	
39	DIRECTION OF SWELL WAVES		MISSING DEGREE TRUE	
40	PERIOD OF SWELL WAVES		MISSING S	
41	HEIGHT OF SWELL WAVES		MISSING M	
42	TYPE OF EQUIPMENT		MISSING CODE TABLE 8081	
43	BATTERY VOLTAGE (LARGE RANGE)		MISSING V	
44	TYPE OF EQUIPMENT		MISSING CODE TABLE 8081	
45	BATTERY VOLTAGE (LARGE RANGE)		MISSING V	
46	TYPE OF EQUIPMENT		MISSING CODE TABLE 8081	
47	BATTERY VOLTAGE (LARGE RANGE)		MISSING V	
48	TYPE OF EQUIPMENT		MISSING CODE TABLE 8081	
49	DROGUE TYPE		MISSING CODE TABLE 2034	
50	LAGRANGIAN DRIFTER DROGUE STATUS		MISSING CODE TABLE 22060	
51	DROGUE DEPTH		MISSING M	
52	LAGRANGIAN DRIFTER SUBMERGENCE (MISSING %	
53	DEPTH CORRECTION INDICATOR	0.000000000000000E+000	CODE TABLE 25086	
54	CABLE LENGTH	0.000000000000000E+000	M	
55	HYDROSTATIC PRESSURE OF LOWER EN		MISSING PA	
56	ICE DEPOSIT (THICKNESS)		MISSING M	
57	METHOD OF WATER TEMPERATURE AND/		MISSING CODE TABLE 2038	
58	INDICATOR FOR DIGITIZATION		MISSING CODE TABLE 2032	
59	METHOD OF SALINITY/DEPTH MEASURE		MISSING CODE TABLE 2033	
60	DELAYED DESCRIPTOR REPLICATION F	0.700000000000000E+001	NUMERIC	
61	DEPTH BELOW SEA/WATER SURFACE	0.150000000000000E+001	M	
62	SEA/WATER TEMPERATURE	0.302420000000000E+003	K	
63	SALINITY	0.341400000000000E+002	PART PER THOUSAND	
64	DEPTH BELOW SEA/WATER SURFACE	0.250000000000000E+002	M	
65	SEA/WATER TEMPERATURE	0.302240000000000E+003	K	
66	SALINITY	0.342000000000000E+002	PART PER THOUSAND	
67	DEPTH BELOW SEA/WATER SURFACE	0.500000000000000E+002	M	
68	SEA/WATER TEMPERATURE	0.302230000000000E+003	K	
69	SALINITY	0.342200000000000E+002	PART PER THOUSAND	
70	DEPTH BELOW SEA/WATER SURFACE	0.750000000000000E+002	M	
71	SEA/WATER TEMPERATURE	0.299220000000000E+003	K	
72	SALINITY	0.345300000000000E+002	PART PER THOUSAND	
73	DEPTH BELOW SEA/WATER SURFACE	0.100000000000000E+003	M	
74	SEA/WATER TEMPERATURE	0.295760000000000E+003	K	
75	SALINITY	0.348200000000000E+002	PART PER THOUSAND	
76	DEPTH BELOW SEA/WATER SURFACE	0.300000000000000E+003	M	
77	SEA/WATER TEMPERATURE	0.282550000000000E+003	K	
78	SALINITY	0.345400000000000E+002	PART PER THOUSAND	
79	DEPTH BELOW SEA/WATER SURFACE	0.750000000000000E+003	M	
80	SEA/WATER TEMPERATURE	0.279620000000000E+003	K	
81	SALINITY	0.345300000000000E+002	PART PER THOUSAND	
82	METHOD OF CURRENT MEASUREMENT		MISSING CODE TABLE 2030	
83	DURATION AND TIME OF CURRENT MEA		MISSING CODE TABLE 2031	
84	DELAYED DESCRIPTOR REPLICATION F	0.000000000000000E+000	NUMERIC	
85	HEIGHT OF BAROMETER ABOVE MEAN S		MISSING M	
86	TYPE OF EQUIPMENT		MISSING CODE TABLE 8081	
87	INSTRUMENT TEMPERATURE		MISSING K	
88	PRESSURE		MISSING PA	
89	PRESSURE REDUCED TO MEAN SEA LEV		MISSING PA	
90	3-HOUR PRESSURE CHANGE		MISSING PA	
91	CHARACTERISTIC OF PRESSURE TENDE		MISSING CODE TABLE 10063	
92	TYPE OF EQUIPMENT		MISSING CODE TABLE 8081	
93	HEIGHT OF SENSOR ABOVE LOCAL GRO		MISSING M	
94	HEIGHT OF SENSOR ABOVE WATER SUR		MISSING M	
95	TEMPERATURE/DRY-BULB TEMPERATURE		MISSING K	
96	DEW-POINT TEMPERATURE		MISSING K	
97	RELATIVE HUMIDITY		MISSING %	
98	HEIGHT OF SENSOR ABOVE LOCAL GRO		MISSING M	
99	HEIGHT OF SENSOR ABOVE WATER SUR		MISSING M	
100	(CBS) ARTIFICIAL CORRECTION OF S		MISSING CODE TABLE 8082	



101	HEIGHT OF SENSOR ABOVE WATER SUR		MISSING M
102	ANEMOMETER TYPE		MISSING CODE TABLE 2169
103	TYPE OF INSTRUMENTATION FOR WIND		MISSING FLAG TABLE 2002
104	TIME SIGNIFICANCE	0.200000000000000000E+001	CODE TABLE 8021
105	TIME PERIOD OR DISPLACEMENT		MISSING MINUTE
106	WIND DIRECTION		MISSING DEGREE TRUE
107	WIND SPEED		MISSING M/S
108	TIME SIGNIFICANCE		MISSING CODE TABLE 8021
109	TIME PERIOD OR DISPLACEMENT		MISSING MINUTE
110	MAXIMUM WIND GUST DIRECTION		MISSING DEGREE TRUE
111	MAXIMUM WIND GUST SPEED		MISSING M/S
112	(CBS) ARTIFICIAL CORRECTION OF S		MISSING CODE TABLE 8082
113	HEIGHT OF SENSOR ABOVE WATER SUR		MISSING M
114	HEIGHT OF SENSOR ABOVE LOCAL GRO		MISSING M
115	TIME PERIOD OR DISPLACEMENT		MISSING HOUR
116	TOTAL PRECIPITATION/TOTAL WATER		MISSING KG/M**2
117	HEIGHT OF SENSOR ABOVE LOCAL GRO		MISSING M
118	TIME SIGNIFICANCE	0.300000000000000000E+001	CODE TABLE 8021
119	TIME PERIOD OR DISPLACEMENT		MISSING HOUR
120	GLOBAL SOLAR RADIATION, INTEGRAT		MISSING J/M**2
121	TIME SIGNIFICANCE		MISSING CODE TABLE 8021
122	OPERATOR OR MANUFACTURER DEFINED		MISSING NUMERIC
123	OPERATOR OR MANUFACTURER DEFINED		MISSING NUMERIC
124	OPERATOR OR MANUFACTURER DEFINED		MISSING NUMERIC



6.4 WMO CLIMATE SYNOP template

ECMWF

BUFR DECODING SOFTWARE VERSION - 7.1
07 June 2005.

Your path for bufr tables is :
/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables/
BUFR TABLES TO BE LOADED B0000000000098012000,D0000000000098012000

1
BUFR SECTION 0
LENGTH OF SECTION 0 (BYTES) 8
TOTAL LENGTH OF BUFR MESSAGE (BYTES) 492
BUFR EDITION NUMBER 3

1
BUFR SECTION 1
LENGTH OF SECTION 1 (BYTES) 24
BUFR EDITION NUMBER 3
ORIGINATING SUB-CENTRE 0
ORIGINATING CENTRE 89
UPDATE SEQUENCE NUMBER 0
FLAG (PRESENCE OF SECTION 2) 0
BUFR MESSAGE TYPE 0
BUFR MESSAGE SUBTYPE 0
VERSION NUMBER OF LOCAL TABLE 0
YEAR 3
MONTH 11
DAY 1
HOUR 0
MINUTE 0
VERSION NUMBER OF MASTER TABLE 12
BUFR MASTER TABLE 0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.

1
BUFR SECTION 3
LENGTH OF SECTION 3 (BYTES) 214
RESERVED 0
NUMBER OF DATA SUBSETS 1
FLAG (DATA TYPE/DATA COMPRESSION) 128

DATA DESCRIPTORS (UNEXPANDED)

1 301090
2 004023
3 008023
4 010004
5 010051
6 007004
7 010009
8 007032
9 012101
10 002051
11 004051
12 012118
13 004052
14 012119
15 013004
16 008023
17 012151
18 007032
19 102005
20 008050
21 008020
22 014032
23 014033
24 008050
25 008020
26 102018
27 008052
28 008022
29 007032
30 008053
31 004003
32 012152
33 008053
34 004003
35 012153
36 008053
37 004003
38 008023

39 012101
40 008053
41 004003
42 008023
43 012101
44 008023
45 007032
46 002002
47 008053
48 004003
49 011046
50 008053
51 004003
52 004004
53 004023
54 007032
55 013060
56 013051
57 004053
58 008050
59 008020
60 102006
61 008052
62 008022
63 008053
64 004003
65 013052
66 007032
67 004001
68 004001
69 004002
70 004003
71 004004
72 004022
73 008023
74 010004
75 010051
76 007004
77 010009
78 007032
79 012101
80 002051
81 004051
82 012118
83 004052
84 012119
85 013004
86 012151
87 007032
88 014032
89 008023
90 004001
91 004001
92 004002
93 004003
94 004004
95 004022
96 007032
97 008023
98 013060
99 004053
100 008023
101 102006
102 008050
103 008020

DATA DESCRIPTORS (EXPANDED)

1 001001 WMO BLOCK NUMBER
2 001002 WMO STATION NUMBER
3 001015 STATION OR SITE NAME
4 002001 TYPE OF STATION
5 004001 YEAR
6 004002 MONTH
7 004003 DAY
8 004004 HOUR
9 004005 MINUTE
10 005001 LATITUDE (HIGH ACCURACY)
11 006001 LONGITUDE (HIGH ACCURACY)
12 007030 HEIGHT OF STATION GROUND ABOVE MEAN SEA LEVEL (SEE NOTE 3)
13 007031 HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL (SEE NOTE 4)
14 004023 TIME PERIOD OR DISPLACEMENT
15 008023 FIRST ORDER STATISTICS
16 010004 PRESSURE
17 010051 PRESSURE REDUCED TO MEAN SEA LEVEL
18 007004 PRESSURE
19 010009 GEOPOTENTIAL HEIGHT
20 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
21 012101 TEMPERATURE/DRY-BULB TEMPERATURE
22 002051 INDICATOR TO SPECIFY OBSERVING METHOD FOR EXTREME TEMPERATURES
23 004051 PRINCIPAL TIME OF DAILY READING OF MAXIMUM TEMPERATURE
24 012118 MAXIMUM TEMPERATURE AT HEIGHT SPECIFIED, PAST 24 HOURS

25 004052 PRINCIPAL TIME OF DAILY READING OF MINIMUM TEMPERATURE
26 012119 MINIMUM TEMPERATURE AT HEIGHT SPECIFIED, PAST 24 HOURS
27 013004 VAPOUR PRESSURE
28 008023 FIRST ORDER STATISTICS
29 012151 STANDARD DEVIATION OF DAILY MEAN TEMPERATURE
30 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
31 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
32 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
33 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
34 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
35 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
36 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
37 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
38 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
39 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
40 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
41 014032 TOTAL SUNSHINE
42 014033 TOTAL SUNSHINE
43 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
44 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
45 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
46 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
47 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
48 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
49 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
50 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
51 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
52 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
53 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
54 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
55 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
56 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
57 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
58 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
59 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
60 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
61 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
62 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
63 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
64 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
65 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
66 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
67 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
68 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
69 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
70 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
71 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
72 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
73 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
74 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
75 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
76 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
77 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
78 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
79 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
80 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
81 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
82 008053 DAY OF OCCURRENCE QUALIFIER
83 004003 DAY
84 012152 HIGHEST DAILY MEAN TEMPERATURE
85 008053 DAY OF OCCURRENCE QUALIFIER
86 004003 DAY
87 012153 LOWEST DAILY MEAN TEMPERATURE
88 008053 DAY OF OCCURRENCE QUALIFIER
89 004003 DAY
90 008023 FIRST ORDER STATISTICS
91 012101 TEMPERATURE/DRY-BULB TEMPERATURE
92 008053 DAY OF OCCURRENCE QUALIFIER
93 004003 DAY
94 008023 FIRST ORDER STATISTICS
95 012101 TEMPERATURE/DRY-BULB TEMPERATURE
96 008023 FIRST ORDER STATISTICS
97 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
98 002002 TYPE OF INSTRUMENTATION FOR WIND MEASUREMENT
99 008053 DAY OF OCCURRENCE QUALIFIER
100 004003 DAY
101 011046 MAXIMUM INSTANTANEOUS WIND SPEED
102 008053 DAY OF OCCURRENCE QUALIFIER
103 004003 DAY
104 004004 HOUR
105 004023 TIME PERIOD OR DISPLACEMENT
106 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
107 013060 TOTAL ACCUMULATED PRECIPITATION
108 013051 FREQUENCY GROUP, PRECIPITATION
109 004053 NUMBER OF DAYS WITH PRECIPITATION EQUAL TO OR MORE THAN 1 MM
110 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
111 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
112 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
113 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
114 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
115 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
116 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
117 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)

118 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
119 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
120 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
121 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
122 008052 CONDITION FOR WHICH NUMBER OF DAYS OF OCCURRENCE FOLLOWS
123 008022 TOTAL NUMBER (WITH RESPECT TO ACCUMULATION OR AVERAGE)
124 008053 DAY OF OCCURRENCE QUALIFIER
125 004003 DAY
126 013052 HIGHEST DAILY AMOUNT OF PRECIPITATION
127 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
128 004001 YEAR
129 004001 YEAR
130 004002 MONTH
131 004003 DAY
132 004004 HOUR
133 004022 TIME PERIOD OR DISPLACEMENT
134 008023 FIRST ORDER STATISTICS
135 010004 PRESSURE
136 010051 PRESSURE REDUCED TO MEAN SEA LEVEL
137 007004 PRESSURE
138 010009 GEOPOTENTIAL HEIGHT
139 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
140 012101 TEMPERATURE/DRY-BULB TEMPERATURE
141 002051 INDICATOR TO SPECIFY OBSERVING METHOD FOR EXTREME TEMPERATURES
142 004051 PRINCIPAL TIME OF DAILY READING OF MAXIMUM TEMPERATURE
143 012118 MAXIMUM TEMPERATURE AT HEIGHT SPECIFIED, PAST 24 HOURS
144 004052 PRINCIPAL TIME OF DAILY READING OF MINIMUM TEMPERATURE
145 012119 MINIMUM TEMPERATURE AT HEIGHT SPECIFIED, PAST 24 HOURS
146 013004 VAPOUR PRESSURE
147 012151 STANDARD DEVIATION OF DAILY MEAN TEMPERATURE
148 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
149 014032 TOTAL SUNSHINE
150 008023 FIRST ORDER STATISTICS
151 004001 YEAR
152 004001 YEAR
153 004002 MONTH
154 004003 DAY
155 004004 HOUR
156 004022 TIME PERIOD OR DISPLACEMENT
157 007032 HEIGHT OF SENSOR ABOVE LOCAL GROUND (OR DECK OF MARINE PLATFORM)
158 008023 FIRST ORDER STATISTICS
159 013060 TOTAL ACCUMULATED PRECIPITATION
160 004053 NUMBER OF DAYS WITH PRECIPITATION EQUAL TO OR MORE THAN 1 MM
161 008023 FIRST ORDER STATISTICS
162 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
163 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
164 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
165 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
166 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
167 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
168 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
169 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
170 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
171 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O
172 008050 QUALIFIER FOR NUMBER OF MISSING VALUES IN CALCULATION OF STATIST
173 008020 TOTAL NUMBER OF MISSING ENTITIES (WITH RESPECT TO ACCUMULATION O

STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1

1	WMO BLOCK NUMBE	0.1100000000E+02	NUMERIC	
2	WMO STATION NUM	0.5200000000E+03	NUMERIC	
3	STATION OR SITE	0.1020000000E+04	CCITTTIA5	PRAHA-LIBUS
4	TYPE OF STATION	0.1000000000E+01	CODE TABLE 2001	
5	YEAR	0.2003000000E+04	YEAR	
6	MONTH	0.1100000000E+02	MONTH	
7	DAY	0.1000000000E+01	DAY	
8	HOUR	0.0000000000E+00	HOUR	
9	MINUTE	0.0000000000E+00	MINUTE	
10	LATITUDE (HIGH	0.5000833000E+02	DEGREE	
11	LONGITUDE (HIGH	0.1444806000E+02	DEGREE	
12	HEIGHT OF STATI	0.3020000000E+03	M	
13	HEIGHT OF BAROM	0.3034000000E+03	M	
14	TIME PERIOD OR	0.3000000000E+02	DAY	
15	FIRST ORDER STA	0.4000000000E+01	CODE TABLE 8023	
16	PRESSURE	0.9829000000E+05	PA	
17	PRESSURE REDUCE	0.1020000000E+06	PA	
18	PRESSURE		MISSING PA	
19	GEOPOTENTIAL HE		MISSING GPM	
20	HEIGHT OF SENSO	0.2030000000E+01	M	
21	TEMPERATURE/DRY	0.2778500000E+03	K	
22	INDICATOR TO SP	0.2000000000E+01	CODE TABLE 2051	
23	PRINCIPAL TIME	0.2000000000E+02	HOUR	
24	MAXIMUM TEMPERA	0.2813500000E+03	K	
25	PRINCIPAL TIME	0.2000000000E+02	HOUR	
26	MINIMUM TEMPER	0.2745500000E+03	K	
27	VAPOUR PRESSURE	0.7600000000E+03	PA	
28	FIRST ORDER STA		MISSING CODE TABLE 8023	
29	STANDARD DEVIAT	0.2800000000E+01	K	
30	HEIGHT OF SENSO		MISSING M	
31	QUALIFIER FOR N	0.1000000000E+01	CODE TABLE 8050	
32	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC	
33	QUALIFIER FOR N	0.2000000000E+01	CODE TABLE 8050	



34	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC
35	QUALIFIER FOR N	0.4000000000E+01	CODE TABLE 8050
36	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC
37	QUALIFIER FOR N	0.7000000000E+01	CODE TABLE 8050
38	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC
39	QUALIFIER FOR N	0.8000000000E+01	CODE TABLE 8050
40	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC
41	TOTAL SUNSHINE	0.8400000000E+02	HOUR
42	TOTAL SUNSHINE	0.1590000000E+03	%
43	QUALIFIER FOR N	0.6000000000E+01	CODE TABLE 8050
44	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC
45	CONDITION FOR W	0.0000000000E+00	CODE TABLE 8052
46	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
47	CONDITION FOR W	0.1000000000E+01	CODE TABLE 8052
48	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
49	CONDITION FOR W	0.2000000000E+01	CODE TABLE 8052
50	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
51	CONDITION FOR W	0.3000000000E+01	CODE TABLE 8052
52	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
53	CONDITION FOR W	0.4000000000E+01	CODE TABLE 8052
54	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
55	CONDITION FOR W	0.5000000000E+01	CODE TABLE 8052
56	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
57	CONDITION FOR W	0.6000000000E+01	CODE TABLE 8052
58	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
59	CONDITION FOR W	0.7000000000E+01	CODE TABLE 8052
60	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
61	CONDITION FOR W	0.8000000000E+01	CODE TABLE 8052
62	TOTAL NUMBER (W	0.1200000000E+02	NUMERIC
63	CONDITION FOR W	0.1600000000E+02	CODE TABLE 8052
64	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
65	CONDITION FOR W	0.1700000000E+02	CODE TABLE 8052
66	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
67	CONDITION FOR W	0.1800000000E+02	CODE TABLE 8052
68	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
69	CONDITION FOR W	0.1900000000E+02	CODE TABLE 8052
70	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
71	CONDITION FOR W	0.2000000000E+02	CODE TABLE 8052
72	TOTAL NUMBER (W	0.1000000000E+01	NUMERIC
73	CONDITION FOR W	0.2100000000E+02	CODE TABLE 8052
74	TOTAL NUMBER (W	0.8000000000E+01	NUMERIC
75	CONDITION FOR W	0.2200000000E+02	CODE TABLE 8052
76	TOTAL NUMBER (W	0.1000000000E+02	NUMERIC
77	CONDITION FOR W	0.2300000000E+02	CODE TABLE 8052
78	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
79	CONDITION FOR W	0.2400000000E+02	CODE TABLE 8052
80	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
81	HEIGHT OF SENSO	0.2030000000E+01	M
82	DAY OF OCCURREN	0.0000000000E+00	CODE TABLE 8053
83	DAY	0.1900000000E+02	DAY
84	HIGHEST DAILY M	0.2832500000E+03	K
85	DAY OF OCCURREN	0.0000000000E+00	CODE TABLE 8053
86	DAY	0.1300000000E+02	DAY
87	LOWEST DAILY ME	0.2726500000E+03	K
88	DAY OF OCCURREN	0.0000000000E+00	CODE TABLE 8053
89	DAY	0.4000000000E+01	DAY
90	FIRST ORDER STA	0.2000000000E+01	CODE TABLE 8023
91	TEMPERATURE/DRY	0.2872500000E+03	K
92	DAY OF OCCURREN	0.0000000000E+00	CODE TABLE 8053
93	DAY	0.1300000000E+02	DAY
94	FIRST ORDER STA	0.3000000000E+01	CODE TABLE 8023
95	TEMPERATURE/DRY	0.2674500000E+03	K
96	FIRST ORDER STA		MISSING CODE TABLE 8023
97	HEIGHT OF SENSO	0.1021000000E+02	M
98	TYPE OF INSTRUM	0.8000000000E+01	FLAG TABLE 2002
99	DAY OF OCCURREN	0.1000000000E+01	CODE TABLE 8053
100	DAY	0.8000000000E+01	DAY
101	MAXIMUM INSTANT	0.1400000000E+02	M/S
102	DAY OF OCCURREN		MISSING CODE TABLE 8053
103	DAY	0.1000000000E+01	DAY
104	HOUR	0.6000000000E+01	HOUR
105	TIME PERIOD OR	0.3000000000E+02	DAY
106	HEIGHT OF SENSO	0.8200000000E+00	M
107	TOTAL ACCUMULAT	0.6000000000E+01	KG/M**2
108	FREQUENCY GROUP	0.0000000000E+00	CODE TABLE 13051
109	NUMBER OF DAYS	0.2000000000E+01	NUMERIC
110	QUALIFIER FOR N	0.5000000000E+01	CODE TABLE 8050
111	TOTAL NUMBER OF	0.0000000000E+00	NUMERIC
112	CONDITION FOR W	0.1000000000E+02	CODE TABLE 8052
113	TOTAL NUMBER (W	0.2000000000E+01	NUMERIC
114	CONDITION FOR W	0.1100000000E+02	CODE TABLE 8052
115	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
116	CONDITION FOR W	0.1200000000E+02	CODE TABLE 8052
117	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
118	CONDITION FOR W	0.1300000000E+02	CODE TABLE 8052
119	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
120	CONDITION FOR W	0.1400000000E+02	CODE TABLE 8052
121	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
122	CONDITION FOR W	0.1500000000E+02	CODE TABLE 8052
123	TOTAL NUMBER (W	0.0000000000E+00	NUMERIC
124	DAY OF OCCURREN	0.0000000000E+00	CODE TABLE 8053
125	DAY	0.2900000000E+02	DAY
126	HIGHEST DAILY A	0.2800000000E+01	KG/M**2



```
127 HEIGHT OF SENSO          MISSING M
128 YEAR                    0.1971000000E+04 YEAR
129 YEAR                    0.2000000000E+04 YEAR
130 MONTH                   0.1100000000E+02 MONTH
131 DAY                     0.1000000000E+01 DAY
132 HOUR                    0.0000000000E+00 HOUR
133 TIME PERIOD OR          0.1000000000E+01 MONTH
134 FIRST ORDER STA         0.4000000000E+01 CODE TABLE 8023
135 PRESSURE                0.9808000000E+05 PA
136 PRESSURE REDUCE        0.1018100000E+06 PA
137 PRESSURE                MISSING PA
138 GEOPOTENTIAL HE        MISSING GPM
139 HEIGHT OF SENSO        0.2030000000E+01 M
140 TEMPERATURE/DRY        0.2767500000E+03 K
141 INDICATOR TO SP        0.2000000000E+01 CODE TABLE 2051
142 PRINCIPAL TIME         0.2000000000E+02 HOUR
143 MAXIMUM TEMPERA        0.2795500000E+03 K
144 PRINCIPAL TIME         0.2000000000E+02 HOUR
145 MINIMUM TEMPER         0.2741500000E+03 K
146 VAPOUR PRESSURE        0.6500000000E+03 PA
147 STANDARD DEVIAT        0.3400000000E+01 K
148 HEIGHT OF SENSO        MISSING M
149 TOTAL SUNSHINE         0.5300000000E+02 HOUR
150 FIRST ORDER STA         MISSING CODE TABLE 8023
151 YEAR                    0.1971000000E+04 YEAR
152 YEAR                    0.2000000000E+04 YEAR
153 MONTH                   0.1100000000E+02 MONTH
154 DAY                     0.1000000000E+01 DAY
155 HOUR                    0.6000000000E+01 HOUR
156 TIME PERIOD OR          0.1000000000E+01 MONTH
157 HEIGHT OF SENSO        0.8200000000E+00 M
158 FIRST ORDER STA         0.4000000000E+01 CODE TABLE 8023
159 TOTAL ACCUMULAT        0.3100000000E+02 KG/M**2
160 NUMBER OF DAYS         0.7000000000E+01 NUMERIC
161 FIRST ORDER STA         MISSING CODE TABLE 8023
162 QUALIFIER FOR N         0.1000000000E+01 CODE TABLE 8050
163 TOTAL NUMBER OF        0.0000000000E+00 NUMERIC
164 QUALIFIER FOR N         0.2000000000E+01 CODE TABLE 8050
165 TOTAL NUMBER OF        0.0000000000E+00 NUMERIC
166 QUALIFIER FOR N         0.3000000000E+01 CODE TABLE 8050
167 TOTAL NUMBER OF        0.0000000000E+00 NUMERIC
168 QUALIFIER FOR N         0.4000000000E+01 CODE TABLE 8050
169 TOTAL NUMBER OF        0.0000000000E+00 NUMERIC
170 QUALIFIER FOR N         0.5000000000E+01 CODE TABLE 8050
171 TOTAL NUMBER OF        0.0000000000E+00 NUMERIC
172 QUALIFIER FOR N         0.6000000000E+01 CODE TABLE 8050
173 TOTAL NUMBER OF        0.0000000000E+00 NUMERIC
```



6.5 WMO SAREP template

ECMWF

BUFR DECODING SOFTWARE VERSION - 7.1
07 June 2005.

Your path for bufr tables is :
/home/ma/maa/bigtmp/wmo_bufr_crex_000250/bufr_000270/bufrtables
BUFR TABLES TO BE LOADED B0000000000098012000,D0000000000098012000

1
BUFR SECTION 0
LENGTH OF SECTION 0 (BYTES) 8
TOTAL LENGTH OF BUFR MESSAGE (BYTES) 146
BUFR EDITION NUMBER 4

1
BUFR SECTION 1
LENGTH OF SECTION 1 (BYTES) 22
BUFR MASTER TABLE 0
ORIGINATING CENTRE 34
ORIGINATING SUB-CENTRE 0
UPDATE SEQUENCE NUMBER 0
FLAG (PRESENCE OF SECTION 2) 0
DATA CATEGORY 12
DATA SUB-CATEGORY 7
LOCAL DATA SUB-CATEGORU 255
VERSION NUMBER OF MASTER TABLE 12
VERSION NUMBER OF LOCAL TABLE 255
YEAR 2004
MONTH 6
DAY 16
HOUR 0
MINUTE 0
SECOND 0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.

1
BUFR SECTION 3
LENGTH OF SECTION 3 (BYTES) 67
RESERVED 0
NUMBER OF DATA SUBSETS 1
FLAG (DATA TYPE/DATA COMPRESSION) 128

DATA DESCRIPTORS (UNEXPANDED)

1 301001
2 301011
3 301012
4 001007
5 001033
6 025150
7 122000
8 031001
9 001027
10 019150
11 019106
12 008005
13 005002
14 006002
15 008005
16 019107
17 019005
18 019006
19 019108
20 019109
21 019110
22 019111
23 019112
24 019113
25 019114
26 019115
27 019116
28 019117
29 019118
30 019119

DATA DESCRIPTORS (EXPANDED)

1 001001 WMO BLOCK NUMBER
2 001002 WMO STATION NUMBER
3 004001 YEAR

```
4 004002 MONTH
5 004003 DAY
6 004004 HOUR
7 004005 MINUTE
8 001007 SATELLITE IDENTIFIER
9 001033 IDENTIFICATION OF ORIGINATING/GENERATING CENTRE
10 025150 SATELLITE INTENSITY ANALYSIS METHOD OF TROPICAL CYCLONE
11 031001 DELAYED DESCRIPTOR REPLICATION FACTOR
12 001027 WMO LONG STORM NAME
13 019150 TYPHOON INTERNATIONAL COMMON NUMBER (TYPHOON COMMITTEE)
14 019106 IDENTIFICATION NUMBER OF TROPICAL CYCLONE
15 008005 METEOROLOGICAL ATTRIBUTE SIGNIFICANCE
16 005002 LATITUDE (COARSE ACCURACY)
17 006002 LONGITUDE (COARSE ACCURACY)
18 008005 METEOROLOGICAL ATTRIBUTE SIGNIFICANCE
19 019107 TIME INTERVAL OF THE TROPICAL CYCLONE ANALYSIS
20 019005 DIRECTION OF MOTION OF FEATURE
21 019006 SPEED OF MOTION OF FEATURE
22 019108 ACCURACY OF GEOGRAPHICAL POSITION OF THE TROPICAL CYCLONE
23 019109 MEAN DIAMETER OF THE OVERCAST CLOUD OF THE TROPICAL CYCLONE
24 019110 APPARENT 24-HOUR CHANGE IN INTENSITY OF TROPICAL CYCLONE
25 019111 CURRENT INTENSITY (CI) NUMBER OF THE TROPICAL CYCLONE
26 019112 DATA TROPICAL (DT) NUMBER OF TROPICAL CYCLONES
27 019113 CLOUD PATTERN TYPE OF DT-NUMBER
28 019114 MODEL EXPECTED TROPICAL CYCLONE (MET) number of THE TROPICAL CYC
29 019115 TREND OF PAST 24-HOUR CHANGE (+: DEVELOPED,-:WEAKENED)
30 019116 PATTERN PROPICAL (PT) NUMBER OF THE TROPICAL CYCLONE
31 019117 CLOUDE PICTURE TYPE OF THE PT-NUMBER
32 019118 FINAL TROPICAL (T) NUMBER OF THE TROPICAL CYCLONE
33 019119 TYPE OF THE FINAL T-NUMBER
```

```
STARTING SUBSET TO BE PRINTED : 1
ENDING SUBSET TO BE PRINTED : 1
```

```
1 WMO BLOCK NUMBE      0.4700000000E+02 NUMERIC
2 WMO STATION NUM      0.6440000000E+03 NUMERIC
3 YEAR                 0.2004000000E+04 YEAR
4 MONTH               0.6000000000E+01 MONTH
5 DAY                 0.1600000000E+02 DAY
6 HOUR                0.0000000000E+00 HOUR
7 MINUTE              0.0000000000E+00 MINUTE
8 SATELLITE IDENT      0.2530000000E+03 CODE TABLE 1007
9 IDENTIFICATION       0.3400000000E+02 CODE TABLE 1033
10 SATELLITE INTEN     0.2000000000E+01 CODE TABLE
11 DELAYED DESCRIP    0.1000000000E+01 NUMERIC
12 WMO LONG STORM      0.1010000000E+04 CCITTIA5          dianmu
13 TYPHOON INTERNA    0.2004000000E+04 CCITTIA5          0406
14 IDENTIFICATION     0.9000000000E+01 NUMERIC
15 METEOROLOGICAL     0.1000000000E+01 CODE TABLE 8005
16 LATITUDE (COARS    0.1430000000E+02 DEGREE
17 LONGITUDE (COAR    0.1364600000E+03 DEGREE
18 METEOROLOGICAL     MISSING CODE TABLE 8005
19 TIME INTERVAL O    0.4000000000E+01 CODE TABLE
20 DIRECTION OF MO    0.3390000000E+03 DEGREE TRUE
21 SPEED OF MOTION    0.4120000000E+01 M/S
22 ACCURACY OF GEO    0.1000000000E+01 CODE TABLE
23 MEAN DIAMETER O    0.3000000000E+01 CODE TABLE
24 APPARENT 24-HOU    0.4000000000E+01 CODE TABLE
25 CURRENT INTENSI    0.7000000000E+01 NUMERIC
26 DATA TROPICAL (    0.7000000000E+01 NUMERIC
27 CLOUD PATTERN T    0.3000000000E+01 CODE TABLE
28 MODEL EXPECTED     0.6000000000E+01 NUMERIC
29 TREND OF PAST 2    0.1500000000E+01 NUMERIC
30 PATTERN PROPICA    0.7000000000E+01 NUMERIC
31 CLOUDE PICTURE     0.1000000000E+01 CODE TABLE
32 FINAL TROPICAL     0.7000000000E+01 NUMERIC
33 TYPE OF THE FIN    0.1000000000E+01 CODE TABLE
```




6.6 WMO TEMP template

BUFR TABLES TO BE LOADED B000000000000012000.TXT,D000000000000012000.TXT

```

1
    BUFR SECTION 0

LENGTH OF SECTION 0 (BYTES)           8
TOTAL LENGTH OF BUFR MESSAGE (BYTES) 1792
BUFR EDITION NUMBER                   3
1
    BUFR SECTION 1

LENGTH OF SECTION 1 (BYTES)           18
BUFR EDITION NUMBER                   3
ORIGINATING SUB-CENTRE                0
ORIGINATING CENTRE                    89
UPDATE SEQUENCE NUMBER                0
FLAG (PRESENCE OF SECTION 2)         0
BUFR MESSAGE TYPE                     2
BUFR MESSAGE SUBTYPE                 0
VERSION NUMBER OF LOCAL TABLE        0
YEAR                                  7
MONTH                                 11
DAY                                  7
HOUR                                  6
MINUTE                                0
VERSION NUMBER OF MASTER TABLE      12
BUFR MASTER TABLE                   0

BUUKEY : KEY DEFINITION NOT KNOWN

PRTKEY : RDB KEY NOT DEFINED IN SECTION 2.
1
    BUFR SECTION 3

LENGTH OF SECTION 3 (BYTES)           10
RESERVED                              0
NUMBER OF DATA SUBSETS                1
FLAG (DATA TYPE/DATA COMPRESSION)     128

    DATA DESCRIPTORS (UNEXPANDED)

1 309052

    DATA DESCRIPTORS (EXPANDED)

1 001001 WMO BLOCK NUMBER
2 001002 WMO STATION NUMBER
3 001011 SHIP OR MOBILE LAND STATION IDENTIFIER
4 002011 RADIOSONDE TYPE
5 002013 SOLAR AND INFRARED RADIATION CORRECTION
6 002014 TRACKING TECHNIQUE/STATUS OF SYSTEM USED
7 002003 TYPE OF MEASURING EQUIPMENT USED
8 008021 TIME SIGNIFICANCE
9 004001 YEAR
10 004002 MONTH
11 004003 DAY
12 004004 HOUR
13 004005 MINUTE
14 004006 SECOND
15 005001 LATITUDE (HIGH ACCURACY)
16 006001 LONGITUDE (HIGH ACCURACY)
17 007030 HEIGHT OF STATION GROUND ABOVE MEAN SEA LEVEL (SEE NOTE 3)
18 007031 HEIGHT OF BAROMETER ABOVE MEAN SEA LEVEL (SEE NOTE 4)
19 007007 HEIGHT
20 033024 STATION ELEVATION QUALITY MARK (FOR MOBILE STATIONS)
21 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
22 020011 CLOUD AMOUNT
23 020013 HEIGHT OF BASE OF CLOUD
24 020012 CLOUD TYPE
25 020012 CLOUD TYPE
26 020012 CLOUD TYPE
27 008002 VERTICAL SIGNIFICANCE (SURFACE OBSERVATIONS)
28 022043 SEA/WATER TEMPERATURE
29 031002 EXTENDED DELAYED DESCRIPTOR REPLICATION FACTOR
30 004086 LONG TIME PERIOD OR DISPLACEMENT
31 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
32 007004 PRESSURE
33 010009 GEOPOTENTIAL HEIGHT
34 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
35 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
36 012101 TEMPERATURE/DRY-BULB TEMPERATURE
37 012103 DEW-POINT TEMPERATURE
38 011001 WIND DIRECTION
39 011002 WIND SPEED
40 004086 LONG TIME PERIOD OR DISPLACEMENT
41 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE

```

42 007004 PRESSURE
43 010009 GEOPOTENTIAL HEIGHT
44 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
45 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
46 012101 TEMPERATURE/DRY-BULB TEMPERATURE
47 012103 DEW-POINT TEMPERATURE
48 011001 WIND DIRECTION
49 011002 WIND SPEED
50 004086 LONG TIME PERIOD OR DISPLACEMENT
51 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
52 007004 PRESSURE
53 010009 GEOPOTENTIAL HEIGHT
54 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
55 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
56 012101 TEMPERATURE/DRY-BULB TEMPERATURE
57 012103 DEW-POINT TEMPERATURE
58 011001 WIND DIRECTION
59 011002 WIND SPEED
60 004086 LONG TIME PERIOD OR DISPLACEMENT
61 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
62 007004 PRESSURE
63 010009 GEOPOTENTIAL HEIGHT
64 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
65 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
66 012101 TEMPERATURE/DRY-BULB TEMPERATURE
67 012103 DEW-POINT TEMPERATURE
68 011001 WIND DIRECTION
69 011002 WIND SPEED
70 004086 LONG TIME PERIOD OR DISPLACEMENT
71 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
72 007004 PRESSURE
73 010009 GEOPOTENTIAL HEIGHT
74 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
75 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
76 012101 TEMPERATURE/DRY-BULB TEMPERATURE
77 012103 DEW-POINT TEMPERATURE
78 011001 WIND DIRECTION
79 011002 WIND SPEED
80 004086 LONG TIME PERIOD OR DISPLACEMENT
81 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
82 007004 PRESSURE
83 010009 GEOPOTENTIAL HEIGHT
84 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
85 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
86 012101 TEMPERATURE/DRY-BULB TEMPERATURE
87 012103 DEW-POINT TEMPERATURE
88 011001 WIND DIRECTION
89 011002 WIND SPEED
90 004086 LONG TIME PERIOD OR DISPLACEMENT
91 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
92 007004 PRESSURE
93 010009 GEOPOTENTIAL HEIGHT
94 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
95 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
96 012101 TEMPERATURE/DRY-BULB TEMPERATURE
97 012103 DEW-POINT TEMPERATURE
98 011001 WIND DIRECTION
99 011002 WIND SPEED
100 004086 LONG TIME PERIOD OR DISPLACEMENT
101 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
102 007004 PRESSURE
103 010009 GEOPOTENTIAL HEIGHT
104 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
105 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
106 012101 TEMPERATURE/DRY-BULB TEMPERATURE
107 012103 DEW-POINT TEMPERATURE
108 011001 WIND DIRECTION
109 011002 WIND SPEED
110 004086 LONG TIME PERIOD OR DISPLACEMENT
111 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
112 007004 PRESSURE
113 010009 GEOPOTENTIAL HEIGHT
114 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
115 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
116 012101 TEMPERATURE/DRY-BULB TEMPERATURE
117 012103 DEW-POINT TEMPERATURE
118 011001 WIND DIRECTION
119 011002 WIND SPEED
120 004086 LONG TIME PERIOD OR DISPLACEMENT
121 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
122 007004 PRESSURE
123 010009 GEOPOTENTIAL HEIGHT
124 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
125 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
126 012101 TEMPERATURE/DRY-BULB TEMPERATURE
127 012103 DEW-POINT TEMPERATURE
128 011001 WIND DIRECTION
129 011002 WIND SPEED
130 004086 LONG TIME PERIOD OR DISPLACEMENT
131 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
132 007004 PRESSURE
133 010009 GEOPOTENTIAL HEIGHT
134 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)

135 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
136 012101 TEMPERATURE/DRY-BULB TEMPERATURE
137 012103 DEW-POINT TEMPERATURE
138 011001 WIND DIRECTION
139 011002 WIND SPEED
140 004086 LONG TIME PERIOD OR DISPLACEMENT
141 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
142 007004 PRESSURE
143 010009 GEOPOTENTIAL HEIGHT
144 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
145 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
146 012101 TEMPERATURE/DRY-BULB TEMPERATURE
147 012103 DEW-POINT TEMPERATURE
148 011001 WIND DIRECTION
149 011002 WIND SPEED
150 004086 LONG TIME PERIOD OR DISPLACEMENT
151 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
152 007004 PRESSURE
153 010009 GEOPOTENTIAL HEIGHT
154 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
155 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
156 012101 TEMPERATURE/DRY-BULB TEMPERATURE
157 012103 DEW-POINT TEMPERATURE
158 011001 WIND DIRECTION
159 011002 WIND SPEED
160 004086 LONG TIME PERIOD OR DISPLACEMENT
161 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
162 007004 PRESSURE
163 010009 GEOPOTENTIAL HEIGHT
164 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
165 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
166 012101 TEMPERATURE/DRY-BULB TEMPERATURE
167 012103 DEW-POINT TEMPERATURE
168 011001 WIND DIRECTION
169 011002 WIND SPEED
170 004086 LONG TIME PERIOD OR DISPLACEMENT
171 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
172 007004 PRESSURE
173 010009 GEOPOTENTIAL HEIGHT
174 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
175 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
176 012101 TEMPERATURE/DRY-BULB TEMPERATURE
177 012103 DEW-POINT TEMPERATURE
178 011001 WIND DIRECTION
179 011002 WIND SPEED
180 004086 LONG TIME PERIOD OR DISPLACEMENT
181 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
182 007004 PRESSURE
183 010009 GEOPOTENTIAL HEIGHT
184 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
185 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
186 012101 TEMPERATURE/DRY-BULB TEMPERATURE
187 012103 DEW-POINT TEMPERATURE
188 011001 WIND DIRECTION
189 011002 WIND SPEED
190 004086 LONG TIME PERIOD OR DISPLACEMENT
191 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
192 007004 PRESSURE
193 010009 GEOPOTENTIAL HEIGHT
194 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
195 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
196 012101 TEMPERATURE/DRY-BULB TEMPERATURE
197 012103 DEW-POINT TEMPERATURE
198 011001 WIND DIRECTION
199 011002 WIND SPEED
200 004086 LONG TIME PERIOD OR DISPLACEMENT
201 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
202 007004 PRESSURE
203 010009 GEOPOTENTIAL HEIGHT
204 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
205 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
206 012101 TEMPERATURE/DRY-BULB TEMPERATURE
207 012103 DEW-POINT TEMPERATURE
208 011001 WIND DIRECTION
209 011002 WIND SPEED
210 004086 LONG TIME PERIOD OR DISPLACEMENT
211 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
212 007004 PRESSURE
213 010009 GEOPOTENTIAL HEIGHT
214 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
215 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
216 012101 TEMPERATURE/DRY-BULB TEMPERATURE
217 012103 DEW-POINT TEMPERATURE
218 011001 WIND DIRECTION
219 011002 WIND SPEED
220 004086 LONG TIME PERIOD OR DISPLACEMENT
221 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
222 007004 PRESSURE
223 010009 GEOPOTENTIAL HEIGHT
224 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
225 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
226 012101 TEMPERATURE/DRY-BULB TEMPERATURE
227 012103 DEW-POINT TEMPERATURE



228 011001 WIND DIRECTION
229 011002 WIND SPEED
230 004086 LONG TIME PERIOD OR DISPLACEMENT
231 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
232 007004 PRESSURE
233 010009 GEOPOTENTIAL HEIGHT
234 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
235 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
236 012101 TEMPERATURE/DRY-BULB TEMPERATURE
237 012103 DEW-POINT TEMPERATURE
238 011001 WIND DIRECTION
239 011002 WIND SPEED
240 004086 LONG TIME PERIOD OR DISPLACEMENT
241 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
242 007004 PRESSURE
243 010009 GEOPOTENTIAL HEIGHT
244 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
245 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
246 012101 TEMPERATURE/DRY-BULB TEMPERATURE
247 012103 DEW-POINT TEMPERATURE
248 011001 WIND DIRECTION
249 011002 WIND SPEED
250 004086 LONG TIME PERIOD OR DISPLACEMENT
251 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
252 007004 PRESSURE
253 010009 GEOPOTENTIAL HEIGHT
254 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
255 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
256 012101 TEMPERATURE/DRY-BULB TEMPERATURE
257 012103 DEW-POINT TEMPERATURE
258 011001 WIND DIRECTION
259 011002 WIND SPEED
260 004086 LONG TIME PERIOD OR DISPLACEMENT
261 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
262 007004 PRESSURE
263 010009 GEOPOTENTIAL HEIGHT
264 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
265 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
266 012101 TEMPERATURE/DRY-BULB TEMPERATURE
267 012103 DEW-POINT TEMPERATURE
268 011001 WIND DIRECTION
269 011002 WIND SPEED
270 004086 LONG TIME PERIOD OR DISPLACEMENT
271 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
272 007004 PRESSURE
273 010009 GEOPOTENTIAL HEIGHT
274 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
275 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
276 012101 TEMPERATURE/DRY-BULB TEMPERATURE
277 012103 DEW-POINT TEMPERATURE
278 011001 WIND DIRECTION
279 011002 WIND SPEED
280 004086 LONG TIME PERIOD OR DISPLACEMENT
281 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
282 007004 PRESSURE
283 010009 GEOPOTENTIAL HEIGHT
284 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
285 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
286 012101 TEMPERATURE/DRY-BULB TEMPERATURE
287 012103 DEW-POINT TEMPERATURE
288 011001 WIND DIRECTION
289 011002 WIND SPEED
290 004086 LONG TIME PERIOD OR DISPLACEMENT
291 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
292 007004 PRESSURE
293 010009 GEOPOTENTIAL HEIGHT
294 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
295 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
296 012101 TEMPERATURE/DRY-BULB TEMPERATURE
297 012103 DEW-POINT TEMPERATURE
298 011001 WIND DIRECTION
299 011002 WIND SPEED
300 004086 LONG TIME PERIOD OR DISPLACEMENT
301 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
302 007004 PRESSURE
303 010009 GEOPOTENTIAL HEIGHT
304 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
305 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
306 012101 TEMPERATURE/DRY-BULB TEMPERATURE
307 012103 DEW-POINT TEMPERATURE
308 011001 WIND DIRECTION
309 011002 WIND SPEED
310 004086 LONG TIME PERIOD OR DISPLACEMENT
311 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
312 007004 PRESSURE
313 010009 GEOPOTENTIAL HEIGHT
314 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
315 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
316 012101 TEMPERATURE/DRY-BULB TEMPERATURE
317 012103 DEW-POINT TEMPERATURE
318 011001 WIND DIRECTION
319 011002 WIND SPEED
320 004086 LONG TIME PERIOD OR DISPLACEMENT

321 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
322 007004 PRESSURE
323 010009 GEOPOTENTIAL HEIGHT
324 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
325 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
326 012101 TEMPERATURE/DRY-BULB TEMPERATURE
327 012103 DEW-POINT TEMPERATURE
328 011001 WIND DIRECTION
329 011002 WIND SPEED
330 004086 LONG TIME PERIOD OR DISPLACEMENT
331 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
332 007004 PRESSURE
333 010009 GEOPOTENTIAL HEIGHT
334 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
335 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
336 012101 TEMPERATURE/DRY-BULB TEMPERATURE
337 012103 DEW-POINT TEMPERATURE
338 011001 WIND DIRECTION
339 011002 WIND SPEED
340 004086 LONG TIME PERIOD OR DISPLACEMENT
341 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
342 007004 PRESSURE
343 010009 GEOPOTENTIAL HEIGHT
344 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
345 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
346 012101 TEMPERATURE/DRY-BULB TEMPERATURE
347 012103 DEW-POINT TEMPERATURE
348 011001 WIND DIRECTION
349 011002 WIND SPEED
350 004086 LONG TIME PERIOD OR DISPLACEMENT
351 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
352 007004 PRESSURE
353 010009 GEOPOTENTIAL HEIGHT
354 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
355 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
356 012101 TEMPERATURE/DRY-BULB TEMPERATURE
357 012103 DEW-POINT TEMPERATURE
358 011001 WIND DIRECTION
359 011002 WIND SPEED
360 004086 LONG TIME PERIOD OR DISPLACEMENT
361 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
362 007004 PRESSURE
363 010009 GEOPOTENTIAL HEIGHT
364 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
365 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
366 012101 TEMPERATURE/DRY-BULB TEMPERATURE
367 012103 DEW-POINT TEMPERATURE
368 011001 WIND DIRECTION
369 011002 WIND SPEED
370 004086 LONG TIME PERIOD OR DISPLACEMENT
371 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
372 007004 PRESSURE
373 010009 GEOPOTENTIAL HEIGHT
374 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
375 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
376 012101 TEMPERATURE/DRY-BULB TEMPERATURE
377 012103 DEW-POINT TEMPERATURE
378 011001 WIND DIRECTION
379 011002 WIND SPEED
380 004086 LONG TIME PERIOD OR DISPLACEMENT
381 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
382 007004 PRESSURE
383 010009 GEOPOTENTIAL HEIGHT
384 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
385 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
386 012101 TEMPERATURE/DRY-BULB TEMPERATURE
387 012103 DEW-POINT TEMPERATURE
388 011001 WIND DIRECTION
389 011002 WIND SPEED
390 004086 LONG TIME PERIOD OR DISPLACEMENT
391 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
392 007004 PRESSURE
393 010009 GEOPOTENTIAL HEIGHT
394 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
395 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
396 012101 TEMPERATURE/DRY-BULB TEMPERATURE
397 012103 DEW-POINT TEMPERATURE
398 011001 WIND DIRECTION
399 011002 WIND SPEED
400 004086 LONG TIME PERIOD OR DISPLACEMENT
401 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
402 007004 PRESSURE
403 010009 GEOPOTENTIAL HEIGHT
404 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
405 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
406 012101 TEMPERATURE/DRY-BULB TEMPERATURE
407 012103 DEW-POINT TEMPERATURE
408 011001 WIND DIRECTION
409 011002 WIND SPEED
410 004086 LONG TIME PERIOD OR DISPLACEMENT
411 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
412 007004 PRESSURE
413 010009 GEOPOTENTIAL HEIGHT

414 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
415 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
416 012101 TEMPERATURE/DRY-BULB TEMPERATURE
417 012103 DEW-POINT TEMPERATURE
418 011001 WIND DIRECTION
419 011002 WIND SPEED
420 004086 LONG TIME PERIOD OR DISPLACEMENT
421 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
422 007004 PRESSURE
423 010009 GEOPOTENTIAL HEIGHT
424 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
425 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
426 012101 TEMPERATURE/DRY-BULB TEMPERATURE
427 012103 DEW-POINT TEMPERATURE
428 011001 WIND DIRECTION
429 011002 WIND SPEED
430 004086 LONG TIME PERIOD OR DISPLACEMENT
431 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
432 007004 PRESSURE
433 010009 GEOPOTENTIAL HEIGHT
434 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
435 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
436 012101 TEMPERATURE/DRY-BULB TEMPERATURE
437 012103 DEW-POINT TEMPERATURE
438 011001 WIND DIRECTION
439 011002 WIND SPEED
440 004086 LONG TIME PERIOD OR DISPLACEMENT
441 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
442 007004 PRESSURE
443 010009 GEOPOTENTIAL HEIGHT
444 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
445 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
446 012101 TEMPERATURE/DRY-BULB TEMPERATURE
447 012103 DEW-POINT TEMPERATURE
448 011001 WIND DIRECTION
449 011002 WIND SPEED
450 004086 LONG TIME PERIOD OR DISPLACEMENT
451 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
452 007004 PRESSURE
453 010009 GEOPOTENTIAL HEIGHT
454 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
455 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
456 012101 TEMPERATURE/DRY-BULB TEMPERATURE
457 012103 DEW-POINT TEMPERATURE
458 011001 WIND DIRECTION
459 011002 WIND SPEED
460 004086 LONG TIME PERIOD OR DISPLACEMENT
461 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
462 007004 PRESSURE
463 010009 GEOPOTENTIAL HEIGHT
464 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
465 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
466 012101 TEMPERATURE/DRY-BULB TEMPERATURE
467 012103 DEW-POINT TEMPERATURE
468 011001 WIND DIRECTION
469 011002 WIND SPEED
470 004086 LONG TIME PERIOD OR DISPLACEMENT
471 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
472 007004 PRESSURE
473 010009 GEOPOTENTIAL HEIGHT
474 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
475 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
476 012101 TEMPERATURE/DRY-BULB TEMPERATURE
477 012103 DEW-POINT TEMPERATURE
478 011001 WIND DIRECTION
479 011002 WIND SPEED
480 004086 LONG TIME PERIOD OR DISPLACEMENT
481 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
482 007004 PRESSURE
483 010009 GEOPOTENTIAL HEIGHT
484 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
485 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
486 012101 TEMPERATURE/DRY-BULB TEMPERATURE
487 012103 DEW-POINT TEMPERATURE
488 011001 WIND DIRECTION
489 011002 WIND SPEED
490 004086 LONG TIME PERIOD OR DISPLACEMENT
491 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
492 007004 PRESSURE
493 010009 GEOPOTENTIAL HEIGHT
494 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
495 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
496 012101 TEMPERATURE/DRY-BULB TEMPERATURE
497 012103 DEW-POINT TEMPERATURE
498 011001 WIND DIRECTION
499 011002 WIND SPEED
500 004086 LONG TIME PERIOD OR DISPLACEMENT
501 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
502 007004 PRESSURE
503 010009 GEOPOTENTIAL HEIGHT
504 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
505 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
506 012101 TEMPERATURE/DRY-BULB TEMPERATURE

507 012103 DEW-POINT TEMPERATURE
508 011001 WIND DIRECTION
509 011002 WIND SPEED
510 004086 LONG TIME PERIOD OR DISPLACEMENT
511 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
512 007004 PRESSURE
513 010009 GEOPOTENTIAL HEIGHT
514 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
515 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
516 012101 TEMPERATURE/DRY-BULB TEMPERATURE
517 012103 DEW-POINT TEMPERATURE
518 011001 WIND DIRECTION
519 011002 WIND SPEED
520 004086 LONG TIME PERIOD OR DISPLACEMENT
521 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
522 007004 PRESSURE
523 010009 GEOPOTENTIAL HEIGHT
524 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
525 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
526 012101 TEMPERATURE/DRY-BULB TEMPERATURE
527 012103 DEW-POINT TEMPERATURE
528 011001 WIND DIRECTION
529 011002 WIND SPEED
530 004086 LONG TIME PERIOD OR DISPLACEMENT
531 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
532 007004 PRESSURE
533 010009 GEOPOTENTIAL HEIGHT
534 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
535 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
536 012101 TEMPERATURE/DRY-BULB TEMPERATURE
537 012103 DEW-POINT TEMPERATURE
538 011001 WIND DIRECTION
539 011002 WIND SPEED
540 004086 LONG TIME PERIOD OR DISPLACEMENT
541 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
542 007004 PRESSURE
543 010009 GEOPOTENTIAL HEIGHT
544 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
545 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
546 012101 TEMPERATURE/DRY-BULB TEMPERATURE
547 012103 DEW-POINT TEMPERATURE
548 011001 WIND DIRECTION
549 011002 WIND SPEED
550 004086 LONG TIME PERIOD OR DISPLACEMENT
551 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
552 007004 PRESSURE
553 010009 GEOPOTENTIAL HEIGHT
554 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
555 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
556 012101 TEMPERATURE/DRY-BULB TEMPERATURE
557 012103 DEW-POINT TEMPERATURE
558 011001 WIND DIRECTION
559 011002 WIND SPEED
560 004086 LONG TIME PERIOD OR DISPLACEMENT
561 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
562 007004 PRESSURE
563 010009 GEOPOTENTIAL HEIGHT
564 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
565 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
566 012101 TEMPERATURE/DRY-BULB TEMPERATURE
567 012103 DEW-POINT TEMPERATURE
568 011001 WIND DIRECTION
569 011002 WIND SPEED
570 004086 LONG TIME PERIOD OR DISPLACEMENT
571 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
572 007004 PRESSURE
573 010009 GEOPOTENTIAL HEIGHT
574 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
575 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
576 012101 TEMPERATURE/DRY-BULB TEMPERATURE
577 012103 DEW-POINT TEMPERATURE
578 011001 WIND DIRECTION
579 011002 WIND SPEED
580 004086 LONG TIME PERIOD OR DISPLACEMENT
581 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
582 007004 PRESSURE
583 010009 GEOPOTENTIAL HEIGHT
584 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
585 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
586 012101 TEMPERATURE/DRY-BULB TEMPERATURE
587 012103 DEW-POINT TEMPERATURE
588 011001 WIND DIRECTION
589 011002 WIND SPEED
590 004086 LONG TIME PERIOD OR DISPLACEMENT
591 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
592 007004 PRESSURE
593 010009 GEOPOTENTIAL HEIGHT
594 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
595 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
596 012101 TEMPERATURE/DRY-BULB TEMPERATURE
597 012103 DEW-POINT TEMPERATURE
598 011001 WIND DIRECTION
599 011002 WIND SPEED

600 004086 LONG TIME PERIOD OR DISPLACEMENT
601 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
602 007004 PRESSURE
603 010009 GEOPOTENTIAL HEIGHT
604 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
605 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
606 012101 TEMPERATURE/DRY-BULB TEMPERATURE
607 012103 DEW-POINT TEMPERATURE
608 011001 WIND DIRECTION
609 011002 WIND SPEED
610 004086 LONG TIME PERIOD OR DISPLACEMENT
611 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
612 007004 PRESSURE
613 010009 GEOPOTENTIAL HEIGHT
614 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
615 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
616 012101 TEMPERATURE/DRY-BULB TEMPERATURE
617 012103 DEW-POINT TEMPERATURE
618 011001 WIND DIRECTION
619 011002 WIND SPEED
620 004086 LONG TIME PERIOD OR DISPLACEMENT
621 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
622 007004 PRESSURE
623 010009 GEOPOTENTIAL HEIGHT
624 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
625 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
626 012101 TEMPERATURE/DRY-BULB TEMPERATURE
627 012103 DEW-POINT TEMPERATURE
628 011001 WIND DIRECTION
629 011002 WIND SPEED
630 004086 LONG TIME PERIOD OR DISPLACEMENT
631 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
632 007004 PRESSURE
633 010009 GEOPOTENTIAL HEIGHT
634 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
635 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
636 012101 TEMPERATURE/DRY-BULB TEMPERATURE
637 012103 DEW-POINT TEMPERATURE
638 011001 WIND DIRECTION
639 011002 WIND SPEED
640 004086 LONG TIME PERIOD OR DISPLACEMENT
641 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
642 007004 PRESSURE
643 010009 GEOPOTENTIAL HEIGHT
644 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
645 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
646 012101 TEMPERATURE/DRY-BULB TEMPERATURE
647 012103 DEW-POINT TEMPERATURE
648 011001 WIND DIRECTION
649 011002 WIND SPEED
650 004086 LONG TIME PERIOD OR DISPLACEMENT
651 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
652 007004 PRESSURE
653 010009 GEOPOTENTIAL HEIGHT
654 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
655 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
656 012101 TEMPERATURE/DRY-BULB TEMPERATURE
657 012103 DEW-POINT TEMPERATURE
658 011001 WIND DIRECTION
659 011002 WIND SPEED
660 004086 LONG TIME PERIOD OR DISPLACEMENT
661 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
662 007004 PRESSURE
663 010009 GEOPOTENTIAL HEIGHT
664 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
665 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
666 012101 TEMPERATURE/DRY-BULB TEMPERATURE
667 012103 DEW-POINT TEMPERATURE
668 011001 WIND DIRECTION
669 011002 WIND SPEED
670 004086 LONG TIME PERIOD OR DISPLACEMENT
671 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
672 007004 PRESSURE
673 010009 GEOPOTENTIAL HEIGHT
674 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
675 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
676 012101 TEMPERATURE/DRY-BULB TEMPERATURE
677 012103 DEW-POINT TEMPERATURE
678 011001 WIND DIRECTION
679 011002 WIND SPEED
680 004086 LONG TIME PERIOD OR DISPLACEMENT
681 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
682 007004 PRESSURE
683 010009 GEOPOTENTIAL HEIGHT
684 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
685 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
686 012101 TEMPERATURE/DRY-BULB TEMPERATURE
687 012103 DEW-POINT TEMPERATURE
688 011001 WIND DIRECTION
689 011002 WIND SPEED
690 004086 LONG TIME PERIOD OR DISPLACEMENT
691 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
692 007004 PRESSURE

693 010009 GEOPOTENTIAL HEIGHT
694 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
695 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
696 012101 TEMPERATURE/DRY-BULB TEMPERATURE
697 012103 DEW-POINT TEMPERATURE
698 011001 WIND DIRECTION
699 011002 WIND SPEED
700 004086 LONG TIME PERIOD OR DISPLACEMENT
701 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
702 007004 PRESSURE
703 010009 GEOPOTENTIAL HEIGHT
704 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
705 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
706 012101 TEMPERATURE/DRY-BULB TEMPERATURE
707 012103 DEW-POINT TEMPERATURE
708 011001 WIND DIRECTION
709 011002 WIND SPEED
710 004086 LONG TIME PERIOD OR DISPLACEMENT
711 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
712 007004 PRESSURE
713 010009 GEOPOTENTIAL HEIGHT
714 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
715 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
716 012101 TEMPERATURE/DRY-BULB TEMPERATURE
717 012103 DEW-POINT TEMPERATURE
718 011001 WIND DIRECTION
719 011002 WIND SPEED
720 004086 LONG TIME PERIOD OR DISPLACEMENT
721 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
722 007004 PRESSURE
723 010009 GEOPOTENTIAL HEIGHT
724 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
725 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
726 012101 TEMPERATURE/DRY-BULB TEMPERATURE
727 012103 DEW-POINT TEMPERATURE
728 011001 WIND DIRECTION
729 011002 WIND SPEED
730 004086 LONG TIME PERIOD OR DISPLACEMENT
731 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
732 007004 PRESSURE
733 010009 GEOPOTENTIAL HEIGHT
734 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
735 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
736 012101 TEMPERATURE/DRY-BULB TEMPERATURE
737 012103 DEW-POINT TEMPERATURE
738 011001 WIND DIRECTION
739 011002 WIND SPEED
740 004086 LONG TIME PERIOD OR DISPLACEMENT
741 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
742 007004 PRESSURE
743 010009 GEOPOTENTIAL HEIGHT
744 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
745 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
746 012101 TEMPERATURE/DRY-BULB TEMPERATURE
747 012103 DEW-POINT TEMPERATURE
748 011001 WIND DIRECTION
749 011002 WIND SPEED
750 004086 LONG TIME PERIOD OR DISPLACEMENT
751 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
752 007004 PRESSURE
753 010009 GEOPOTENTIAL HEIGHT
754 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
755 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
756 012101 TEMPERATURE/DRY-BULB TEMPERATURE
757 012103 DEW-POINT TEMPERATURE
758 011001 WIND DIRECTION
759 011002 WIND SPEED
760 004086 LONG TIME PERIOD OR DISPLACEMENT
761 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
762 007004 PRESSURE
763 010009 GEOPOTENTIAL HEIGHT
764 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
765 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
766 012101 TEMPERATURE/DRY-BULB TEMPERATURE
767 012103 DEW-POINT TEMPERATURE
768 011001 WIND DIRECTION
769 011002 WIND SPEED
770 004086 LONG TIME PERIOD OR DISPLACEMENT
771 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
772 007004 PRESSURE
773 010009 GEOPOTENTIAL HEIGHT
774 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
775 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
776 012101 TEMPERATURE/DRY-BULB TEMPERATURE
777 012103 DEW-POINT TEMPERATURE
778 011001 WIND DIRECTION
779 011002 WIND SPEED
780 004086 LONG TIME PERIOD OR DISPLACEMENT
781 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
782 007004 PRESSURE
783 010009 GEOPOTENTIAL HEIGHT
784 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
785 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)

786 012101 TEMPERATURE/DRY-BULB TEMPERATURE
787 012103 DEW-POINT TEMPERATURE
788 011001 WIND DIRECTION
789 011002 WIND SPEED
790 004086 LONG TIME PERIOD OR DISPLACEMENT
791 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
792 007004 PRESSURE
793 010009 GEOPOTENTIAL HEIGHT
794 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
795 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
796 012101 TEMPERATURE/DRY-BULB TEMPERATURE
797 012103 DEW-POINT TEMPERATURE
798 011001 WIND DIRECTION
799 011002 WIND SPEED
800 004086 LONG TIME PERIOD OR DISPLACEMENT
801 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
802 007004 PRESSURE
803 010009 GEOPOTENTIAL HEIGHT
804 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
805 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
806 012101 TEMPERATURE/DRY-BULB TEMPERATURE
807 012103 DEW-POINT TEMPERATURE
808 011001 WIND DIRECTION
809 011002 WIND SPEED
810 004086 LONG TIME PERIOD OR DISPLACEMENT
811 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
812 007004 PRESSURE
813 010009 GEOPOTENTIAL HEIGHT
814 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
815 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
816 012101 TEMPERATURE/DRY-BULB TEMPERATURE
817 012103 DEW-POINT TEMPERATURE
818 011001 WIND DIRECTION
819 011002 WIND SPEED
820 031001 DELAYED DESCRIPTOR REPLICATION FACTOR
821 004086 LONG TIME PERIOD OR DISPLACEMENT
822 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
823 007004 PRESSURE
824 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
825 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
826 011061 ABSOLUTE WIND SHEAR IN 1 KM LAYER BELOW
827 011062 ABSOLUTE WIND SHEAR IN 1 KM LAYER ABOVE
828 004086 LONG TIME PERIOD OR DISPLACEMENT
829 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
830 007004 PRESSURE
831 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
832 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
833 011061 ABSOLUTE WIND SHEAR IN 1 KM LAYER BELOW
834 011062 ABSOLUTE WIND SHEAR IN 1 KM LAYER ABOVE
835 004086 LONG TIME PERIOD OR DISPLACEMENT
836 008042 EXTENDED VERTICAL SOUNDING SIGNIFICANCE
837 007004 PRESSURE
838 005015 LATITUDE DISPLACEMENT (HIGH ACCURACY)
839 006015 LONGITUDE DISPLACEMENT (HIGH ACCURACY)
840 011061 ABSOLUTE WIND SHEAR IN 1 KM LAYER BELOW
841 011062 ABSOLUTE WIND SHEAR IN 1 KM LAYER ABOVE

BUFR SECTION 4 (DATA), SUBSET 1

1 WMO BLOCK NUMBER 0.11000000000000E+002 NUMERIC
2 WMO STATION NUMBER 0.52000000000000E+003 NUMERIC
3 SHIP OR MOBILE LAND STATION IDEN 0.10090000000000E+004 CCITTIA5
4 RADIOSONDE TYPE 0.80000000000000E+002 CODE TABLE 2011
5 SOLAR AND INFRARED RADIATION COR 0.40000000000000E+001 CODE TABLE 2013
6 TRACKING TECHNIQUE/STATUS OF SYS 0.60000000000000E+001 CODE TABLE 2014
7 TYPE OF MEASURING EQUIPMENT USED 0.50000000000000E+001 CODE TABLE 2003
8 TIME SIGNIFICANCE 0.18000000000000E+002 CODE TABLE 8021
9 YEAR 0.20070000000000E+004 YEAR
10 MONTH 0.11000000000000E+002 MONTH
11 DAY 0.70000000000000E+001 DAY
12 HOUR 0.50000000000000E+001 HOUR
13 MINUTE 0.30000000000000E+002 MINUTE
14 SECOND 0.00000000000000E+000 SECOND
15 LATITUDE (HIGH ACCURACY) 0.50008330000000E+002 DEGREE
16 LONGITUDE (HIGH ACCURACY) 0.14448060000000E+002 DEGREE
17 HEIGHT OF STATION GROUND ABOVE M 0.30200000000000E+003 M
18 HEIGHT OF BAROMETER ABOVE MEAN S 0.30340000000000E+003 M
19 HEIGHT 0.30400000000000E+003 M
20 STATION ELEVATION QUALITY MARK (MISSING CODE TABLE 33024
21 VERTICAL SIGNIFICANCE (SURFACE O 0.70000000000000E+001 CODE TABLE 8002
22 CLOUD AMOUNT 0.70000000000000E+001 CODE TABLE 20011
23 HEIGHT OF BASE OF CLOUD 0.12500000000000E+004 M
24 CLOUD TYPE 0.35000000000000E+002 CODE TABLE 20012
25 CLOUD TYPE 0.20000000000000E+002 CODE TABLE 20012
26 CLOUD TYPE 0.10000000000000E+002 CODE TABLE 20012
27 VERTICAL SIGNIFICANCE (SURFACE O MISSING CODE TABLE 8002
28 SEA/WATER TEMPERATURE MISSING K
29 EXTENDED DELAYED DESCRIPTOR REPL 0.79000000000000E+002 NUMERIC
30 LONG TIME PERIOD OR DISPLACEMENT 0.00000000000000E+000 SECOND
31 EXTENDED VERTICAL SOUNDING SIGNI 0.65536000000000E+005 FLAG TABLE 8042
32 PRESSURE 0.10000000000000E+006 PA
33 GEOPOTENTIAL HEIGHT 0.17700000000000E+003 GPM
34 LATITUDE DISPLACEMENT (HIGH ACCU 0.00000000000000E+000 DEGREE

35	LONGITUDE DISPLACEMENT (HIGH ACC	0.0000000000000000E+000	DEGREE
36	TEMPERATURE/DRY-BULB TEMPERATURE		MISSING K
37	DEW-POINT TEMPERATURE		MISSING K
38	WIND DIRECTION		MISSING DEGREE TRUE
39	WIND SPEED		MISSING M/S
40	LONG TIME PERIOD OR DISPLACEMENT	0.0000000000000000E+000	SECOND
41	EXTENDED VERTICAL SOUNDING SIGNI	0.1454080000000000E+006	FLAG TABLE 8042
42	PRESSURE	0.9844000000000000E+005	PA
43	GEOPOTENTIAL HEIGHT	0.3040000000000000E+003	GPM
44	LATITUDE DISPLACEMENT (HIGH ACCU	0.1000000000000000E-001	DEGREE
45	LONGITUDE DISPLACEMENT (HIGH ACC	0.1000000000000000E-001	DEGREE
46	TEMPERATURE/DRY-BULB TEMPERATURE	0.2766000000000000E+003	K
47	DEW-POINT TEMPERATURE	0.2744000000000000E+003	K
48	WIND DIRECTION	0.2680000000000000E+003	DEGREE TRUE
49	WIND SPEED	0.2900000000000000E+001	M/S
50	LONG TIME PERIOD OR DISPLACEMENT	0.3000000000000000E+002	SECOND
51	EXTENDED VERTICAL SOUNDING SIGNI	0.2048000000000000E+004	FLAG TABLE 8042
52	PRESSURE	0.9613000000000000E+005	PA
53	GEOPOTENTIAL HEIGHT	0.4960000000000000E+003	GPM
54	LATITUDE DISPLACEMENT (HIGH ACCU	0.1000000000000000E-001	DEGREE
55	LONGITUDE DISPLACEMENT (HIGH ACC	0.1000000000000000E-001	DEGREE
56	TEMPERATURE/DRY-BULB TEMPERATURE	0.2748000000000000E+003	K
57	DEW-POINT TEMPERATURE	0.2734000000000000E+003	K
58	WIND DIRECTION	0.2600000000000000E+003	DEGREE TRUE
59	WIND SPEED	0.1200000000000000E+002	M/S
60	LONG TIME PERIOD OR DISPLACEMENT	0.8400000000000000E+002	SECOND
61	EXTENDED VERTICAL SOUNDING SIGNI	0.6553600000000000E+005	FLAG TABLE 8042
62	PRESSURE	0.9250000000000000E+005	PA
63	GEOPOTENTIAL HEIGHT	0.8060000000000000E+003	GPM
64	LATITUDE DISPLACEMENT (HIGH ACCU	0.1000000000000000E-001	DEGREE
65	LONGITUDE DISPLACEMENT (HIGH ACC	0.2000000000000000E-001	DEGREE
66	TEMPERATURE/DRY-BULB TEMPERATURE	0.2730000000000000E+003	K
67	DEW-POINT TEMPERATURE	0.2720000000000000E+003	K
68	WIND DIRECTION	0.2740000000000000E+003	DEGREE TRUE
69	WIND SPEED	0.1400000000000000E+002	M/S
70	LONG TIME PERIOD OR DISPLACEMENT	0.9500000000000000E+002	SECOND
71	EXTENDED VERTICAL SOUNDING SIGNI	0.2048000000000000E+004	FLAG TABLE 8042
72	PRESSURE	0.9184000000000000E+005	PA
73	GEOPOTENTIAL HEIGHT	0.8620000000000000E+003	GPM
74	LATITUDE DISPLACEMENT (HIGH ACCU	0.1000000000000000E-001	DEGREE
75	LONGITUDE DISPLACEMENT (HIGH ACC	0.2000000000000000E-001	DEGREE
76	TEMPERATURE/DRY-BULB TEMPERATURE	0.2728000000000000E+003	K
77	DEW-POINT TEMPERATURE	0.2717000000000000E+003	K
78	WIND DIRECTION	0.2780000000000000E+003	DEGREE TRUE
79	WIND SPEED	0.1420000000000000E+002	M/S
80	LONG TIME PERIOD OR DISPLACEMENT	0.1950000000000000E+003	SECOND
81	EXTENDED VERTICAL SOUNDING SIGNI	0.2048000000000000E+004	FLAG TABLE 8042
82	PRESSURE	0.8584000000000000E+005	PA
83	GEOPOTENTIAL HEIGHT	0.1400000000000000E+004	GPM
84	LATITUDE DISPLACEMENT (HIGH ACCU	0.0000000000000000E+000	DEGREE
85	LONGITUDE DISPLACEMENT (HIGH ACC	0.4000000000000000E-001	DEGREE
86	TEMPERATURE/DRY-BULB TEMPERATURE	0.2695000000000000E+003	K
87	DEW-POINT TEMPERATURE	0.2666000000000000E+003	K
88	WIND DIRECTION	0.3130000000000000E+003	DEGREE TRUE
89	WIND SPEED	0.1180000000000000E+002	M/S
90	LONG TIME PERIOD OR DISPLACEMENT	0.2110000000000000E+003	SECOND
91	EXTENDED VERTICAL SOUNDING SIGNI	0.6553600000000000E+005	FLAG TABLE 8042
92	PRESSURE	0.8500000000000000E+005	PA
93	GEOPOTENTIAL HEIGHT	0.1478000000000000E+004	GPM
94	LATITUDE DISPLACEMENT (HIGH ACCU	0.0000000000000000E+000	DEGREE
95	LONGITUDE DISPLACEMENT (HIGH ACC	0.4000000000000000E-001	DEGREE
96	TEMPERATURE/DRY-BULB TEMPERATURE	0.2690000000000000E+003	K
97	DEW-POINT TEMPERATURE	0.2658000000000000E+003	K
98	WIND DIRECTION	0.3130000000000000E+003	DEGREE TRUE
99	WIND SPEED	0.1260000000000000E+002	M/S
100	LONG TIME PERIOD OR DISPLACEMENT	0.3800000000000000E+003	SECOND
101	EXTENDED VERTICAL SOUNDING SIGNI	0.1228800000000000E+005	FLAG TABLE 8042
102	PRESSURE	0.7558000000000000E+005	PA
103	GEOPOTENTIAL HEIGHT	0.2392000000000000E+004	GPM
104	LATITUDE DISPLACEMENT (HIGH ACCU	-0.1000000000000000E-001	DEGREE
105	LONGITUDE DISPLACEMENT (HIGH ACC	0.6000000000000000E-001	DEGREE
106	TEMPERATURE/DRY-BULB TEMPERATURE	0.2618000000000000E+003	K
107	DEW-POINT TEMPERATURE	0.2581000000000000E+003	K
108	WIND DIRECTION	0.3240000000000000E+003	DEGREE TRUE
109	WIND SPEED	0.1530000000000000E+002	M/S
110	LONG TIME PERIOD OR DISPLACEMENT	0.3900000000000000E+003	SECOND
111	EXTENDED VERTICAL SOUNDING SIGNI	0.4096000000000000E+004	FLAG TABLE 8042
112	PRESSURE	0.7497000000000000E+005	PA
113	GEOPOTENTIAL HEIGHT	0.2454000000000000E+004	GPM
114	LATITUDE DISPLACEMENT (HIGH ACCU	-0.2000000000000000E-001	DEGREE
115	LONGITUDE DISPLACEMENT (HIGH ACC	0.6000000000000000E-001	DEGREE
116	TEMPERATURE/DRY-BULB TEMPERATURE	0.2625000000000000E+003	K
117	DEW-POINT TEMPERATURE	0.2505000000000000E+003	K
118	WIND DIRECTION	0.3270000000000000E+003	DEGREE TRUE
119	WIND SPEED	0.1560000000000000E+002	M/S
120	LONG TIME PERIOD OR DISPLACEMENT	0.4300000000000000E+003	SECOND
121	EXTENDED VERTICAL SOUNDING SIGNI	0.1228800000000000E+005	FLAG TABLE 8042
122	PRESSURE	0.7265000000000000E+005	PA
123	GEOPOTENTIAL HEIGHT	0.2695000000000000E+004	GPM
124	LATITUDE DISPLACEMENT (HIGH ACCU	-0.2000000000000000E-001	DEGREE
125	LONGITUDE DISPLACEMENT (HIGH ACC	0.7000000000000000E-001	DEGREE
126	TEMPERATURE/DRY-BULB TEMPERATURE	0.2624000000000000E+003	K
127	DEW-POINT TEMPERATURE	0.2563000000000000E+003	K

128	WIND DIRECTION	0.338000000000000E+003	DEGREE TRUE
129	WIND SPEED	0.167000000000000E+002	M/S
130	LONG TIME PERIOD OR DISPLACEMENT	0.450000000000000E+003	SECOND
131	EXTENDED VERTICAL SOUNDING SIGNI	0.204800000000000E+004	FLAG TABLE 8042
132	PRESSURE	0.715100000000000E+005	PA
133	GEOPOTENTIAL HEIGHT	0.281700000000000E+004	GPM
134	LATITUDE DISPLACEMENT (HIGH ACCU	-0.200000000000000E-001	DEGREE
135	LONGITUDE DISPLACEMENT (HIGH ACC	0.700000000000000E-001	DEGREE
136	TEMPERATURE/DRY-BULB TEMPERATURE	0.262200000000000E+003	K
137	DEW-POINT TEMPERATURE	0.255900000000000E+003	K
138	WIND DIRECTION	0.341000000000000E+003	DEGREE TRUE
139	WIND SPEED	0.172000000000000E+002	M/S
140	LONG TIME PERIOD OR DISPLACEMENT	0.477000000000000E+003	SECOND
141	EXTENDED VERTICAL SOUNDING SIGNI	0.655360000000000E+005	FLAG TABLE 8042
142	PRESSURE	0.700000000000000E+005	PA
143	GEOPOTENTIAL HEIGHT	0.298000000000000E+004	GPM
144	LATITUDE DISPLACEMENT (HIGH ACCU	-0.300000000000000E-001	DEGREE
145	LONGITUDE DISPLACEMENT (HIGH ACC	0.700000000000000E-001	DEGREE
146	TEMPERATURE/DRY-BULB TEMPERATURE	0.261400000000000E+003	K
147	DEW-POINT TEMPERATURE	0.256200000000000E+003	K
148	WIND DIRECTION	0.340000000000000E+003	DEGREE TRUE
149	WIND SPEED	0.175000000000000E+002	M/S
150	LONG TIME PERIOD OR DISPLACEMENT	0.600000000000000E+003	SECOND
151	EXTENDED VERTICAL SOUNDING SIGNI	0.409600000000000E+004	FLAG TABLE 8042
152	PRESSURE	0.632500000000000E+005	PA
153	GEOPOTENTIAL HEIGHT	0.375100000000000E+004	GPM
154	LATITUDE DISPLACEMENT (HIGH ACCU	-0.500000000000000E-001	DEGREE
155	LONGITUDE DISPLACEMENT (HIGH ACC	0.800000000000000E-001	DEGREE
156	TEMPERATURE/DRY-BULB TEMPERATURE	0.257300000000000E+003	K
157	DEW-POINT TEMPERATURE	0.256300000000000E+003	K
158	WIND DIRECTION	0.336000000000000E+003	DEGREE TRUE
159	WIND SPEED	0.214000000000000E+002	M/S
160	LONG TIME PERIOD OR DISPLACEMENT	0.805000000000000E+003	SECOND
161	EXTENDED VERTICAL SOUNDING SIGNI	0.204800000000000E+004	FLAG TABLE 8042
162	PRESSURE	0.536000000000000E+005	PA
163	GEOPOTENTIAL HEIGHT	0.498200000000000E+004	GPM
164	LATITUDE DISPLACEMENT (HIGH ACCU	-0.900000000000000E-001	DEGREE
165	LONGITUDE DISPLACEMENT (HIGH ACC	0.110000000000000E+000	DEGREE
166	TEMPERATURE/DRY-BULB TEMPERATURE	0.250100000000000E+003	K
167	DEW-POINT TEMPERATURE	0.247800000000000E+003	K
168	WIND DIRECTION	0.343000000000000E+003	DEGREE TRUE
169	WIND SPEED	0.245000000000000E+002	M/S
170	LONG TIME PERIOD OR DISPLACEMENT	0.880000000000000E+003	SECOND
171	EXTENDED VERTICAL SOUNDING SIGNI	0.122880000000000E+005	FLAG TABLE 8042
172	PRESSURE	0.502200000000000E+005	PA
173	GEOPOTENTIAL HEIGHT	0.545700000000000E+004	GPM
174	LATITUDE DISPLACEMENT (HIGH ACCU	-0.100000000000000E+000	DEGREE
175	LONGITUDE DISPLACEMENT (HIGH ACC	0.120000000000000E+000	DEGREE
176	TEMPERATURE/DRY-BULB TEMPERATURE	0.247600000000000E+003	K
177	DEW-POINT TEMPERATURE	0.245500000000000E+003	K
178	WIND DIRECTION	0.339000000000000E+003	DEGREE TRUE
179	WIND SPEED	0.313000000000000E+002	M/S
180	LONG TIME PERIOD OR DISPLACEMENT	0.885000000000000E+003	SECOND
181	EXTENDED VERTICAL SOUNDING SIGNI	0.655360000000000E+005	FLAG TABLE 8042
182	PRESSURE	0.500100000000000E+005	PA
183	GEOPOTENTIAL HEIGHT	0.548700000000000E+004	GPM
184	LATITUDE DISPLACEMENT (HIGH ACCU	-0.100000000000000E+000	DEGREE
185	LONGITUDE DISPLACEMENT (HIGH ACC	0.120000000000000E+000	DEGREE
186	TEMPERATURE/DRY-BULB TEMPERATURE	0.247700000000000E+003	K
187	DEW-POINT TEMPERATURE	0.245800000000000E+003	K
188	WIND DIRECTION	0.339000000000000E+003	DEGREE TRUE
189	WIND SPEED	0.317000000000000E+002	M/S
190	LONG TIME PERIOD OR DISPLACEMENT	0.895000000000000E+003	SECOND
191	EXTENDED VERTICAL SOUNDING SIGNI	0.819200000000000E+004	FLAG TABLE 8042
192	PRESSURE	0.495100000000000E+005	PA
193	GEOPOTENTIAL HEIGHT	0.556000000000000E+004	GPM
194	LATITUDE DISPLACEMENT (HIGH ACCU	-0.110000000000000E+000	DEGREE
195	LONGITUDE DISPLACEMENT (HIGH ACC	0.120000000000000E+000	DEGREE
196	TEMPERATURE/DRY-BULB TEMPERATURE	0.247700000000000E+003	K
197	DEW-POINT TEMPERATURE	0.245800000000000E+003	K
198	WIND DIRECTION	0.339000000000000E+003	DEGREE TRUE
199	WIND SPEED	0.325000000000000E+002	M/S
200	LONG TIME PERIOD OR DISPLACEMENT	0.910000000000000E+003	SECOND
201	EXTENDED VERTICAL SOUNDING SIGNI	0.211200000000000E+004	FLAG TABLE 8042
202	PRESSURE	0.488300000000000E+005	PA
203	GEOPOTENTIAL HEIGHT	0.565900000000000E+004	GPM
204	LATITUDE DISPLACEMENT (HIGH ACCU	-0.110000000000000E+000	DEGREE
205	LONGITUDE DISPLACEMENT (HIGH ACC	0.130000000000000E+000	DEGREE
206	TEMPERATURE/DRY-BULB TEMPERATURE	0.247000000000000E+003	K
207	DEW-POINT TEMPERATURE	0.245100000000000E+003	K
208	WIND DIRECTION	0.339000000000000E+003	DEGREE TRUE
209	WIND SPEED	0.334000000000000E+002	M/S
210	LONG TIME PERIOD OR DISPLACEMENT	0.112500000000000E+004	SECOND
211	EXTENDED VERTICAL SOUNDING SIGNI	0.655360000000000E+005	FLAG TABLE 8042
212	PRESSURE	0.400000000000000E+005	PA
213	GEOPOTENTIAL HEIGHT	0.707300000000000E+004	GPM
214	LATITUDE DISPLACEMENT (HIGH ACCU		MISSING DEGREE
215	LONGITUDE DISPLACEMENT (HIGH ACC		MISSING DEGREE
216	TEMPERATURE/DRY-BULB TEMPERATURE	0.236900000000000E+003	K
217	DEW-POINT TEMPERATURE	0.233800000000000E+003	K
218	WIND DIRECTION		MISSING DEGREE TRUE
219	WIND SPEED		MISSING M/S
220	LONG TIME PERIOD OR DISPLACEMENT	0.126000000000000E+004	SECOND



221	EXTENDED VERTICAL SOUNDING SIGNI	0.204800000000000E+004	FLAG TABLE 8042
222	PRESSURE	0.352000000000000E+005	PA
223	GEOPOTENTIAL HEIGHT	0.794500000000000E+004	GPM
224	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
225	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
226	TEMPERATURE/DRY-BULB TEMPERATURE	0.229200000000000E+003	K
227	DEW-POINT TEMPERATURE	0.225200000000000E+003	K
228	WIND DIRECTION	MISSING	DEGREE TRUE
229	WIND SPEED	MISSING	M/S
230	LONG TIME PERIOD OR DISPLACEMENT	0.127500000000000E+004	SECOND
231	EXTENDED VERTICAL SOUNDING SIGNI	0.819200000000000E+004	FLAG TABLE 8042
232	PRESSURE	0.347100000000000E+005	PA
233	GEOPOTENTIAL HEIGHT	0.804000000000000E+004	GPM
234	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
235	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
236	TEMPERATURE/DRY-BULB TEMPERATURE	0.228400000000000E+003	K
237	DEW-POINT TEMPERATURE	0.224400000000000E+003	K
238	WIND DIRECTION	MISSING	DEGREE TRUE
239	WIND SPEED	MISSING	M/S
240	LONG TIME PERIOD OR DISPLACEMENT	0.135500000000000E+004	SECOND
241	EXTENDED VERTICAL SOUNDING SIGNI	0.122880000000000E+005	FLAG TABLE 8042
242	PRESSURE	0.319300000000000E+005	PA
243	GEOPOTENTIAL HEIGHT	0.859600000000000E+004	GPM
244	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
245	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
246	TEMPERATURE/DRY-BULB TEMPERATURE	0.226900000000000E+003	K
247	DEW-POINT TEMPERATURE	0.222300000000000E+003	K
248	WIND DIRECTION	MISSING	DEGREE TRUE
249	WIND SPEED	MISSING	M/S
250	LONG TIME PERIOD OR DISPLACEMENT	0.142000000000000E+004	SECOND
251	EXTENDED VERTICAL SOUNDING SIGNI	0.655360000000000E+005	FLAG TABLE 8042
252	PRESSURE	0.300000000000000E+005	PA
253	GEOPOTENTIAL HEIGHT	0.900600000000000E+004	GPM
254	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
255	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
256	TEMPERATURE/DRY-BULB TEMPERATURE	0.223200000000000E+003	K
257	DEW-POINT TEMPERATURE	0.218600000000000E+003	K
258	WIND DIRECTION	MISSING	DEGREE TRUE
259	WIND SPEED	MISSING	M/S
260	LONG TIME PERIOD OR DISPLACEMENT	0.149000000000000E+004	SECOND
261	EXTENDED VERTICAL SOUNDING SIGNI	0.450560000000000E+005	FLAG TABLE 8042
262	PRESSURE	0.278300000000000E+005	PA
263	GEOPOTENTIAL HEIGHT	0.949200000000000E+004	GPM
264	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
265	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
266	TEMPERATURE/DRY-BULB TEMPERATURE	0.219700000000000E+003	K
267	DEW-POINT TEMPERATURE	0.215100000000000E+003	K
268	WIND DIRECTION	MISSING	DEGREE TRUE
269	WIND SPEED	MISSING	M/S
270	LONG TIME PERIOD OR DISPLACEMENT	0.158200000000000E+004	SECOND
271	EXTENDED VERTICAL SOUNDING SIGNI	0.655360000000000E+005	FLAG TABLE 8042
272	PRESSURE	0.250000000000000E+005	PA
273	GEOPOTENTIAL HEIGHT	0.101820000000000E+005	GPM
274	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
275	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
276	TEMPERATURE/DRY-BULB TEMPERATURE	0.220300000000000E+003	K
277	DEW-POINT TEMPERATURE	0.206300000000000E+003	K
278	WIND DIRECTION	MISSING	DEGREE TRUE
279	WIND SPEED	MISSING	M/S
280	LONG TIME PERIOD OR DISPLACEMENT	0.159500000000000E+004	SECOND
281	EXTENDED VERTICAL SOUNDING SIGNI	0.409600000000000E+004	FLAG TABLE 8042
282	PRESSURE	0.246600000000000E+005	PA
283	GEOPOTENTIAL HEIGHT	0.102700000000000E+005	GPM
284	LATITUDE DISPLACEMENT (HIGH ACCU	MISSING	DEGREE
285	LONGITUDE DISPLACEMENT (HIGH ACC	MISSING	DEGREE
286	TEMPERATURE/DRY-BULB TEMPERATURE	0.219800000000000E+003	K
287	DEW-POINT TEMPERATURE	0.204200000000000E+003	K
288	WIND DIRECTION	MISSING	DEGREE TRUE
289	WIND SPEED	MISSING	M/S
290	LONG TIME PERIOD OR DISPLACEMENT	0.161500000000000E+004	SECOND
291	EXTENDED VERTICAL SOUNDING SIGNI	0.208000000000000E+004	FLAG TABLE 8042
292	PRESSURE	0.241800000000000E+005	PA
293	GEOPOTENTIAL HEIGHT	0.103980000000000E+005	GPM
294	LATITUDE DISPLACEMENT (HIGH ACCU	-0.360000000000000E+000	DEGREE
295	LONGITUDE DISPLACEMENT (HIGH ACC	0.260000000000000E+000	DEGREE
296	TEMPERATURE/DRY-BULB TEMPERATURE	0.219700000000000E+003	K
297	DEW-POINT TEMPERATURE	0.202500000000000E+003	K
298	WIND DIRECTION	0.341000000000000E+003	DEGREE TRUE
299	WIND SPEED	0.509000000000000E+002	M/S
300	LONG TIME PERIOD OR DISPLACEMENT	0.179000000000000E+004	SECOND
301	EXTENDED VERTICAL SOUNDING SIGNI	0.204800000000000E+004	FLAG TABLE 8042
302	PRESSURE	0.206200000000000E+005	PA
303	GEOPOTENTIAL HEIGHT	0.114340000000000E+005	GPM
304	LATITUDE DISPLACEMENT (HIGH ACCU	-0.430000000000000E+000	DEGREE
305	LONGITUDE DISPLACEMENT (HIGH ACC	0.300000000000000E+000	DEGREE
306	TEMPERATURE/DRY-BULB TEMPERATURE	0.223200000000000E+003	K
307	DEW-POINT TEMPERATURE	0.193000000000000E+003	K
308	WIND DIRECTION	0.333000000000000E+003	DEGREE TRUE
309	WIND SPEED	0.322000000000000E+002	M/S
310	LONG TIME PERIOD OR DISPLACEMENT	0.180500000000000E+004	SECOND
311	EXTENDED VERTICAL SOUNDING SIGNI	0.819200000000000E+004	FLAG TABLE 8042
312	PRESSURE	0.203200000000000E+005	PA
313	GEOPOTENTIAL HEIGHT	0.115270000000000E+005	GPM

```
314 LATITUDE DISPLACEMENT (HIGH ACCU -0.4300000000000000E+000 DEGREE
315 LONGITUDE DISPLACEMENT (HIGH ACCU 0.3000000000000000E+000 DEGREE
316 TEMPERATURE/DRY-BULB TEMPERATURE 0.2236000000000000E+003 K
317 DEW-POINT TEMPERATURE 0.1926000000000000E+003 K
318 WIND DIRECTION 0.3330000000000000E+003 DEGREE TRUE
319 WIND SPEED 0.3260000000000000E+002 M/S
320 LONG TIME PERIOD OR DISPLACEMENT 0.1821000000000000E+004 SECOND
321 EXTENDED VERTICAL SOUNDING SIGNI 0.6553600000000000E+005 FLAG TABLE 8042
322 PRESSURE 0.2000000000000000E+005 PA
323 GEOPOTENTIAL HEIGHT 0.1163200000000000E+005 GPM
324 LATITUDE DISPLACEMENT (HIGH ACCU -0.4300000000000000E+000 DEGREE
325 LONGITUDE DISPLACEMENT (HIGH ACCU 0.3000000000000000E+000 DEGREE
326 TEMPERATURE/DRY-BULB TEMPERATURE 0.2233000000000000E+003 K
327 DEW-POINT TEMPERATURE 0.1895000000000000E+003 K
328 WIND DIRECTION 0.3330000000000000E+003 DEGREE TRUE
329 WIND SPEED 0.3370000000000000E+002 M/S
330 LONG TIME PERIOD OR DISPLACEMENT 0.1855000000000000E+004 SECOND
331 EXTENDED VERTICAL SOUNDING SIGNI 0.1843200000000000E+005 FLAG TABLE 8042
332 PRESSURE 0.1926000000000000E+005 PA
333 GEOPOTENTIAL HEIGHT 0.1187600000000000E+005 GPM
334 LATITUDE DISPLACEMENT (HIGH ACCU -0.4400000000000000E+000 DEGREE
335 LONGITUDE DISPLACEMENT (HIGH ACC 0.3100000000000000E+000 DEGREE
336 TEMPERATURE/DRY-BULB TEMPERATURE 0.2216000000000000E+003 K
337 DEW-POINT TEMPERATURE 0.1901000000000000E+003 K
338 WIND DIRECTION 0.3340000000000000E+003 DEGREE TRUE
339 WIND SPEED 0.3580000000000000E+002 M/S
340 LONG TIME PERIOD OR DISPLACEMENT 0.1875000000000000E+004 SECOND
341 EXTENDED VERTICAL SOUNDING SIGNI 0.8192000000000000E+004 FLAG TABLE 8042
342 PRESSURE 0.1885000000000000E+005 PA
343 GEOPOTENTIAL HEIGHT 0.1201800000000000E+005 GPM
344 LATITUDE DISPLACEMENT (HIGH ACCU -0.4500000000000000E+000 DEGREE
345 LONGITUDE DISPLACEMENT (HIGH ACC 0.3100000000000000E+000 DEGREE
346 TEMPERATURE/DRY-BULB TEMPERATURE 0.2206000000000000E+003 K
347 DEW-POINT TEMPERATURE 0.1897000000000000E+003 K
348 WIND DIRECTION 0.3360000000000000E+003 DEGREE TRUE
349 WIND SPEED 0.3400000000000000E+002 M/S
350 LONG TIME PERIOD OR DISPLACEMENT 0.1920000000000000E+004 SECOND
351 EXTENDED VERTICAL SOUNDING SIGNI 0.8192000000000000E+004 FLAG TABLE 8042
352 PRESSURE 0.1781000000000000E+005 PA
353 GEOPOTENTIAL HEIGHT 0.1238600000000000E+005 GPM
354 LATITUDE DISPLACEMENT (HIGH ACCU -0.4600000000000000E+000 DEGREE
355 LONGITUDE DISPLACEMENT (HIGH ACC 0.3200000000000000E+000 DEGREE
356 TEMPERATURE/DRY-BULB TEMPERATURE 0.2225000000000000E+003 K
357 DEW-POINT TEMPERATURE 0.1895000000000000E+003 K
358 WIND DIRECTION 0.3400000000000000E+003 DEGREE TRUE
359 WIND SPEED 0.2530000000000000E+002 M/S
360 LONG TIME PERIOD OR DISPLACEMENT 0.1925000000000000E+004 SECOND
361 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
362 PRESSURE 0.1769000000000000E+005 PA
363 GEOPOTENTIAL HEIGHT 0.1243000000000000E+005 GPM
364 LATITUDE DISPLACEMENT (HIGH ACCU -0.4600000000000000E+000 DEGREE
365 LONGITUDE DISPLACEMENT (HIGH ACC 0.3200000000000000E+000 DEGREE
366 TEMPERATURE/DRY-BULB TEMPERATURE 0.2221000000000000E+003 K
367 DEW-POINT TEMPERATURE 0.1891000000000000E+003 K
368 WIND DIRECTION 0.3400000000000000E+003 DEGREE TRUE
369 WIND SPEED 0.2450000000000000E+002 M/S
370 LONG TIME PERIOD OR DISPLACEMENT 0.1965000000000000E+004 SECOND
371 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
372 PRESSURE 0.1701000000000000E+005 PA
373 GEOPOTENTIAL HEIGHT 0.1268400000000000E+005 GPM
374 LATITUDE DISPLACEMENT (HIGH ACCU -0.4700000000000000E+000 DEGREE
375 LONGITUDE DISPLACEMENT (HIGH ACC 0.3300000000000000E+000 DEGREE
376 TEMPERATURE/DRY-BULB TEMPERATURE 0.2210000000000000E+003 K
377 DEW-POINT TEMPERATURE 0.1879000000000000E+003 K
378 WIND DIRECTION 0.3310000000000000E+003 DEGREE TRUE
379 WIND SPEED 0.2170000000000000E+002 M/S
380 LONG TIME PERIOD OR DISPLACEMENT 0.2020000000000000E+004 SECOND
381 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
382 PRESSURE 0.1614000000000000E+005 PA
383 GEOPOTENTIAL HEIGHT 0.1302200000000000E+005 GPM
384 LATITUDE DISPLACEMENT (HIGH ACCU -0.4800000000000000E+000 DEGREE
385 LONGITUDE DISPLACEMENT (HIGH ACC 0.3400000000000000E+000 DEGREE
386 TEMPERATURE/DRY-BULB TEMPERATURE 0.2213000000000000E+003 K
387 DEW-POINT TEMPERATURE 0.1881000000000000E+003 K
388 WIND DIRECTION 0.3200000000000000E+003 DEGREE TRUE
389 WIND SPEED 0.2440000000000000E+002 M/S
390 LONG TIME PERIOD OR DISPLACEMENT 0.2085000000000000E+004 SECOND
391 EXTENDED VERTICAL SOUNDING SIGNI 0.8192000000000000E+004 FLAG TABLE 8042
392 PRESSURE 0.1527000000000000E+005 PA
393 GEOPOTENTIAL HEIGHT 0.1338200000000000E+005 GPM
394 LATITUDE DISPLACEMENT (HIGH ACCU -0.4900000000000000E+000 DEGREE
395 LONGITUDE DISPLACEMENT (HIGH ACC 0.3500000000000000E+000 DEGREE
396 TEMPERATURE/DRY-BULB TEMPERATURE 0.2218000000000000E+003 K
397 DEW-POINT TEMPERATURE 0.1884000000000000E+003 K
398 WIND DIRECTION 0.3270000000000000E+003 DEGREE TRUE
399 WIND SPEED 0.3030000000000000E+002 M/S
400 LONG TIME PERIOD OR DISPLACEMENT 0.2105000000000000E+004 SECOND
401 EXTENDED VERTICAL SOUNDING SIGNI 0.6553600000000000E+005 FLAG TABLE 8042
402 PRESSURE 0.1500000000000000E+005 PA
403 GEOPOTENTIAL HEIGHT 0.1349800000000000E+005 GPM
404 LATITUDE DISPLACEMENT (HIGH ACCU -0.5000000000000000E+000 DEGREE
405 LONGITUDE DISPLACEMENT (HIGH ACC 0.3500000000000000E+000 DEGREE
406 TEMPERATURE/DRY-BULB TEMPERATURE 0.2214000000000000E+003 K
```



407	DEW-POINT TEMPERATURE	0.1881000000000000E+003	K
408	WIND DIRECTION	0.3310000000000000E+003	DEGREE TRUE
409	WIND SPEED	0.3160000000000000E+002	M/S
410	LONG TIME PERIOD OR DISPLACEMENT	0.2145000000000000E+004	SECOND
411	EXTENDED VERTICAL SOUNDING SIGNI	0.2048000000000000E+004	FLAG TABLE 8042
412	PRESSURE	0.1451000000000000E+005	PA
413	GEOPOTENTIAL HEIGHT	0.1371100000000000E+005	GPM
414	LATITUDE DISPLACEMENT (HIGH ACCU	-0.5100000000000000E+000	DEGREE
415	LONGITUDE DISPLACEMENT (HIGH ACC	0.3600000000000000E+000	DEGREE
416	TEMPERATURE/DRY-BULB TEMPERATURE	0.2202000000000000E+003	K
417	DEW-POINT TEMPERATURE	0.1873000000000000E+003	K
418	WIND DIRECTION	0.3350000000000000E+003	DEGREE TRUE
419	WIND SPEED	0.3080000000000000E+002	M/S
420	LONG TIME PERIOD OR DISPLACEMENT	0.2275000000000000E+004	SECOND
421	EXTENDED VERTICAL SOUNDING SIGNI	0.8192000000000000E+004	FLAG TABLE 8042
422	PRESSURE	0.1280000000000000E+005	PA
423	GEOPOTENTIAL HEIGHT	0.1451000000000000E+005	GPM
424	LATITUDE DISPLACEMENT (HIGH ACCU	-0.5400000000000000E+000	DEGREE
425	LONGITUDE DISPLACEMENT (HIGH ACC	0.4000000000000000E+000	DEGREE
426	TEMPERATURE/DRY-BULB TEMPERATURE	0.2155000000000000E+003	K
427	DEW-POINT TEMPERATURE	0.1840000000000000E+003	K
428	WIND DIRECTION	0.3170000000000000E+003	DEGREE TRUE
429	WIND SPEED	0.3800000000000000E+002	M/S
430	LONG TIME PERIOD OR DISPLACEMENT	0.2280000000000000E+004	SECOND
431	EXTENDED VERTICAL SOUNDING SIGNI	0.1843200000000000E+005	FLAG TABLE 8042
432	PRESSURE	0.1275000000000000E+005	PA
433	GEOPOTENTIAL HEIGHT	0.1453800000000000E+005	GPM
434	LATITUDE DISPLACEMENT (HIGH ACCU	-0.5400000000000000E+000	DEGREE
435	LONGITUDE DISPLACEMENT (HIGH ACC	0.4000000000000000E+000	DEGREE
436	TEMPERATURE/DRY-BULB TEMPERATURE	0.2156000000000000E+003	K
437	DEW-POINT TEMPERATURE	0.1840000000000000E+003	K
438	WIND DIRECTION	0.3170000000000000E+003	DEGREE TRUE
439	WIND SPEED	0.3800000000000000E+002	M/S
440	LONG TIME PERIOD OR DISPLACEMENT	0.2340000000000000E+004	SECOND
441	EXTENDED VERTICAL SOUNDING SIGNI	0.8192000000000000E+004	FLAG TABLE 8042
442	PRESSURE	0.1204000000000000E+005	PA
443	GEOPOTENTIAL HEIGHT	0.1490100000000000E+005	GPM
444	LATITUDE DISPLACEMENT (HIGH ACCU	-0.5500000000000000E+000	DEGREE
445	LONGITUDE DISPLACEMENT (HIGH ACC	0.4100000000000000E+000	DEGREE
446	TEMPERATURE/DRY-BULB TEMPERATURE	0.2177000000000000E+003	K
447	DEW-POINT TEMPERATURE	0.1858000000000000E+003	K
448	WIND DIRECTION	0.3250000000000000E+003	DEGREE TRUE
449	WIND SPEED	0.2840000000000000E+002	M/S
450	LONG TIME PERIOD OR DISPLACEMENT	0.2430000000000000E+004	SECOND
451	EXTENDED VERTICAL SOUNDING SIGNI	0.2048000000000000E+004	FLAG TABLE 8042
452	PRESSURE	0.1109000000000000E+005	PA
453	GEOPOTENTIAL HEIGHT	0.1542100000000000E+005	GPM
454	LATITUDE DISPLACEMENT (HIGH ACCU	-0.5700000000000000E+000	DEGREE
455	LONGITUDE DISPLACEMENT (HIGH ACC	0.4300000000000000E+000	DEGREE
456	TEMPERATURE/DRY-BULB TEMPERATURE	0.2149000000000000E+003	K
457	DEW-POINT TEMPERATURE	0.1836000000000000E+003	K
458	WIND DIRECTION	0.3320000000000000E+003	DEGREE TRUE
459	WIND SPEED	0.2160000000000000E+002	M/S
460	LONG TIME PERIOD OR DISPLACEMENT	0.2545000000000000E+004	SECOND
461	EXTENDED VERTICAL SOUNDING SIGNI	0.7987200000000000E+005	FLAG TABLE 8042
462	PRESSURE	0.1000000000000000E+005	PA
463	GEOPOTENTIAL HEIGHT	0.1606600000000000E+005	GPM
464	LATITUDE DISPLACEMENT (HIGH ACCU	-0.5900000000000000E+000	DEGREE
465	LONGITUDE DISPLACEMENT (HIGH ACC	0.4500000000000000E+000	DEGREE
466	TEMPERATURE/DRY-BULB TEMPERATURE	0.2110000000000000E+003	K
467	DEW-POINT TEMPERATURE	0.1830000000000000E+003	K
468	WIND DIRECTION	0.3190000000000000E+003	DEGREE TRUE
469	WIND SPEED	0.2250000000000000E+002	M/S
470	LONG TIME PERIOD OR DISPLACEMENT	0.2615000000000000E+004	SECOND
471	EXTENDED VERTICAL SOUNDING SIGNI	0.4096000000000000E+005	FLAG TABLE 8042
472	PRESSURE	0.9440000000000000E+004	PA
473	GEOPOTENTIAL HEIGHT	0.1642100000000000E+005	GPM
474	LATITUDE DISPLACEMENT (HIGH ACCU	-0.6000000000000000E+000	DEGREE
475	LONGITUDE DISPLACEMENT (HIGH ACC	0.4600000000000000E+000	DEGREE
476	TEMPERATURE/DRY-BULB TEMPERATURE	0.2099000000000000E+003	K
477	DEW-POINT TEMPERATURE	0.1828000000000000E+003	K
478	WIND DIRECTION	0.3160000000000000E+003	DEGREE TRUE
479	WIND SPEED	0.2010000000000000E+002	M/S
480	LONG TIME PERIOD OR DISPLACEMENT	0.2630000000000000E+004	SECOND
481	EXTENDED VERTICAL SOUNDING SIGNI	0.8192000000000000E+004	FLAG TABLE 8042
482	PRESSURE	0.9310000000000000E+004	PA
483	GEOPOTENTIAL HEIGHT	0.1650700000000000E+005	GPM
484	LATITUDE DISPLACEMENT (HIGH ACCU	-0.6000000000000000E+000	DEGREE
485	LONGITUDE DISPLACEMENT (HIGH ACC	0.4700000000000000E+000	DEGREE
486	TEMPERATURE/DRY-BULB TEMPERATURE	0.2108000000000000E+003	K
487	DEW-POINT TEMPERATURE	0.1833000000000000E+003	K
488	WIND DIRECTION	0.3130000000000000E+003	DEGREE TRUE
489	WIND SPEED	0.1900000000000000E+002	M/S
490	LONG TIME PERIOD OR DISPLACEMENT	0.2655000000000000E+004	SECOND
491	EXTENDED VERTICAL SOUNDING SIGNI	0.2048000000000000E+004	FLAG TABLE 8042
492	PRESSURE	0.9090000000000000E+004	PA
493	GEOPOTENTIAL HEIGHT	0.1665000000000000E+005	GPM
494	LATITUDE DISPLACEMENT (HIGH ACCU	-0.6000000000000000E+000	DEGREE
495	LONGITUDE DISPLACEMENT (HIGH ACC	0.4700000000000000E+000	DEGREE
496	TEMPERATURE/DRY-BULB TEMPERATURE	0.2102000000000000E+003	K
497	DEW-POINT TEMPERATURE	0.1832000000000000E+003	K
498	WIND DIRECTION	0.3080000000000000E+003	DEGREE TRUE
499	WIND SPEED	0.1770000000000000E+002	M/S

```
500 LONG TIME PERIOD OR DISPLACEMENT 0.2790000000000000E+004 SECOND
501 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
502 PRESSURE 0.8030000000000000E+004 PA
503 GEOPOTENTIAL HEIGHT 0.1741400000000000E+005 GPM
504 LATITUDE DISPLACEMENT (HIGH ACCU -0.6200000000000000E+000 DEGREE
505 LONGITUDE DISPLACEMENT (HIGH ACC 0.5000000000000000E+000 DEGREE
506 TEMPERATURE/DRY-BULB TEMPERATURE 0.2101000000000000E+003 K
507 DEW-POINT TEMPERATURE 0.1831000000000000E+003 K
508 WIND DIRECTION 0.3220000000000000E+003 DEGREE TRUE
509 WIND SPEED 0.2450000000000000E+002 M/S
510 LONG TIME PERIOD OR DISPLACEMENT 0.2920000000000000E+004 SECOND
511 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
512 PRESSURE 0.7040000000000000E+004 PA
513 GEOPOTENTIAL HEIGHT 0.1821600000000000E+005 GPM
514 LATITUDE DISPLACEMENT (HIGH ACCU -0.6400000000000000E+000 DEGREE
515 LONGITUDE DISPLACEMENT (HIGH ACC 0.5200000000000000E+000 DEGREE
516 TEMPERATURE/DRY-BULB TEMPERATURE 0.2073000000000000E+003 K
517 DEW-POINT TEMPERATURE 0.1805000000000000E+003 K
518 WIND DIRECTION 0.3380000000000000E+003 DEGREE TRUE
519 WIND SPEED 0.1690000000000000E+002 M/S
520 LONG TIME PERIOD OR DISPLACEMENT 0.2926000000000000E+004 SECOND
521 EXTENDED VERTICAL SOUNDING SIGNI 0.6553600000000000E+005 FLAG TABLE 8042
522 PRESSURE 0.7000000000000000E+004 PA
523 GEOPOTENTIAL HEIGHT 0.1825200000000000E+005 GPM
524 LATITUDE DISPLACEMENT (HIGH ACCU -0.6400000000000000E+000 DEGREE
525 LONGITUDE DISPLACEMENT (HIGH ACC 0.5200000000000000E+000 DEGREE
526 TEMPERATURE/DRY-BULB TEMPERATURE 0.2071000000000000E+003 K
527 DEW-POINT TEMPERATURE 0.1818000000000000E+003 K
528 WIND DIRECTION 0.3380000000000000E+003 DEGREE TRUE
529 WIND SPEED 0.1670000000000000E+002 M/S
530 LONG TIME PERIOD OR DISPLACEMENT 0.2970000000000000E+004 SECOND
531 EXTENDED VERTICAL SOUNDING SIGNI 0.8192000000000000E+004 FLAG TABLE 8042
532 PRESSURE 0.6710000000000000E+004 PA
533 GEOPOTENTIAL HEIGHT 0.1850600000000000E+005 GPM
534 LATITUDE DISPLACEMENT (HIGH ACCU -0.6500000000000000E+000 DEGREE
535 LONGITUDE DISPLACEMENT (HIGH ACC 0.5200000000000000E+000 DEGREE
536 TEMPERATURE/DRY-BULB TEMPERATURE 0.2053000000000000E+003 K
537 DEW-POINT TEMPERATURE 0.1793000000000000E+003 K
538 WIND DIRECTION 0.3320000000000000E+003 DEGREE TRUE
539 WIND SPEED 0.1910000000000000E+002 M/S
540 LONG TIME PERIOD OR DISPLACEMENT 0.3025000000000000E+004 SECOND
541 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
542 PRESSURE 0.6380000000000000E+004 PA
543 GEOPOTENTIAL HEIGHT 0.1881300000000000E+005 GPM
544 LATITUDE DISPLACEMENT (HIGH ACCU -0.6600000000000000E+000 DEGREE
545 LONGITUDE DISPLACEMENT (HIGH ACC 0.5300000000000000E+000 DEGREE
546 TEMPERATURE/DRY-BULB TEMPERATURE 0.2058000000000000E+003 K
547 DEW-POINT TEMPERATURE 0.1798000000000000E+003 K
548 WIND DIRECTION 0.3310000000000000E+003 DEGREE TRUE
549 WIND SPEED 0.2330000000000000E+002 M/S
550 LONG TIME PERIOD OR DISPLACEMENT 0.3160000000000000E+004 SECOND
551 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
552 PRESSURE 0.5500000000000000E+004 PA
553 GEOPOTENTIAL HEIGHT 0.1970400000000000E+005 GPM
554 LATITUDE DISPLACEMENT (HIGH ACCU -0.6800000000000000E+000 DEGREE
555 LONGITUDE DISPLACEMENT (HIGH ACC 0.5500000000000000E+000 DEGREE
556 TEMPERATURE/DRY-BULB TEMPERATURE 0.2071000000000000E+003 K
557 DEW-POINT TEMPERATURE 0.1806000000000000E+003 K
558 WIND DIRECTION 0.3300000000000000E+003 DEGREE TRUE
559 WIND SPEED 0.1840000000000000E+002 M/S
560 LONG TIME PERIOD OR DISPLACEMENT 0.3247000000000000E+004 SECOND
561 EXTENDED VERTICAL SOUNDING SIGNI 0.6553600000000000E+005 FLAG TABLE 8042
562 PRESSURE 0.5000000000000000E+004 PA
563 GEOPOTENTIAL HEIGHT 0.2028600000000000E+005 GPM
564 LATITUDE DISPLACEMENT (HIGH ACCU -0.6900000000000000E+000 DEGREE
565 LONGITUDE DISPLACEMENT (HIGH ACC 0.5600000000000000E+000 DEGREE
566 TEMPERATURE/DRY-BULB TEMPERATURE 0.2066000000000000E+003 K
567 DEW-POINT TEMPERATURE 0.1800000000000000E+003 K
568 WIND DIRECTION 0.3010000000000000E+003 DEGREE TRUE
569 WIND SPEED 0.1230000000000000E+002 M/S
570 LONG TIME PERIOD OR DISPLACEMENT 0.3265000000000000E+004 SECOND
571 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
572 PRESSURE 0.4890000000000000E+004 PA
573 GEOPOTENTIAL HEIGHT 0.2041700000000000E+005 GPM
574 LATITUDE DISPLACEMENT (HIGH ACCU -0.6900000000000000E+000 DEGREE
575 LONGITUDE DISPLACEMENT (HIGH ACC 0.5600000000000000E+000 DEGREE
576 TEMPERATURE/DRY-BULB TEMPERATURE 0.2067000000000000E+003 K
577 DEW-POINT TEMPERATURE 0.1795000000000000E+003 K
578 WIND DIRECTION 0.2950000000000000E+003 DEGREE TRUE
579 WIND SPEED 0.1360000000000000E+002 M/S
580 LONG TIME PERIOD OR DISPLACEMENT 0.3385000000000000E+004 SECOND
581 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
582 PRESSURE 0.4420000000000000E+004 PA
583 GEOPOTENTIAL HEIGHT 0.2103800000000000E+005 GPM
584 LATITUDE DISPLACEMENT (HIGH ACCU -0.7000000000000000E+000 DEGREE
585 LONGITUDE DISPLACEMENT (HIGH ACC 0.5800000000000000E+000 DEGREE
586 TEMPERATURE/DRY-BULB TEMPERATURE 0.2077000000000000E+003 K
587 DEW-POINT TEMPERATURE 0.1800000000000000E+003 K
588 WIND DIRECTION 0.3170000000000000E+003 DEGREE TRUE
589 WIND SPEED 0.1010000000000000E+002 M/S
590 LONG TIME PERIOD OR DISPLACEMENT 0.3415000000000000E+004 SECOND
591 EXTENDED VERTICAL SOUNDING SIGNI 0.2048000000000000E+004 FLAG TABLE 8042
592 PRESSURE 0.4290000000000000E+004 PA
```



```

593 GEOPOTENTIAL HEIGHT 0.212230000000000E+005 GPM
594 LATITUDE DISPLACEMENT (HIGH ACCU -0.700000000000000E+000 DEGREE
595 LONGITUDE DISPLACEMENT (HIGH ACC 0.580000000000000E+000 DEGREE
596 TEMPERATURE/DRY-BULB TEMPERATURE 0.208000000000000E+003 K
597 DEW-POINT TEMPERATURE 0.180100000000000E+003 K
598 WIND DIRECTION 0.305000000000000E+003 DEGREE TRUE
599 WIND SPEED 0.910000000000000E+001 M/S
600 LONG TIME PERIOD OR DISPLACEMENT 0.346500000000000E+004 SECOND
601 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
602 PRESSURE 0.405000000000000E+004 PA
603 GEOPOTENTIAL HEIGHT 0.215740000000000E+005 GPM
604 LATITUDE DISPLACEMENT (HIGH ACCU -0.700000000000000E+000 DEGREE
605 LONGITUDE DISPLACEMENT (HIGH ACC 0.590000000000000E+000 DEGREE
606 TEMPERATURE/DRY-BULB TEMPERATURE 0.209800000000000E+003 K
607 DEW-POINT TEMPERATURE 0.180500000000000E+003 K
608 WIND DIRECTION 0.267000000000000E+003 DEGREE TRUE
609 WIND SPEED 0.105000000000000E+002 M/S
610 LONG TIME PERIOD OR DISPLACEMENT 0.349000000000000E+004 SECOND
611 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
612 PRESSURE 0.393000000000000E+004 PA
613 GEOPOTENTIAL HEIGHT 0.217560000000000E+005 GPM
614 LATITUDE DISPLACEMENT (HIGH ACCU -0.700000000000000E+000 DEGREE
615 LONGITUDE DISPLACEMENT (HIGH ACC 0.590000000000000E+000 DEGREE
616 TEMPERATURE/DRY-BULB TEMPERATURE 0.208400000000000E+003 K
617 DEW-POINT TEMPERATURE 0.179900000000000E+003 K
618 WIND DIRECTION 0.253000000000000E+003 DEGREE TRUE
619 WIND SPEED 0.118000000000000E+002 M/S
620 LONG TIME PERIOD OR DISPLACEMENT 0.360000000000000E+004 SECOND
621 EXTENDED VERTICAL SOUNDING SIGNI 0.409600000000000E+005 FLAG TABLE 8042
622 PRESSURE 0.350000000000000E+004 PA
623 GEOPOTENTIAL HEIGHT 0.224600000000000E+005 GPM
624 LATITUDE DISPLACEMENT (HIGH ACCU -0.700000000000000E+000 DEGREE
625 LONGITUDE DISPLACEMENT (HIGH ACC 0.620000000000000E+000 DEGREE
626 TEMPERATURE/DRY-BULB TEMPERATURE 0.204800000000000E+003 K
627 DEW-POINT TEMPERATURE 0.177900000000000E+003 K
628 WIND DIRECTION 0.275000000000000E+003 DEGREE TRUE
629 WIND SPEED 0.192000000000000E+002 M/S
630 LONG TIME PERIOD OR DISPLACEMENT 0.369500000000000E+004 SECOND
631 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
632 PRESSURE 0.318000000000000E+004 PA
633 GEOPOTENTIAL HEIGHT 0.230230000000000E+005 GPM
634 LATITUDE DISPLACEMENT (HIGH ACCU -0.700000000000000E+000 DEGREE
635 LONGITUDE DISPLACEMENT (HIGH ACC 0.640000000000000E+000 DEGREE
636 TEMPERATURE/DRY-BULB TEMPERATURE 0.207300000000000E+003 K
637 DEW-POINT TEMPERATURE 0.179000000000000E+003 K
638 WIND DIRECTION 0.295000000000000E+003 DEGREE TRUE
639 WIND SPEED 0.203000000000000E+002 M/S
640 LONG TIME PERIOD OR DISPLACEMENT 0.375200000000000E+004 SECOND
641 EXTENDED VERTICAL SOUNDING SIGNI 0.655360000000000E+005 FLAG TABLE 8042
642 PRESSURE 0.300000000000000E+004 PA
643 GEOPOTENTIAL HEIGHT 0.233840000000000E+005 GPM
644 LATITUDE DISPLACEMENT (HIGH ACCU -0.710000000000000E+000 DEGREE
645 LONGITUDE DISPLACEMENT (HIGH ACC 0.660000000000000E+000 DEGREE
646 TEMPERATURE/DRY-BULB TEMPERATURE 0.208300000000000E+003 K
647 DEW-POINT TEMPERATURE 0.178800000000000E+003 K
648 WIND DIRECTION 0.291000000000000E+003 DEGREE TRUE
649 WIND SPEED 0.175000000000000E+002 M/S
650 LONG TIME PERIOD OR DISPLACEMENT 0.382000000000000E+004 SECOND
651 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
652 PRESSURE 0.280000000000000E+004 PA
653 GEOPOTENTIAL HEIGHT 0.238130000000000E+005 GPM
654 LATITUDE DISPLACEMENT (HIGH ACCU -0.710000000000000E+000 DEGREE
655 LONGITUDE DISPLACEMENT (HIGH ACC 0.680000000000000E+000 DEGREE
656 TEMPERATURE/DRY-BULB TEMPERATURE 0.209300000000000E+003 K
657 DEW-POINT TEMPERATURE 0.180000000000000E+003 K
658 WIND DIRECTION 0.280000000000000E+003 DEGREE TRUE
659 WIND SPEED 0.248000000000000E+002 M/S
660 LONG TIME PERIOD OR DISPLACEMENT 0.385500000000000E+004 SECOND
661 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
662 PRESSURE 0.271000000000000E+004 PA
663 GEOPOTENTIAL HEIGHT 0.240150000000000E+005 GPM
664 LATITUDE DISPLACEMENT (HIGH ACCU -0.710000000000000E+000 DEGREE
665 LONGITUDE DISPLACEMENT (HIGH ACC 0.690000000000000E+000 DEGREE
666 TEMPERATURE/DRY-BULB TEMPERATURE 0.210400000000000E+003 K
667 DEW-POINT TEMPERATURE 0.180400000000000E+003 K
668 WIND DIRECTION 0.287000000000000E+003 DEGREE TRUE
669 WIND SPEED 0.222000000000000E+002 M/S
670 LONG TIME PERIOD OR DISPLACEMENT 0.390500000000000E+004 SECOND
671 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
672 PRESSURE 0.257000000000000E+004 PA
673 GEOPOTENTIAL HEIGHT 0.243240000000000E+005 GPM
674 LATITUDE DISPLACEMENT (HIGH ACCU -0.720000000000000E+000 DEGREE
675 LONGITUDE DISPLACEMENT (HIGH ACC 0.700000000000000E+000 DEGREE
676 TEMPERATURE/DRY-BULB TEMPERATURE 0.210000000000000E+003 K
677 DEW-POINT TEMPERATURE 0.180000000000000E+003 K
678 WIND DIRECTION 0.297000000000000E+003 DEGREE TRUE
679 WIND SPEED 0.188000000000000E+002 M/S
680 LONG TIME PERIOD OR DISPLACEMENT 0.395500000000000E+004 SECOND
681 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
682 PRESSURE 0.243000000000000E+004 PA
683 GEOPOTENTIAL HEIGHT 0.246690000000000E+005 GPM
684 LATITUDE DISPLACEMENT (HIGH ACCU -0.720000000000000E+000 DEGREE
685 LONGITUDE DISPLACEMENT (HIGH ACC 0.710000000000000E+000 DEGREE

```

```
686 TEMPERATURE/DRY-BULB TEMPERATURE 0.208600000000000E+003 K
687 DEW-POINT TEMPERATURE 0.179500000000000E+003 K
688 WIND DIRECTION 0.286000000000000E+003 DEGREE TRUE
689 WIND SPEED 0.203000000000000E+002 M/S
690 LONG TIME PERIOD OR DISPLACEMENT 0.406500000000000E+004 SECOND
691 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
692 PRESSURE 0.216000000000000E+004 PA
693 GEOPOTENTIAL HEIGHT 0.254140000000000E+005 GPM
694 LATITUDE DISPLACEMENT (HIGH ACCU -0.720000000000000E+000 DEGREE
695 LONGITUDE DISPLACEMENT (HIGH ACC 0.740000000000000E+000 DEGREE
696 TEMPERATURE/DRY-BULB TEMPERATURE 0.210400000000000E+003 K
697 DEW-POINT TEMPERATURE 0.180300000000000E+003 K
698 WIND DIRECTION 0.266000000000000E+003 DEGREE TRUE
699 WIND SPEED 0.160000000000000E+002 M/S
700 LONG TIME PERIOD OR DISPLACEMENT 0.410000000000000E+004 SECOND
701 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
702 PRESSURE 0.207000000000000E+004 PA
703 GEOPOTENTIAL HEIGHT 0.256480000000000E+005 GPM
704 LATITUDE DISPLACEMENT (HIGH ACCU -0.720000000000000E+000 DEGREE
705 LONGITUDE DISPLACEMENT (HIGH ACC 0.750000000000000E+000 DEGREE
706 TEMPERATURE/DRY-BULB TEMPERATURE 0.211000000000000E+003 K
707 DEW-POINT TEMPERATURE 0.180800000000000E+003 K
708 WIND DIRECTION 0.254000000000000E+003 DEGREE TRUE
709 WIND SPEED 0.164000000000000E+002 M/S
710 LONG TIME PERIOD OR DISPLACEMENT 0.413500000000000E+004 SECOND
711 EXTENDED VERTICAL SOUNDING SIGNI 0.655360000000000E+005 FLAG TABLE 8042
712 PRESSURE 0.200000000000000E+004 PA
713 GEOPOTENTIAL HEIGHT 0.258730000000000E+005 GPM
714 LATITUDE DISPLACEMENT (HIGH ACCU -0.720000000000000E+000 DEGREE
715 LONGITUDE DISPLACEMENT (HIGH ACC 0.760000000000000E+000 DEGREE
716 TEMPERATURE/DRY-BULB TEMPERATURE 0.209600000000000E+003 K
717 DEW-POINT TEMPERATURE 0.180300000000000E+003 K
718 WIND DIRECTION 0.242000000000000E+003 DEGREE TRUE
719 WIND SPEED 0.174000000000000E+002 M/S
720 LONG TIME PERIOD OR DISPLACEMENT 0.416000000000000E+004 SECOND
721 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
722 PRESSURE 0.195000000000000E+004 PA
723 GEOPOTENTIAL HEIGHT 0.260290000000000E+005 GPM
724 LATITUDE DISPLACEMENT (HIGH ACCU -0.720000000000000E+000 DEGREE
725 LONGITUDE DISPLACEMENT (HIGH ACC 0.760000000000000E+000 DEGREE
726 TEMPERATURE/DRY-BULB TEMPERATURE 0.208700000000000E+003 K
727 DEW-POINT TEMPERATURE 0.179800000000000E+003 K
728 WIND DIRECTION 0.236000000000000E+003 DEGREE TRUE
729 WIND SPEED 0.180000000000000E+002 M/S
730 LONG TIME PERIOD OR DISPLACEMENT 0.424000000000000E+004 SECOND
731 EXTENDED VERTICAL SOUNDING SIGNI 0.409600000000000E+005 FLAG TABLE 8042
732 PRESSURE 0.179000000000000E+004 PA
733 GEOPOTENTIAL HEIGHT 0.265340000000000E+005 GPM
734 LATITUDE DISPLACEMENT (HIGH ACCU -0.710000000000000E+000 DEGREE
735 LONGITUDE DISPLACEMENT (HIGH ACC 0.780000000000000E+000 DEGREE
736 TEMPERATURE/DRY-BULB TEMPERATURE 0.207000000000000E+003 K
737 DEW-POINT TEMPERATURE 0.179000000000000E+003 K
738 WIND DIRECTION 0.245000000000000E+003 DEGREE TRUE
739 WIND SPEED 0.210000000000000E+002 M/S
740 LONG TIME PERIOD OR DISPLACEMENT 0.437500000000000E+004 SECOND
741 EXTENDED VERTICAL SOUNDING SIGNI 0.204800000000000E+004 FLAG TABLE 8042
742 PRESSURE 0.158000000000000E+004 PA
743 GEOPOTENTIAL HEIGHT 0.273120000000000E+005 GPM
744 LATITUDE DISPLACEMENT (HIGH ACCU -0.700000000000000E+000 DEGREE
745 LONGITUDE DISPLACEMENT (HIGH ACC 0.820000000000000E+000 DEGREE
746 TEMPERATURE/DRY-BULB TEMPERATURE 0.209700000000000E+003 K
747 DEW-POINT TEMPERATURE 0.180600000000000E+003 K
748 WIND DIRECTION 0.265000000000000E+003 DEGREE TRUE
749 WIND SPEED 0.234000000000000E+002 M/S
750 LONG TIME PERIOD OR DISPLACEMENT 0.458000000000000E+004 SECOND
751 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
752 PRESSURE 0.126000000000000E+004 PA
753 GEOPOTENTIAL HEIGHT 0.287220000000000E+005 GPM
754 LATITUDE DISPLACEMENT (HIGH ACCU -0.690000000000000E+000 DEGREE
755 LONGITUDE DISPLACEMENT (HIGH ACC 0.900000000000000E+000 DEGREE
756 TEMPERATURE/DRY-BULB TEMPERATURE 0.212200000000000E+003 K
757 DEW-POINT TEMPERATURE 0.182200000000000E+003 K
758 WIND DIRECTION 0.264000000000000E+003 DEGREE TRUE
759 WIND SPEED 0.344000000000000E+002 M/S
760 LONG TIME PERIOD OR DISPLACEMENT 0.464500000000000E+004 SECOND
761 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
762 PRESSURE 0.117000000000000E+004 PA
763 GEOPOTENTIAL HEIGHT 0.291400000000000E+005 GPM
764 LATITUDE DISPLACEMENT (HIGH ACCU -0.690000000000000E+000 DEGREE
765 LONGITUDE DISPLACEMENT (HIGH ACC 0.930000000000000E+000 DEGREE
766 TEMPERATURE/DRY-BULB TEMPERATURE 0.210900000000000E+003 K
767 DEW-POINT TEMPERATURE 0.182200000000000E+003 K
768 WIND DIRECTION 0.268000000000000E+003 DEGREE TRUE
769 WIND SPEED 0.378000000000000E+002 M/S
770 LONG TIME PERIOD OR DISPLACEMENT 0.470500000000000E+004 SECOND
771 EXTENDED VERTICAL SOUNDING SIGNI 0.819200000000000E+004 FLAG TABLE 8042
772 PRESSURE 0.109000000000000E+004 PA
773 GEOPOTENTIAL HEIGHT 0.295880000000000E+005 GPM
774 LATITUDE DISPLACEMENT (HIGH ACCU -0.690000000000000E+000 DEGREE
775 LONGITUDE DISPLACEMENT (HIGH ACC 0.960000000000000E+000 DEGREE
776 TEMPERATURE/DRY-BULB TEMPERATURE 0.216500000000000E+003 K
777 DEW-POINT TEMPERATURE 0.184700000000000E+003 K
778 WIND DIRECTION 0.263000000000000E+003 DEGREE TRUE
```

```

779 WIND SPEED 0.3920000000000000E+002 M/S
780 LONG TIME PERIOD OR DISPLACEMENT 0.4783000000000000E+004 SECOND
781 EXTENDED VERTICAL SOUNDING SIGNI 0.6553600000000000E+005 FLAG TABLE 8042
782 PRESSURE 0.1000000000000000E+004 PA
783 GEOPOTENTIAL HEIGHT 0.3015400000000000E+005 GPM
784 LATITUDE DISPLACEMENT (HIGH ACCU -0.6900000000000000E+000 DEGREE
785 LONGITUDE DISPLACEMENT (HIGH ACC 0.1010000000000000E+001 DEGREE
786 TEMPERATURE/DRY-BULB TEMPERATURE 0.2155000000000000E+003 K
787 DEW-POINT TEMPERATURE 0.1840000000000000E+003 K
788 WIND DIRECTION 0.2560000000000000E+003 DEGREE TRUE
789 WIND SPEED 0.4300000000000000E+002 M/S
790 LONG TIME PERIOD OR DISPLACEMENT 0.4825000000000000E+004 SECOND
791 EXTENDED VERTICAL SOUNDING SIGNI 0.1843200000000000E+005 FLAG TABLE 8042
792 PRESSURE 0.9600000000000000E+003 PA
793 GEOPOTENTIAL HEIGHT 0.3042600000000000E+005 GPM
794 LATITUDE DISPLACEMENT (HIGH ACCU -0.6800000000000000E+000 DEGREE
795 LONGITUDE DISPLACEMENT (HIGH ACC 0.1030000000000000E+001 DEGREE
796 TEMPERATURE/DRY-BULB TEMPERATURE 0.2164000000000000E+003 K
797 DEW-POINT TEMPERATURE 0.1856000000000000E+003 K
798 WIND DIRECTION 0.2610000000000000E+003 DEGREE TRUE
799 WIND SPEED 0.4370000000000000E+002 M/S
800 LONG TIME PERIOD OR DISPLACEMENT 0.4960000000000000E+004 SECOND
801 EXTENDED VERTICAL SOUNDING SIGNI 0.2112000000000000E+004 FLAG TABLE 8042
802 PRESSURE 0.8100000000000000E+003 PA
803 GEOPOTENTIAL HEIGHT 0.3151000000000000E+005 GPM
804 LATITUDE DISPLACEMENT (HIGH ACCU -0.6800000000000000E+000 DEGREE
805 LONGITUDE DISPLACEMENT (HIGH ACC 0.1110000000000000E+001 DEGREE
806 TEMPERATURE/DRY-BULB TEMPERATURE 0.2164000000000000E+003 K
807 DEW-POINT TEMPERATURE 0.1862000000000000E+003 K
808 WIND DIRECTION 0.2560000000000000E+003 DEGREE TRUE
809 WIND SPEED 0.3920000000000000E+002 M/S
810 LONG TIME PERIOD OR DISPLACEMENT 0.4980000000000000E+004 SECOND
811 EXTENDED VERTICAL SOUNDING SIGNI 0.1228800000000000E+005 FLAG TABLE 8042
812 PRESSURE 0.7800000000000000E+003 PA
813 GEOPOTENTIAL HEIGHT 0.3170800000000000E+005 GPM
814 LATITUDE DISPLACEMENT (HIGH ACCU MISSING DEGREE
815 LONGITUDE DISPLACEMENT (HIGH ACC MISSING DEGREE
816 TEMPERATURE/DRY-BULB TEMPERATURE 0.2168000000000000E+003 K
817 DEW-POINT TEMPERATURE 0.1863000000000000E+003 K
818 WIND DIRECTION MISSING DEGREE TRUE
819 WIND SPEED MISSING M/S
820 DELAYED DESCRIPTOR REPLICATION F 0.3000000000000000E+001 NUMERIC
821 LONG TIME PERIOD OR DISPLACEMENT 0.1855000000000000E+004 SECOND
822 EXTENDED VERTICAL SOUNDING SIGNI 0.1843200000000000E+005 FLAG TABLE 8042
823 PRESSURE 0.1926000000000000E+005 PA
824 LATITUDE DISPLACEMENT (HIGH ACCU -0.4400000000000000E+000 DEGREE
825 LONGITUDE DISPLACEMENT (HIGH ACC 0.3100000000000000E+000 DEGREE
826 ABSOLUTE WIND SHEAR IN 1 KM LAYE 0.1110000000000000E+002 M/S
827 ABSOLUTE WIND SHEAR IN 1 KM LAYE 0.1430000000000000E+002 M/S
828 LONG TIME PERIOD OR DISPLACEMENT 0.2280000000000000E+004 SECOND
829 EXTENDED VERTICAL SOUNDING SIGNI 0.1843200000000000E+005 FLAG TABLE 8042
830 PRESSURE 0.1275000000000000E+005 PA
831 LATITUDE DISPLACEMENT (HIGH ACCU -0.5400000000000000E+000 DEGREE
832 LONGITUDE DISPLACEMENT (HIGH ACC 0.4000000000000000E+000 DEGREE
833 ABSOLUTE WIND SHEAR IN 1 KM LAYE 0.1100000000000000E+002 M/S
834 ABSOLUTE WIND SHEAR IN 1 KM LAYE 0.1760000000000000E+002 M/S
835 LONG TIME PERIOD OR DISPLACEMENT 0.4825000000000000E+004 SECOND
836 EXTENDED VERTICAL SOUNDING SIGNI 0.1843200000000000E+005 FLAG TABLE 8042
837 PRESSURE 0.9600000000000000E+003 PA
838 LATITUDE DISPLACEMENT (HIGH ACCU -0.6800000000000000E+000 DEGREE
839 LONGITUDE DISPLACEMENT (HIGH ACC 0.1030000000000000E+001 DEGREE
840 ABSOLUTE WIND SHEAR IN 1 KM LAYE 0.5800000000000000E+001 M/S
841 ABSOLUTE WIND SHEAR IN 1 KM LAYE 0.5800000000000000E+001 M/S

```