

Tips

ACCESSORIES

P-176



P-176.50/60 Flexible Tip

PZT ceramic stacks cannot withstand bending forces. The P-176.50/60 flexible tips are available for applications where it is not possible to avoid those forces. They can be screwed into the standard top pieces of the P-842/3 and P-844/5 translators.

P-176.Bxx Ball Tips

To avoid bending moments and shear forces on the PZT ceramics, a ball tip is available that can be screwed into the top piece of the individual translators.

P-176.Fxx Flat tips

Flat tips are available and can be screwed into the top piece of the individual translators.

Order Information

P-176.50

Flexible Tips for P-842 / P-843

P-176.60

Flexible Tips for P-844 / P-845

P-176.B12

Ball Tip for P-212

P-176.B16

Ball Tip for P-216

P-176.B25

Ball Tip for P-225 and P-235

P-176.F12

Flat tip for P-212

P-176.F16

Flat tip for P-216

P-176.F25

Flat tip for P-225

P-176.F35

Flat tip for P-235

Related Products

[P-842 Preloaded Piezo Actuators](#)

[P-843 Preloaded Piezo Actuators](#)

[P-844 Preloaded Piezo Actuators](#)

[P-845 Preloaded Piezo Actuators](#)

[P-212 PICA Power Piezo Actuator](#)

[P-216 PICA Power Piezo Actuator](#)

[P-225 PICA Power Piezo Actuators](#)

[P-235 PICA Power Piezo Actuators](#)

Drawings / Images

P-176.60 Flexible Tip.
Dimensions in mm.

