

USER MENU

Model No.: ULP16-MD(Dual speaker)

1. Power ON/OFF

Power ON: Press and hold the power button till to GREEN LED blinking or light up.

Power OFF: Press and hold the power button till to the RED LED flashing.

2. Pairing(Register mode)

a). Press and hold the power button to turn headset power ON, the power LED should blinking in Green color.

b). Enter the pairing mode: Press the volume down button ▼ at 3 times continually, then press and hold the volume up ▲ till to the RED and Green LED blinking at alternately.

c). Main headset enter the pairing mode first then also the Remote to pairing mode.

d). The Green LED of Remote headset will several blink quickly then turn off after paired, press the power button to quit the pairing mode, keep the Main headset on the pairing mode then can pair with more Remote or press the power button to quit the pairing mode.

e). Repeat the above step “d” for more Remote headset paired with the same Main headset, or press the power button to finish the pairing(register).

f). Press SW of Main headset can make total 15 Remote headset register in 2 separated group.

The Main headset can accept maximum 15 remotes register in full duplex, the power LED will be flashing in ORANGE color when register remote reach 15., press power button to quit the pairing mode)

3. Talking and listening

a). The main headset and remote headset will start to search each other after power ON, the GREEN LED flash 1 time each 3 seconds. The headset will be link together automatically when the pairing ID confirmed by main headset and LED turn ON in GREEN color.

b). Press the volume up ▲ and down ▼ button to adjust headset speaker sound volume.

4. CONFERENCE on MAIN

Press the switch located lower side of ear cup to make 15 headsets to separate 2 group or all in CONFERENCE if the remote headset has registered in 2 group.

5. Mic Muted

The headset Microphone stopped automatically when the Mic boom swivel up.

FCC Warning:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

IC Warning:

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

L'exploitation est autorisée aux deux conditions suivantes:

(1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en

The device has been tested and comply with FCC/ISED SAR limits.

L'Unité a été testée et répond aux limites FCC/ISED SAR.



To prevent possible hearing damage, do not listen at high volume levels for long periods