

Item # 851117, A2X-1965 Plenum Rated Pump



A2X-1965 Plenum Rated Pump

- UL 2043 Plenum Rated
- Dual Voltage Commercial Grade Condensate Pump
- Heavy Duty Cast Aluminum Reservoir
- Dual Voltage Thermally Protected Motor
- Stainless Steel Motor Shaft
- Replaces KESCO 1965

PLENUM RATED*

*Hartell's Model A2-X-1965 DV has been tested to, and yielded results that fell within the acceptance criteria of UL Standard 2043, Third Edition, "Fire Test for Heat and Visible Smoke Release for Discrete Products and Their Accessories Installed in Air-Handling Spaces."

SPECIFICATIONS

Model	A2-X-1965
Voltage	115 V 230 V
Inlet (ID)	1 3/8 inches
Outlet Size	3/8 inches
Outlet Connection Type	FNPT
Motor Power at 3000 rpm	1/10 hp
Motor Speed	3000 rpm
Cord and Plug	No cord & plug, wire leads only ft
Auxiliary Switch	Yes
20' Tubing	No
Unit Dimensions (W x D x H)	6" x 9" x 10"

Width	6 inches
Depth	9 inches
Height	10 inches
Flow Rate at Lift of 6'	185 gal/h
Flow Rate at Lift of 12'	139 gal/h
Flow Rate at Lift of 18'	79 gal/h
Flow Rate at Lift of 20'	51 gal/h
Weight	14 lb
Reservoir	1 gal
Shut off	22 ft
Head Size	22 ft
Max. Temperature	150 °F
Mast. Ctn.	4 pcs.