

ACCESSORIES

Switch/Sensor Mounting Options:



Grey Bracket Assembly



Liquid Smart® Floor Mount



Quick Mount



Grey Bracket



Hose Clamp

Part #	Description:
• 95-34	Grey Bracket Assembly <i>*For use with all switches/sensors, includes hose clamp & hardware</i>
• 95-05	Liquid Smart® Floor Mount <i>*For use with Liquid Smart® Sensor, monitoring at floor level</i>
• 95-03	Quick Mount - White PVC Snap On <i>*For use with all switches/sensors on 1 1/2" pipe</i>
• 95-02	Grey Bracket - PVC <i>*For use with all switches/sensors</i>
• 95-01	Hose Clamp - Stainless Steel <i>*For use with all switches/sensors/floats</i>

Float Mounting Options:



Loop Type Float Mount



Alligator Type Float Mount



Cable Weight

Part #	Description:
• 95-35	Loop Type Stainless Steel Pipe Clamp <i>*For use with all standard floats to control direction of swing</i>
• 95-36	Alligator Type Stainless Steel Pipe Clamp <i>*For use with all standard floats</i>
• 95-37	Cable Weight <i>*For use with all standard floats</i> <i>Wire Accommodated: 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3</i>


Wire Grips/Terminal Adapters/Enclosure Mounting:



Water Tight Wire Grip



PVC Hub



Pipe/Pole Mounting Hardware

Part #	Description:
• 95-38	Wire Grip Cable Connector - Small <i>Cable Range: .17" - .45"</i>
• 95-39	Wire Grip Cable Connector - Large <i>Cable Range: .435" - .705"</i>
• 95-40	PVC Hub Terminal Adapter <i>2" to connect to PVC conduit</i>
• 95-41	Pipe/Pole Mounting Hardware <i>*For mounting enclosures to a vertical pipe or pole</i>

www.seewaterinc.com
 951.487.8073 • 888.733.9283 • info@seewaterinc.com
 22220 Opportunity Way, Suite 104 • Riverside, CA 92518



"Your trusted source for quality control panels"

ACCESSORIES

Solenoid Valves:



Solenoid Valve, 120VAC

Part #	Description:
• 95-16	Solenoid Valve - Normally Closed *120VAC, 60Hz. 1.5"
• 95-17	Solenoid Valve - Normally Open *120VAC, 60Hz. 1.5"
• 95-18	Solenoid Valve - Normally Closed *120VAC, 60Hz. 2"
• 95-19	Solenoid Valve - Normally Open *120VAC, 60Hz. 2"

Solar Components:



Solar Panel



Solar Panel Mounting Kit

Part #	Description:
• 95-42	Solar Panel *10 Watt 12V Solar Panel w/ 15' Cable
• 95-41	Solar Panel Mounting Kit *Vertical Pole Mount, Alum, 14", fixed tilt, includes 1-ubolt & 2-hrdw. sets

SEESLT Pressure Transducer Accessories:



Dessicant Filter



316 SS Cable Hanger

Part #	Description:
• 95-32	Dessicant Filter *For vent tube. Removes humidity for protection of the sensor. Changes color to show saturation.
• 95-33	316 SS Cable Hanger *NPT for attaching chain for easy lift from application.

ACCESSORIES

Remote Secondary Alarms:



RSA-50



RSA-100

Part #	Description:
• RSA-50	Remote Secondary Alarm <i>Works in conjunction with any See Water wastewater control panel</i>
• RSA-100	Remote Secondary Alarm <i>Works in conjunction with any See Water Oil Smart® control panel</i>

Auto Dialer:



SEE-AVD

Part #	Description:
• SEE-AVD	Auto Dialer <i>Works in conjunction with a standard phone line connection and provides a 16 second pre-recorded message notifying of alarm. The dialer connects to any device with a normally open or normally closed contact. Includes 12VDC plug in power supply.</i>

Pedestal Assembly Post:



Pedestal Assembly Post

Part #	Description:
• 95-47	Pedestal Assembly Post <i>Works in conjunction with enclosures up to 18" x 16" x 10"</i>

www.seewaterinc.com
 951.487.8073 • 888.733.9283 • info@seewaterinc.com
 22220 Opportunity Way, Suite 104 • Riverside, CA 92518



ACCESSORIES

Float Switches:



Normally Open
Narrow Angle Float



Normally Open
Low Voltage
Narrow Angle Float



Normally Open
Wide Angle
Piggyback Float



Normally Open
Wide Angle
Dual Float

Control Switches:

Normally Open Narrow Angle Float:

- 95-08
Rated for 5 amps @ 125V or 250V, 20' Cord
- 95-25
Rated for 5 amps @ 125V or 250V, 30' Cord
- 95-26
Rated for 5 amps @ 125V or 250V, 50' Cord
- 95-27
Rated for 5 amps @ 125V or 250V, 100' Cord

Normally Open Low Voltage Narrow Angle Float:

- 95-43
Low voltage rated for 0.160-100mA @ 5V-125V, 20' Cord
- 95-44
Low voltage rated for 0.160-100mA @ 5V-125V, 30' Cord
- 95-45
Low voltage rated for 0.160-100mA @ 5V-125V, 50' Cord
- 95-46
Low voltage rated for 0.160-100mA @ 5V-125V, 100' Cord

Normally Closed Low Voltage Narrow Angle Float:

- 95-48
Low voltage normally closed rated for 0.160-100mA @ 5V-125V

Normally Open Wide Angle Float:

- 95-09
Rated for 5 amps @ 125V or 250V

Pump Switches:

Normally Open Wide Angle Piggyback Float:

- 95-28
Rated for 13 amps @ 120V, 20' cord and piggyback plug

Normally Open Wide Angle Dual Float:

- 95-24
Rated for 13 amps @ 120V or 240V, 20' cord
- 95-55
Rated for 13 amps @ 120V, 20' cord and piggyback plug

Specifications:

- UL listed for water and sewage
- Floats are constructed of durable PVC/polypropylene
- Simple installation
- Includes mounting hardware
- Designed for effluent, sewage and dewatering applications