



16 Channel D1 DVR

QT526

Features:

- Weatherproof cameras for indoor or outdoor use
- 16 Channel Real-time D1 Resolution DVR
- Remote internet monitoring (up to 10 users at the same time)
- Mobile Phone Surveillance
- Compatible with MAC and PC
- Customize up to 8 additional cameras when you need
- Zoom in on live or playback footage with 2X digital zoom!
- Receive instant email alerts and snapshot images when motion is detected
- Send email alerts up to 3 different email addresses
- Backup and retain important footage on a PC, Flash Drive or USB Hard Drive
- Video is captured in real-time, broadcast-quality D1 on each channel (704x480 pixel resolution at a rate of 30 frames per second per camera), which results in smooth, continuous video motion and a larger D1 video image for improved recognition of people
- Manage and monitor multiple QT-series DVRs with Central Management Software (CMS).

What's Included:

- (1) 16 Channel D1 real-time DVR
- (1) Power supply for DVR 12V /5A
- RJ-45 Ethernet network cable
- BNC to RCA Video cable
- Remote control
- USB Mouse
- CD with manuals and software
- Quick Start Guide

Remote Monitoring Compatibility:



symbian

System Compatibility:



Windows XP, Vista, 7



Mac OS X 10.6 & 10.7

Specification:

DVR

| | |
|-----------------------------|--|
| DVR Model | QT526 |
| Video Compression | Advanced H.264 |
| Max Hard Drive Storage | Supports 2 SATA HDD up to 4 TB |
| Backup Via | PC, Flash Drive, USB Hard Drive |
| Power | DC 12V / 5A (Adapter Included) |
| Operating Temperature | 50°F-104°F / 10°C-40°C |
| D1 Recording Option | 480 FPS (30 FPS Per Channel) |
| D1 Playback Resolution | 704x480 |
| Recording Mode | Motion Detection, Time Schedule, Alarm Trigger, Manual |
| USB Interface | USB Mouse, USB Backup |
| Video Inputs/Outputs | 16 BNC Input(s)/1 VGA Output(s)/1 BNC Output(s) |
| Audio Inputs/Outputs | 4 RCA Input(s) /1 RCA Output(s) |
| Alarm Sensor Inputs/Outputs | 16 Input(s)/1 Output(s) |
| Network Interface | RJ-45 for Router Connection Enabling Remote Monitoring |
| DVR Dimensions/Weight | 17"x 15.5"x 2.25" / 8.4lbs |

Cameras

| | |
|--------------------------|---------------------------------------|
| Camera Model | QM6006B |
| Weatherproof | Weatherproof Indoor & Outdoor |
| Horizontal Resolution | 600 TV Lines |
| Image Sensor | Enhanced Infrared Cut Filter, , Color |
| Infrared LEDs | 42 |
| Night Vision Range | Up to 120 ft |
| Lens | 5mm Lens 50° to 55° Field of View |
| Mount | 3-Axis Stands |
| Camera Cables | 60 Feet of Cable with Each Camera |
| Camera Dimensions/Weight | 5.7"x 3.5"x 2.6" / 0.5lb |

Viewing

| | |
|-----------------------------|---|
| Live Display Resolution | 704x480 |
| Display Modes | Single Camera, Split Screen Multi-Camera, Auto-Sequence |
| Video Search | Time, Motion Detection, Alarm Trigger, Manual |
| Computer System Support | Windows XP, Vista, 7, Mac OS X 10.6 & 10.7 |
| Compatible Browsers | Google Chrome, Internet Explorer, Mozilla Firefox, Safari |
| Mobile Phone Support | Android, BlackBerry 5, 6 & 7, iPhone/iPad, Windows Mobile Pro 5, 6 & Phone 7, Symbian |
| Simultaneous Remote Viewers | Up to 10 Users |
| Stream | Dual Stream |