

# QT554

<b>DVR Technology</b>	Analog
<b>Channels</b>	4
<b>Recording Resolution</b>	960H / D1 / CIF
<b>Live Viewing Resolution</b>	1080P/720P/1280x1024/1024x768
<b>Live Display FPS</b>	30 FPS per Channel
<b>Hard Drive</b>	Supports 1 HDD up to 4TB
<b>Remote Monitoring</b>	10 Simultaneous Users
<b>Compatibility</b>	Mac and PC
<b>Connects With</b>	Local Cameras
<b>Monitor Connections</b>	HDMI, VGA, BNC



## DVR

Video Compression	H.264
Live Display Resolution	1080p, 720p, 720x480
Live Display FPS	30 FPS
Display Modes	1, 4, Auto Sequence
Languages	English, Chinese (Simplified & Traditional), Czech, French, Portuguese, Spanish, Turkish, Bulgarian, Greek, Italian, German, Russian, Polish, Japanese, Indonesian, Thai, Hungarian, Lithuanian, Vietnamese, Dutch, Swedish, Norwegian, Persian, Arabic, Romanian

## RECORDING RESOLUTION OPTIONS

960H Resolution	960 x 480
D1 Resolution	704 x 408
CIF Resolution	352 x 240

## RECORDING

Recording Modes	Manual, Time Schedule, Motion Detection, Alarm
Backup Methods	PC, Flash, USB Hard Drive

## PLAYBACK ON DVR

Playback Speed	960H at 30 FPS per channel	120 FPS Total
	D1 at 30 FPS per channel	120 FPS Total
	CIF at 30 FPS per channel	120 FPS Total
Number Channels	8 Simultaneous	

## REMOTE MONITORING

Scan 'N View	Yes
Dual Stream	CIF
Simultaneous Users	10

## COMPATIBILITY

Software Support	QT View
Mobile Support	iPhone, iPad, Android
Computer Support	WinXP, Vista, Win7/8, Mac OS 10.7/10.8/10.9/10.10

## VIDEO, AUDIO & ALARM PORTS

Video in	4 BNC
Video Out	HDMI, VGA, BNC
Alarm In	None
Alarm Out	None
Audio In	1 RCA
Audio Out	1 RCA

## COMMUNICATION PORTS

Network	RJ45 10/100 Mbps
USB	2 USB 2.0
eSATA	None

## ACCESSORIES

Control	USB Mouse, Remote Control
Connectors / Cables	HDMI Cable, BNC/RCA Adapter, Ethernet Cable
Mounting Hardware	Screws for Hard Drives
Other	Quick Start Guide

(QT554 cont'd...)

**HARD DRIVES**

Maximum Size	4TB
Number Supported	1

**PTZ**

PTZ Support	None
Supported Protocols	Does not apply

**POWER**

Power Supply	12v 2a
Power Consumption	3w (w/o HD)

**PHYSICAL**

Weight	1.2 lbs
Dimensions	8"W X 8.25"D X 2"H
Operating Temperature	32° - 122°F

