

QTH44

DVR Technology	BNC HD
Channels	4
Recording Resolution	1080p / 720p / 960H
Live Viewing Resolution	1080p / 720p
Live Display FPS	30 FPS per Channel (1080p) 30 FPS per Channel (720p/960H)
Hard Drive	Supports 1 HDD up to 6TB
Remote Monitoring	10 Simultaneous Users
Compatibility	Mac and PC
Connects With	Local Cameras
Monitor Connections	HDMI, VGA



Supports QTH BNC HD Cameras & Analog Cameras

DVR

Video Compression	H.264
Live Display Resolution	1080p, 720p, 1280x1024, 1024x768, 800x600
Live Display FPS	30 FPS
Display Modes	1, 4, 8, Auto Sequence
Languages	English, Chinese (Simplified & Traditional), Czech, French, Portuguese, Spanish, Turkish, Bulgarian, Greek, Italian, German, Russian, Polish, Japanese, Indonesian, Thai, Hungarian, Lithuanian, Vietnamese, Dutch, Swedish, Norwegian, Persian, Arabic, Romanian

RECORDING RESOLUTION OPTIONS

1080p Resolution	1920 x 1080 pixels
720P Resolution	1280 x 720 pixels
960H Resolution	960 x 480 pixels

RECORDING MODES

Recording Modes	Manual, Time Schedule, Motion Detection, Sensor
Backup Methods	PC, Flash, USB Hard Drive

PLAYBACK ON DVR

Playback Speed	1080p at 12 FPS per channel	48 FPS total
	720P at 30 FPS per channel	120 FPS total
	960H at 30 FPS per channel	120 FPS total
Number Channels	4 Simultaneous Local Playback	

REMOTE MONITORING

Scan 'N View	Yes
Dual Stream	CIF
Simultaneous Users	10

COMPATIBILITY

Software Support	QT View
Mobile Support	iPhone, iPad, Android
Computer Support	WinXP, Vista, Win7/8/10 Mac OS 10.7/10.8/10.9/10.10

VIDEO, AUDIO & ALARM PORTS

Video in	4 BNC
Video Out	HDMI, VGA,
Alarm In	4
Alarm Out	1
Audio In	4 RCA
Audio Out	1 RCA

COMMUNICATION PORTS

Network	RJ45 10/100 Mbps
USB	2 USB 2.0
eSATA	None

ACCESSORIES

Control	USB Mouse, Remote Control
Connectors / Cables	HDMI Cable,
Mounting Hardware	Screws for Hard Drives
Other	Quick Start Guide

(QTH44 cont'd...)

HARD DRIVES

Maximum Size	6TB
Number Supported	1

PTZ

PTZ Support	RS485
Supported Protocols	COC, Null, Pelco D, Pelco D, Lilin, Minking, Neon, Star, VIDO, DSCP, VISCA, Samsung, RM110, HY

POWER

Power Supply	12v 3a
Power Consumption	<5w (w/o HD)

PHYSICAL

Weight	3.3 lbs
Dimensions	11.75"W X 9.75"D X 2"H
Operating Temperature	14° - 130°F

