

A Division of Pride Mobility Products* Corp.

Quantume 1420

Quantum[®] 1420 shown with Synergy[®] Seating System and PG Remote Plus controller

Versatility and power come together.

The Quantum[®] 1420 accepts a full range of specialty seating and electronics options for a balanced blend of rehab versatility and high performance courtesy of patented mid-wheel drive technology and Active-Trac[®] Suspension.



Specifications

DRIVE WHEELS	16″
CASTERS	Front: 8" solid Rear: 9"
SUSPENSION	Active-Trac [®] and rear caster suspension
MAXIMUM SPEED ¹	Up to 4.5 mph ³
BRAKES	Intelligent Braking (electronic, regenerative disc brakes)
GROUND CLEARANCE ⁴	4.5″
TURNING RADIUS ⁴	25.75″
OVERALL SIZE ⁴	Length: 46″ Width: 27.25″
SEATING	Synergy [®] Seat (standard) Adjustable Width: 10"-24" Adjustable Depth: 10"-24" TRU-Balance [®] 2 Power Positioning System Adjustable Width: 14"-24" Adjustable Depth: 14"-24" High-back seat; Power elevating seat; Manual recliner; solid seat pan (option)
DRIVE TRAIN	Two-motor, mid-wheel drive; high-torque motor package (standard)
BATTERIES	Two 12 volt, deep cycle, Group 24
RANGE PER CHARGE ¹	Up to 20 miles ¹
BATTERY CHARGER	8A, Lester off-board (standard)
ELECTRONICS	70A, PG Remote Plus controller
WEIGHT CAPACITY	500 lbs. maximum (user weight)
BASE WEIGHT	141.5 lbs.
BATTERY WEIGHT	53.5 lbs. (each)
WARRANTY	Lifetime limited warranty on frame 2-year warranty on electronics 18-month warranty on drive motor

Shroud Colors





Blue



Champagne Sunburst Orange

(US) 866-800-2002 (Canada) 888-570-1113 www.quantumrehab.com



A Division of Pride Mobility Products* Corp.

Features

- Patented two-motor, mid-wheel drive design provides superb power and acceleration
- Active-Trac[®] and rear caster suspension for outstanding outdoor performance
- Adjustable front anti-tips to meet your preferences and terrain challenges
- 8A, Lester off-board charger
- Battery-conserving sleep mode available with Remote Plus controller

Options

- Solid tires
- Cup holder
- Weather cover
- Swing-away joystick
- · Swing-away footrests
- Elevating leg rests
- Holders for oxygen/crutch/cane/walker
- Angle-adjustable footplates
- 70° and 80° HD drop-in footrests
- 5A, on-board / 8A, off-board charger

Code Coverage

Q1420 2SPHD - SS	(Code: K0837)*
Q1420 2SPVHD - SS	(Code: K0839)**
Q1420 3SPHD - SS	(Code: K0858)*
Q1420 3SPHD - C	(Code: K0859)*
Q1420 3SPVHD - SS	(Code: K0860)**
Q1420 3MPHD - SS	(Code: K0862)*
Q1420 3MPVHD - SS	(Code: K0863)**
Q1420 4HD - SS	(Code: K0870)*
Q1420 4SPHD - SS	(Code: K0879)*
Q1420 4MPHD - SS	(Code: K0886)*

- * 450 lbs. weight capacity
- ** 500 lbs. weight capacity

FOOTNOTES:

- **1)** Range and speed vary with user weight, terrain type, battery charge, battery condition and tire pressure.
- **2)** 400 lbs. weight capacity with TRU-Balance Power Tilt; 300 lbs. weight capacity with TRU-Balance Recline or Tilt & Recline
- **3)** High speed option available up to 6 mph; standard in Group 4 units
- **4)** Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or 3 %.