

Resolution

RE203 Wireless Panic Transmitter

User and Installation Instructions

Introduction

The RE203 Wireless Panic Transmitter is a wireless 1-button transmitter for security system use. Typical use of this device is for sending a panic alarm to the system. The transmitter is shown in Figure 1.



Figure 1: RE203

Successful activation of the transmitter is indicated by a short, bright LED flash.

The Wireless Panic Transmitter uses a small lithium coin cell battery, designed to provide long battery life.

Transmitter Programming

Each RE203 Wireless Panic Transmitter is shipped with a unique serial number pre-programmed into the transmitter. Upon installation, the RE203 must be programmed into the security control panel. The control panel's documentation should be consulted for full instructions.

Specifications

Dimensions: 1.125 x 1.5 x 0.5"

RF transmission frequency: 345.025MHz

Operating Temperature: 10° to 120°F (-12° to 49°C)

Battery Type: CR2032 Lithium Coin Cell

FCC Notice

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference that may be received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the Resolution Engineering, Inc could void the user's authority to operate this equipment.

FCC ID: U5X-RE203

IC Notice

This product meets the applicable Industry Canada technical specifications/Le présent matériel est conforme aux spécifications techniques applicables d'Industrie Canada.

Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

IC: 8310A-RE203
