



SALES FACT SHEET



Classic[®] S E R I E S

Features

- 1 1/2 ton [5.3 kW] through 5 ton [17.6 kW] models are between 42 1/2 to 55 1/2 inches [1080 to 1410 mm] tall and 22 inches [559 mm] deep.
- Versatile 4-way convertible design for upflow, downflow, horizontal left and horizontal right applications.
- Factory-installed high efficiency indoor coil.
- All models meet or exceed 330 to 400 CFM [156 to 189 L/s] per ton at .3 inches [.7 kPa] of external static pressure.
- Enhanced airflow up to .7" external static pressure.
- Sturdy construction with 1.0 inch [.24 kPa] of reinforced foil faced jacket insulation for excellent thermal and sound insulation.
- Field-installed auxiliary electric heater kits provide exact heat for indoor comfort. Kits include circuit breakers which meet UL and cUL requirements for service disconnect.

AIR HANDLERS

RHSA- Standard Efficiency

featuring R-22 Refrigerant

RHSL- Standard Efficiency

featuring Earth-Friendly

R-410A Refrigerant



GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

CompressorFive (5) Years

*Any Other PartFive (5) Years

Condenser Coil leaks caused by factory defectsFive (5) Years

*This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.

<u>R</u>	<u>H</u>	<u>S</u>	<u>A</u>	<u>—</u>	<u>HM</u>	<u>24</u>	<u>17</u>	<u>J</u>	<u>A</u>		
RHEEM	<u>CLASSIFICATION</u>	S = STANDARD MODEL (PSC MOTOR)	<u>REFRIGERANT</u>		A/C OR HP MULTI- POSITION (VERTICAL UPFLOW/ HORIZONTAL LEFT IS THE FACTORY CONFIGURATION)	<u>CAPACITY</u>	<u>CABINET SIZE</u>	<u>VOLTAGE</u>	<u>DESIGN VARIATION</u>		
	H = AIR HANDLER		A = R-22 L = R-410A			18 = 18,000 BTU/HR [5.27 kW] 24 = 24,000 BTU/HR [7.03 kW] 30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR [10.55 kW] 42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR [14.06 kW] 60 = 60,000 BTU/HR [17.58 kW]	17 = 17.5" [431.8 mm] (800-1200 CFM) 21 = 21" [533.4 mm] (1400-1600 CFM) 24 = 24.5" [609.6 mm] (1600-1800 CFM)	A = 115/1/60 D = 480/3/60 J = 208/240/1/60	A = 1ST DESIGN		
								<table border="1"> <tr> <td>Price</td> <td>Starting at: \$</td> </tr> </table>		Price	Starting at: \$
Price	Starting at: \$										

