

INSTRUCTIONS FOR OPERATION

SETTING THE OPERATING CONTROLS

- 1. This unit operates on a 9 volts battery (not included).**
To prevent possible damage if the battery should leak , be sure to remove the battery when the unit is not use .
- 2. Store the controller away from excess heat or humidity .**
- 3. This remote control unit is required with 32 code combinations. To prevent possible interference from or to other remote units such as garage door openers, car alarm or security system . If you find that your fan and light kit go on and off without using your control , simply change the combination code in your transmitter and receiver .**
- 4. Operation buttons on the panel of transmitter .**
 - HIGH key – For fan High speed .**
 - MED key – For fan Medium speed .**
 - LOW key – For fan Low speed .**
 - OFF key – For fan speed off .**
 - LIGHT key – For light brightness and ON/OFF control .**
- 5. Start the fan :**
Press the selected speed button to run the fan at the desired .
- 6. Turn off the fan :**
Press the OFF button .
- 7. Light control :**
Turn the light on or off by only touching the **LIGHT CONTROL** button .
Keep pressing the button in excess of 0.7 second it becomes a dimmer , the light varies cyclically in 0.8 second .
One of the important feature of this control is **AUTO-RESUME** . After power on , it allows the light return to where it was off .

GENERAL INFORMATION :

This **REMOTE** controller is designed to separately control your ceiling fan speed and light brightness . The **Light ON/OFF** button will control the light brightness **ON/OFF** . The red indicator on the transmitter will light when the button is pressed .

INSTRUCTIONS FOR INSTALLATION AND OPERATION OF FAN SPEED CONTROLLER

- A. Setting the code on your new transmitter .**
- 1. Remove battery cover .**
Press firmly below arrow and slide battery cover off .

2. Slide code switches to your choice of UP and DOWN position .
Factory setting is all UP . Do not use this setting .
Use ball point pen or small screwdriver .
Slide firmly up or down .

B. Setting the code on your new Receiver unit .

1. Slide code switches to the same positions as set on your transmitter .
They must be set to same positions to work .
2. Replace battery cover on transmitter .
3. Make sure the code switches are on the left positions .

NOTICE :

The changes or modifications not expressly approved by the party responsible for compliance could void user's authority to operate the equipment .

IMPORTANT NOTE:

To comply with the FCC RF exposure compliance requirements, no change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATIONS IS SUBJECT INTERFERENCE AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFEERENCE THAT MAY CAUSE UNDESRIED OPERATION.