- Ø

- H +

*FRONT

iHome Model: iLW200

WIRELESS

TOUCH CONTROLS

POWERLIGHT PRO

Foldable LED Lamp with Wireless & USB Charging

WIRELESS CHARGING VINCLESS CHAKGING
Place device face up on the charging rest. LED
Status Indicators will show charging status:
Rapid blinking LED: Device is not charging
(reposition device)
Slow blinking LED: Device is charging
Solid LED: Device is fully charged

POWER ON/OFF U

LIGHT COLOR TEMPERATURE M

BRIGHTNESS +/-

be Be sure to hold the lamp base while sting the angle of the light head. tion: Do not try to push the joints beyond their stment range, as this will cause damage.

REAR CONTROL DC JACK (12V/2A) (for power supply)

MAINTENANCE

- Place the unit on a level surface away from sources of direct sunlight or excessive heat.

- Protect your furniture when placing your unit on a natural wood and lacquered finish. A cloth or other protective material should be placed between it and the furniture.

IMPORTANT SAFETY INSTRUCTIONS
Please heed all warnings, read and follow all instructions and keep these instructions handy for future reference.

2. The product is intended for use indoors only, in dry, enclosed rooms. Never in a wate environment or with
3. This product is intended for use indoors only, in dry, enclosed rooms. Never in a wate environment or with
4. Unplug unit and clean only with or you (soll). Stronger cleaning agents, such as Betrazen, thinner or similar
materials can damage the surface of the unit.

3. This product is intended for use indoors only, in dry, enclosed rooms. Never in a wate environment or with
a third product of the unit.

4. Unplug this product should be satisface of the unit.

5. Heat - This product should be satisfaced away from these sources such as relations, heat registers, stoves or
other appliances (including amplifiers) that produce heat.

6. Heat - This product should be satisfaced away from these sources such as relations, heat registers, stoves or
other appliances (including amplifiers) that produce heat.

6. Heat - This product change is planing store or when unused for long periods of time.

9. Demage Requiring Service - This product should be serviced by qualified service personnel where:

9. Demage Requiring Service - This product should be serviced by qualified service personnel where:

9. Demage Requiring Service - This product should be serviced by qualified service personnel where:

1. Unput this became considerable in the product of the enclosure

1. The product is suitable for use in tropical and/or moderate climates.

1. The product is suitable for use in tropical and/or moderate climates.

1. The instructions of the product is used as the disconnect device, it shall remain readily operable.

1. The mains plug of power adaptor is used as the disconnect device, it shall remain readily operable.

1. The mains plug of power adaptor is used as the disconnect device, it shall remain readily operable.

1. The mains plug of power adaptor is used as the disconnec

compliance.

This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body. The supplement should be used a submitty to operate the equipment.

Cold requipment est use unitimed depositions are addistance (CAPAC Sealises pour unemoniment non controlls. L'emittable riferations exempt de lisenance l'exempt de lisen

veloppement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux x conditions silventes: L'appareil ne doit pas produire de brouillage; L'appareil oft accepte trut brouillage andicéléctrique subi, même si le brouillage est susceptible d'en compromettre le discr conditions saventes:

(i) L'appereil doit los produire de brouillage;

(2) L'appereil doit per poullage radiodectrique subi, même si le brouillage est susceptible d'un compromettre le fractionnement.

L'appereil doit accepter tout brouillage radiodectrique subi, même si le brouillage est susceptible d'un compromettre le l'appereil est conforme se visignes di devoition RF ISED, les utilisateurs peuvent obtainé des informations canadiennes l'appereil est conforme si les des conformes.

Cet despinement de les resistales et utilises avec une distance minimise de 20 cm entre le radiateur et votre corps.

Tout chargement ou modification non expressement approuvé par la partie responsable de la conformité peut ennuier l'actionité de l'alclaires et subiser l'equipment.

CAN ICES 3 (8) / NMB-3 (8), CAN ISS-2/8 / CNR-2/8

© 2023 SDI Technologies, Inc. All rights reserved

Printed in China

