Model: iSB04 QSG (English) Size: 153mm x 98mm Date : August 16,2017

Accordian style

iHome control Intelligent Home Solutions Quick Start Guide

FRONT

Wi-Fi DUAL LEAK SENSOR Monitor your home from anywhere with your smartphone

- WiFi network transmitting at 2.4GHz; WPA2 security type
- Apple device running iOS 9.3 or later *or* Android device running KitKat 4.4 or later connected to your preferred WiFi network

NOTE: If you intend to use a mix of devices (iOS AND Android), please set up the Sensor using your iOS device and then *share* to your Android device(s).

Questions? 1.800.288.2792 www.ihome.com

Overview: About Your Dual Leak Sensor Wi-Fi Status Indicators Flashing Green: Sensor is ready to connect to a Wi-Fi Cable Clasp ____ network Solid Green: Sensor is connected to a Wi-Fi network (appears briefly after setup) • Flashing Red: Sensor failed setup, please try setup agair Secondary Leak Access 1111 Main Leak / Buzzer \Action Button

Installing Batteries

Your sensor comes with 2 AA batteries which must be installed before use.



Gently pull the front of the sensor forward using the battery access tab on top of the sensor to release the front of the main unit.



2 Place the batteries in the battery compartment as shown. Make sure polarity (+/-) matches the markings in the



ress the front and back cabinet together.

Wi-Fi Setup

NOTE: We recommend performing setup in the same location you intend to

- 1 Download and open the 🖁 iHome Control app from the App Store or Google Play. Login to or create an iHome account
- 2 Press sensors icon and then the Add Device Button.
- 3 Press and hold the Action Button on your sensor for 5 seconds until green LED is
- 4 Enter the following setup code when prompted in the app.



NOTE: If you see a solid or flashing RED LED, press and hold the Action Button for 5 seconds and then repeat steps 2 and 3

Sensor Placement and Operation

When placing your leak sensors:

- Ensure the leak detection probes are placed face down in a location that may experience water flow early. This may be a low point in a basement, in or near a sump pump, behind a washing machine, near sinks, toilets, hot water heaters, etc.
- The goal is to notify you of unexpected water as soon as possible.
- The secondary detection probe provides an extra point for leak monitoring and is placed in an area near the main probe (for example, main probe under sink, extension probe under toilet). Please use the included cable clasp to ensure that the detection probe remains face down. Remove the backing from the double-stick tape and press down on a clean, smooth surface.
- Your sensor is equipped with a loud buzzer that will sound any time liquid is detected. You may press the action button on your sensor to silence the buzzer and acknowledge the warning.

Note: The product is intended for early leak detection and is not intended to be submerged in water at any time.

Meet the iHome Control family of Intelligent Home solutions

iHome Control provides 24-7 remote home monitoring from anywhere. The free iHome Control app keeps you aware of changes in your home environment even when you're not home. For information about compatible products and to purchase Sensors and SmartPlugs, visit iHome.com.



Notices

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

Detection Probe

(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

To assure continued FCC compliance:

- . Any changes or modifications not expressly approved by the grantee of this device could void the user's authority to operate the equipment.
- 2. This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

FEDERAL COMMUNICATIONS COMMISSION INTERFERENCE STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

his equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

Cet appareil radio est conforme au CNR-247d'Industrie Canada. L'utilisation de ce dispositif est autorisée seulement aux deux conditions suivantes : (1) il ne doit pas produire de brouillage, et (2) l'utilisateur du dispositif doit être prêt à accepter tout brouillage radioélectrique reçu, même si ce brouillage est susceptible de compromettre le fonctionnement du dispositif.

Cet équipement est conforme aux limites d'exposition aux rayonnements IC établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec un minimum de 20 cm de distance entre la source de rayonnement et votre

CAN ICES-(B)/NMB-3(B)

GENERAL BATTERY PRECAUTIONS

- Never use or charge a battery if it appears to be leaking,
- discolored, deformed, or in any way abnormal. Do not mix old and new batteries
- Use onlynew batteries of the type recommended
- Avoid charging a rechargeable battery when the temperature is not within
- 5°C 35°C (41° 95° Fahrenheit) Never expose a battery to any liquid.
- Never expose a battery to excessive heat such as direct sunlight or fire. Never use a battery
- pack in an unventilated vehicle
- where excessive internal temperatures may be encountered.
- Always keep batteries out of the reach of infants and small children.
- Remove batteries if device will not be used for a prolonged period to avoid corrosion which
- can damage the unit Dispose of batteries that are leaking
- Dispose of batteries in accordance with local regulations



For warranty information:
visit https://www.ihomeaudio.com/support/

iSB02_2017_QSG_v4

BACK