



PHANTOM 2 VISION+

User Manual



PHANTOM 2 VISION+User Manual V1.0

February 14, 2014 Revised

Congratulations on purchasing your new DJI product. Please thoroughly read the entire contents of this manual to fully use and understand the product.

It is advised that you regularly check the PHANTOM 2 VISION+'s product page at www.dji.com which is updated on a regular basis. This will provide services such as product information, technical updates and manual corrections. Due to any unforeseen changes or product upgrades, the information contained within this manual is subject to change without notice.

If you have any questions or concerns regarding your product, please contact your DJI authorized dealer or DJI Customer Service.

Before Use

Disclaimer & Warning

Please read this disclaimer carefully before using this product. This product is not suitable for people under age of 18. By using this product, you hereby agree to this disclaimer and signify that you have read them fully. You agree that you are responsible for your own conduct and content while using this product, and for any consequence thereof. You agree to use this product only for the purposes that are proper and in accordance with the terms and any applicable policies and guidelines DJI may make available.

Instructions

This product is an excellent flight platform offering an excellent flight experience in low altitude outdoor or larger indoor space, only if it is powered normally and in a good working condition.

1. This product is designed to achieve excellent performance when used with genuine DJI accessories. DJI shall not be liable for any damages to this product and/ or accidents by the malfunctions of non-genuine DJI accessories.
2. Despite this product having a built-in autopilot system and our efforts in making the operation of the controller as safe as possible when the main power battery is connected, we strongly recommend users to remove all propellers when calibrating and setting the parameters.
3. Make sure all connections are good, and keep children and animals away during firmware upgrade, system calibration and parameter setup.

Cautions for Aircraft User

Please check the following steps carefully every time before flight.

1. Always fly the multi-rotor in the safe condition and keep your multi-rotor away from the obstacles, crowds and high-voltage lines, etc.
2. Do not overload the multi-rotor.
3. Check whether the propeller and the motor are installed correctly and firmly before flight. Make sure the rotation direction of each propeller is correct. Do not get close to or even touch the working motors or propellers to avoid serious injury.
4. Try to avoid interference between the remote control transmitter and other wireless equipment.
5. Make sure that the R/C battery and flight battery are fully charged.
6. Make sure to switch on the transmitter first, then power on the multi-rotor before takeoff. Power off the multi-rotor first, then switch off the transmitter after landing.
7. Check whether all parts of the multi-rotor are in good condition before flight. Do not fly with aging or

damaged parts.

8. Do not use in the magnetic interference area, radio interference area. This will lead to communication or other failures.
9. Do not use in the server weather condition such as rainy day, snow, windy (more than moderated breeze), hail, lighting, tornadoes and hurricanes etc.
10. Before flying, please read all instruction on the quick start guide and detail user guide and other useful information included in the package or the official website.

Cautions for Airborne Camera Use

1. Do not allow the camera into contact with, or become immersed in, water or other liquids. If the exterior comes into contact with liquids or moisture air, wipe it dry with a soft, absorbent cloth
2. Do not use substance containing alcohol, benzene, thinners or other flammable substances to clean or maintain the camera.
3. Do not store the camera in humid or dusty area.
4. Avoid using, placing or storing the camera in the places subject to strong sunlight or high temperatures.
5. Stop operating the camera immediately if it emits smoke or noxious fumes.
6. Shoot several trail images to verify that the camera is operating and being operated correctly before you try to photograph or shoot important pictures.

Using Lithium Polymer (LiPo) Batteries

LiPo batteries can be extremely hazardous and requires special attention when you are handling them. Observe the following recommendations for the use of these batteries.

1. LiPo batteries must be charged with a LiPo charger. Never attempt to charge LiPo batteries with a charger that is not specifically designed for charging LiPo batteries.
2. Never overcharge LiPo batteries. Overcharging may result in an explosion or fire. Do not charge above 4.2V per cell. When the battery is fully charge, disconnect it from the charger.
3. Ensure the chargers are properly set when using the selectable or adjustable charger.
4. Never leave the battery charger unattended during charging.
5. Do not charge the batter (i) while still connect to the aircraft, (ii) inside a vehicle, and (iii) near flammable materials or on a flammable surface such as carpet or wood.
6. Never charge a swollen battery, a leaky battery or one which has been damaged.
7. It is recommended that batteries be charged and store in a fireproof container.
8. Examine the charger regularly for damage to the cord, plug, enclosure or other parts. Never use a damaged charger.
9. Disconnect the charger when not in use.

10. Do not clean the charger with a solvent denatured alcohol or other flammable solvents.

Usage and Storage

Keep the batteries out of the reach of children and pets.

Never discharge batteries below 3V per cell.

Do not heat the battery.

Do not insert or remove the batteries if the plastic cover had been torn or compromised in any way.

Do not insert or remove the batteries in the charger or the craft while the power is on.

Do not expose the batteries to excessive physical shock.

Never use a swollen battery or a leaky battery, or one which is damaged or giving off an unusual odor.

Clean the battery terminals with a dry and clean cloth.

Do not expose batteries to extreme temperatures including excessive heat. Do not leave the batteries inside of the vehicle on hot days.

Do not allow batteries to come into contact with any kind of liquid. Do not leave batteries out in rain or near a source of moisture.

Do not leave batteries in a microwave oven or in a pressurized container.

Do not attempt to dismantle, pierce or cut a battery and do not attempt to repair the batteries by yourself.

Do not place loose battery cells on any conductive surface, such as metal-topped table. Do not put the loose cell in pocket, bag or drawer where they may short-circuit against other items or the battery terminals could be pressed against each other.

Do not place or use the batteries in strong electrostatic or electromagnetic surface or surrounding area which may result in battery damage.

Do not place any heavy object on the batteries or charger. Avoid dropping the batteries to the ground.

Avoid direct contact with the electrolyte contained within the batteries as the electrolyte and electrolysis vapors is harmful to your health.

Remove batteries when finish using the craft.

Battery Disposal

Discarding the batteries in your general household wastes impacts the environment. Please dispose the batteries in an environmental-friendly manner.

Do not dispose of batteries in the fire.

Damaged or unusable batteries must be disposed of in a container specially reserved for this special purpose.

When disposing of the batteries, follow appropriate local guideline and regulations. For further information contact your local solid waste authority or your battery store.

Make sure flight battery is firmly installed before flying.

Always use DJI approved battery.

Always use DJI approved charger to recharge the flight battery.

Limitation of Liability

DJI accepts no liability for damage(s) or injuries incurred directly or indirectly from the use of this product in the following conditions:

1. Damage(s) or injuries incurred when users are drunk, taking drugs, drug anesthesia, dizziness, fatigue, nausea and any other conditions no matter physically or mentally that could impair your ability.
2. Damage(s) or injuries caused by subjective intentional operations. Any mental damage compensation caused by accident.
3. Any mental damage compensation caused by accident.
4. Failure to follow the guidance of the manual to assemble or operate.
5. Malfunctions caused by refit or replacement with non-DJI accessories and parts.
6. Damage(s) or injuries caused by using third party products or fake DJI products.
7. Damage(s) or injuries caused by mis-operation or subjective mis-judgment.
8. Damage(s) or injuries caused by mechanical failures due to erosion, aging.
9. Damage(s) or injuries caused by continued flying after low voltage protection alarm is triggered.
10. Damage(s) or injuries caused by knowingly flying the aircraft in abnormal condition (such as water, oil, soil, sand and other unknown material ingress into the aircraft or the assembly is not completed, the main components have obvious faults, obvious defect or missing accessories).
11. Damage(s) or injuries caused by flying in the following situations such as the aircraft in magnetic interference area, radio interference area, government regulated no-fly zones or the pilot is in backlight, blocked, fuzzy sight, and poor eyesight is not suitable for operating and other conditions not suitable for operating.
12. Damage(s) or injuries caused by using in bad weather, such as a rainy day or windy (more than moderate breeze), snow, hail, lightning, tornadoes, hurricanes etc.
13. Damage(s) or injuries caused when the aircraft is in the following situations: collision, fire, explosion, floods, tsunamis, subsidence, ice trapped, avalanche, debris flow, landslide, earthquake, etc.
14. Damage(s) or injuries caused by infringement such as any data, audio or video material recorded by the use of aircraft.
15. Damage(s) or injuries caused by the misuse of the battery, protection circuit, RC model and battery chargers.
16. Consequential damages caused by any malfunction of an equipment or accessory, including memory cards, that result in the failure on an image or video to be recorded or to be recorded in a way that machine readable.
17. Any consequential damages caused by operations that do not follow all instruction in the quick start guide,

detail user guide and other useful information included in the package or the official website.

18. Operators do not obey the local law or regulation.
19. Other losses that are not covered by the scope of DJI liability.
20. Other losses that are not covered by the scope of DJI Innovations liability

Warning

1. This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This product complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation;

NOTE: The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications or changes to this product. Such modifications or changes could void the user's authority to operate the product

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
 - Increase the separation between the equipment and receiver.
 - Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
 - Consult the dealer or an experienced radio/TV technician for help
2. When using this product, ensure that the antenna of the device is at least 20 cm from any person. Due to the used enclosed material, this product shall only be connected to a USB interface of version 2.0 or higher. The connection to so called "power USB" is prohibited.

CAUTION: RISK OF EXLPOSITION IF BATTERY IS REPLACED BY AN INNCONNECT TYPE. DISPOSE OF USED BATTERIES ACCRODING TO THE INSTRCUTION.

Hereby, DJI declares that this product is in compliance with the essential requirement and other relevant provision of Directive 1995/5/EC.

3. Please note that this product is intended for personal use and should never be used in a manner that infringes upon or contravenes international or domestic law and regulations.

You shall not use this product:

- a) Defame, abuse, harass, stalk, threaten or otherwise violate the legal rights (such as right of privacy and publicity) of others;
- b) Photograph people or their privacy area without their consent or photograph any non-photograph area with the prior authorizations;
- c) Use this product for any illegal or inappropriate purpose other than general personal use (such as spy, unauthorized investigation and unauthorized detection);
- d) Violate or disregard any other applicable local laws, administrative rules and social habits.





Please be advise that in certain area that copying of images and videos from shooting, performances, exhibitions, or commercial properties by mean of a camera of other devices may contravene copyright or other legal right even if the image or video was shot for personal use.

If you have any problem you cannot solve during installation, please contact the DJI authorized dealers.

Name of the products, brand, etc. appearing in this manual are trademarks or registered trademarks of their respective owner companies. This product and manual are copyrighted by DJI with all right reserved No part of this product or manual shall be reproduced in any form without the prior written consent or authorization of DJI. No patent liability is assumed with respect to the use of product or information contained herein.

Using this manual

Symbol in this manual

	Forbidden operations
	Important notes
	Tips
	References or definitions

Convention

Except specific explain, all the descriptions of PHANTOM 2 VISION+ in this manual assume that the working mode is PHANTOM 2 VISION mode rather than Naza-M mode.

Using Suggestions

DJI has produced tutorials and printed manuals to help you take full use of PHANTOM 2 VISION+.

- (1) PHANTOM PILOT TRAINING GUIDE
- (2) PHANTOM 2 VISION+ QUICK START GUIDE
- (3) PHANTOM 2 VISION+ USER MANUAL

It's suggested to watch tutorial videos in first, and conduct your first flight according to PHANTOM 2 VISION+ QUICK START GUIDE. It's practical if you refer to PHANTOM PILOT TRAINING GUIDE to enhance your flight skills,

and you can obtain the most comprehensive details in PHANTOM 2 VISION+ MANUAL. For experienced users, especially who controls DJI PHANTOM 2 VISION well; you can refer to PHANTOM PILOT TRAINING GUIDE to take off your aircraft quickly as well.

Watching Tutorial Videos

This user manual contains detailed installation and usage procedures of the product. In addition to this manual, we provide a range of quick start videos. It is advised that you watch them fully before attempting to use the product.

Approach 1	Direct link.	http://www.dji.com/phantom2visionplus/training	
Approach 2	Scan the QR code to get the quick start video link.		Preparing for flight.

Downloading the DJI VISION App

Before attempting to use the product, please download and install the DJI VISION App. Download the DJI VISION App by the approaches listed below:

Approach 1	Download from the App Store or Google Play.	iOS user	Search "DJI VISION" from App Store.
		Android user	Search "DJI VISION" from Google Play.
Approach 2	Scan the QR code to obtain the download link.		Scan the QR code and download.

Table of Contents

BEFORE USE	2
DISCLAIMER & WARNING	2
INSTRUCTIONS	2
CAUTIONS FOR AIRCRAFT USER	2
CAUTIONS FOR AIRBORNE CAMERA USE	3
USING LITHIUM POLYMER (LIPO) BATTERIES	3
USAGE AND STORAGE	4
BATTERY DISPOSAL	4
LIMITATION OF LIABILITY	5
WARNING	6
USING THIS MANUAL	7
SYMBOL IN THIS MANUAL	7
CONVENTION	7
USING SUGGESTIONS	7
WATCHING TUTORIAL VIDEOS.....	8
DOWNLOADING THE DJI VISION APP	8
TABLE OF CONTENTS	9
OVERVIEW	13
1 IN THE BOX	13
2 INTRODUCTION	15
3 QUICK START GUIDE	16
ASSEMBLIES AND USAGES	17
1 REMOVING THE GIMBAL CLAMP	17
2 PREPARING BATTERY	17
2.1 DJI INTELLIGENT BATTERY	17
2.2 USAGES.....	18
<i>Powering on/off</i>	18
<i>Checking the battery level</i>	19
<i>Checking the battery life</i>	19
2.3 CHARGING THE INTELLIGENT BATTERY	20
2.4 INSTALL THE BATTERY	20
2.5 CORRECT BATTERY USAGE NOTES	21
3 PREPARING PHANTOM 2 VISION+ AIRCRAFT	22

3.1 INTRODUCTION	22
3.2 BUILT-IN FLIGHT CONTROL SYSTEM INSTRUCTIONS	22
<i>Assistant Software Port</i>	23
3.3 LED FLIGHT INDICATORS DESCRIPTION	23
<i>Front LEDs</i>	23
3.4 CAMERA	24
<i>Removing the camera lens cap</i>	25
<i>Camera function button</i>	25
<i>Camera Data Port</i>	25
<i>Camera Indicator</i>	25
3.5 TRIAXIAL GIMBAL.....	26
<i>Gimbal specifications</i>	26
<i>Micro-SD Slot</i>	26
<i>Gimbal Motor Error Warning</i>	26
4 ATTACHING THE PROPELLERS.....	28
4.1 INTRODUCTION	28
4.2 ASSEMBLY.....	28
4.3 REMOVING THE PROPELLERS.....	28
4.4 NOTES	29
5 PREPARING THE REMOTE CONTROLLER.....	30
5.1 THE REMOTE CONTROLLER.....	30
5.2 POWER ON THE REMOTE CONTROLLER	30
5.3 REMOTE CONTROLLER POWER INDICATOR STATUS INFORMATION	31
5.4 ANTENNA ORIENTATION	32
5.5 REMOTE CONTROLLER OPERATION.....	32
5.6 LINK BETWEEN THE REMOTE CONTROLLER AND RECEIVER.....	34
<i>Link Procedures</i>	34
<i>Link Indicator</i>	34
5.7 COMPLIANCE VERSION CONFIGURATION.....	34
6 PREPARING THE RANGE EXTENDER.....	36
6.1 THE RANGE EXTENDER.....	36
<i>SYSTEM Indicator</i>	36
<i>Power Indicator (POWER)</i>	36
<i>Reset Button</i>	37
6.2 USAGE.....	37
<i>Charging the Range Extender</i>	37
<i>Powering on the Range Extender</i>	37
<i>Battery capacity level display</i>	37
<i>Low battery capacity warning</i>	38
6.3 RENAME SSID OF RANGE EXTENDER.....	38
6.4 BINDING THE CAMERA & RANGE EXTENDER	38
7 DOWNLOADING AND INSTALLING THE DJI VISION APP.....	41
7.1 DOWNLOAD AND INSTALL	41
7.2 REGISTER & LOGIN.....	41
<i>[1] Register</i>	41

[2] Login	42
[3] Usage tips	42
8 CONNECTING THE CAMERA	44
8.1 CONNECTING PROCEDURES	44
FLIGHT	46
<i>Flight Environment Requirement</i>	46
1 CALIBRATING THE COMPASS	46
1.1 CALIBRATION PROCEDURES	46
1.2 RECALIBRATION SCENARIOS	47
2 STARTING THE MOTORS	48
3 TAKEOFF/LANDING PROCEDURES	48
4 FAILSAFE FUNCTION	49
4.1 POSSIBLE FAILSAFE SCENARIO	49
4.2 FAILSAFE PROCEDURE	49
<i>Failsafe on the DJI VISION App</i>	50
4.3 REGAINING CONTROL DURING FAILSAFE PROCEDURE	50
5 LOW BATTERY CAPACITY WARNING FUNCTION	52
<i>First Level Battery Low Warning</i>	52
<i>Second Level Battery Low Warning</i>	52
<i>DJI VISION App Low Battery Capacity Warning</i>	52
DJI VISION APP USAGE	53
1 DJI VISION APP MAIN MENU	53
2 CAMERA PAGE	54
[1] RETURN	54
[2] CAMERA PITCH CONTROL	54
<i>Normal Mode</i>	54
<i>Accelerometer Sensor Mode</i>	54
[3] FLIGHT ATTITUDE AND RADAR FUNCTION	56
[4] FLIGHT PARAMETERS	56
[5] WI-FI SIGNAL INTENSITY	57
[6] AIRCRAFT BATTERY LEVEL	57
[7] AIRCRAFT GPS STATUS	57
[8] MICRO-SD CARD STATUS	57
[9] REMAINING SHOTS	57
[10] SHUTTER BUTTON	58
[11] VIDEO RECORDING BUTTON	58
[12] CAMERA SETTINGS	58
[13] HIDE OR SHOW FLIGHT PARAMETERS	58
3 CAMERA SETTINGS	59
[1] CAPTURE MODE	59
[2] PHOTO SIZE	59





[3] VIDEO RESOLUTION.....	59
[4] PHOTO FORMAT	60
[5] SELECTABLE ISO.....	60
[6] WHITE BALANCE	60
[7] EXPOSURE METERING.....	60
[8] EXPOSURE COMPENSATION	61
[9] SHARPNESS	61
[10] ANTI-FLICKER.....	61
[11] RESTORE DEFAULT SETTINGS.....	61
[12] FORMAT MICRO-SD CARD	61
4 ALBUM PAGE.....	62
SD CARD ALBUM	62
MOBILE DEVICE ALBUM	64
5 NEWS PAGE	66
6 SETTINGS PAGE	67
[1] TOOLBAR AUTO HIDE.....	67
[2] WHEN CONNECTION LOST	67
<i>[17] Stop Recording:.....</i>	<i>67</i>
[3] CAMERA SETTINGS DISPLAY.....	68
[4] PREVIEW QUALITY	68
[5] PARAMETER UNIT.....	68
[6] YAW AXIAL CONTROL.....	69
[7] AUTO FLIPS.....	69
[8] BATTERY LOW WARNING	69
[9] TUTORIAL	69
[10] CLEAR NEWS CACHE.....	69
[11] BINDING	69
[12] RENAME SSID OF RANGE EXTENDER	69
[13] FIND MY PHANTOM 2 VISION+	70
[14] ACCOUNT	70
[15] RATE	70
[16] ABOUT	70
ASSISTANT SOFTWARE	71
1 INSTALLING DRIVER AND PHANTOM 2 VISION+ ASSISTANT SOFTWARE.....	71
INSTALLING AND RUNNING ON WINDOWS.....	71
INSTALLING AND RUNNING ON MAC OS X.....	71
2 USING THE ASSISTANT SOFTWARE.....	73
2.1 USING THE PHANTOM 2 VISION+ ASSISTANT SOFTWARE	73
<i>Firmware upgrade of the PHANTOM 2 VISION+</i>	<i>73</i>
2.2 PHANTOM RC ASSISTANT SOFTWARE USAGE.....	74
APPENDIX.....	76
1 LED FLIGHT INDICATOR STATUS.....	76
2 SPECIFICATIONS	77













Overview

PHANTOM 2 VISION+ is an excellent flight platform and it is an upgrade version of PHANTOM 2 VISION, upgrading to a flying video camera from a flying camera. DJI VISION App enable you to remote control the camera and the PHANTOM 2 VISION+ aircraft, achieving real-time video transmission FPV flight and album synchronization. PHANTOM 2 VISION+ has integrated the high performance camera, triaxial gimbal and stable flight control system to provide unique flight experiences.

1 In the Box

Before using this product, please check that all the following items have been included in the package. If any part listed in the table is missing, please contact your local dealer.

NO.	Name	Pic.	Qty.	Remarks
1	Aircraft		1	Integrated with gimbal and camera
2	Remote Controller		1	Mounted with Mobile Device Holder and Range Extender
3	Propeller Pairs		4	4 with black nut and 4 with grey nut
4	Intelligent Battery		1	Mounted in the aircraft



5	Lens Cap		1	Mounted in the aircraft
6	Gimbal Clamp		1	Mounted in the aircraft
7	Micro-SD Card		1	Mounted in the aircraft
8	Charger		1	
9	Power Cables		1	GB&CE
10	Plug Set		1	SAA&ANSI
11	Micro-USB Cable		1	
12	Propeller Detaching Wrench		1	
13	Spared Damping Absorbers		4	
14	Spared Screws		11	M3X5(6pcs) M3X8(5pcs)
15	Stickers		1	
16	Manuals		4	《DISCLAIMER》 《PHANTOM PILOT TRAIN GUIDE》 《PHANTOM 2 VISION+ QUICK START GUIDE》 《PHANTOM 2 VISION+ USER

				MANUAL》
17	AA Batteries		4	Supply power for the remote controller

2 Introduction

The complete package of PHANTOM 2 VISION+ consists of aircraft, camera, gimbal, propulsion system, flight control system, remote control system and Wi-Fi communicating system. The flight control system is integrated within the aircraft. The remote control system operates at 5.8GHz band and the receiver is built-in the aircraft too. The built-in Wi-Fi module and range extender comprise the 2.4GHz Wi-Fi communicating system, which is used for video transmitting.

Remote Controller
 •5.8GHz
 •2 sticks, 7channels



- Exterior
 - Triaxial gimbal
 - Camera
 - Propulsion (motors and propellers)
- Built-in
 - Flight control system
 - Wi-Fi module
 - 5.8GHz receiver
 - ESCs

- Working mode of the aircraft
- PHANTOM 2 VISION mode: Ready to Fly
Ready to Fly (non-GPS)
 - Naza-M mode: GPS mode
ATTI. mode
Manual mode/Failsafe

Figure 1

The working mode of the aircraft is configurable by using the PHANTOM 2 VISION+ assistant software.



You can switch the aircraft working mode to PHANTOM 2 VISION mode or Naza-M mode. Please adhere to the [NAZA-M V2 Quick Start Manual](#) to obtain the performances of Naza-M mode.

PHANTOM 2 VISION mode: Current flight status is appointed by the flight system automatically by estimating whether no less than 6 GPS satellites has been searched. In this mode, users can calibrate the remote controller, adjust the gain values, and use Failsafe and Low battery capacity warning functions.

Naza-m mode: Compared with PHANTOM 2 VISION mode, users can switch the flight control mode manually and IOC function is added.



Ready to Fly: When the available GPS satellites searched by PHANTOM 2 VISION+ are no less than 6, the flight control system will work in a safe status.

Ready to Fly (non-GPS): When the available GPS satellites searched by PHANTOM 2 VISION+ are less than 6, the flight control system will work in a less safe status.

3 Quick Start Guide

1. Watch tutorial videos and read manuals.
2. Open the box and check.
3. Remove gimbal clamp.
4. Prepare remote controller batteries, and get intelligent battery, range extender and mobile device charged.
5. Download DJI VISION App via your mobile device, register and login.
6. Install Micro-SD card and attach propellers to aircraft.
7. Install remote controller batteries. Set control mode and compliance version for remote controller using PHANTOM RC Assistant Software if required
8. Install intelligent battery into aircraft.
9. Power on remote controller, range extender and aircraft.
10. Run DJI VISION App; connect Wi-Fi named Phantom_XXXXXX.
11. After the mobile device has connected to camera, attach your mobile device to mobile device holder.
12. Execute CSC to start and stop motors, ensure they are normally working.
13. Finish compass calibration outdoors.
14. Flight and FPV experience, including control the aircraft by remote controller and carry out App function.
15. Fly back and land aircraft when low battery capacity warning.

Assemblies and Usages

Please adhere to following assemblies and usages to prepare for flight.

1 Removing the Gimbal Clamp

Do not remove the gimbal clamp prior to the assembly. As the figure below to pull out the clamp along the unlock direction.




Figure 2



Do not power on the aircraft when the gimbal clamp is attached, otherwise may damage the gimbal.



Please attach the gimbal clamp to protect the gimbal and camera during delivery or long time preservation.

2 Preparing Battery


Before using the PHANTOM 2 VISION+, make sure the following devices have enough power battery.

Devices	Power supply
Remote controller	Install 4 AA batteries.
Range extender	Ensure fully charged via charging port (Micro-USB port), please adhere to the charging method of range extender in this manual
Aircraft(including gimbal and camera)	Get power from the DJI intelligent battery
Mobile device	Make sure your mobile device has enough power if using DJI VISION App


Below are the introduction and usages of DJI intelligent battery.

2.1 DJI Intelligent Battery

The intelligent battery is specially designed for the PHANTOM 2 VISION+, with a battery capacity of 5200mAh, voltage of 11.1V and charge-discharge management functionality. The battery should only be charged with the DJI charger specified by DJI.



Intelligent Battery




C Charger

DJI Intelligent Battery Functions	
(1) Balance Charging	Automatically balance the voltage of each battery cell during charging.
(2) Capacity Display	Display the current battery level.
(3) Communicating	The main controller communicates with the battery via communication ports for battery voltage, capacity, current and other information.
(4) Overcharging Protection	Charging stops automatically when the battery voltage reaches 12.8V to prevent overcharging damage.
(5) Over Discharging Protection	Discharging stops automatically when the battery voltage reaches 8.4V to prevent over discharging damage.
(6) Short Circuit Protection	Automatically cuts off the power supply when a short circuit is detected.
(7) Sleep Protection	The battery will enter sleep mode after 10 minutes of inactivity to save power. The static current is 10nA in sleep mode when the battery is powered on without connecting to other devices.
(8) Charging Temperature Detection	The battery will charge only when its temperature is within 0°C~55°C. If the battery temperature is out of this range, the battery will stop charging.



- (1) Before use, please read and follow the user manual, disclaimer, and the warnings on the battery. Users take full responsibility for all operations and usage.
- (2) The battery should only be charged with the charger provided by DJI. DJI does not take any responsibility for operation of any charger from a third party.

2.2 Usages



Powering on/off

Powering on: When the battery is powered off; press the battery power button once and then press and hold for 2

seconds to turn on the intelligent battery. The battery power indicator will be solid red and the battery level indicator will indicate current battery capacity level after power on.




Powering off: When the battery is powered on, press the battery power button once and then press and hold for 2 seconds to turn off the intelligent battery. The LED indicators all go out after power off.





































Checking the battery level

When the battery is powered off; pressing the battery power button once will indicate the current battery level. Refer to the table below for details.

The battery level indicators will show the current battery level during both the charging and discharging process as well as battery life. The indicators are defined below.























-  : The LED is solid on
-  : The LED will blink regularly
-  : The LED is light off

Battery level during discharging process				
LED1	LED2	LED3	LED4	Current battery level
				87.5%~100%
				75%~87.5%
				62.5%~75%
				50%~62.5%
				37.5%~50%
				25%~37.5%
				12.5%~25%
				0%~12.5%
				<0%

Checking the battery life

When the battery is powered off;press and hold the battery power button for 5 seconds to check the battery life. The battery level indicators will show the life and the battery power indicator will blink for 10 seconds, then all LEDs will light out andthe intelligent battery will turn off.

Battery life				
LED1	LED2	LED3	LED4	Current battery life
				90%~100%
				80%~90%
				70%~80%
				60%~70%
				50%~60%


■	●	■	■	40%~50%
■	■	■	■	30%~40%
●	■	■	■	20%~30%
■	■	■	■	Less than 20%



More battery information is available in the battery tab of the PHANTOM 2 VISION+Assistant Software.

2.3 Charging the Intelligent Battery

1. Connect the charger to a wall socket (Use the plug set if necessary).
2. Connect the battery to the charger. If the current capacity of the battery is over 75%, you should power on the battery to begin charging.
3. The Battery Level indicators display current capacity level as the battery charges. Please refer to battery level indicator description for details.
4. The battery is fully charged when the Battery Level indicator lights are off. Please disconnect the charger and battery when the charging is completed.




Charging process				
LED1	LED2	LED3	LED4	Current battery level
●	■	■	■	0%~25%
●	●	■	■	25%~50%
●	●	●	■	50%~75%
●	●	●	●	75%~100%
■	■	■	■	Fully charged



If current battery level is over 75%, the battery should be powered on to charge.

2.4 Install the Battery

Push the battery into the battery compartment correctly as the following diagram shows. Make sure to slide the battery into the compartment until you hear a 'click' sound to confirm the battery is installed correctly.



An incorrectly installed battery may cause one of the following to occur: (1) Bad contact. (2) Unavailable battery information. (3) Unsafe for flight. (4) Unable to take off.




2.5 Correct Battery Usage Notes

1. **Never plug or unplug the battery into the aircraft when it is powered on.**
2. The battery should be charged in an environment that is between 0°C to 40°C, and be discharged in an environment that is between -20°C to 50°C. Both charging and discharging should be in an environment where the relative humidity is lower than 80%.
3. It's recommended to charge and discharge the battery thoroughly once every 20 charge/discharge cycles. Users should discharge the battery until there is less than 8% power left or until the battery can no longer be turned on. Users should then fully recharge the battery to maximum capacity. This power cycling procedure will ensure the battery is working at its optimal level.
4. For long term storage please place the battery with only a 40~50% capacity in a strong battery box securely. We recommend discharging and charging the battery completely once every 3 months to keep it in good condition. The capacity should be varied in such a cycle (40%~50%)—0%—100%—(40%~50%).
5. It's suggested you purchase a new battery after you have discharged your current battery over 300 times. Please completely discharge a battery prior to disposal.
6. It's suggested that you purchase a new battery if the current battery is swollen or damaged in any way.
7. Never try to recharge or fly with a battery that is swollen or damaged in any way.
8. Never charge the battery unattended. Always charge the battery on a non-flammable surface such as concrete and never near any flammable materials.
9. Safety is extremely important and users can get more information in the DISCLAIMER.

3 Preparing PHANTOM 2 VISION+ Aircraft

PHANTOM 2 VISION+ aircraft is a quadrotor with built-in flight control system and has integrated with gimbal and camera, it also has a Micro-USB port on the aircraft for connecting to Assistant Software and another Micro-USB port on the gimbal for connecting Micro-SD card of camera. The aircraft has battery compartment specialized for the intelligent battery, it also has LED flight indicators for status indicating. All these features make the PHANTOM 2 VISION+ easy to assemble and configure.

3.1 Introduction



[1]	Propeller
[2]	Motor
[3]	Nose Sticker
[4]	Nose LED
[5]	FC Assistant Port(Micro-USB port)
[6]	Vibration Absorber
[7]	Camera LED Indicator
[8]	Camera Function Button
[9]	Triaxial Gimbal
[10]	Camera Lens
[11]	Rear LED
[12]	DJISmart Battery
[13]	Receiver Antenna
[14]	Landing Gear
[15]	Camera Data Port(Micro-USB port)
[16]	Compass
[17]	Micro-SD Slot

3.2 Built-in Flight Control System Instructions

PHANTOM 2 VISION+ is equipped with DJI Naza-M V2 flight control system which helps to improve operability and stability. With the flight control system, users can control the entire aircraft's functions in flight such as Pitch (forwards and backwards), Roll (left and right), Elevator (up and down) and Yaw (turn left or right). When the aircraft enters the IOC, failsafe or low battery capacity mode, the flight control system will navigate the aircraft to ensure flight stability and safe.

Modules	Functions
Main controller	Acts as the brains of the complete flight control system responsible for connecting and controlling all the modules together.
IMU	Has a built-in inertial sensor and a barometric altimeter that measures both attitude and altitude.
GPS& Compass	The compass reads geomagnetic information which assists the GPS (Global Position System) to accurately calculate the position and height of the aircraft in order to implement the stable hovering function.
LED Indicators	Indicates the status of flight control system.

Assistant Software Port


The flight control system communicates with the PC Assistant Software via a Micro-USB cable by connecting it with Assistant Software Port and PC. Users can use the assistant software to configure the aircraft and upgrade firmware after connecting successfully.

3.3 LED Flight Indicators Description


After powering on the intelligent battery, the LED flight indicators light up to show the aircraft's current status and nose direction.

Front LEDs

The front LEDs are for indicating where the nose of the aircraft is. They light up **solid red** only after the motors have started spinning.



LED Flight Indicators Description



Normal status	LED flight indicators	Notes
Power On Self-Test		----
Warming Up		Aircraft cannot take off.
Ready to Fly		Slow blinking green.
Ready to Fly (non-GPS)		Slow blinking yellow.
Abnormal status	LED flight indicators	
Remote Controller Signal Lost		Fast blinking yellow. Refer to <Failsafe Function>.
1 st Level Low Battery Capacity Warning		Slow blinking red.
2 nd Level Low Battery Capacity Warning		Fast blinking red.
Not Stationary or Sensor Bias is too big		Keep aircraft stationary or perform IMU calibration.
Error*		Cannot fly.
Compass Needs Calibration		Refer to <Calibrating the Compass>.

- (1) The aircraft should be kept stationary on level open ground before takeoff.
- (2) Make sure the aircraft's status is in Ready to Fly or Ready to Fly (non-GPS) mode before takeoff.
- (3) If an error occurs (LED is solid red), please connect to the PHANTOM 2 VISION+ Assistant Software for more detailed information.



- 1) IMU calibration is required: Recalibrate IMU using the Assistant Software.
- 2) IMU is abnormal: Should be repaired.
- 3) Compass is abnormal: Should be repaired.
- 4) Remote controller's mid-point is set abnormally: Refer to <How to solve large margin(s) mid point error?>.

3.4 Camera


The camera of PHANTOM 2 VISION+ will be powered on once the intelligent battery installed in the aircraft is powered on. Capture the videos or photos either by pressing the camera function button or using the DJI VISION App. The camera supports multi-capture, continuous capture and timed capture, supports both RAW and JPEG photo formats, supports HD Recording (1080p30/1080i60).

Camera specifications

Resolution	14 Megapixels
FOV	140° / 120° / 90°
Sensor size	1/2.3"

Removing the camera lens cap

Remove the lens cap before using the camera. Put the lens cap back on when you finish using the camera.



Camera function button

Capture function: Press the button once (hold less than 2 seconds) to take a single capture.

Record function: Press the button once (hold no less than 2 seconds) to begin recording. Press once again to stop.








Camera Data Port

Connect the camera data port to PC via a Micro-USB cable; users can copy the photos or videos from the Micro-SD card to your PC conveniently.

Camera Indicator

The Camera Indicator provides the information on the working status of the camera and Wi-Fi module.

Camera indicator	Wi-Fi status	Camera status
● Solid	OFF	Power On; Idle State
● Slow Blink (0.2s on, 1.8s off)	ON	Idle State
● Blink (0.1s on, 0.3s off, 0.1s on, 1.8s off)	ON	The Micro-SD card is connected to the PC via camera data ports successfully
● Fast Blink (0.1s on, 0.3s off)	ON	Synchronizing photos or videos
● Solid	OFF	Recording
● Blink Once (0.2s on, 0.3s off)	ON/OFF	Taking a single picture.
● Blink 3 Times (0.1s on, 0.1s off)	ON/OFF	Taking 3 or 5 photos per shot
● Fast Blink (0.1s on, 0.3s off)	ON/OFF	Firmware Upgrading

 (0.2s green, 1.8s yellow)	ON	Recording
 Solid	ON/OFF	Critical error
 Slow Blink (0.2s on, 1.8s off)	ON/OFF	CMOS sensor error
 Blink Once(0.2s on, 0.3s off)	ON/OFF	Operation failed
 Blink 3 Times(0.1s on, 0.1s off)	ON/OFF	Micro-SD card error
 Fast Blink(0.1s on, 0.3s off)	ON/OFF	Upgrade error
 (0.5s green, 0.5s yellow, 0.5s red, 0.5s Off)	ON/OFF	Overheated Camera

3.5 Triaxial Gimbal

The gimbal of PHANTOM 2 VISION+ will be powered on and self-check once the intelligent battery installed in the aircraft is powered on. The pitch motion of the gimbal can be controlled by the DJI VISION App, the roll and yaw motion is controlled by the flight control system automatically, to achieve real time adjustment of gimbal gesture and automatic stability during flight.

Gimbal specifications	
Control accuracy	$\pm 0.03^\circ$
Controllable range	Pitch : $-90^\circ \sim +15^\circ$
Maximum angular velocity	Pitch : $90^\circ/s$

Micro-SD Slot

Make sure that the Micro-SD card is inserted before you take any photos or record any videos. PHANTOM 2 VISION+ has a standard 4GB Micro-SD card, maximum supported Micro-SD card capacity is 32GB. The DJI VISION App may not be able to read the Micro-SD card prepared by the user. It is suggested that you use the DJI VISION App to format the Micro-SD card when using the card for the first time.

Refer to <Camera Settings> for details on how to format the Micro-SD card.

Gimbal Motor Error Warning

Before the aircraft taking off, if a gimbal motor error is detected, there will be gimbal motor error warning prompted in the camera GUI of DJI VISION App. The warning will disappear after the trouble resolved.



Below two cases may cause the gimbal motor error.







- 1) Forget removing the gimbal clamp: make sure the clamp is removed before power on the aircraft.
- 2) The gimbal receives excessive external force (collision or artificial reason): please take care of the gimbal after power on.

4 Attaching the Propellers


Please use the original 9-inch propellers which are classified by the color of each central nut. Damaged propellers can be replaced by purchasing new ones if necessary.


4.1 Introduction

Propellers	Grey Nut (9443)	Black Nut (9443 R)
Diagram		
Assembly Location	Attach to the motor thread that does not have a black dot .	Attach to the motor thread that has a black dot .
Fastening/Un-fastening Instructions	 Lock: Tighten the propeller in this direction.	 Unlock: Remove the propeller in this direction.

4.2 Assembly

- (Fig.1) Remove the four warning cards from the motors after you read them.
- (Fig.2) Prepare the two grey nut propellers and two black nut propellers. Make sure to match the black nut propellers with the correctly marked black dot motors. Tighten the propellers according to the fastening instructions.



 Propellers are self-tightening during flight. **DO NOT** use any thread locker on the threads.



- (1) Make sure to match the propeller nut colors with the corresponding motors.
- (2) It is advised to wear protective gloves during propeller assembly and removal.

4.3 Removing the Propellers

(Fig.3) Keep the motor deadlocked in place with the assistant wrench (or one hand) and remove the propeller according to the un-fastening instructions.




Fig.3

4.4 Notes

1. Check that the propellers and motors are installed correctly and firmly before every flight.
2. Ensure that all propellers are in good condition before each flight. DO NOT use any ageing, chipped, or broken propellers.
3. To avoid injury, STAND CLEAR of and DO NOT touch the propellers or motors when they are spinning.
4. ONLY use original DJI propellers for a better and safer flight experience.