

## ERRATA

(SP4 User Guide)

- P 12 ■ Supplementary to “Important Safety Instruction”:

### Power Supply Cord

The power supply cord is the disconnect device. Ensure that the socket outlet is installed near the equipment and can be easily accessed.

### Telephone Line Cord

To reduce the risk of fire, use only No. 26 AWG or larger telephone line cord.

- P 26 ■ Supplementary to “The Back Panel” section:



---

**WARNING:** To reduce the risk of fire, use only No. 26 AWG or larger telephone line cord to connect to the telephone jacks on the SOMAport.

---

- P 33 ■ Supplementary to “Connecting the Power Supply and Powering on the SOMAport” section:



---

**WARNING:** The power supply cord is the disconnect device. Ensure that the socket outlet is installed near the equipment and can be easily accessed.

---

- P 38 ■ Supplementary to “Connection Telephones to SOMAport” section:



---

**WARNING:** Telephone jacks on the SOMAport are for connecting the telephones only. Do not connect the telephone line cord from these jacks to the public telephone network. Otherwise, you may pose a risk of electric shock or electrocution.

---

- P 75 ■ Supplementary to “Internal antenna” specification

Internal antenna gain: 0.36 dBi (700MHz)  
3.0 dBi (Other frequencies)