

EMP5605H**High Power 5GHz 11n Mini-PCI Adapter****5GHz IEEE802.11a/n 2T2R 300Mbps High Performance****Package Contents**

1 x MiniPCI Adapter (EMP5605H)

Engenius miniPCI series radio modules perform extreme high power and economize the power consumption on the system platform.

EMP5605H is an 802.11a/n WiFi 2x2 mini-PCI module designed specifically for integration to maximum performance ratio. EMP5605H delivers the ultimate wireless triple play experience for video, voice, and data transmission in the home, for the business, and on the road.

With enhanced features on the ESD protection, industrial-based operating temperature, economized system power consumption, industrial-best sensitivity than normal module, MMCX connectors, and stable heating protection design, makes the module is easily to integrate into a wide range of any platform.

EMP5605H

High Power 5GHz 11n Mini-PCI Adapter

5GHz IEEE802.11a/n 2T2R 300Mbps High Performance

Features

Industrial-best sensitivity -90dBm@6Mbps, -72dBm@54Mbps, -89dBm@MCS0/MCS8, -70dBm@MCS7/MCS15

Enables bandwidth up to 300Mbps Fast throughput for 802.11a and 802.11n

2T2R design architecture Higher and greater reliable throughputs over range

MMCX antenna connector Two MMCX connectors

Specification

Hardware Specification

Standard	WECA(WiFi & WiFi5 Compliance), IEEE802.11a/n, RoHS		
Chipset	Atheros AR9220		
Physical Interface	32-bit Mini-PCI Type III A 2 x MMCX Connector		
Power Requirements	External DC power in supported, Voltage=5V		
Current Consumption Information	Tx Current Consumption	Continuous Tx@802.11a	<1.7A
		Continuous Tx@802.11n	<2A
	Rx Current Consumption	Continuous Rx	<600mA
	Card on Current	Data Communicating with AP	<450mA
	Sleep Current	Sleep Mode	<100mA

RF Specification

Frequency Band	802.11a 5.15 ~ 5.35GHz, 5.725~5.825GHz		
Data rate	300 Mbps		
Receive Sensitivity (Typical)	802.11n(20MHz)	802.11n(40MHz)	802.11a
	-89dBm @ MCS0/MCS8 -70dBm @ MCS7/MCS15	-86dBm @ MCS0/MCS8 -68dBm @ MCS7/MCS15	-90dBm @ 6Mbps -72dBm @ 54Mbps

Software Specification

Security	WPA, WPA2, 64/128 bits WEP, TKIP and AES Hardware-base IEEE 802.11i encryption engine
-----------------	--

Environment & Mechanical

Temperature Range	-30°C to 80°C
Humidity (non-condensing)	0%~95% typical
Dimensions	66mm (L) x 59.5mm (W) x 5mm (H)
Weight	16g

EMP5605H**High Power 5GHz 11n Mini-PCI Adapter**

5GHz IEEE802.11a/n 2T2R 300Mbps High Performance

U.S. Regulatory Wireless Notice**Federal Communication Commission Interference Statement**

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

IMPORTANT NOTE:**FCC Radiation Exposure Statement:**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Operations in the 5.15-5.25GHz band are restricted to indoor usage only.

EMP5605H**High Power 5GHz 11n Mini-PCI Adapter**

5GHz IEEE802.11a/n 2T2R 300Mbps High Performance

This device is intended only for OEM integrators under the following conditions:

- 1) The antenna must be installed such that 20 cm is maintained between the antenna and users, and
- 2) The transmitter module may not be co-located with any other transmitter or antenna,

As long as 2 conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed (for example, digital device emissions, PC peripheral requirements, etc.).

IMPORTANT NOTE: In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

End Product Labeling

This transmitter module is authorized only for use in device where the antenna may be installed such that 20 cm may be maintained between the antenna and users. The final end product must be labeled in a visible area with the following: "Contains FCC ID: U2M-MP5605H"

Manual Information To the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.