

Finally.

A **COMPACT** PROJECTOR
TO CARRY YOUR **BIG** IDEAS.



INTRODUCING THE 3.5 LB., 1100 ANSI LUMEN
MICRO-PORTABLE
PROJECTOR WITH ZOOM LENS.

Notevision M15

SHARP

P G - M 1 5 X / M 1 5 S

Notevision M15



There's nothing compact about the way it performs.

Now there's a Sharp DLP projector that brings you all the technology, all the features and all the flexibility you need to look absolutely brilliant. All in something that fits in the palm of your hand. It's the new extraordinarily small, extraordinarily light, extraordinarily advanced Sharp M15 micro-portable projector.

You and your presentations will be more brilliant than ever thanks to the M15 1100 ANSI Lumen brightness. You'll have new flexibility in how you present your ideas because the M15 has easy-to-use connections for computers (both PC and Mac), audio and video. Automatic image set-up and Digital Keystone Correction (+/- 19°), high-end XGA resolution (a full 1024 x 768 native resolution) with Intelligent Resizing up to SXGA (1280 x 1024 pixels) deliver your ideas with a new sharpness and clarity. And a wireless remote with mouse control gives you total control from anywhere in the room.

And perhaps most important, is the exclusive Sharp ER warranty – the industry-leading parts and labor warranty with 24 hour emergency repair/replacement service. So even if there's a problem, Sharp will come through for you. Fast.

The new Sharp M15 micro-portable DLP projector. Brighter, to make you look even better.

Superior Image Quality

RESOLUTION	PG-M15X - Native XGA (1024 x 768) up to SXGA PG-M15S - Native SVGA (800 x 600) up to SXGA
TV LINES	580
PANEL TYPE	0.7" DMD™
H&V FREQUENCY	fh 31.5 - 80 kHz /fv 56 - 85 Hz
DOT CLOCK	25 - 135 MHz
LAMP	130 Watts AC, User-replaceable
LAMP PART #	BQC-PGM15X//1

Powerful Performance

RESIZING	ImageACE Resizing
BRIGHTNESS	1100 ANSI Lumens w/ 85% CCR
CONTRAST RATIO	500:1(full on/off)
LENS TYPE	1.2:1 Manual Zoom/Focus
ASPECT RATIO	4:3 & 16:9
AUDIO SYSTEM	2.0 Watt Monaural
POWER DISSIPATION	680 BTU/hour
POWER CONSUMPTION	180 Watts
POWER SOURCE	100-240 V AC, 50/60 Hz

Reliable and Easy to Use

COMPATIBILITY	PC & MAC
VIDEO SYSTEM	NTSC/PAL/PAL-N/PAL-M/SECAM/NTSC 4.43
REMOTE CONTROL	IR w/Mouse Control
IR CARRIER FREQUENCY	38 kHz
DIMENSIONS	8.9" (W) x 2.0" (H) x 6.9" (D) (Main Body)
FAN NOISE	37 dB
WEIGHT	3.5 lbs.
LIMITED WARRANTY	3 Years Parts/Labor & 2 Years Sharp ER (Express Repair), Lamp 90 Days

Inputs/Outputs

1 Computer InputDVI-I (29 Pin)
2 Video InputsComposite (RCA) and S-video (4 Pin DIN)
1 Audio Input3.5mm Stereo Minijack
1 RS-232C Input7 Pin DIN to 9 Pin D-Sub
1 Component Video Input(Shared with Computer Input-DVI-I)
1 Computer Output15 Pin HD (analog only)

Included Accessories

Wireless Remote Control, Two AAA Size Batteries, 6' Power Cord, 6' Computer RGB Cable, 6' Audio Cable (3.5mm Stereo), Audio Cable (3.5mm Stereo to RCA), USB Mouse Control Cable, 6' Mouse Control Cable, 6' Video Cable, 6' S-Video Cable, 6' RS-232 Conversion Cable, DVI/15 pin HD Adapter, Soft Pouch, Projector Operation Manual, Projector Quick Reference Guide, 6' DVI to 15-pin HD Cable

Optional Accessories

AN-M100PCBAG	Soft Sided Carry-on Bag (Projector & PC)
AN-M100CC	Hard Shell Carrying Case (Projector only)
AN-M100SC	*ATA* Style Shipping Case (Projector only)
AN-M100WB	Wheeled *Tilt-N-Go* Bag (Projector & PC)
AN-C200BAG	Soft Sided Carry-on Bag (Projector only)
AN-PGCM85	Ceiling Bracket for PG-M15X/M15S
AN-EP101B	Extension Pole for Ceiling Bracket

Projection Distances

M15X	Screen Diagonal.....40" to 250" Minimum Distance.....5'4" to 33'4" Maximum Distance.....6'5" to 40"
M15S	Screen Diagonal.....40" to 250" Minimum Distance.....5'7" to 35" Maximum Distance.....6'8" to 41'8"

Design and specifications are subject to change without notice. All trademarks are property of their respective holders.



SHARP ELECTRONICS CORPORATION
Professional LCD Products Group • Sharp Plaza, Mahwah, NJ 07430-2135
1-888-GO-SHARP (467-4277) • www.SharpLCD.com
Corporate Headquarters (201) 529-8200
E-Mail: ProLCD@SharpSEC.com • Fax Back (630) 378-9987