



MX690, MX890, SLX User Guide Supplement: X1

INTER-GROUP AVAILABILITY: SLX X1 944-952MHz

The following table describes Frequency and Channel availability in each of 6 Groups.

Channel	Group 1	2	3	4	5	6
	Full range, Robust, 5 channels			Full range, Max frequencies, 6 channels		
1	944.250	951.750	944.375	944.125	951.875	944.250
2	945.875	950.125	946.000	946.125	949.875	946.250
3	948.125	947.875	948.250	947.625	948.375	947.750
4	949.500	946.500	949.625	948.750	947.250	948.875
5	951.500	944.500	951.625	950.500	945.500	950.625
6				951.750	944.250	951.875

SLX RECEIVER ACCESSORIES

Furnished UA400 1/4 Wave Antenna (774-952Mhz)
Optional UA820X 1/2 Wave Antenna (944-952Mhz)

COMPLIANCE INFORMATION

Certified under FCC Part 74, FCC ID DD4SLX2A. Certified under FCC Part 74, FCC ID DD4SLX1A.
Certified under FCC Part 74, FCC ID DD4MX690A. Certified under FCC Part 74, FCC ID DD4MX890A.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by Shure Incorporated could void your authority to operate the equipment.