



AirPrime SL8080

Hardware Integration Guide



SIERRA
WIRELESS

2400058
Rev 0.1 (Draft A)

Important Notice

Due to the nature of wireless communications, transmission and reception of data can never be guaranteed. Data may be delayed, corrupted (i.e., have errors) or be totally lost. Although significant delays or losses of data are rare when wireless devices such as the Sierra Wireless modem are used in a normal manner with a well-constructed network, the Sierra Wireless modem should not be used in situations where failure to transmit or receive data could result in damage of any kind to the user or any other party, including but not limited to personal injury, death, or loss of property. Sierra Wireless accepts no responsibility for damages of any kind resulting from delays or errors in data transmitted or received using the Sierra Wireless modem, or for failure of the Sierra Wireless modem to transmit or receive such data.

Safety and Hazards

Do not operate the Sierra Wireless modem in areas where blasting is in progress, where explosive atmospheres may be present, near medical equipment, near life support equipment, or any equipment which may be susceptible to any form of radio interference. In such areas, the Sierra Wireless modem **MUST BE POWERED OFF**. The Sierra Wireless modem can transmit signals that could interfere with this equipment.

Do not operate the Sierra Wireless modem in any aircraft, whether the aircraft is on the ground or in flight. In aircraft, the Sierra Wireless modem **MUST BE POWERED OFF**. When operating, the Sierra Wireless modem can transmit signals that could interfere with various onboard systems.

Note: Some airlines may permit the use of cellular phones while the aircraft is on the ground and the door is open. Sierra Wireless modems may be used at this time.

The driver or operator of any vehicle should not operate the Sierra Wireless modem while in control of a vehicle. Doing so will detract from the driver or operator's control and operation of that vehicle. In some states and provinces, operating such communications devices while in control of a vehicle is an offence.

Limitation of Liability

The information in this manual is subject to change without notice and does not represent a commitment on the part of Sierra Wireless. SIERRA WIRELESS AND ITS AFFILIATES SPECIFICALLY DISCLAIM LIABILITY FOR ANY AND ALL DIRECT, INDIRECT, SPECIAL, GENERAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS OR REVENUE OR ANTICIPATED PROFITS OR REVENUE ARISING OUT OF THE USE OR INABILITY TO USE ANY SIERRA WIRELESS PRODUCT, EVEN IF SIERRA WIRELESS AND/OR ITS AFFILIATES HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR THEY ARE FORESEEABLE OR FOR CLAIMS BY ANY THIRD PARTY.

Notwithstanding the foregoing, in no event shall Sierra Wireless and/or its affiliates aggregate liability arising under or in connection with the Sierra Wireless product, regardless of the number of events, occurrences, or claims giving rise to liability, be in excess of the price paid by the purchaser for the Sierra Wireless product.

Patents

This product includes technology licensed from QUALCOMM® 3G.

Manufactured or sold by Sierra Wireless or its licensees under one or more patents licensed from InterDigital Group.

Copyright

©2010 Sierra Wireless. All rights reserved.

Trademarks

AirCard® and Watcher® are registered trademarks of Sierra Wireless. Sierra Wireless™, AirPrime™, AirLink™, AirVantage™ and the Sierra Wireless logo are trademarks of Sierra Wireless.

Windows® and Windows Vista® are registered trademarks of Microsoft Corporation.

Macintosh® and Mac OS® are registered trademarks of Apple Inc., registered in the U.S. and other countries.

QUALCOMM® is a registered trademark of QUALCOMM Incorporated. Used under license.

Other trademarks are the property of their respective owners.

Contact Information

Sales Desk:	Phone:	1-604-232-1488
	Hours:	8:00 AM to 5:00 PM Pacific Time
	E-mail:	sales@sierrawireless.com
Post:	Sierra Wireless 13811 Wireless Way Richmond, BC Canada V6V 3A4	
Fax:	1-604-231-1109	
Web:	www.sierrawireless.com	

Consult our website for up-to-date product descriptions, documentation, application notes, firmware upgrades, troubleshooting tips, and press releases:

www.sierrawireless.com

Revision History

Revision number	Release date	Changes
0.1	September 2010	<ul style="list-style-type: none"> Initial creation



Contents

Introduction	7
Hardware development components	7
Power Interface	9
Power supply	9
Electrostatic discharge (ESD)	9
Power states	10
RF Integration	11
Supported RF bands	11
Ground connection guidelines	11
Shielding guidelines	11
Antenna guidelines	12
Choosing the correct antenna and cabling	12
Determining the antenna's location	12
RF desense sources	12
Audio Interface	15
Audio function codec responsibilities	16
Regulatory Information	17
Important notice	17
Safety and hazards	17
Important compliance information for North American users	18
Acronyms and Definitions	19

1: Introduction

1

The Sierra Wireless AirPrime SL8080 soldered-down module forms the radio component for the products in which it is embedded.

Module-specific performance and physical characteristics are described in the corresponding product specification document.

Note: An understanding of network technology, and experience in integrating hardware components into electronic equipment is assumed.

Hardware development components

Sierra Wireless manufactures two hardware development components to facilitate the hardware integration process:

- AirPrime SL Socket-Up Board—Adapter board into which an SL module is embedded. This board may be used as a stand-alone platform for basic hardware development.
- AirPrime SL Development Kit—Hardware development platform that integrates with the socket-up board. The development kit provides access to all of the interfaces supported by the SL module.

For instructions on using the SL Development Kit, see the *SL Development Kit Quick Start Guide*.

2: Power Interface

Power supply

The host device must provide power to the AirPrime soldered-down module over pins 42 and 44 (VCC_3V6) as detailed in [Table 2-1](#).

Table 2-1: Power supply requirements

Requirement type	Value
Power supply	3.6 V (nominal)
Voltage range (V_{min} – V_{max})	3.3–4.3 V
Current (instantaneous (≤ 5 ms))	3 A
Current (continuous)	700 mA

Note: The host must provide safe and continuous power to the module; the module does NOT have protection circuits to guard against electrical overstress.

Electrostatic discharge (ESD)

The host device must provide adequate ESD protection on digital circuits and antenna ports as detailed in [Table 2-2](#).

Note: The level of protection required depends on your application.

Table 2-2: ESD specifications

Category	Connection	Specification
Operational	RF port (antenna launch and RF connector)	<ul style="list-style-type: none">IEC-61000-4-2—Level (Electrostatic Discharge Immunity Test)
Non-operational	Host connector interface	Unless otherwise specified: <ul style="list-style-type: none">JESD22-A114-B +/- 2kV Human Body ModelJESD22-C101 +/- 300V Charged Device Model
Signals	USIM connector	ESD protection is highly recommended at the point where the USIM contacts are exposed, and for any other signals that would be subjected to ESD by the user.
	Other host signals	

Power states

The SL8080 module has five power states as detailed in [Table 2-3](#).

Table 2-3: Supported SL808X power states

State	Description	Host powered	Modem powered	USB interface active	RF enabled
Normal (Default state)	<ul style="list-style-type: none"> Capable of placing/receiving calls or establishing data connections on network USB interface is fully active Current consumption in a call or data connection is affected by: <ul style="list-style-type: none"> Radio band in use Tx power Receive gain settings Data rate Number of active Tx time slots 	✓	✓	✓	✓
Low power	<ul style="list-style-type: none"> 'Airplane' mode—Rx/Tx are disabled; USB interface is active State entered automatically when critical voltage/temperature thresholds are exceeded. Host should consider powering off module to prevent damage to unit. 	✓	✓	✓	✗
Sleep	<ul style="list-style-type: none"> Normal state of module between calls or data connections. Module cycles between wake (polling the network) and sleep, at network provider-determined interval. 	✓	✓	✗	✗
Off	<ul style="list-style-type: none"> Host power is connected Module is powered down (drawing minimal current from host power supply) 	✓	✗	✗	✗
Disconnected	<ul style="list-style-type: none"> Host power is disconnected from module All module-related voltages are at 0 V. 	✗	✗	✗	✗

Supported RF bands

Table 3-1: RF bands

Technology	Band	Frequencies (MHz)		Supported
		Tx	Rx	
GSM	GSM 850	824–849	869–894	✓
	EGSM 900	880–915	925–960	✓
	DCS 1800	1710–1785	1805–1880	✓
	PCS 1900	1850–1910	1930–1990	✓
WCDMA ^a	Band I (WCDMA 2100)	1920–1980	2110–2170	-
	Band II (WCDMA 1900)	1850–1910	1930–1990	✓
	Band V (WCDMA 850)	824–849	869–894	✓
	Band VIII (WCDMA 900)	880–915	925–960	-

a. WCDMA channel spacing is 5 MHz, but this can be adjusted to optimize performance in a particular deployment scenario.

Ground connection guidelines

When connecting the module to system ground:

- Prevent noise leakage by establishing a very good ground connection to the module through the host connector.
- Minimize ground noise leakage into the RF. Depending on the host board design, noise could *potentially* be coupled to the module from the host board. This is mainly an issue for host designs that have signals traveling along the length of the module, or circuitry operating at both ends of the module interconnects.

Shielding guidelines

The module is fully shielded to protect against EMI and to ensure compliance with FCC Part 15 - “Radio Frequency Devices” (or equivalent regulations in other jurisdictions).

Note: This shielding must NOT be removed.

Antenna guidelines

Choosing the correct antenna and cabling

Consider the following points for appropriate antenna selection:

- The antenna (and associated circuitry) should have a nominal impedance of $50\ \Omega$ with a return loss of better than 10 dB across each frequency band of operation.
- The system gain value affects both radiated power *and* regulatory (FCC, IC, CE, etc.) test results.

Determining the antenna's location

Consider the following points when deciding where to place the antenna:

- Antenna location may affect RF performance. Although the module is shielded to prevent interference in most applications, the placement of the antenna is still very important—if the host device is insufficiently shielded, high levels of broadband or spurious noise can degrade the module's performance.
- Connecting cables between the module and the antenna must have $50\ \Omega$ impedance. If the impedance of the module is mismatched, RF performance is reduced significantly.
- Antenna cables should be routed, if possible, away from noise sources (switching power supplies, LCD assemblies, etc.). If the cables are near the noise sources, the noise may be coupled into the RF cable and into the antenna.

RF desense sources

Common sources of interference that may affect the module's RF performance (RF desense) include

- Power supply noise
 - Can lead to noise in the RF signal
 - Module power supply ripple limit $\leq 100\ \text{mV}_{\text{p-p}}$ 1 Hz–100 kHz
- Interference from other embedded wireless devices
 - Any harmonics, sub-harmonics, or cross-products of signals that fall in the module's Rx range may cause spurious response, resulting in decreased Rx performance.
 - Tx power and corresponding broadband noise may overload or increase the noise floor of the module's receiver, resulting in RF desense.
 - Severity of interference depends on proximity of other antennas to the module's antennas
- Host electronic device-generated RF
 - Proximity of host electronics to the module's antenna can contribute to decreased Rx performance.
 - Some devices include microprocessor and memory, display panel and display drivers, and switching mode power supplies.

Note: In practice, there are usually numerous interfering frequencies and harmonics. The net effect can be a series of desensitized receive channels.

4: Audio Interface

The module supports analog and PCM audio as summarized in [Table 4-1](#) and [Table 4-2](#). Refer to the product specification document for detailed information about the audio interfaces.

Table 4-1: Audio interface features

Audio type	Feature	Details
Analog	Implementation	<ul style="list-style-type: none">• Supports analog audio processing• Does not provide on-board filtering (except for blocking capacitors on microphone lines)• Host must provide bias and signal filters• Host should terminate unused audio lines with pull-down resistors
Digital (PCM)	Implementation	<ul style="list-style-type: none">• Primary PCM supported to interface with external codec
	Power	<ul style="list-style-type: none">• 1.8V (use VREG_MSME_1V8 as logic reference)

Table 4-2: Audio pins

Audio type	Name	Pin	Description	Notes
Analog	MIC_P	53	Microphone positive terminal	<ul style="list-style-type: none">• In series with 0.1 μF DC blocking capacitor
	MIC_N	54	Microphone negative terminal	<ul style="list-style-type: none">• In series with 0.1 μF DC blocking capacitor
	SPK_N	56	Speaker negative terminal	
	SPK_P	57	Speaker positive terminal	
Digital (PCM)	PCM_SYNC	64	PCM synchronization bit	<ul style="list-style-type: none">• 8 KHz
	PCM_DOUT	65	PCM output	
	PCM_DIN	66	PCM input	
	PCM_CLK	67	PCM clock	<ul style="list-style-type: none">• 2 MHz for primary PCM mode

Audio function codec responsibilities

The responsibilities of the module codec and host codec for special functions are detailed in [Table 4-3](#) on page 16.

Table 4-3: Codecs responsible for special functions

	Function	Responsible codec	
		Module	Host
FIR filtering	Tx and Rx paths	✓	-
Noise suppression	Required due to high sensitivity and gain in Tx path	✓	-
Echo cancellation	Different for each audio path and environment (handset, headset, car kit, speakerphone)	✓	-
High pass filtering/slope filtering functions	Required per phone acoustic requirements	✓	-
AGC (Automatic Gain Control)	Normalizes audio volumes in varying acoustic environments	✓	-
DTMF tones	Generation and detection of DTMF tones is required in both directions of the phone interface	✓	-
Comfort noise	Low level noise injected into Rx path for user 'connection' experience	✓	-
Simple ringers	Digital and analog tones, melody ringers, MIDI with limited memory storage	✓	-
Voice memo	Performed by host if significant memory storage is required	-	✓
Polyphonic ringtones	Host ovten supports WAV, MIDI formats with significant memory storage	-	✓
Path switching	Turn on audio path depending on user interface selection, or headset detection	-	✓
Path mixing	Required for voice memo recording and playback via multiple audio paths	-	✓
Transducer interfaces	Host provides acoustic drivers. Must occur outside of path switching and mixing	-	✓
Adjustable gain/volume settings	Based on user interface selections	✓	✓
DTMF/ringer tone generation		✓	✓

Important notice

Because of the nature of wireless communications, transmission and reception of data can never be guaranteed. Data may be delayed, corrupted (i.e., have errors) or be totally lost. Although significant delays or losses of data are rare when wireless devices such as the Sierra Wireless modem are used in a normal manner with a well-constructed network, the Sierra Wireless modem should not be used in situations where failure to transmit or receive data could result in damage of any kind to the user or any other party, including but not limited to personal injury, death, or loss of property. Sierra Wireless and its affiliates accept no responsibility for damages of any kind resulting from delays or errors in data transmitted or received using the Sierra Wireless modem, or for failure of the Sierra Wireless modem to transmit or receive such data.

Safety and hazards

Do not operate your SL8080 modem:

- In areas where blasting is in progress
- Where explosive atmospheres may be present including refuelling points, fuel depots, and chemical plants
- Near medical equipment, life support equipment, or any equipment which may be susceptible to any form of radio interference. In such areas, the SL8080 modem **MUST BE POWERED OFF**. Otherwise, the SL8080 modem can transmit signals that could interfere with this equipment.

In an aircraft, the SL8080 modem **MUST BE POWERED OFF**. Otherwise, the SL8080 modem can transmit signals that could interfere with various onboard systems and may be dangerous to the operation of the aircraft or disrupt the cellular network. Use of a cellular phone in an aircraft is illegal in some jurisdictions. Failure to observe this instruction may lead to suspension or denial of cellular telephone services to the offender, or legal action or both.

Some airlines may permit the use of cellular phones while the aircraft is on the ground and the door is open. The SL8080 modem may be used normally at this time.

Important compliance information for North American users

The SL8080 modem has been granted modular approval for mobile applications. Integrators may use the SL8080 modem in their final products without additional FCC/IC (Industry Canada) certification if they meet the following conditions. Otherwise, additional FCC/IC approvals must be obtained.

1. At least 20 cm separation distance between the antenna and the user's body must be maintained at all times.
2. To comply with FCC / IC regulations limiting both maximum RF output power and human exposure to RF radiation, the maximum antenna gain including cable loss in a mobile-only exposure condition must not exceed 6 dBi in the cellular band and 3.5 dBi in the PCS band.
3. The SL8080 modem and its antenna must not be co-located or operating in conjunction with any other transmitter or antenna within a host device.
4. A label must be affixed to the outside of the end product into which the SL8080 modem is incorporated, with a statement similar to the following:
 - For SL8080:
This device contains FCC ID: N7NSL8080
This equipment contains equipment certified under IC: 2417C-SL8080
5. A user manual with the end product must clearly indicate the operating requirements and conditions that must be observed to ensure compliance with current FCC / IC RF exposure guidelines.

The end product with an embedded SL8080 modem may also need to pass the FCC Part 15 unintentional emission testing requirements and be properly authorized per FCC Part 15.

Note: If this module is intended for use in a portable device, you are responsible for separate approval to satisfy the SAR requirements of FCC Part 2.1093 and IC RSS-102.

»» B: Acronyms and Definitions

B

Table B-1: Acronyms and definitions

Acronym or term	Definition
AGC	Automatic Gain Control
BER	Bit Error Rate - a measure of receive sensitivity
BLER	Block Error Rate
Call Box	Base Station Simulator - Agilent E8285A or 8960, Rohde & Schwarz CMU200
CDMA	Code Division Multiple Access
dB	Decibel = $10 \times \log_{10} (P1/P2)$ <i>P1 is calculated power; P2 is reference power</i> Decibel = $20 \times \log_{10} (V1/V2)$ <i>V1 is calculated voltage, V2 is reference voltage</i>
dBm	Decibels, relative to 1 mW - Decibel(mW) = $10 \times \log_{10} (Pwr (mW)/1mW)$
DUT	Device Under Test
EDGE	Enhanced Data rates for GSM Evolution
EM	Embedded Module
ESD	ElectroStatic Discharge
FER	Frame Error Rate - a measure of receive sensitivity
GPRS	General Packet Radio Services
GPS	Global Positioning System
GSM	Global System for Mobile communications
Hz	Hertz = 1 cycle/second
inrush current	Peak current drawn when a device is connected or powered on
IS-2000	3G radio standards for voice and data (CDMA only)
IS-95	2G radio standards targeted for voice (cdmaONE)
LDO	Low Drop Out - refers to linear regulator
MHz	MegaHertz = $10E6$ Hertz (Hertz = 1 cycle/second)
MIO	Module Input/Output
MPE	Maximum Permissible Exposure—the level of radiation to which a person may be exposed without hazardous effect or adverse biological changes
OTA	Over-The-Air or Radiated through the antenna

Table B-1: Acronyms and definitions

Acronym or term	Definition
PCS	Personal Communication System - PCS spans the 1.9 GHz radio spectrum
RF	Radio Frequency
RMS	Root Mean Square
SA	Selective Availability
Sensitivity (Audio)	Measure of lowest power signal that the receiver can measure
Sensitivity (RF)	Measure of lowest power signal at the receiver input that can provide a prescribed BER/BLER/SNR value at the receiver output.
SIM	Subscriber Identity Module
SL8080	Sierra Wireless AirPrime soldered-down module used on GSM/UMTS networks
SNR	Signal to Noise Ratio
SOF	Start of Frame - a USB function
UART	Universal Asynchronous Receiver Transmitter
UMTS	Universal Mobile Telecommunications System
USB	Universal Serial Bus
USIM	Universal Subscriber Identity Module
VCC	Supply voltage
WCDMA	Wideband Code Division Multiple Access—In this document, the term “UMTS” is used instead of “WCDMA”.
XIM	In this document, XIM is used as part of the contact identifiers for the USIM interface (XIM_VCC, XIM_CLK, etc.).



SIERRA
WIRELESS