

Enjoy listening to MP3/WMA files on CD or directly from your iPod® or Walkman® player plugged in to the front aux input of your Sony® CDX-GT260MP car stereo receiver. Plus, experience great sound quality from the built-in equalizer and powerful 52x4 watt high power amplifier.



## Bullets

- Detach face with LCD display and front aux input
- MP3/WMA music file playback
- EQ3 Stage 2 and 52 watt x 4 high power amplifier
- 2 Volt rear/sub selectable preamp outputs with HPF/LPF
- Radio Data System (RDS)
- Convenient wireless remote (RM-X201)
- Red key illumination

## Features

### Detach face with front aux input

The easy-to-read single line LCD display shows clock, station ID and track data when playing back your digital MP3/WMA files from the internal CD drive. Front auxiliary input lets you connect almost any portable audio device to your car's sound system.

### MP3/WMA music playback

Play CDs, CD-Rs, and CD-RWs, including discs loaded with digital MP3s and WMA files.

### Internal high power and EQ

The CDX-GT260MP delivers 52 watts of peak power to all four speakers for powerful output (208 watts total power). The 3 band EQ3 allows users to customize the sound centered at 60 Hz, 1000 Hz and 10 kHz frequencies.

### RCA outputs for external amplifiers

When you're ready to expand your sound system, the CDX-GT260MP offers selectable rear or subwoofer pre-amp RCA outputs for external amplifiers. Set the built in electronic HPF/LPF crossovers to improve sound quality and reduce system distortion.

### Radio Data System

Radio Data System (RDS) feature displays radio broadcast information such as artist and track information when listening to compatible AM/FM stations. RDS also allows expanded channel playback with compatible radio station broadcasts.

### Wireless card remote

Control your receiver while keeping your eyes on the road with the included wireless card remote (RM-X201).

### Key illumination

Red key illumination helps you locate buttons quickly during evening playback.

## Specifications

### Amplifier Section

Max power output	52 watts x 4 at 4 ohms
Power Ad Hoc	CEA2006 Standard Power: 17 Watts RMS per channel into 4 Ohms, 4 channels driven from 20 Hz to 20 kHz with less than 1% THD+N.
Speaker Impedance	4-8 Ohms

### AMP & General Feature

Aux-In	Yes (Front)
--------	-------------

EQ	EQ3:3 band EQ with +/- 10 dB adjustment at 60 Hz, 1 kHz and 10 kHz.
High Pass Filter	Selectable on/off at: 80, 100, 120, 140 or 160 Hz.
Loudness	Yes
Low Pass Filter	Selectable on/off at: 80, 100, 120, 140 or 160 Hz.
Output Power (4ohm, 1kHz,16V)(W)	52 watts x 4
Pre Out	(1) Rear / Sub switchable
Rear/Sub initial	Sub

## Audio

Band	AM / FM
Equalizer	EQ3: 3 band EQ with +/- 10 dB adjustment at 60 Hz, 1 kHz and 10 kHz.
Format(s) Supported	MP3/WMA files
Preout Impedance	220 ohms
Preout Voltage	2 volt
S/N Ratio	Audio Power: CEA2006 S/N 80 dBA
Signal-to-Noise Ratio (dB)	CD: 120 dB
Station Preset(s)	18 FM / 12 AM
Tuner Frequency Range	FM (MHz): 87.5-107.9 AM (kHz): 530-1710
Tuner Type	SSIR-EXA with RDS
Wow and Flutter	Below measurable limit

## AUX in Feature

Level Adjustment	Yes (-8dB / +18dB)
------------------	--------------------

## Convenience

Tilt Range	0-45° mounting angle
------------	----------------------

## Convenience Features

Dimmer Adjust	Manual
Key Illumination	Red
On-Screen Clock	12H

## Display

Display Color	Black / Negative Color
Display Technology	LCD
Text Displayed	Source, artist, track, playback time, menu and clock
Text Lines	1 line of information

## Display Panel

Auto off mode	Yes
Dimmer Adjust	Manual

## Panel Design

Display color (Color Variation/Nega or Posi)	Black color / Negative
Display Device (LCD/FL/OEL/TFT)	LCD
Key Illumination	Red
Panel finish color	Black (Bare)

## General

CEA2006 output power	17
CEA2006 S/N	80

Dimensions (WxHxD) (mm)	178x50x180
Maximum output power (4ohm, 1kHz, 16V)(W)	52
Mounting dimensions (WxHxD)(mm)	182 x 53 x 162
Preout impedance (ohms)	220
Preout output level (V)	2
Weight (kg)	1.2

## Inputs and Outputs

12V Trigger Output(s)	Power amplifier turn on
Antenna Terminal(s)	AM/FM Antenna Input Terminal
Audio In	Front Aux in with variable level
Infrared Port	Wireless remote
RCA Audio Output(s)	Rear/Subwoofer selectable RCA pre-amp outputs
Remote Jack	Optional wired remote terminal

## Other Features

Card Remote ( ): Option	RM-X201
CD lock mode	Yes
Clock	12H
Rotary commander ( ):Option	(RM-X4S)
Security	Detachable

## Tuner

FM Usable Sensitivity	8 dBf
Frequency Response	FM: 20-15,000 Hz
S/N Ratio	80 dB (stereo)
Selectivity	75 dB at 400 kHz
Stereo Separation	50 dB at 1 KHz
FM: Channel separation (dB)	50 dB at 1 kHz
FM: Frequency response (Hz)	20 - 15k
FM: Intermediate frequency (MHz)	25KHz
FM: S/N ratio (mono) (dB)	80 dB stereo
FM: Selectivity (400 kHz) (dB)	75 dB
FM: Tuning range (MHz)	87.5-107.9
FM: Usable sensitivity (75 ohm) (dBf)	8 dBf
MW: Tuning range(kHz)	530-1710
MW/LW/SW: Sensitivity (75 ohm) MW/LW/SW(uV)	26/-/-

## Tuner Feature

Preset	FM18/AM12
RDS/EON (NA Only:RBDS, Others:RDS)	Yes (RBDS)

## Weights and Measurements

Dimensions (Approx.)	178 x 50 x 180 mm, 7.125 x 2 x 7.125 inch (w/h/d)
Dimensions (Approx) Depth	7.125" (180 mm)
Dimensions (Approx) Height	2" (50 mm)
Dimensions (Approx) Width	7.125" (178 mm)
Weight (Approx.)	1.2 kg (2 lb. 11 oz.)

## Supplied Accessories

Supplied Accessories

Parts for installation and connections (1 set)  
RM-X201 wireless remote



© 2011 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony and the Sony logo are trademarks of Sony. iPod is a trademark of Apple Inc. Features and specifications are subject to change without notice. Updated: September 8, 2011