


INSTALLATION INSTRUCTIONS FOR MODEL 1000



StatSiGNAL Systems, Inc.
Atlanta, Georgia

Model 1000 Repeater/Transceiver
FCCID: PK9R001

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Use the instructions below to install the Repeater Module for the StatSiGNAL System

1. Remove the unit from its shipping carton.
2. Identify a shelf or table top close to a window or outside wall which is between the repeater and the units to which it will communicate. Air flow to the unit may be blocked because the unit generates very little heat (less than 200 milliwatts).
3. Set the Repeater on the shelf or table top with its antenna in a vertical position.
4. Connect 110VAC to the unit using the power cord for the Repeater. The unit requires less than 0.002 amps.

At this point, the Repeater is ready to function. The Site Controller will load all necessary data to it when the unit is found by that controller.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the Model 1000 off, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Consult StatSiGNAL or an experienced radio/TC technician for help.