Cutting Head Part Numbers

| | | | | | | Trimmenti | na Diametera | | | | FS 38 FS 40 C-E | |
|---------------------|-------------|--|-----------------|---------|---------------|--|-----------------|--------|------------------|----------|-------------------------------|----------------------|
| | | | Head/Blade Type | | Part Number | Trimmer Line Diameters Standard Optional | | FSE 60 | FSA 65 FSA 85 | FSA 90 R | FS 45* FS 46* FS 50 C-E | FS 55 FS 56 C-F** |
| HT GRASS TRIMMERS | | STIHL SuperCut™ head: | STIHL SuperCut™ | 20-2 | 4002 710 2184 | .095" | _ | | | | | • |
| | | Fully automatic, double nylon line is automatically kept at the proper cutting length. | STIHL SuperCut™ | 40-2 | 4003 710 2142 | .095" | _ | | | | | |
| | | AUTOCUT® head: | AUTOCUT® C | 4-2 | 4006 710 2123 | .080" | | | | | | |
| | | Double line for trimming and mowing. Nylon line is fed | AUTOCUT® | 5-2 | 4006 710 2103 | .080" | _ | | | | | |
| | | automatically by TapAction™. AUTOCUT® C 5-2 | AUTOCUT® C | 5-2 | 4006 710 2106 | .080" | _ | | | | | |
| | | EasySpool™ version available. | AUTOCUT® C | 25-2 | 4002 710 2196 | .095" | _ | | | | | |
| | | | AUTOCUT® | 11-2 | 4004 710 2192 | .095" | .080" | | | | | |
| | RS | | AUTOCUT® | 25-2 | 4002 710 2191 | .095" | .105" | | | | | |
| | JIME | | AUTOCUT® | 30-2 | 4002 710 2187 | .095" | .105" | | | | | |
| | TR | | AUTOCUT® | 40-2 | 4003 710 2189 | .095" | .105" | | | | | |
| | SS | | AUTOCUT® | 40-4 | 4005 710 2102 | .095" | .105" | | | | | |
| | GR/ | FixCut™ head: | FixCut™ | 5-2 | 4006 710 2118 | .095" | .080" | | | | • | |
| | LIGHT | Lightweight and quick loading. Insert 8" piece of trimmer line in each eyelet. | FixCut™ | 25-2 | 4002 710 2158 | .095" | .080/.120/.130" | | | • | | • |
| | ĭ | | FixCut™ | 30-2 | 4001 710 2103 | _ | .080/.095/.105" | | | • | | • |
| | | DuroCut head: | DuroCut | 5-2 | 4006 710 2125 | .080" | .065"/.095" | | | | • | |
| | | Ideal trimmer head for users who prefer manual heads that require precut lengths | DuroCut | 20-2 | 4002 710 2167 | .120" | .080/.095/.105" | | | | | • |
| | | of nylon line, even when operating in severe applications. | DuroCut | 40-4 | 4005 710 2106 | .155" | .120/.130" | | | | | |
| | | TrimCut™ head: | TrimCut™ | 31-2 | 4002 710 2156 | .105" | .095" | | | | | • |
| | | Manual-feed nylon head is particularly suitable for mowing low-growing grass around solid obstacles. | TrimCut™ | 41-2 | 4003 710 2108 | .105" | .095" | | | | | |
| | | | TrimCut™ | 51-2 | 4005 710 2104 | .105" | .095" | | | | | |
| HEAVY CBASS/MOM/ING | | STIHL PolyCut™ head: | STIHL PolyCut™ | 5-3 | 4004 710 2180 | | | | | | | |
| | JING | A universal cutting tool for trimming large areas. Fitted with three thermoplastic blades. | STIHL PolyCut™ | 6-3 | 4006 710 2104 | | | | | | • | |
| | <u>ا0</u> ۷ | | STIHL PolyCut™ | 20-3 | 4002 710 2189 | | | | | | | • |
| | SS/N | | STIHL PolyCut™ | 41-3 | 4003 710 2114 | | | | | | | |
| | 3RAS | Metal blade: | Grass-4 | 25.4 mm | 4001 713 3801 | | | | | | | ** |
| | | Steel, four cutting edges, for working on large areas of tough weeds and heavy grass. | Grass-4 | 20 mm | 4000 713 3801 | | | | | | | |
| | Ę | Metal blade: | Grass-8 | 25.4 mm | 4001 713 3803 | | | | | | | ** |
| | | Steel, 8 teeth, for cutting thick, dry weeds and reeds. | Grass-8 | 20 mm | 4000 713 3802 | | | | | | | |
| BRISH | ï | Brush knife: | Brush Knife | 25.4 mm | 4112 713 4100 | | | | | | | |
| | RUS | Steel, for thinning and clearing tough, tangled weeds, undergrowth | Brush Knife | 20 mm | 4119 713 4100 | | | | | | | |
| | Ω | and scrub. | Brush Knife | 20 mm | 4110 713 4100 | | | | | | | |
| FORESTRY | | Circular saw blade, | Scratcher | 25.4 mm | 4112 713 4201 | | | | | | | |
| | | scratcher tooth: Steel, for gnarled bushes and | Scratcher | 20 mm | 4000 713 4200 | | | | | | | |
| | ΠY | Abita Anna Amustra | Scratcher | 20 mm | 4000 713 4205 | | | | | | | |
| | TEST | dilli dee duiks. | Scratcher | 20 mm | 4104 713 4200 | | | | | | | |
| | <u>6</u> | Circular saw blade, chisel tooth: | Chisel | 25.4 mm | 4112 713 4203 | | | | | | | |
| | | Steel, for gnarled bushes and thin tree trunks (depends on diameter | Chisel | 20 mm | 4119 713 4200 | | | | | | | |
| | | of trunk and techniques used). | Chisel | 20 mm | 4110 713 4204 | | | | | | | |
| | | | | | | | | | | | | |

Cutting Head Part Numbers

| FS 55 R FS 55 RC-E | | FS 80 R | | | | | | | | | FSB-KM with | FS-KM | FS-KM with | |
|--|-------|---------------------|------------------------|-----------------|------------------|----------------------|------------------|---------------------------|----------|--------------------------|----------------------|-----------------------------|--------------------------|--|
| FS 56 RC-E FS 70 R, FS 90 R, FS 94 R | | FS 90 R FS 110 R | FS 100 RX FS 110 RX | FS 90 FS 110 | FS 240 | FS 240 R | FS 310 | FS 360 C-F | | FS 560 C-EM FS 550 | KM 55 R, 56 RC-F. | with KM 55 R, KM 56 R | KM 90 R, 94 R, 110 R, | |
| FS 94 R | FS 80 | FS 130 R | FS 110 RX | FS 130 | FS 240 FS 250 | FS 240 R FS 250 R | FS 310 FS 350 | FS 360 C-E FS 460 C-EM | FS 450 K | FS 550 | 90 R, 110 R | KM 56 R | 130 R | |
| • | • | • | • | • | • | • | | | | | | • | • | |
| | | | | | | | • | • | • | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| _2 | • | • | • | • | | | | | | | | • | • | |
| | | | | | | | | | | | • | | | |
| • | • | • | • | • | • | • | | | | | | • | • | |
| | | | | | • | • | | | | | | | | |
| | | | | | | | • | • | | | | | | |
| | | | | | | | | | • | • | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| • | • | • | • | • | • | • | | | | | | • | • | |
| • | • | • | | • | 1 | 1 | | | | | | • | • | |
| | | | | | | | | | | | | | | |
| • | • | • | • | • | • | • | | | | | | • | • | |
| | | | | | | | • | • | • | • | | | | |
| 2 | • | • | • | • | • | • | | | | | | • | • | |
| • | • | | | | _ | | | | | | | | _ | |
| | | | | | | | • | • | • | | | | | |
| | | | | | | | | | | • | | | | |
| | | | | | | | | | | | • | | | |
| | | | | | | | | | | | | | | |
| • | • | • | • | • | • | • | | | | | | • | • | |
| | | | | | | | • | • | • | • | | | | |
| • | • | • | | • | • | • | | | | | | | | |
| - | | | | | | | | | | | | | _ | |
| _ | | _ | | _ | | | • | • | • | | | | | |
| • | • | | | • | • | • | | | | | | | • | |
| | | | | | | | • | • | • | • | | | | |
| | • | | | • | • | • | | | | | | | | |
| | | | | | | | • | • | • | | | | | |
| | | | | | | | | | | • | | | | |
| | • | | | • | • | | | | | | | | | |
| | | | | | | | • | • | • | | | | | |
| | | | | | | | • | A | A | | | | | |
| | | | | | | | | • | • | • | | | | |
| | | | | | | | | | | ◆ *** | | | | |
| | • | | | • | • | | | | | | | | | |
| | | | | | | | • | • | • | | | | | |
| | | | | | | | | • | • | • | | | | |
| | | | | | | | | | | | | | | |

* Trimmers equipped with loop handles. For models that are/were available with optional handles, "R" denotes loop handle version.

Note: Numbers with "mm" show arbor size.

Consult your instruction manual or your authorized STIHL Dealer for approved cutting head/deflector combinations.

- Approved for use with designated unit as originally equipped.
 - ** When using Grass-4 and Grass-8 metal cutting blades with FS 56 C-E, trimmer must be equipped with deflector. Not necessary for FS 55. See dealer for more details.
- Approved for use with loop handle (R) only if equipped with barrier bar deflector kit and a single or double shoulder harness.
- Approved for use with bike handle, double harness and limit stop.
 - *** Not for use on FS 560 C-EM
- Not for use on FS 240 or FS 240 R
- 2 Not for use on FS 94 R

NOTE: Barrier bar and large deflector must be attached when using a metal blade with loop (R) handle trimmer.

IMPORTANT INFORMATION

WARNING: Improper use of any brushcutter trimmer can cause serious or fatal injury. Read, understand and follow all safety instructions in your instruction manual. To reduce the risk of injury from blade contact, circular saw blades may be used on FS brushcutters that have a bicycle handle and double shoulder harness and not on FS brushcutters with a "J" handle or loop handle (R). Other rigid blades may be used on FS brushcutters having a bicycle handle, a "J" handle, or a loop handle equipped with a barrier bar. To reduce the risk of eye injury, always wear proper eye protection. Always use the appropriate deflector for the type of cutting attachment, as explained in your instruction manual.