

# VANDAL-PROOF IR CAMERA




CDR-1201

CDR-1201H

## Features

- 1/3" Sony Super HAD CCD, 420-540TVL
- Minimum Illumination :0.5Lux/F1.2(LED OFF) ,0Lux(LED ON )
- Automatically switch to B/W mode under low light when illumination under 3-5Lux
- Max.25-30 Meters working distance with IR-LED on
- Designed as a waterproof structure
- "Against-Dismantle" Function
- Vandal proof Dome Cameras are extensively used in Prisons, Courthouses, Public Places, Banks, and Cash Carriers

## Dimensions



## Specifications

MODEL	CDR-1201H	CDR-1201
Signal System	PAL/NTSC	
Image Sensor	1/3"SONY CCD	
NO. of Effective Pixels	PAL:752X582;NTSC:768X484	PAL:500X382;NTSC:510X404
Horizontal Resolution	540 TV Lines	420 TV Lines
Minimum Illumination	0.1Lux/F2.0(LED OFF); 0Lux ( LED ON)	
Day/NightAutomatically Switch	Illumination< 3-5 Lux/F1.2	
S/N Ratio	More than 52dB	
Electronic Shutter	1/50-1/100,000sec(PAL), 1/60-1/100,000sec(NTSC)	
White Balance	Automatic	
AGC	Automatic	
BLC	On/off	
View Angle	45°	
Sync mode	INT	
Lens	3.5-8 mm vari-focal lens	
IR-LED	36 PCS LED;850nm	
Working Distance	80'	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Power Supply	DC 12V(+/-10%)	
Operation Temperature	-10°C to +50°C	
Body	Aluminum	
Weight	2.4 lbs	



SVA Group USA Inc.  
1316 John Reed Court, City of Industry, CA 91745  
Tel: 626-363-9500 | Fax: 626-363-9508  
1-888-8-ASK-SVA  
<http://www.sva-usa.com>